

**United States of America
FEDERAL COMMUNICATIONS COMMISSION
EXPERIMENTAL
RADIO STATION CONSTRUCTION PERMIT
AND LICENSE**

EXPERIMENTAL

(Nature of Service)

XT FX

(Class of Station)

WG2XHT

(Call Sign)

0038-EX-CM-2018

(File Number)

NAME Textron Aviation, Inc.

Subject to the provisions of the Communications Act of 1934, subsequent acts, and treaties, and all regulations heretofore or hereafter made by this Commission, and further subject to the conditions and requirements set forth in this license, the licensee hereof is hereby authorized to use and operate the radio transmitting facilities hereinafter described for radio communications in accordance with the program of experimentation described by the licensee in its application for license.

Operation: In accordance with Sec. 5.3(g) of the Commission's Rules

Station Locations

- (1) Wichita (SEDGWICK), KS - NL 37-38-25; WL 97-25-22
- (2) Wichita (SEDGWICK), KS - NL 37-38-25; WL 97-25-22
- (3) Wichita (SEDGWICK), KS - NL 37-38-25; WL 97-25-22
- (4) Wichita (SEDGWICK), KS - NL 37-38-25; WL 97-25-21
- (5) Wichita (SEDGWICK), KS - NL 37-38-26; WL 97-25-22
- (6) Wichita (SEDGWICK), KS - NL 37-38-27; WL 97-25-22
- (7) Wichita (SEDGWICK), KS - NL 37-38-27; WL 97-25-21
- (8) Wichita (SEDGWICK), KS - NL 37-38-27; WL 97-25-22
- (9) Wichita (SEDGWICK), KS - NL 37-38-27; WL 97-25-22
- (10) Wichita (SEDGWICK), KS - NL 37-38-27; WL 97-25-21
- (11) Wichita (SEDGWICK), KS - NL 37-38-28; WL 97-25-22
- (12) Wichita (SEDGWICK), KS - NL 37-38-28; WL 97-25-22
- (13) Wichita (SEDGWICK), KS - NL 37-38-28; WL 97-25-21

Frequency Information

Wichita (SEDGWICK), KS - NL 37-38-25; WL 97-25-22

Frequency	Station Class	Emission Designator	Authorized Power	Frequency Tolerance (+/-)
1575.42 MHz	FX	24M0G1D	100 pW (ERP)	

This authorization effective February 20, 2018 and
will expire 3:00 A.M. EST August 10, 2018

**FEDERAL
COMMUNICATIONS
COMMISSION**



Frequency Information

Wichita (SEDGWICK), KS - NL 37-38-25; WL 97-25-22

Frequency	Station Class	Emission Designator	Authorized Power	Frequency Tolerance (+/-)
1575.42 MHz	FX	24M0G1D	50.1 pW (ERP)	

Wichita (SEDGWICK), KS - NL 37-38-25; WL 97-25-22

Frequency	Station Class	Emission Designator	Authorized Power	Frequency Tolerance (+/-)
1575.42 MHz	FX	24M0G1D	100 pW (ERP)	

Wichita (SEDGWICK), KS - NL 37-38-25; WL 97-25-21

Frequency	Station Class	Emission Designator	Authorized Power	Frequency Tolerance (+/-)
1575.42 MHz	FX	24M0G1D	50.1 pW (ERP)	

Wichita (SEDGWICK), KS - NL 37-38-26; WL 97-25-22

Frequency	Station Class	Emission Designator	Authorized Power	Frequency Tolerance (+/-)
1575.42 MHz	FX	24M0G1D	100 pW (ERP)	

Frequency Information

Wichita (SEDGWICK), KS - NL 37-38-27; WL 97-25-22

Frequency	Station Class	Emission Designator	Authorized Power	Frequency Tolerance (+/-)
1575.42 MHz	FX	24M0G1D	100 pW (ERP)	

Wichita (SEDGWICK), KS - NL 37-38-27; WL 97-25-21

Frequency	Station Class	Emission Designator	Authorized Power	Frequency Tolerance (+/-)
1575.42 MHz	FX	24M0G1D	50.1 pW (ERP)	

Wichita (SEDGWICK), KS - NL 37-38-27; WL 97-25-22

Frequency	Station Class	Emission Designator	Authorized Power	Frequency Tolerance (+/-)
1575.42 MHz	FX	24M0G1D	50.1 pW (ERP)	

Wichita (SEDGWICK), KS - NL 37-38-27; WL 97-25-22

Frequency	Station Class	Emission Designator	Authorized Power	Frequency Tolerance (+/-)
1575.42 MHz	FX	24M0G1D	100 pW (ERP)	

Frequency Information

Wichita (SEDGWICK), KS - NL 37-38-27; WL 97-25-21

Frequency	Station Class	Emission Designator	Authorized Power	Frequency Tolerance (+/-)
1575.42 MHz	FX	24M0G1D	50.1 pW (ERP)	

Wichita (SEDGWICK), KS - NL 37-38-28; WL 97-25-22

Frequency	Station Class	Emission Designator	Authorized Power	Frequency Tolerance (+/-)
1575.42 MHz	FX	24M0G1D	50.1 pW (ERP)	

Wichita (SEDGWICK), KS - NL 37-38-28; WL 97-25-22

Frequency	Station Class	Emission Designator	Authorized Power	Frequency Tolerance (+/-)
1575.42 MHz	FX	24M0G1D	50.1 pW (ERP)	

Wichita (SEDGWICK), KS - NL 37-38-28; WL 97-25-21

Frequency	Station Class	Emission Designator	Authorized Power	Frequency Tolerance (+/-)
1575.42 MHz	FX	24M0G1D	50.1 pW (ERP)	

Special Conditions:

- (1) GPS re-radiators are limited to a maximum ERP value that will result in power levels not to exceed a power spectral density of -140 dBm/24 MHz measured at a distance of 100 ft outside the building of operation. Any malfunction, misalignment, or tampering of the equipment or its location which results in an increased power spectral density outside the building could cause harmful radio frequency interference to GPS receivers, including those in aircraft and/or ground based facilities.

Special Conditions:

- (2) The station identification requirements of Section 5.115 of the Commission's Rules are waived.
- (3) Licensee should be aware that other stations may be licensed on these frequencies and if any interference occurs, the licensee of this authorization will be subject to immediate shut down.
- (4) Stop Buzzer contacts: Dan Hankins at 620-332-0432/ 620-870-9388 and Douglas Best at 316-515-5625.
- (5) Licensee shall maintain testing according to the NTIA requirements of section 8.3.28 as stated in the filed application.
- (6) GPS users in the area of potential interference to GPS reception must be notified that GPS information may be impacted for periods of time.
- (7) Textron Aviation shall post signs on doors to the test area notifying that, "GPS re-radiator is in use and the GPS information you receive may be in error."
- (8) The test equipment shall only be used indoors and shall be under the control of Textron Aviation Inc.
- (9) Operation is limited to activity for the purpose of testing radio navigation satellite service (RNSS) equipment and systems.
- (10) No EIRP greater than -140 dBm/24 MHz at 100 feet is used.