

Environmental Assessment

Boeing Proprietary

Submitted by:

Christopher T. Fleming
 Southwest Region Frequency Manager
 The Boeing Company
 714-896-5363 (Office)
 714-655-3290 (Cell)
christopher.t.fleming@boeing.com

Per CFR 47, section 1.1307.b(1), Table 1, all applications for experimental operations with an ERP greater than 100 watts require evaluation for compliance with human exposure limits defined in section 1.1310, and if exceeded require submission of an Environmental Assessment as defined in section 1.1311.

The below calculations define the minimum safe working distance for both Occupational and General Public, which are based on the maximum permissible exposure limits of 5 mW/cm² and 1 mW/cm² respectively. These calculations were conducted using the highest gain antenna used in this operation.

TX Peak Power (mW)	501190000.00
TX Peak Power (dBm)	87.00
Maximum Antenna Gain dBi	0.00
EIRP (dBm)	87.00
Maximum Duty Cycle (Dc)	0.50
EIRP Watts	501190.00
Avg EIRP Watts	250595.00
TX Avg Power mW (Pavg)	
Pp*Dc	250595000.00

Non Dimensional Antenna Gain		
Gt = 10^{dB/10}	1	
	Occupational	General Public
Minimum Safe Distance - Meters	20	45
Distance in Centimeters (R)	2000	4500
AVG Power Density mW/CmCm		
Pd At distance=R		
(Pavg*Gt)/(4*Pi)*R²	4.985429121	0.984776123

Only authorized occupational workers will be allowed access to the area of operation. In addition the transmitter will be secured prior to conducting maintenance, and the area will be monitored during the operation to ensure that personnel are clear of any radiation hazard area.