



Per CFR 47, section 1.1307.b(1), Table 1, all applications for experimental operations with an ERP greater than 100 watts require evaluation for compliance with human exposure limits defined in section 1.1310, and if exceeded require submission of an Environmental Assessment as defined in section 1.1311.

The below calculations define the minimum safe working distance for both Occupational and General Public, which are based on the maximum permissible exposure limits of 5 mW/cm² and 1 mW/cm² respectively.

The antenna is a patch antenna array with an 8 degree maximum beam width. The antenna will be operated in a controlled area, and will be directed towards the aircraft in flight. Only authorized occupational workers will be allowed access to the area of operation. In addition the transmitter will be secured prior to conducting maintenance, and the area will be monitored during the operation to ensure that personnel are clear of any radiation hazard area.

Transmitter Peak Power (Watts):	2000
Maximum Antenna Gain (dBi):	32
Duty Cycle (%):	1
Transmitter Power (dBm):	63.0103
EIRP (dBm):	95.0103
Non-dimensional Antenna Gain:	1584.8932
Transmitter Avg Power (Watts):	20
EIRP Watts:	3169786.3849
Avg EIRP Watts:	31697.8638

Minimum Safe Distance

	Occupational	General Public
Meters:	7.1027	15.8822
Feet:	23.3026	52.1063