

NTIA Space record data form

NTIA requires the following data for space related experiments using government shared spectrum. For each transmit frequency, please provide the data for both ends of the transmit-receive link. Use Part A to describe the satellite to ground information. Part B is for all ground to space transmit links.

Part A: Space to Earth Downlink Data

Satellite Transmitter Data (Required for Each Frequency)

Transmit Frequency: 437.740 Mhz		
Satellite Name: QubeSat		
Data Field	Data Answer	Description/Comments
Transmit Power (PWR)	PWR = 1W	TRANSMIT POWER SUPPLIED TO THE ANTENNA INPUT TERMINAL, EXAMPLE, PWR01 W2 TRANSMIT POWER UNITS INCLUDE: W = WATT, K = KILOWATT, M = MEGAWATT
Necessary Bandwidth	12 kHz	THE WIDTH OF FREQUENCY BAND WHICH IS JUST SUFFICIENT TO SUCCESSFULLY TRANSFER DATA. FORMULAS CAN BE FOUND IN ANNEX J OF THE NTIA MANUAL.
RF Emissions Data	NA	2-SIDED EMISSION BANDWIDTH VALUES
-3 dB bandwidth		
-20 dB bandwidth		
-40 dB bandwidth		
-60 dB bandwidth		
Modulation Type	2-FSK	THE METHOD USED TO SUPERIMPOSE DATA ON THE CARRIER, EXAMPLE, BPSK, QPSK, GMSK.
Data Rate	5500 bits/sec	INFORMATION DATA RATE
Forward Error Correction Coding	Is FEC used? Yes ☐ No ☒ FEC Type: _____, FEC Rate: _____,	
Total Symbol Rate	5500 bits/sec	DATA RATE COMBINED WITH FEC AND FRAME OVERHEAD RESULTING IN THE TOTAL SYMBOL RATE AT THE INPUT TO THE SYMBOL MAPPER/MODULATOR.
Does transmitter have a beacon mode?	Yes ☐ No ☒	BEACON MODE IS NORMALLY CONSIDERED A REGULAR AND PERIODIC SHORT DURATION TRANSMISSION THAT IS OFTEN USED TO ASSIST WITH TRACKING, DOPPLER COMPENSATION, OR SMALL SATELLITE IDENTIFICATION WHOSE TRANSMISSIONS ARE NOT LIMITED TO DURATIONS WHEN SUPPORTING GROUND STATIONS ARE VISIBLE.
If transmitter has a beacon mode, can the beacon be commanded off?	Yes ☐ No ☐	

Transmit Antenna Polarization (XAP)	XAP = J	POLARIZATIONS INCLUDE: H = HORIZONTAL, V = VERTICAL, S = HORIZONTAL AND VERTICAL, L = LEFT HAND CIRCULAR, R = RIGHT HAND CIRCULAR, T = RIGHT AND LEFT HAND CIRCULAR, J = LINEAR POLARIZATION
Transmit Antenna Orientation (XAZ)	XAZ = EC	NB= NARROWBEAM EC = EARTH COVERAGE
Transmit Antenna Dimension (XAD)	ANTENNA GAIN: 2.2 dBi, BEAMWIDTH: 116 degrees, XAD = 02G116B	NTIA FORMAT (XAD), EXAMPLE, FOR 16 DBI ANTENNA GAIN AND 30 DEGREE BEAMWIDTH XAD01 16G030B
Type of satellite (State = SPCE) (City = Geo or Nongeo)	Type = NONGEOSTATIONARY	CHOOSE EITHER: GEOSTATIONARY OR NONGEOSTATIONARY
For Geostationary Satellites	Longitude =	IF ANY SATELLITES ARE GEOSTATIONARY, REPORT ITS LATITUDE AS 000000N (XLA AND/OR RLA) AND REPORT ITS LONGITUDE IN DDDMMSS FORMAT (XLG AND/OR RLG).
For Nongeostationary (Orbital Data)	INCLINATION ANGLE: 41 degrees, APOGEE IN KILOMETERS: 500 km, PERIGEE IN KILOMETERS: 500km, ORBITAL PERIOD IN HOURS: 1 hr AND FRACTIONS OF HOURS IN DECIMAL: 0.58, THE NUMBER OF SATELLITES IN THE SYSTEM: 1 ORB = ORB,41.0IN00500AP00500PE001.58H01NRT01	IF ANY SATELLITES ARE NONGEOSTATIONARY, REPORT ITS INCLINATION ANGLE, APOGEE IN KILOMETERS, PERIGEE IN KILOMETERS, ORBITAL PERIOD IN HOURS AND FRACTIONS OF HOURS IN DECIMAL, THE NUMBER OF SATELLITES IN THE SYSTEM, THEN T01, EXAMPLE, REM04 *ORB,98.0IN00510AP00510PE001.58H01NRT01, AND FOR SPACE-TO-SPACE COMMUNICATIONS WITH ANOTHER NONGEOSTATIONARY SATELLITE ADD AN ADDITIONAL *ORB FOR IT ENDING IN R01, EXAMPLE, REM05 *ORB,72.9IN03209AP00655PE013.46H01NRR01
For SunSynchronous Nongeostationary Orbits	Mean Local Time of Ascending Node (MLTAN) = _____	MLTAN IS THE ANGLE BETWEEN AN ORBIT'S ASCENDING NODE AND THE MEAN SUN, OFTEN EXPRESSED AS UNIT OF TIME (HH:MM)
Earth Station Data (Receiver) at Each Earth Station Location		
State (RSC)	RSC = California	
City Name (RAL)	RAL = Berkeley	
Latitude (DDMMSS)	Lat = 375231 N	
Longitude (DDMMSS)	Lon = 1221527 W	

Receive Antenna Polarization (RAP)	RAP = R	POLARIZATIONS INCLUDE: H = HORIZONTAL, V = VERTICAL, S = HORIZONTAL AND VERTICAL, L = LEFT HAND CIRCULAR, R = RIGHT HAND CIRCULAR, T = RIGHT AND LEFT HAND CIRCULAR, J = LINEAR POLARIZATION
Receive Antenna Orientation (RAZ)	RAZ = 10 degrees	THE EARTH STATION RECEIVER ANTENNA MINIMUM OPERATING ANGLE OF ELEVATION (RAZ), V00 TO V90, EXAMPLE, RAZ01 V00
Receive Antenna Dimensions (RAD)	ANTENNA GAIN: 18.7 dBi, BEAMWIDTH: 42 degrees, AZIMUTHAL RANGE: , THE SITE ELEVATION ABOVE MEAN SEA LEVEL IN METERS: 111m, THE ANTENNA HEIGHT ABOVE TERRAIN IN METERS: 25m, RAD = RAD01 19G042B001-360A00111H025	EXAMPLE ASSUMING NONGEOSTATIONARY, 16 DBI GAIN, 30 DEGREE BEAMWIDTH, AZIMUTHAL RANGE FROM 001-360, SITE ELEVATION OF 357 METERS, AND ANTENNA HEIGHT ABOVE TERRAIN OF 6 METERS: RAD01 16G030B001-360A00357H006
Receive Antenna Additional Information (For Parabolic Antennas)	ANTENNA DIAMETER _____, ANTENNA EFFICIENCY _____, Not Parabolic	
Number of Satellite Contacts Supported Per Day	3	NUMBER OF TIMES THE SATELLITE WILL COMMUNICATE WITH THE EARTH STATION IN THE SPACE TO EARTH DIRECTION (DOWNLINKS) EACH DAY
Expected Duration of Each Contact	7 minutes	AVERAGE DURATION OF EACH CONTACT
Supported Operations	Satellite Health and Status Data ☒ Mission Payload Data ☒	SATELLITE HEALTH AND STATUS TELEMETRY AND/OR MISSION PAYLOAD DATA
FCC notes: 1. Use S-Note S945. 2. REM AGN, Cubesat, QUBESAT		

Part B: Ground Stations, Earth to Space link data:

Earth Station Transmitter Data (Required for Each Frequency at Each Earth Station Location)

Transmit Frequency: 437.740 MHz		
State (XSC)	XSC = California	
City Name (XAL)	XAL = Berkeley	
Latitude (DDMMSS)	Lat = 375231 N	
Longitude (DDDMMSS)	Lon = 1221527 W	
Transmit Power (PWR)	PWR = 15W	TRANSMIT POWER SUPPLIED TO THE ANTENNA INPUT TERMINAL, EXAMPLE, PWR01 W2 TRANSMIT POWER UNITS INCLUDE: W = WATT, K = KILOWATT, M = MEGAWATT
Necessary Bandwidth	12 kHz	THE WIDTH OF FREQUENCY BAND WHICH IS JUST SUFFICIENT TO SUCCESSFULLY TRANSFER DATA. FORMULAS CAN BE FOUND IN ANNEX J OF THE NTIA MANUAL.
RF Emissions Data	NA	2-SIDED EMISSION BANDWIDTH VALUES
-3 dB bandwidth		
-20 dB bandwidth		
-40 dB bandwidth		
-60 dB bandwidth		
Modulation Type	2-FSK	THE METHOD USED TO SUPERIMPOSE DATA ON THE CARRIER, EXAMPLE, BPSK, QPSK, GMSK.
Data Rate	5500 bits/sec	INFORMATION DATA RATE
Forward Error Correction Coding	Is FEC used? Yes ☐ No ☒ FEC Type: _____, FEC Rate: _____	
Total Symbol Rate	5500 bits/sec	DATA RATE COMBINED WITH FEC AND FRAME OVERHEAD RESULTING IN THE TOTAL SYMBOL RATE AT THE INPUT TO THE SYMBOL MAPPER/MODULATOR.
Transmit Antenna Polarization (XAP)	XAP = R	POLARIZATIONS INCLUDE: H = HORIZONTAL, V = VERTICAL, S = HORIZONTAL AND VERTICAL, L = LEFT HAND CIRCULAR, R = RIGHT HAND CIRCULAR, T = RIGHT AND LEFT HAND CIRCULAR, J = LINEAR POLARIZATION
Transmit Antenna Orientation (XAZ)	10 DEGREES XAZ01 V10	THE EARTH STATION TRANSMITTER ANTENNA MINIMUM OPERATING ANGLE OF ELEVATION (XAZ), V00 TO V90, EXAMPLE, XAZ01 V00

Transmit Antenna Dimensions (XAD)	ANTENNA GAIN: 18.7 dBi, BEAMWIDTH: 42 degrees, AZIMUTHAL RANGE: , THE SITE ELEVATION ABOVE MEAN SEA LEVEL IN METERS: 111m, THE ANTENNA HEIGHT ABOVE TERRAIN IN METERS: 25m, XAD = XAD01 19G042B001-360A00111H025	EXAMPLE ASSUMING NONGEOSTATIONARY, 16 DBI GAIN, 30 DEGREE BEAMWIDTH, AZIMUTHAL RANGE FROM 001-360, SITE ELEVATION OF 357 METERS, AND ANTENNA HEIGHT ABOVE TERRAIN OF 6 METERS: XAD01 16G030B001-360A00357H006
Transmit Antenna Additional Information (For Parabolic Antennas)	ANTENNA DIAMETER _____, ANTENNA EFFICIENCY _____, Not Parabolic	
Number of Satellite Contacts Supported Per Day	3	NUMBER OF TIMES THE EARTH STATION WILL COMMUNICATE WITH THE SATELLITE IN THE EARTH TO SPACE DIRECTION (UPINKS) EACH DAY
Expected Duration of Each Contact	7 minutes	AVERAGE DURATION OF EACH CONTACT
Satellite Receive Specifications		
Receive Antenna Polarization (RAP)	RAP = J	POLARIZATIONS INCLUDE: H = HORIZONTAL, V = VERTICAL, S = HORIZONTAL AND VERTICAL, L = LEFT HAND CIRCULAR, R = RIGHT HAND CIRCULAR, T = RIGHT AND LEFT HAND CIRCULAR, J = LINEAR POLARIZATION
Receive Antenna Orientation (RAZ)	RAZ = EC	NB= NARROWBEAM EC = EARTH COVERAGE
Receive Antenna Dimension (RAD)	ANTENNA GAIN: 2.2 dBi, BEAMWIDTH: 116 degrees RAD01 02G116B	NTIA FORMAT(RAD), EXAMPLE, FOR 16 DBI ANTENNA GAIN AND 30 DEGREE BEAMWIDTH RAD01 16G030B
Type of satellite (State = SPCE) City = Geo or Nongeo	Type = NONGEOSTATIONARY	CHOOSE EITHER: GEOSTATIONARY OR NONGEOSTATIONARY
For Geostationary Satellites	Longitude =	IF ANY SATELLITES ARE GEOSTATIONARY, REPORT ITS LATITUDE AS 000000N (XLA AND/OR RLA) AND REPORT ITS LONGITUDE IN DDDMMSS FORMAT (XLG AND/OR RLG).

For Nongeostationary (Orbital Data)	INCLINATION ANGLE: 41 degrees, APOGEE IN KILOMETERS: 500 km, PERIGEE IN KILOMETERS: 500 km, ORBITAL PERIOD IN HOURS: 1hr AND FRACTIONS OF HOURS IN DECIMAL: 0.58, THE NUMBER OF SATELLITES IN THE SYSTEM: 1 ORB = ORB,41.0IN00500AP00500PE001.58H01NRR01	IF ANY SATELLITES ARE NONGEOSTATIONARY, REPORT ITS INCLINATION ANGLE, APOGEE IN KILOMETERS, PERIGEE IN KILOMETERS, ORBITAL PERIOD IN HOURS AND FRACTIONS OF HOURS IN DECIMAL, THE NUMBER OF SATELLITES IN THE SYSTEM, THEN T01, EXAMPLE, REM04 *ORB,98.0IN00510AP00510PE001.58H01NRT01, AND FOR SPACE-TO-SPACE COMMUNICATIONS WITH ANOTHER NONGEOSTATIONARY SATELLITE ADD AN ADDITIONAL *ORB FOR IT ENDING IN R01, EXAMPLE, REM05 *ORB,72.9IN03209AP00655PE013.46H01NRR01
For SunSynchronous Nongeostationary Orbits	Mean Local Time of Ascending Node (MLTAN) = _____	MLTAN IS THE ANGLE BETWEEN AN ORBIT'S ASCENDING NODE AND THE MEAN SUN, OFTEN EXPRESSED AS UNIT OF TIME (HH:MM)