



Space Dynamics
LABORATORY
Utah State University Research Foundation

FCC FORM 442: Exhibit A

FlexSAR-X Experimentation Description

Submitted To:

Federal Communications Commission
Office of Engineering and Technology

Submitted By:

Space Dynamics Laboratory
Utah State University Research Foundation
1695 North Research Park Way
North Logan, Utah 84341

DOCUMENT NUMBER:
REVISION:
DATE:

SDL/13-252
B
JUNE 5, 2015

TABLE OF CONTENTS

1. INTRODUCTION	1
2. PROGRAM OF RESEARCH DESCRIPTION	1
2.1 Equipment Description	1
2.2 Theory of Operation.....	3
3. DESCRIPTION OF EXPERIMENT	4
3.1 Experiment Objectives.....	4
3.2 Proposed Locations.....	4
3.3 Equipment Used	5
4. PROGRAM CONTRIBUTION AND IMPACT	5
5. CONTACT INFORMATION	6

1. INTRODUCTION

The Space Dynamics Laboratory (SDL) submits this document as Exhibit A of FCC Form 442 and in accordance with Section 5.3(b), (d) and (h) of CFR Title 47 for the purpose of testing and further developing its Flexible Synthetic Aperture Radar (FlexSAR-X), which operates between 9.5 and 10 GHz . SDL respectfully requests a modification to its previously granted license, call sign WG2XQF. This document provides supporting information and justification for the license original application and the modification. The modification is an increase in transmit power.

2. PROGRAM OF RESEARCH DESCRIPTION

The FlexSAR-X program is a development effort funded internally at SDL. The objective is to build and test a SAR system that is capable of working in X-band as a research tool for airborne SAR applications.

2.1 EQUIPMENT DESCRIPTION

The FlexSAR-X system consists of a Versa Module Eurocard (VME) chassis, solid state power amplifiers (SSPA) and an antenna. The VME chassis is 19"W x 15.75"H x 19.5"D, weighs 40 lbs and contains cards that provide a stable local oscillator, frequency conversion, pulse generation, analog to digital conversion, signal processing, and command and control. A chirp pulse is generated by direct digital synthesis (DDS) as it sweeps from low to high frequency, then up-converted to L-band and finally up-converted to X-band. The receiver reverses the process by down-converting from X-band to L-band and then from L-band to baseband. Bandpass and lowpass filters are incorporated on each stage of the transmitter and receiver to suppress unwanted out-of-band frequencies. The SSPA is only enabled during transmission of a pulse.

Each antenna polarization, horizontal and vertical (H and V), has a dedicated channel. The transmitter and receiver share the same antenna polarizations and are isolated from each other by a circulator. Each channel is connected to an SSPA before being connected to the antenna through the circulator. The FRF-138, an X-band antenna built by First RF Corp, is used for transmit and receive.




Figure 1. The FlexSAR-X VME chassis.

The FlexSAR-X system specifications are detailed in Table 1. The modification to the existing license are shown in bold.

Table 1. FlexSAR-X Specifications

RF Hardware	Space Dynamics Laboratory
Frequency	9500 to 10,000 MHz
Waveform Modulation	Pulse
Peak Transmitter Power	100 W (50 dBm)
Avg Transmitter Power	12.5 W (41 dBm) (max)
Pulse Repetition	16,000 pps (typ), 20,000 pps (max)
Transmitter Type	Linear Frequency Modulated Pulse
Transmitter Tuning	Direct Digital Synthesizer
Transmitter Frequency	0.0000001 ppm
Transmitter Power Amp	
Manufacture	Aethercomm
Model Number	SSPA 9.5-10.5-25
Transmitter Harmonic	
2 nd (dBc)	-60.4
Maximum Spurious	-70.0
Fundamental Curve	
-3.0 dBc	9560.10, 10085.00 MHz
-20 dBc	9543.00, 10130.68 MHz
-40 dBc	9513.00, 10155.80 MHz
-60 dBc	9459.00, 10185.95 MHz
Transmitter Filter	Bandpass, pre-power amplifier
Antenna Manufacture	First RF Corp
Antenna Model Number	FRF-138
Antenna Gain	18.0 dBi
Antenna Beamwidth	
Horizontal	40 degrees
Vertical	10 degrees
Antenna Mounting	Antennas are aircraft-mounted, under aircraft

2.2 THEORY OF OPERATION

The FlexSAR-X system collects data from an airborne platform while being controlled by an onboard operator. The RF card chassis is mounted inside the aircraft, and the antenna is mounted on the left side of the fuselage with a pointing vector perpendicular to the flight




Figure 2. The antenna is mounted such that energy is directed to the left and angled downward towards the ground.

direction and slanted downward 45 to 60 degrees, as shown in Figure 2. During the pre-flight planning process, areas of interest are identified that present scenes and objects to test the imaging fidelity of the SAR system.

FlexSAR-X can operate in one of four modes:

1. Transmit on H polarization and receive on H polarization (HH)
2. Transmit on V polarization and receive on V polarization (VV)
3. Alternate between modes 1 and 2 above for every other pulse, which is called interleaved mode (HH/VV)
4. Alternate transmitting on H and V polarizations every other pulse but receive on both H and V polarization channels. This is called quadrature mode (HH HV/VH VV)

The aircraft typically flies a race-track pattern around the area of interest, with FlexSAR-X actively transmitting and receiving energy during the straight portion of the track, as shown in Figure 3. Top-down view of a typical flight path used to collect data of an area of interest. The race-track pattern is pre-planned to present the scene at a nominal altitude and slant range. Typical operating altitude is 5000 ft AGL with slant ranges of 5000 to 8660 ft. The onboard operator monitors the aircraft position and heading to determine when the areas of interest enter the beam of the antenna. The operator turns on and off the transmitter when the area of interest enters and leaves the beam, respectively. The system operation modes and transmit on/off are

controlled by the operator from a software application developed by SDL, but there are also panel switches that can disable the transmitter in the event the software is not functioning. The operator is an experienced member of SDL staff.




Figure 3. Top-down view of a typical flight path used to collect data of an area of interest.

3. DESCRIPTION OF EXPERIMENT

3.1 EXPERIMENT OBJECTIVES

The primary purpose for flight testing the FlexSAR-X system is to observe system performance in a real-world environment. This includes the characterization of key metrics, such as signal-to-noise ratio, and provides feedback for engineering further improvements. Also, it is desired to obtain a better understanding of how system parameters affect the sensor's ability to resolve certain objects of interest in different clutter backgrounds.

3.2 PROPOSED LOCATIONS

SDL seeks authority to carry out its test flights in three locations as specified in the table and shown on the map in Figure 4. The areas were chosen due to the variety of natural and man-made scenes that will exercise the FlexSAR-X system's capability. The areas are defined by a center coordinate and radius as follows:

Table 2. Location Specifications

	Center Latitude	Center Longitude	Radius (km)	Altitude (ft)
Logan	41°46'42"	111°51'12"	40	<8200 AGL
Great Salt Lake	40°59'45"	112°52'51"	60	<8200 AGL
Evanston	41°16'24"	111°01'46"	60	<8200 AGL

A map of the proposed location and the surrounding area is shown in Figure 4.




Figure 4. Map of the proposed locations and surrounding area. Map courtesy of Google Maps.

Areas of interest within this circular area of operation will be chosen to meet test objectives and aircraft flight paths planned accordingly. These areas of interest are typically 1.5 miles in width and 3 miles in length.

3.3 EQUIPMENT USED

The flight test will be carried out using a Cessna 337 aircraft. The FlexSAR-X system as described in Section 2.1 will be installed on the aircraft along with a Novatel CPT GPS/INS, and a Rockwell Collins IGS-200 GPS/INS. The First RF FRF-138 antenna will be mounted on the left side of the aircraft.

4. PROGRAM CONTRIBUTION AND IMPACT

FlexSAR-X will be key to advancing the art of airborne SAR processing and image formation work at SDL and Utah State University (USU). It will enable SDL to work with other researchers, engineers and scientists across the country to expand SAR capability. Not only will SDL be able to use FlexSAR-X data for its own studies and advancement of SAR, but it will also be able to provide data to researchers at other institutions as well. FlexSAR-X can be easily configured for various airborne collection scenarios and studies, including concurrent collections with other sensors. The RF hardware will be studied and characterized in an effort to further refine and improve SAR measurements and images.

5. CONTACT INFORMATION

Questions regarding this application should be referred to the following individuals.

Mark Jensen

RF Engineer

Space Dynamics Laboratory

PH: (435) 713-3478

Scott A. Anderson

Branch Head, Tactical Sensors

Space Dynamics Laboratory

PH: (435) 713-3444