

NTIA Space record data form

NTIA requires the following data for space related experiments using government shared spectrum. For each transmit frequency, please provide the data for both ends of the transmit-receive link. Use Part A to describe the satellite to ground information. Part B is for all ground to space transmit links.

Part A: Space to Earth Downlink Data

Satellite Transmitter Data (Required for Each Frequency)

Transmit Frequency: 2257.5 MHz (Beam: SDN)		
Satellite Name: WSERIES11		
Data Field	Data Answer	Description/Comments
Transmit Power (PWR)	PWR01 = 3.35W PWR02 = 8.81W	TRANSMIT POWER SUPPLIED TO THE ANTENNA INPUT TERMINAL, EXAMPLE, PWR01 W2 TRANSMIT POWER UNITS INCLUDE: W = WATT, K = KILOWATT, M = MEGAWATT
Necessary Bandwidth	NBW01 1.90 MHz NBW02 5.00 MHz	THE WIDTH OF FREQUENCY BAND WHICH IS JUST SUFFICIENT TO SUCCESSFULLY TRANSFER DATA. FORMULAS CAN BE FOUND IN ANNEX J OF THE NTIA MANUAL.
RF Emissions Data		2-SIDED EMISSION BANDWIDTH VALUES
-3 dB bandwidth		
-20 dB bandwidth		
-40 dB bandwidth		
-60 dB bandwidth		
Modulation Type	QPSK	THE METHOD USED TO SUPERIMPOSE DATA ON THE CARRIER, EXAMPLE, BPSK, QPSK, GMSK.
Data Rate	DR01 1.5 Mbps DR02 4 Mbps	INFORMATION DATA RATE
Forward Error Correction Coding	Is FEC used? Yes ☒ No ☐ FEC Type: <u>RS + CC</u> , FEC Rate: <u>(223,255) + 1/2</u> ,	
Total Symbol Rate	SR01 1.74 Msps SR02 4.58 Msps	DATA RATE COMBINED WITH FEC AND FRAME OVERHEAD RESULTING IN THE TOTAL SYMBOL RATE AT THE INPUT TO THE SYMBOL MAPPER/MODULATOR.
Does transmitter have a beacon mode?	Yes ☐ No ☒	BEACON MODE IS NORMALLY CONSIDERED A REGULAR AND PERIODIC SHORT DURATION TRANSMISSION THAT IS OFTEN USED TO ASSIST WITH TRACKING, DOPPLER COMPENSATION, OR SMALL SATELLITE IDENTIFICATION WHOSE TRANSMISSIONS ARE NOT LIMITED TO DURATIONS WHEN SUPPORTING GROUND STATIONS ARE VISIBLE.

If transmitter has a beacon mode, can the beacon be commanded off?	Yes ☐ No ☐	
Transmit Antenna Polarization (XAP)	XAP = R	POLARIZATIONS INCLUDE: H = HORIZONTAL, V = VERTICAL, S = HORIZONTAL AND VERTICAL, L = LEFT HAND CIRCULAR, R = RIGHT HAND CIRCULAR, T = RIGHT AND LEFT HAND CIRCULAR, J = LINEAR POLARIZATION
Transmit Antenna Orientation (XAZ)	XAZ = EC	NB= NARROWBEAM EC = EARTH COVERAGE
Transmit Antenna Dimension (XAD)	ANTENNA GAIN <u>2.5</u> , BEAMWIDTH <u>60</u> , XAD01 02G060B	NTIA FORMAT (XAD), EXAMPLE, FOR 16 DBI ANTENNA GAIN AND 30 DEGREE BEAMWIDTH XAD01 16G030B
Type of satellite (State = SPCE) (City = Geo or Nongeo)	Type = Non-Geostationary	CHOOSE EITHER: GEOSTATIONARY OR NONGEOSTATIONARY
For Geostationary Satellites	Longitude =	IF ANY SATELLITES ARE GEOSTATIONARY, REPORT ITS LATITUDE AS 000000N (XLA AND/OR RLA) AND REPORT ITS LONGITUDE IN DDDMMSS FORMAT (XLG AND/OR RLG).
For Nongeostationary (Orbital Data)	INCLINATION ANGLE <u>97.5</u> , APOGEE IN KILOMETERS <u>510</u> , PERIGEE IN KILOMETERS <u>510</u> , ORBITAL PERIOD IN HOURS <u>1</u> AND FRACTIONS OF HOURS IN DECIMAL <u>605</u> , THE NUMBER OF SATELLITES IN THE SYSTEM <u>1</u> , ORB,97.5IN00510AP00510PE1.60H01NRT01	IF ANY SATELLITES ARE NONGEOSTATIONARY, REPORT ITS INCLINATION ANGLE, APOGEE IN KILOMETERS, PERIGEE IN KILOMETERS, ORBITAL PERIOD IN HOURS AND FRACTIONS OF HOURS IN DECIMAL, THE NUMBER OF SATELLITES IN THE SYSTEM, THEN T01, EXAMPLE, REM04 *ORB,98.0IN00510AP00510PE001.58H01NRT01, AND FOR SPACE-TO-SPACE COMMUNICATIONS WITH ANOTHER NONGEOSTATIONARY SATELLITE ADD AN ADDITIONAL *ORB FOR IT ENDING IN R01, EXAMPLE, REM05 *ORB,72.9IN03209AP00655PE013.46H01NRR01
For SunSynchronous Nongeostationary Orbits	Mean Local Time of Ascending Node (MLTAN) = <u>N/A</u>	MLTAN IS THE ANGLE BETWEEN AN ORBIT'S ASCENDING NODE AND THE MEAN SUN, OFTEN EXPRESSED AS UNIT OF TIME (HH:MM)
Earth Station Data (Receiver) at Each Earth Station Location		

State (RSC)	RSC01 NORWAY RSC02 ANTARTICA RSC03 SPAIN RSC04 CHILE RSC05 SOUTH AFRICA RSC06 SOUTH KOREA RSC07 NEW ZEALAND RSC08 NORWAY RSC09 ICELAND RSC10 PORTUGAL RSC11 SRI LANKA RSC12 CANADA	
City Name (RAL)	RAL01 SVALBARD RAL02 TROLL RAL03 PUERTOLLANO RAL04 PUNTA ARENAS RAL05 HARTEBEESTHOEK RAL06 JEJU RAL07 AWARUA RAL08 ANDOYA RAL09 BLONDUOS RAL10 SANTA MARIA RAL11 KANDY RAL12 INUVIK	
Latitude (DDMMSS)	LAT01 781353N LAT02 720009S LAT03 384021N LAT04 525610S LAT05 255309S LAT06 332314N LAT07 463143S LAT08 691752N LAT09 643851N LAT10 365950N LAT11 071627N LAT12 691932N	
Longitude (DDDMMSS)	LON01 0152440E LON02 00023131E LON03 0040943W LON04 0705212W LON05 0274220E LON06 1261900E LON07 1682247E LON08 0160556E LON09 0201441W LON10 0250810W LON11 0804328E LON12 1333645W	

Receive Antenna Polarization (RAP)	RAP =R	POLARIZATIONS INCLUDE: H = HORIZONTAL, V = VERTICAL, S = HORIZONTAL AND VERTICAL, L = LEFT HAND CIRCULAR, R = RIGHT HAND CIRCULAR, T = RIGHT AND LEFT HAND CIRCULAR, J = LINEAR POLARIZATION
Receive Antenna Orientation (RAZ)	RAZ01 V05 RAZ02 V05 RAZ03 V05 RAZ04 V05 RAZ05 V05 RAZ06 V05 RAZ07 V05 RAZ08 V05 RAZ09 V05 RAZ10 V05 RAZ11 V05 RAZ12 V05	THE EARTH STATION RECEIVER ANTENNA MINIMUM OPERATING ANGLE OF ELEVATION (RAZ), V00 TO V90, EXAMPLE, RAZ01 V00
Receive Antenna Dimensions (RAD)	ANTENNA GAIN <u>34.6</u> , BEAMWIDTH <u>2.5</u> , AZIMUTHAL RANGE <u>360</u> , THE SITE ELEVATION ABOVE MEAN SEA LEVEL IN METERS _____, THE ANTENNA HEIGHT ABOVE TERRAIN IN METERS _____, RAD01 35G003B001-360A00484H006 RAD02 35G003B001-360A01365H006 RAD03 35G003B001-360A00685H006 RAD04 35G003B001-360A00186H006 RAD05 35G003B001-360A01543H006 RAD06 35G003B001-360A00239H006 RAD07 35G003B001-360A00010H006 RAD08 35G003B001-360A00005H006 RAD09 35G003B001-360A00053H006 RAD10 35G003B001-360A00194H006 RAD11 35G003B001-360A00462H006 RAD12 35G003B001-360A00042H006	EXAMPLE ASSUMING NONGEOSTATIONARY, 16 DBI GAIN, 30 DEGREE BEAMWIDTH, AZIMUTHAL RANGE FROM 001-360, SITE ELEVATION OF 357 METERS, AND ANTENNA HEIGHT ABOVE TERRAIN OF 6 METERS: RAD01 16G030B001-360A00357H006
Receive Antenna Additional Information (For Parabolic Antennas)	ANTENNA DIAMETER <u>3.7m</u> , ANTENNA EFFICIENCY <u>94%</u> ,	
Number of Satellite Contacts Supported Per Day	32	NUMBER OF TIMES THE SATELLITE WILL COMMUNICATE WITH THE EARTH STATION IN THE SPACE TO EARTH DIRECTION (DOWNLINKS) EACH DAY

Expected Duration of Each Contact	10 minutes	AVERAGE DURATION OF EACH CONTACT
Supported Operations	Satellite Health and Status Data ☒ Mission Payload Data ☐	SATELLITE HEALTH AND STATUS TELEMETRY AND/OR MISSION PAYLOAD DATA
FCC notes: 1. Use S-Note S945. 2. REM AGN, WSERIES11		

Transmit Frequency: 8272.5 MHz (Beam: XDN)		
Satellite Name: WSERIES11		
Data Field	Data Answer	Description/Comments
Transmit Power (PWR)	PWR01 = 2W PWR02 = 2W	TRANSMIT POWER SUPPLIED TO THE ANTENNA INPUT TERMINAL, EXAMPLE, PWR01 W2 TRANSMIT POWER UNITS INCLUDE: W = WATT, K = KILOWATT, M = MEGAWATT
Necessary Bandwidth	NBW01 37.00 MHz NBW02 65.00 MHz	THE WIDTH OF FREQUENCY BAND WHICH IS JUST SUFFICIENT TO SUCCESSFULLY TRANSFER DATA. FORMULAS CAN BE FOUND IN ANNEX J OF THE NTIA MANUAL.
RF Emissions Data		2-SIDED EMISSION BANDWIDTH VALUES
-3 dB bandwidth		
-20 dB bandwidth		
-40 dB bandwidth		
-60 dB bandwidth		
Modulation Type	QPSK	THE METHOD USED TO SUPERIMPOSE DATA ON THE CARRIER, EXAMPLE, BPSK, QPSK, GMSK.
Data Rate	DR01 28.5 Mbps DR02 50.2 Mbps	INFORMATION DATA RATE
Forward Error Correction Coding	Is FEC used? Yes ☒ No ☐ FEC Type: <u>DVB-S2</u> , FEC Rate: <u>1/2</u> ,	
Total Symbol Rate	SR01 29.60 Msps SR02 52.00 Msps	DATA RATE COMBINED WITH FEC AND FRAME OVERHEAD RESULTING IN THE TOTAL SYMBOL RATE AT THE INPUT TO THE SYMBOL MAPPER/MODULATOR.
Does transmitter have a beacon mode?	Yes ☐ No ☒	BEACON MODE IS NORMALLY CONSIDERED A REGULAR AND PERIODIC SHORT DURATION TRANSMISSION THAT IS OFTEN USED TO ASSIST WITH TRACKING, DOPPLER COMPENSATION, OR SMALL SATELLITE IDENTIFICATION WHOSE TRANSMISSIONS ARE NOT LIMITED TO DURATIONS WHEN SUPPORTING GROUND STATIONS ARE VISIBLE.

If transmitter has a beacon mode, can the beacon be commanded off?	Yes ☐ No ☐	
Transmit Antenna Polarization (XAP)	XAP = R	POLARIZATIONS INCLUDE: H = HORIZONTAL, V = VERTICAL, S = HORIZONTAL AND VERTICAL, L = LEFT HAND CIRCULAR, R = RIGHT HAND CIRCULAR, T = RIGHT AND LEFT HAND CIRCULAR, J = LINEAR POLARIZATION
Transmit Antenna Orientation (XAZ)	XAZ = NB	NB= NARROWBEAM EC = EARTH COVERAGE
Transmit Antenna Dimension (XAD)	ANTENNA GAIN <u>17</u> , BEAMWIDTH <u>15</u> , XAD01 17G015B	NTIA FORMAT (XAD), EXAMPLE, FOR 16 DBI ANTENNA GAIN AND 30 DEGREE BEAMWIDTH XAD01 16G030B
Type of satellite (State = SPCE) (City = Geo or Nongeo)	Type = Non-Geostationary	CHOOSE EITHER: GEOSTATIONARY OR NONGEOSTATIONARY
For Geostationary Satellites	Longitude =	IF ANY SATELLITES ARE GEOSTATIONARY, REPORT ITS LATITUDE AS 000000N (XLA AND/OR RLA) AND REPORT ITS LONGITUDE IN DDDMMSS FORMAT (XLG AND/OR RLG).
For Nongeostationary (Orbital Data)	INCLINATION ANGLE <u>97.5</u> , APOGEE IN KILOMETERS <u>510</u> , PERIGEE IN KILOMETERS <u>510</u> , ORBITAL PERIOD IN HOURS <u>1</u> AND FRACTIONS OF HOURS IN DECIMAL <u>605</u> , THE NUMBER OF SATELLITES IN THE SYSTEM <u>1</u> , ORB,97.5IN00510AP00510PE1.60H01NRT01	IF ANY SATELLITES ARE NONGEOSTATIONARY, REPORT ITS INCLINATION ANGLE, APOGEE IN KILOMETERS, PERIGEE IN KILOMETERS, ORBITAL PERIOD IN HOURS AND FRACTIONS OF HOURS IN DECIMAL, THE NUMBER OF SATELLITES IN THE SYSTEM, THEN T01, EXAMPLE, REM04 *ORB,98.0IN00510AP00510PE001.58H01NRT01, AND FOR SPACE-TO-SPACE COMMUNICATIONS WITH ANOTHER NONGEOSTATIONARY SATELLITE ADD AN ADDITIONAL *ORB FOR IT ENDING IN R01, EXAMPLE, REM05 *ORB,72.9IN03209AP00655PE013.46H01NRR01
For SunSynchronous Nongeostationary Orbits	Mean Local Time of Ascending Node (MLTAN) = <u>N/A</u>	MLTAN IS THE ANGLE BETWEEN AN ORBIT'S ASCENDING NODE AND THE MEAN SUN, OFTEN EXPRESSED AS UNIT OF TIME (HH:MM)
Earth Station Data (Receiver) at Each Earth Station Location		

State (RSC)	RSC01 NORWAY RSC02 ANTARTICA RSC03 SPAIN RSC04 CHILE RSC05 SOUTH AFRICA RSC06 SOUTH KOREA RSC07 NEW ZEALAND RSC08 NORWAY RSC09 ICELAND RSC10 PORTUGAL RSC11 SRI LANKA RSC12 CANADA	
City Name (RAL)	RAL01 SVALBARD RAL02 TROLL RAL03 PUERTOLLANO RAL04 PUNTA ARENAS RAL05 HARTEBEESTHOEK RAL06 JEJU RAL07 AWARUA RAL08 ANDOYA RAL09 BLONDUOS RAL10 SANTA MARIA RAL11 KANDY RAL12 INUVIK	
Latitude (DDMMSS)	LAT01 781353N LAT02 720009S LAT03 384021N LAT04 525610S LAT05 255309S LAT06 332314N LAT07 463143S LAT08 691752N LAT09 643851N LAT10 365950N LAT11 071627N LAT12 691932N	
Longitude (DDDMMSS)	LON01 0152440E LON02 00023131E LON03 0040943W LON04 0705212W LON05 0274220E LON06 1261900E LON07 1682247E LON08 0160556E LON09 0201441W LON10 0250810W LON11 0804328E LON12 1333645W	

Receive Antenna Polarization (RAP)	RAP =R	POLARIZATIONS INCLUDE: H = HORIZONTAL, V = VERTICAL, S = HORIZONTAL AND VERTICAL, L = LEFT HAND CIRCULAR, R = RIGHT HAND CIRCULAR, T = RIGHT AND LEFT HAND CIRCULAR, J = LINEAR POLARIZATION
Receive Antenna Orientation (RAZ)	RAZ01 V05 RAZ02 V05 RAZ03 V05 RAZ04 V05 RAZ05 V05 RAZ06 V05 RAZ07 V05 RAZ08 V05 RAZ09 V05 RAZ10 V05 RAZ11 V05 RAZ12 V05	THE EARTH STATION RECEIVER ANTENNA MINIMUM OPERATING ANGLE OF ELEVATION (RAZ), V00 TO V90, EXAMPLE, RAZ01 V00
Receive Antenna Dimensions (RAD)	ANTENNA GAIN <u>47.6</u> , BEAMWIDTH <u>0.66</u> , AZIMUTHAL RANGE <u>360</u> , THE SITE ELEVATION ABOVE MEAN SEA LEVEL IN METERS _____ , THE ANTENNA HEIGHT ABOVE TERRAIN IN METERS _____ , RAD01 47G001B001-360A00484H006 RAD02 47G001B001-360A01365H006 RAD03 47G001B001-360A00685H006 RAD04 47G001B001-360A00186H006 RAD05 47G001B001-360A01543H006 RAD06 47G001B001-360A00239H006 RAD07 47G001B001-360A00010H006 RAD08 47G001B001-360A00005H006 RAD09 47G001B001-360A00053H006 RAD10 47G001B001-360A00194H006 RAD11 47G001B001-360A00462H006 RAD12 47G001B001-360A00042H006	EXAMPLE ASSUMING NONGEOSTATIONARY, 16 DBI GAIN, 30 DEGREE BEAMWIDTH, AZIMUTHAL RANGE FROM 001-360, SITE ELEVATION OF 357 METERS, AND ANTENNA HEIGHT ABOVE TERRAIN OF 6 METERS: RAD01 16G030B001-360A00357H006
Receive Antenna Additional Information (For Parabolic Antennas)	ANTENNA DIAMETER <u>3.7m</u> , ANTENNA EFFICIENCY <u>94%</u> ,	
Number of Satellite Contacts Supported Per Day	32	NUMBER OF TIMES THE SATELLITE WILL COMMUNICATE WITH THE EARTH STATION IN THE SPACE TO EARTH DIRECTION (DOWNLINKS) EACH DAY

Expected Duration of Each Contact	10 minutes	AVERAGE DURATION OF EACH CONTACT
Supported Operations	Satellite Health and Status Data ☐ Mission Payload Data ☒	SATELLITE HEALTH AND STATUS TELEMETRY AND/OR MISSION PAYLOAD DATA
FCC notes: 1. Use S-Note S945. 2. REM AGN, WSERIES11		

Part B: Ground Stations, Earth to Space link data:

Earth Station Transmitter Data (Required for Each Frequency at Each Earth Station Location)

Transmit Frequency: 2078.781 MHz		
State (XSC)	XSC01 NORWAY XSC02 ANTARTICA XSC03 SPAIN XSC04 CHILE XSC05 SOUTH AFRICA XSC06 SOUTH KOREA XSC07 NEW ZEALAND XSC08 NORWAY XSC09 ICELAND XSC10 PORTUGAL XSC11 SRI LANKA XSC12 CANADA	
City Name (XAL)	XAL01 SVALBARD XAL02 TROLL XAL03 PUERTOLLANO XAL04 PUNTA ARENAS XAL05 HARTEBEESTHOEK XAL06 JEJU XAL07 AWARUA XAL08 ANDOYA XAL09 BLONDUOS XAL10 SANTA MARIA XAL11 KANDY XAL12 INUVIK	
Latitude (DDMMSS)	LAT01 781353N LAT02 720009S LAT03 384021N LAT04 525610S LAT05 255309S LAT06 332314N LAT07 463143S LAT08 691752N LAT09 643851N LAT10 365950N LAT11 071627N LAT12 691932N	

Longitude (DDMMSS)	LON01 0152440E LON02 00023131E LON03 0040943W LON04 0705212W LON05 0274220E LON06 1261900E LON07 1682247E LON08 0160556E LON09 0201441W LON10 0250810W LON11 0804328E LON12 1333645W	
Transmit Power (PWR)	PWR = 25W	TRANSMIT POWER SUPPLIED TO THE ANTENNA INPUT TERMINAL, EXAMPLE, PWR01 W2 TRANSMIT POWER UNITS INCLUDE: W = WATT, K = KILOWATT, M = MEGAWATT
Necessary Bandwidth	NBW01 175 kHz NBW02 400 kHz NBW03 1 MHz	THE WIDTH OF FREQUENCY BAND WHICH IS JUST SUFFICIENT TO SUCCESSFULLY TRANSFER DATA. FORMULAS CAN BE FOUND IN ANNEX J OF THE NTIA MANUAL.
RF Emissions Data		2-SIDED EMISSION BANDWIDTH VALUES
-3 dB bandwidth		
-20 dB bandwidth		
-40 dB bandwidth		
-60 dB bandwidth		
Modulation Type	QPSK	THE METHOD USED TO SUPERIMPOSE DATA ON THE CARRIER, EXAMPLE, BPSK, QPSK, GMSK.
Data Rate	DR01 125 kbps DR02 292 kbps DR03 729 kbps	INFORMATION DATA RATE
Forward Error Correction Coding	Is FEC used? Yes ☒ No ☐ FEC Type: <u>RS + CC</u> , FEC Rate: <u>(223,255) + 1/2</u> ,	
Total Symbol Rate	SR01 145.2 ksps SR02 333.3 ksps SR03 833.3 ksps	DATA RATE COMBINED WITH FEC AND FRAME OVERHEAD RESULTING IN THE TOTAL SYMBOL RATE AT THE INPUT TO THE SYMBOL MAPPER/MODULATOR.
Transmit Antenna Polarization (XAP)	XAP =R	POLARIZATIONS INCLUDE: H = HORIZONTAL, V = VERTICAL, S = HORIZONTAL AND VERTICAL, L = LEFT HAND CIRCULAR, R = RIGHT HAND CIRCULAR, T = RIGHT AND LEFT HAND CIRCULAR, J = LINEAR POLARIZATION
Transmit Antenna Orientation (XAZ)	XAZ01 V05	THE EARTH STATION TRANSMITTER ANTENNA MINIMUM OPERATING ANGLE OF ELEVATION (XAZ), V00 TO V90, EXAMPLE, XAZ01 V00

Transmit Antenna Dimensions (XAD)	ANTENNA GAIN <u>34.0</u> , BEAMWIDTH <u>2.7</u> , AZIMUTHAL RANGE <u>360</u> , THE SITE ELEVATION ABOVE MEAN SEA LEVEL IN METERS _____, THE ANTENNA HEIGHT ABOVE TERRAIN IN METERS _____ XAD01 34G003B001-360A00484H006 XAD02 34G003B001-360A01365H006 XAD03 34G003B001-360A00685H006 XAD04 34G003B001-360A00186H006 XAD05 34G003B001-360A01543H006 XAD06 34G003B001-360A00239H006 XAD07 34G003B001-360A00010H006 XAD08 34G003B001-360A00005H006 XAD09 34G003B001-360A00053H006 XAD10 34G003B001-360A00194H006 XAD11 34G003B001-360A00462H006 XAD12 34G003B001-360A00042H006	EXAMPLE ASSUMING NONGEOSTATIONARY, 16 DBI GAIN, 30 DEGREE BEAMWIDTH, AZIMUTHAL RANGE FROM 001-360, SITE ELEVATION OF 357 METERS, AND ANTENNA HEIGHT ABOVE TERRAIN OF 6 METERS: XAD01 16G030B001-360A00357H006
Transmit Antenna Additional Information (For Parabolic Antennas)	ANTENNA DIAMETER <u>3.7m</u> , ANTENNA EFFICIENCY <u>94%</u>	
Number of Satellite Contacts Supported Per Day	32	NUMBER OF TIMES THE EARTH STATION WILL COMMUNICATE WITH THE SATELLITE IN THE EARTH TO SPACE DIRECTION (UPINKS) EACH DAY
Expected Duration of Each Contact	10 minutes	AVERAGE DURATION OF EACH CONTACT
Satellite Receive Specifications		
Receive Antenna Polarization (RAP)	RAP = R	POLARIZATIONS INCLUDE: H = HORIZONTAL, V = VERTICAL, S = HORIZONTAL AND VERTICAL, L = LEFT HAND CIRCULAR, R = RIGHT HAND CIRCULAR, T = RIGHT AND LEFT HAND CIRCULAR, J = LINEAR POLARIZATION
Receive Antenna Orientation (RAZ)	RAZ = EC	NB= NARROWBEAM EC = EARTH COVERAGE
Receive Antenna Dimension (RAD)	ANTENNA GAIN <u>2.5</u> , BEAMWIDTH <u>60</u> , RAD01 02G060B	NTIA FORMAT(RAD), EXAMPLE, FOR 16 DBI ANTENNA GAIN AND 30 DEGREE BEAMWIDTH RAD01 16G030B

Type of satellite (State = SPCE) City = Geo or Nongeo	Type =Non-Geostationary	CHOOSE EITHER: GEOSTATIONARY OR NONGEOSTATIONARY
For Geostationary Satellites	Longitude =	IF ANY SATELLITES ARE GEOSTATIONARY, REPORT ITS LATITUDE AS 000000N (XLA AND/OR RLA) AND REPORT ITS LONGITUDE IN DDDMMSS FORMAT (XLG AND/OR RLG).
For Nongeostationary (Orbital Data)	INCLINATION ANGLE <u>97.5</u> , APOGEE IN KILOMETERS <u>510</u> , PERIGEE IN KILOMETERS <u>510</u> , ORBITAL PERIOD IN HOURS <u>1</u> AND FRACTIONS OF HOURS IN DECIMAL <u>605</u> , THE NUMBER OF SATELLITES IN THE SYSTEM <u>1</u> , ORB,97.5IN00510AP00510PE1.60H01NRT 01	IF ANY SATELLITES ARE NONGEOSTATIONARY, REPORT ITS INCLINATION ANGLE, APOGEE IN KILOMETERS, PERIGEE IN KILOMETERS, ORBITAL PERIOD IN HOURS AND FRACTIONS OF HOURS IN DECIMAL, THE NUMBER OF SATELLITES IN THE SYSTEM, THEN T01, EXAMPLE, REM04 *ORB,98.0IN00510AP00510PE001.58H01NRT01, AND FOR SPACE-TO-SPACE COMMUNICATIONS WITH ANOTHER NONGEOSTATIONARY SATELLITE ADD AN ADDITIONAL *ORB FOR IT ENDING IN R01, EXAMPLE, REM05 *ORB,72.9IN03209AP00655PE013.46H01NRR01
For SunSynchronous Nongeostationary Orbits	Mean Local Time of Ascending Node (MLTAN) = <u>N/A</u>	MLTAN IS THE ANGLE BETWEEN AN ORBIT'S ASCENDING NODE AND THE MEAN SUN, OFTEN EXPRESSED AS UNIT OF TIME (HH:MM)

Part C: Space to Space Link

Satellite Transmitter Data (Required for Each Frequency)

Transmit Frequency: 1618.725 – 1626.500 MHz (Iridium FDMA dependent)		
Satellite Name: WSERIES11		
Data Field	Data Answer	Description/Comments
Transmit Power (PWR)	PWR01 = 1.4W	TRANSMIT POWER SUPPLIED TO THE ANTENNA INPUT TERMINAL, EXAMPLE, PWR01 W2 TRANSMIT POWER UNITS INCLUDE: W = WATT, K = KILOWATT, M = MEGAWATT
Necessary Bandwidth	NBW01 35 kHz	THE WIDTH OF FREQUENCY BAND WHICH IS JUST SUFFICIENT TO SUCCESSFULLY TRANSFER DATA. FORMULAS CAN BE FOUND IN ANNEX J OF THE NTIA MANUAL.
RF Emissions Data		2-SIDED EMISSION BANDWIDTH VALUES
-3 dB bandwidth		
-20 dB bandwidth		
-40 dB bandwidth		
-60 dB bandwidth		
Modulation Type	DQPSK	THE METHOD USED TO SUPERIMPOSE DATA ON THE CARRIER, EXAMPLE, BPSK, QPSK, GMSK.
Data Rate	DR01 50kbps	INFORMATION DATA RATE
Forward Error Correction Coding	Is FEC used? Yes ☐ No ☒ FEC Type: _____, FEC Rate: _____,	
Total Symbol Rate	SR01 25 ksps	DATA RATE COMBINED WITH FEC AND FRAME OVERHEAD RESULTING IN THE TOTAL SYMBOL RATE AT THE INPUT TO THE SYMBOL MAPPER/MODULATOR.
Does transmitter have a beacon mode?	Yes ☐ No ☒	BEACON MODE IS NORMALLY CONSIDERED A REGULAR AND PERIODIC SHORT DURATION TRANSMISSION THAT IS OFTEN USED TO ASSIST WITH TRACKING, DOPPLER COMPENSATION, OR SMALL SATELLITE IDENTIFICATION WHOSE TRANSMISSIONS ARE NOT LIMITED TO DURATIONS WHEN SUPPORTING GROUND STATIONS ARE VISIBLE.
If transmitter has a beacon mode, can the beacon be commanded off?	Yes ☐ No ☐	
Transmit Antenna Polarization (XAP)	XAP = R	POLARIZATIONS INCLUDE: H = HORIZONTAL, V = VERTICAL, S = HORIZONTAL AND VERTICAL, L = LEFT HAND CIRCULAR, R = RIGHT HAND CIRCULAR, T = RIGHT AND LEFT HAND CIRCULAR, J = LINEAR POLARIZATION

Transmit Antenna Orientation (XAZ)	XAZ = EC	NB= NARROWBEAM EC = EARTH COVERAGE
Transmit Antenna Dimension (XAD)	ANTENNA GAIN <u>3</u> , BEAMWIDTH <u>60</u> , XAD01 03G060B	NTIA FORMAT (XAD), EXAMPLE, FOR 16 DBI ANTENNA GAIN AND 30 DEGREE BEAMWIDTH XAD01 16G030B
Type of satellite (State = SPCE) (City = Geo or Nongeo)	Type = Non-Geostationary	CHOOSE EITHER: GEOSTATIONARY OR NONGEOSTATIONARY
For Geostationary Satellites	Longitude =	IF ANY SATELLITES ARE GEOSTATIONARY, REPORT ITS LATITUDE AS 000000N (XLA AND/OR RLA) AND REPORT ITS LONGITUDE IN DDDMMSS FORMAT (XLG AND/OR RLG).
For Nongeostationary (Orbital Data)	INCLINATION ANGLE <u>97.5</u> , APOGEE IN KILOMETERS <u>510</u> , PERIGEE IN KILOMETERS <u>510</u> , ORBITAL PERIOD IN HOURS <u>1</u> AND FRACTIONS OF HOURS IN DECIMAL <u>605</u> , THE NUMBER OF SATELLITES IN THE SYSTEM <u>1</u> , ORB,97.5IN00510AP00510PE1.60H01NRT 01	IF ANY SATELLITES ARE NONGEOSTATIONARY, REPORT ITS INCLINATION ANGLE, APOGEE IN KILOMETERS, PERIGEE IN KILOMETERS, ORBITAL PERIOD IN HOURS AND FRACTIONS OF HOURS IN DECIMAL, THE NUMBER OF SATELLITES IN THE SYSTEM, THEN T01, EXAMPLE, REM04 *ORB,98.0IN00510AP00510PE001.58H01NRT01, AND FOR SPACE-TO-SPACE COMMUNICATIONS WITH ANOTHER NONGEOSTATIONARY SATELLITE ADD AN ADDITIONAL *ORB FOR IT ENDING IN R01, EXAMPLE, REM05 *ORB,72.9IN03209AP00655PE013.46H01NRR01
For SunSynchronous Nongeostationary Orbits	Mean Local Time of Ascending Node (MLTAN) = <u>N/A</u>	MLTAN IS THE ANGLE BETWEEN AN ORBIT'S ASCENDING NODE AND THE MEAN SUN, OFTEN EXPRESSED AS UNIT OF TIME (HH:MM)

Satellite Receive Specifications (HIBLEO-2)		
Receive Antenna Polarization (RAP)	RAP =R	POLARIZATIONS INCLUDE: H = HORIZONTAL, V = VERTICAL, S = HORIZONTAL AND VERTICAL, L = LEFT HAND CIRCULAR, R = RIGHT HAND CIRCULAR, T = RIGHT AND LEFT HAND CIRCULAR, J = LINEAR POLARIZATION
Receive Antenna Orientation (RAZ)	RAZ = NB	NB= NARROWBEAM EC = EARTH COVERAGE
Receive Antenna Dimension (RAD)	ANTENNA GAIN <u>20</u> , BEAMWIDTH <u>12</u> , RAD01 20G012B	NTIA FORMAT(RAD), EXAMPLE, FOR 16 DBI ANTENNA GAIN AND 30 DEGREE BEAMWIDTH RAD01 16G030B

Type of satellite (State = SPCE) City = Geo or Nongeo	Type =Non-Geostationary	CHOOSE EITHER: GEOSTATIONARY OR NONGEOSTATIONARY
For Geostationary Satellites	Longitude =	IF ANY SATELLITES ARE GEOSTATIONARY, REPORT ITS LATITUDE AS 000000N (XLA AND/OR RLA) AND REPORT ITS LONGITUDE IN DDDMMSS FORMAT (XLG AND/OR RLG).
For Nongeostationary (Orbital Data)	INCLINATION ANGLE_____, APOGEE IN KILOMETERS_____, PERIGEE IN KILOMETERS_____, ORBITAL PERIOD IN HOURS _____AND FRACTIONS OF HOURS IN DECIMAL_____, THE NUMBER OF SATELLITES IN THE SYSTEM_____, ORB,86.4IN00780AP00780PE001.73H66N RR01	IF ANY SATELLITES ARE NONGEOSTATIONARY, REPORT ITS INCLINATION ANGLE, APOGEE IN KILOMETERS, PERIGEE IN KILOMETERS, ORBITAL PERIOD IN HOURS AND FRACTIONS OF HOURS IN DECIMAL, THE NUMBER OF SATELLITES IN THE SYSTEM, THEN T01, EXAMPLE, REM04 *ORB,98.0IN00510AP00510PE001.58H01NRT01, AND FOR SPACE-TO-SPACE COMMUNICATIONS WITH ANOTHER NONGEOSTATIONARY SATELLITE ADD AN ADDITIONAL *ORB FOR IT ENDING IN R01, EXAMPLE, REM05 *ORB,72.9IN03209AP00655PE013.46H01NRR01
For SunSynchronous Nongeostationary Orbits	Mean Local Time of Ascending Node (MLTAN) = _____ N/A	MLTAN IS THE ANGLE BETWEEN AN ORBIT'S ASCENDING NODE AND THE MEAN SUN, OFTEN EXPRESSED AS UNIT OF TIME (HH:MM)