

About ViaSat

ViaSat is in the business to connect the world. As a global broadband services and technology company, we are connecting international communities to the internet by offering residential internet service; enabling passengers and operations crews to stream high-bandwidth media, applications, and content when traveling globally on commercial, business or government aircraft and maritime vessels; and empowering international warfighters on the front lines of battle with real-time, secure internet-based intelligence, surveillance, and reconnaissance for high-requirement missions. We deliver and protect information – when and where it is needed most – with our trusted communications ground systems, infrastructure, and services.

Purpose

In addition to providing broadband internet service, ViaSat also design and manufactures a variety of antennas. The purpose of this request for an experimental license is to test the performance of antennas and ensure they meet the design specification.

Description of Experiment

The proposed testing facility consists of a reference RF signal source antenna (“Reference Signal Antenna”) that will be located at 3095 Satellite Boulevard, Building 800, Duluth Georgia (37°57’48” N, 84°6’51” W). The Reference Signal Antenna will be roof-mounted approximately 1.25 miles from the manufacturing site (33°57’47”N, 84°05’46”W), where the test antennas will be located. The Reference Signal Antenna will be directional and will be pointed approximately due east, at the manufacturing site. Due to the height of the roof mount and the ground profile, the elevation angle of the Reference Signal Antenna will be –1.2 degrees. The beamwidth of the Reference Signal Antenna at 26500 MHz is 9°.

The Reference Signal Antenna will consist of a pyramidal horn antenna manufactured by Scientific Atlanta, model 12A-26, fitted with an Agilent transmitter, model number N5183A or equivalent, which will generate a non-modulated continuous wave (“CW”) test signal at a frequency between 26500 – 27000 MHz and 37500 - 40500 MHz with emission designator N0N. The Reference Signal Antenna is intended to simulate a satellite, and thus, will transmit at the very low radio frequency levels that are normally received from a satellite: about 1.3 mW and , below the 1 mW/cm2 limit for persons in the General Population/Uncontrolled environment specified in Office of Engineering and Technology (“OET”) Bulletin No. 65.

In each test, the Reference Signal Antenna will transmit the CW test signal to the test antenna. Although the antennas being tested will have both transmit and receive capabilities, performance of transmit capabilities can adequately be tested by observing the receive performance in the transmit band because of the reciprocal nature of the performance in each of the transmit and receive bands. Therefore, ViaSat requests experimental license authority for only the Reference Signal Antenna.

The figure below shows the location of the transmitter and the receive test antenna located in Duluth, Georgia.



Interference to Other Services

Operation of the Reference Signal Antenna as proposed by this application is not likely to cause interference to any other licensed services or systems. As described above, the CW test signal will be emitted at extremely low power levels. Additionally, due to the narrow beam-width and the horizontal orientation of the CW test signal, the potential for interference is remote.

RF Radiation Compliance

The operation of these user terminals will be in full compliance with the Commission's radio frequency (RF) exposure guidelines, pursuant to Table 1 of Section 1.1307(b)(1) which states routine environment evaluation is not required for Experimental Radio Services if the power is less than 100 Watts ERP. The maximum power from the terminal will be 0.24 W ERP. Additionally, the terminal will be secured from access by the general public and will be operated by experienced test personnel.