

RF EXPOSURE EVALUATION

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency(RF) Radiation as specified in §1.1307(b)

FCC ID: 2A22Z-R811H

EUT Specification

EUT	Botslab Video Doorbell 2 Pro(Wi-Fi HomeBase)
Model Number	R811-H
Series Model	R812-H, R813-H, R811
Input Rating	AC100V~240V 0.3A MAX 50/60Hz
Frequency band (Operating)	<input checked="" type="checkbox"/> BT: 2.402GHz ~ 2.480GHz <input checked="" type="checkbox"/> WLAN: 2.412GHz ~ 2.462GHz <input checked="" type="checkbox"/> WLAN: 5.18GHz ~ 5.32GHz / 5.50GHz ~ 5.70GHz <input checked="" type="checkbox"/> WLAN: 5.745GHz ~ 5825GHz
Device category	<input type="checkbox"/> Portable (<20cm separation) <input checked="" type="checkbox"/> Mobile (>20cm separation)
Exposure classification	<input type="checkbox"/> Occupational/Controlled exposure (S = 5mW/cm ²) <input checked="" type="checkbox"/> General Population/Uncontrolled exposure (S=1mW/cm ²)
Antenna diversity	<input type="checkbox"/> Single antenna <input checked="" type="checkbox"/> Multiple antennas <input type="checkbox"/> Tx diversity <input type="checkbox"/> Rx diversity <input type="checkbox"/> Tx/Rx diversity
Max. output power (peak power)	BLE: 5.58 dBm IEEE 802.11b: 17.14 dBm IEEE 802.11g: 17.25 dBm IEEE 802.11n-HT20: 19.56 dBm IEEE 802.11n-HT40: 18.29 dBm 5180 MHz to 5240 MHz: 12.82 dBm 5260 MHz to 5320 MHz: 12.82 dBm 5500 MHz to 5700 MHz: 13.32 dBm 5745 MHz to 5825 MHz: 13.05 dBm
Antenna gain (Max)	BLE: -6.43 dBi 2.4GHz WIFI: ANT1: 2.29 dBi, ANT2: 2.17dBi 5.8G WIFI: 1.87 dBi
Evaluation applied	<input checked="" type="checkbox"/> MPE Evaluation <input type="checkbox"/> SAR Evaluation

Limits for Maximum Permissible Exposure(MPE)

Frequency Range(MHz)	Electric Field Strength(V/m)	Magnetic Field Strength(A/m)	Power Density(mW/cm ²)	Average Time
(A) Limits for Occupational/Control Exposures				
300-1500	--	--	F/300	6
1500-100000	--	--	5	6
(B) Limits for General Population/Uncontrol Exposures				
300-1500	--	--	F/1500	6
1500-100000	--	--	1	30

Friis transmission formula: $Pd=(Pout \cdot G) / (4 \cdot \pi \cdot R^2)$

Where

Pd = Power density in mW/cm², $Pout$ =output power to antenna in Mw

G = gain of antenna in linear scale, $Pi=3.1416$

R = distance between observation point and center of the radiator in cm=20cm

Pd the limit of MPE, 1mW/cm². If we know the maximum gain of the antenna and total power input to the antenna, through the calculation, we will know the distance where the MPE limit is reached.

Measurement Result

Operation Mode	Channel Frequency (MHz)	Max Measured Power (dBm)	Tune up tolerance (dBm)	Max tune up conducted power (dBm)	Output Peak power (mW)	Ant. Gain (dBi)	Ant. Gain (numeric)	Power density at 20cm (mW/cm ²)	Power density Limits (mW/cm ²)
BLE (2Mbps)	2402	5.58	6±1	7	5.012	-6.43	0.228	0.000227	1
2.4GHz WIFI (802.11n-HT20)	2462	19.56	20±1	21	125.893	2.29	1.694	0.042435	1
5.8GHz WIFI (802.11ac-HT20)	5700	13.32	13±1	14	25.119	1.87	1.538	0.007686	1

The Product unsupported at the same time to Transmitting. According to KDB

447498, and no simultaneous SAR measurement is required.

Signature:

