

COLOUR TABLE	
CODE	PANTONE NO.
A	PROCESS BLACK C
B	PER MAT'L (WHITE)
C	PANTONE 654 C

Artwork (Paths)

42.00 mm

54.30 mm

FGA #: 808-0889

Model: Xantrex BLE Module

This Class B digital device complies with Part 15B of the FCC and ICES Rules. Operation is subject to the following two conditions: (1) This device may not cause harmful interference. (2) This device must accept any interference received, including interference that may cause undesired operation.

CAN ICES-3(B) / NMB-3(B)
FCC ID: 2A258-XBLEM-BT
IC: 23407-XBLEMBT

For indoor use only. Not intended for areas requiring ignition protection.

www.xantrex.com
Designed in Canada, Assembled in China

xantrex

A MISSION CRITICAL ELECTRONICS BRAND

Status

Xantrex BLE Module

FGA #: 808-0889

Model: Xantrex BLE Module

This Class B digital device complies with Part 15B of the FCC and ICES Rules. Operation is subject to the following two conditions: (1) This device may not cause harmful interference. (2) This device must accept any interference received, including interference that may cause undesired operation.

CAN ICES-3(B) / NMB-3(B)
FCC ID: 2A258-XBLEM-BT
IC: 23407-XBLEMBT

For indoor use only. Not intended for areas requiring ignition protection.

www.xantrex.com
Designed in Canada, Assembled in China

xantrex

A MISSION CRITICAL ELECTRONICS BRAND

Status

Xantrex BLE Module

CONFIDENTIAL INFORMATION OF XANTREX LLC

© COPYRIGHT 2021 XANTREX LLC. ALL RIGHTS RESERVED. ALL TRADEMARKS ARE OWNED BY XANTREX LLC OR ITS AFFILIATED COMPANIES AND SHALL NOT BE USED OR REPRODUCED IN ANY FORM OR FOR ANY PURPOSE WHATSOEVER, WITHOUT THE EXPRESS WRITTEN PERMISSION OF XANTREX LLC.

TOLERANCES:
(UNLESS OTHERWISE SHOWN)

X
+/- 1

X.X
+/- 0.5

ANGLES
+/- 1°

TITLE:
LABEL TOP USER INTERFACE DISPLAY XANTREX BT MODULE

DIMENSIONS ARE IN MILLIMETERS UNLESS OTHERWISE SHOWN

AUT David Miller

DES David Miller

2021-03-24

2021-03-24

SIZE
C

SCALE: 1:1

DWG No.
270-5013-01-01

REV
B

SHT
1 of 1

NOTES:

1. ALL UNTOLERANCED DIMENSIONS ARE BASIC.

2. LABEL AND ADHESIVE SYSTEM MUST BE APPROVED FOR APPLICATION TO CLEAN, TEXTURED PLASTIC INJECTION MOLDED SURFACE FOR INDOOR AND OUTDOOR USE IN THE RANGE OF -25 TO 50 DEG C.

BOTH LABEL AND PRINTING PROCESS SHALL BE CERTIFIED TO:

- CSA STANDARD C22.2 NO. 0.15 - ADHESIVE LABELS (TYPE A MINIMUM, TYPE B IS ACCEPTABLE) AND/OR

- UL969 IN THE RANGE -25 TO 65°C.

3. BASE MATERIAL: 0.20MM POLYESTER (PET), AUTOTEX V200 VELVET MATTE FINISH OR EQUIVALENT. WINDOW HAS NO TEXTURE.

4. ADHESIVE BACKING: 3M 9495 MP OR 3M 468 OR EQUIVALENT.

5. COLOUR: SEE COLOUR CHART FOR DETAILS

8. FINISHED PART MUST BE ROHS COMPLIANT PER 2011/65/EU AND ALL AMENDEMENTS. IF THERE IS A CONFLICT BETWEEN THE SPECIFICATIONS AND ROHS COMPLIANCE THE VENDOR MUST CONTACT XANTREX FOR CLARIFICATION.

9. FIRST OFF LABEL SAMPLE MUST BE SUBMITTED FOR APPROVAL TO XANTREX.

10. ALL ARTWORK HAS BEEN CONVERTED TO PATHS (OUTLINES).

REV

CHANGES

AUT

DATE

CHK'D

TC

REG

BC

A

ECO #### - INITIAL RELEASE

Luke R

2021-08-19

David M

Harry X

Dean J

Josephine T

B

ECO #### - UPADTED FCC ID, ADDED CE, LOGO

Luke R

2021-09-24

David M

Harry X

Dean J

Josephine T