



RF EXPOSURE Test Report

Report No.: MTI230629016-11E4

Date of issue: 2023-08-25

Applicant: DONGGUAN CITY SITENG ELECTRONICS CO., LTD

Product: Photo Printer

Model(s): DHP511, DHP512, DHP513, DHP514, DHP515, DHP516,
DHP517, DHP518, DHP519, DHP520

FCC ID: 2A288-DHP511

Shenzhen Microtest Co., Ltd.

<http://www.mtitest.com>

Instructions

1. The report shall not be partially reproduced without the written consent of the laboratory;
2. The test results of this report are only responsible for the samples submitted;
3. This report is invalid without the seal and signature of the laboratory;
4. This report is invalid if transferred, altered or tampered with in any form without authorization;
5. Any objection to this report shall be submitted to the laboratory within 15 days from the date of receipt of the report.



Test Result Certification	
Applicant:	DONGGUAN CITY SITENG ELECTRONICS CO., LTD
Address:	Block A, Jingbo Industrial Park, Buxin Industrial Area, Yan Tian Village, Fenggang Town, Dongguan, Guangdong, China
Manufacturer:	SITENG ELECTRONICS CO.,LTD
Address:	A Building,jingbo Industrial Park,Zhentian West Roat,Buxin Industrial zone,YanTian Village,Fenggang Town,Dongguan City,Guangdong Province,China
Product description	
Product name:	Photo Printer
Trademark:	N/A
Model name:	DHP511
Serial Model:	DHP512, DHP513, DHP514, DHP515, DHP516, DHP517, DHP518, DHP519, DHP520
Standards:	N/A
Test procedure:	KDB 447498 D01 v06
Date of Test	
Date of test:	2023-06-10 to 2023-08-10
Test result:	Pass

Test Engineer :

Maleah Deng

(Maleah Deng)

Reviewed By: :

Leon Chen

(Leon Chen)

Approved By: :

Tom Xue

(Tom Xue)

RF EXPOSURE EVALUATION

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) Radiation as specified in §1.1307(b)

Limits for Maximum Permissible Exposure (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(A) Limits for Occupational/Controlled Exposure				
0.3-3.0	614	1.63	*100	6
3.0-30	1842/f	4.89/f	*900/f ²	6
30-300	61.4	0.163	1.0	6
300-1,500			f/300	6
1,500-100,000			5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3-1.34	614	1.63	*100	30
1.34-30	824/f	2.19/f	*180/f ²	30
30-300	27.5	0.073	0.2	30
300-1,500			f/1500	30
1,500-100,000			1.0	30

f = frequency in MHz * = Plane-wave equivalent power density

MPE Calculation Method

Friis transmission formula: $P_d = (P_{out} \cdot G) / (4 \cdot \pi \cdot R^2)$

Where

P_d = Power density in mW/cm²

P_{out} = output power to antenna in mW

G = Numeric gain of the antenna relative to isotropic antenna

π = 3.1415926

R = distance between observation point and center of the radiator in cm (20cm)

P_d the limit of MPE, 1mW/cm². If we know the maximum gain of the antenna and total power input to the antenna, through the calculation, we will know the distance where the MPE limit is reached.

Measurement Result

BT/BLE:

Operation Frequency: 2402-2480MHz,

Power density limited: 1mW/ cm²

2.4GWiFi:

Operation Frequency: WIFI 802.11b/g/n HT20: 2412-2462MHz, WIFI 802.11n HT40: 2422-2450MHz;

Power density limited: 1mW/ cm²

Antenna Type: PCB Antenna (Bluetooth & 2.4G WIFI)

Antenna gain: -7.13 dBi(Bluetooth & 2.4G WIFI)

R=20cm

$mW=10^{(dBm/10)}$

antenna gain Numeric= $10^{(dBi/10)}=10^{(-7.13/10)}=0.19$

BR+EDR:

Channel Freq. (MHz)	modulation	conducted power (dBm)	Tune-up power (dBm)	Max		Antenna		Evaluation result (mW/cm ²)	Power density Limits (mW/cm ²)
				tune-up power		Gain			
				(dBm)	(mW)	(dBi)	Numeric		
2402	GFSK	4.98	5±1	6	3.981	-7.13	0.19	0.0002	1
2441		4.45	4±1	5	3.162	-7.13	0.19	0.0001	1
2480		4.26	4±1	5	3.162	-7.13	0.19	0.0001	1
2402	π/4-DQPSK	5.64	5±1	6	3.981	-7.13	0.19	0.0002	1
2441		4.62	4±1	5	3.162	-7.13	0.19	0.0001	1
2480		4.62	4±1	5	3.162	-7.13	0.19	0.0001	1
2402	8DPSK	5.96	6±1	7	5.012	-7.13	0.19	0.0002	1
2441		4.95	5±1	6	3.981	-7.13	0.19	0.0002	1
2480		4.98	5±1	6	3.981	-7.13	0.19	0.0002	1

BLE:

Channel Freq. (MHz)	modulation	conducted power (dBm)	Tune-up power (dBm)	Max		Antenna		Evaluation result (mW/cm ²)	Power density Limits (mW/cm ²)
				tune-up power		Gain			
				(dBm)	(mW)	(dBi)	Numeric		
2402	BLE-1M	2.47	2±1	3	1.995	-7.13	0.19	0.0001	1
2440		1.79	1±1	2	1.585	-7.13	0.19	0.0001	1
2480		1.54	1±1	2	1.585	-7.13	0.19	0.0001	1

2.4GWiFi:

Channel Freq. (MHz)	modulation	conducted power (dBm)	Tune-up power (dBm)	Max		Antenna Gain	Evaluation result at 20cm	Power density Limits (mW/cm ²)
				tune-up power				
				(dBm)	(dBm)	(dBm)	(mW)	Numeric
2412	802.11b	16.28	16±1	17	50.119	0.19	0.00193	1
2437		15.80	15±1	16	39.811	0.19	0.00153	1
2462		16.08	16±1	17	50.119	0.19	0.00193	1
2412	802.11g	21.79	21±1	22	158.489	0.19	0.00611	1
2437		20.86	20±1	21	125.893	0.19	0.00485	1
2462		21.29	21±1	22	158.489	0.19	0.00611	1
2412	802.11n H20	20.05	20±1	21	125.893	0.19	0.00485	1
2437		19.26	19±1	20	100.000	0.19	0.00385	1
2462		19.62	19±1	20	100.000	0.19	0.00385	1
2422	802.11n H40	20.02	20±1	21	125.893	0.19	0.00485	1
2437		19.75	19±1	20	100.000	0.19	0.00385	1
2452		19.31	19±1	20	100.000	0.19	0.00385	1

Conclusion:

The device can transmitter simultaneously.

BR&EDR+2.4G WIFI =0.0002+0.00611=0.00631

BLE+2.4G WIFI=0.0001+0.00611=0.00621

For the max result: $0.00631 \leq 1.0$ SAR, No SAR is required.

----END OF REPORT----