





CSE Plot on Ch 78 between 30MHz ~ 3 GHz



Date: 24.APR.2023 17:18:35

CSE Plot on Ch 78 between 2 GHz ~ 25 GHz



Date: 24.APR.2023 17:19:07



3.8 Radiated Band Edges and Spurious Emission Measurement

3.8.1 Limit of Radiated Band Edges and Spurious Emission

In any 100 kHz bandwidth outside the intentional radiator frequency band, all harmonics/spurious must be at least 20 dB below the highest emission level within the authorized band. In addition, radiated emissions which fall in the restricted bands must also comply with the limits as below.

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 – 0.490	2400/F(kHz)	300
0.490 – 1.705	24000/F(kHz)	30
1.705 – 30.0	30	30
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3

3.8.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.




3.8.3 Test Procedures

1. The EUT was placed on a turntable with 0.8 meter for frequency below 1GHz and 1.5 meter for frequency above 1GHz respectively above ground.
2. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
3. For each suspected emission, the EUT was arranged to its worst case and then tune the Antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level to comply with the guidelines.
4. Set to the maximum power setting and enable the EUT transmit continuously.
5. Use the following spectrum analyzer settings:
 - (1) Span shall wide enough to fully capture the emission being measured;
 - (2) Set RBW=100 kHz for $f < 1 \text{ GHz}$, RBW=1MHz for $f > 1\text{GHz}$; VBW \geq RBW; Sweep = auto; Detector function = peak; Trace = max hold for peak
 - (3) For average measurement: use duty cycle correction factor method per 15.35(c).
Duty cycle = On time/100 milliseconds
On time = $N_1 * L_1 + N_2 * L_2 + \dots + N_{n-1} * L_{n-1} + N_n * L_n$
Where N_1 is number of type 1 pulses, L_1 is length of type 1 pulses, etc.
Average Emission Level = Peak Emission Level + $20 * \log(\text{Duty cycle})$
6. Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level
7. For testing below 1GHz, if the emission level of the EUT in peak mode was 3 dB lower than the limit specified, then peak values of EUT will be reported, otherwise, the emissions will be repeated one by one using the CISPR quasi-peak method and reported.
8. For testing above 1GHz, the emission level of the EUT in peak mode was 20dB lower than peak limit (that means the emission level in average mode also complies with the limit in average mode), then peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.

Note: The average levels were calculated from the peak level corrected with duty cycle correction factor (-24.79dB) derived from $20 \log(\text{dwell time}/100\text{ms})$. This correction is only for signals that hop with the fundamental signal, such as band-edge and harmonic. Other spurious signals that are independent of the hopping signal would not use this correction.

3.8.4 Test Setup


For radiated emissions below 30MHz



For radiated emissions from 30MHz to 1GHz



For radiated emissions above 1GHz





3.8.5 Test Results of Radiated Spurious Emissions (9 kHz ~ 30 MHz)

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line was not reported.

There is a comparison data of both open-field test site and semi-Anechoic chamber, and the result came out very similar.

3.8.6 Test Result of Radiated Spurious at Band Edges

Please refer to Appendix C.

3.8.7 Test Result of Radiated Spurious Emission (30MHz ~ 10th Harmonic or 40GHz, whichever is lower)

Please refer to Appendix C.

3.8.8 Duty cycle correction factor for average measurement

Please refer to Appendix D.



3.9 AC Conducted Emission Measurement

3.9.1 Limit of AC Conducted Emission

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

Frequency of emission (MHz)	Conducted limit (dBµV)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency.

3.9.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.9.3 Test Procedures

1. The EUT was placed 0.4 meter from the conducting wall of the shielding room was kept at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connecting to the other LISN.
4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
5. The FCC states that a 50 ohm, 50 microhenry LISN should be used.
6. Both sides of AC line were checked for maximum conducted interference.
7. The frequency range from 150 kHz to 30 MHz was searched.
8. Set the test-receiver system to Peak Detect Function and specified bandwidth (IF Bandwidth = 9kHz) with Maximum Hold Mode. Then measurement is also conducted by Average Detector and Quasi-Peak Detector Function respectively.

3.9.4 Test Setup



3.9.5 Test Result of AC Conducted Emission

Please refer to Appendix B.



3.10 Antenna Requirements

3.10.1 Standard Applicable

If directional gain of transmitting antennas is greater than 6dBi, the power shall be reduced by the same level in dB comparing to gain minus 6dBi. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the rule.

3.10.2 Antenna Anti-Replacement Construction

An embedded-in antenna design is used.

3.10.3 Antenna Gain

The antenna peak gain of EUT is less than 6 dBi. Therefore, it is not necessary to reduce maximum peak output power limit.



4 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Spectrum Analyzer	R&S	FSV40	101078	10Hz~40GHz	Apr. 06, 2023	Apr. 23, 2023~ Apr. 24, 2023	Apr. 05, 2024	Conducted (TH01-SZ)
Pulse Power Sensor	Anritsu	MA2411B	1339473	30MHz~40GHz	Dec. 27, 2022	Apr. 23, 2023~ Apr. 24, 2023	Dec. 26, 2023	Conducted (TH01-SZ)
Power Meter	Anritsu	ML2495A	1542004	50MHz Bandwidth	Dec. 27, 2022	Apr. 23, 2023~ Apr. 24, 2023	Dec. 26, 2023	Conducted (TH01-SZ)
EMI Receiver	R&S	ESR7	101630	9kHz~7GHz;	Jul. 07, 2022	May 16, 2023	Jul. 06, 2023	Conduction (CO01-SZ)
AC LISN	R&S	ENV216	100063	9kHz~30MHz	Sep. 15, 2022	May 16, 2023	Sep. 14, 2023	Conduction (CO01-SZ)
AC LISN (for auxiliary equipment)	EMCO	3816/2SH	00103892	9kHz~30MHz	Oct. 17, 2022	May 16, 2023	Oct. 16, 2023	Conduction (CO01-SZ)
AC Power Source	Chroma	61602	616020000891	100Vac~250Vac	Jul. 07, 2022	May 16, 2023	Jul. 06, 2023	Conduction (CO01-SZ)
EMI Test Receiver&SA	Agilent	N9038A	MY52260185	20Hz~26.5GHz	Dec. 26, 2022	May 22, 2023~ Jun. 28, 2023	Dec. 25, 2023	Radiation (03CH01-SZ)
EXA Spectrum Analyzer	KEYSIGHT	N9010A	MY55150213	10Hz~44GHz	Jul. 07, 2022	May 22, 2023~ Jun. 28, 2023	Jul. 06, 2023	Radiation (03CH01-SZ)
Loop Antenna	R&S	HFH2-Z2	100354	9kHz~30MHz	Jul. 28, 2022	May 22, 2023~ Jun. 28, 2023	Jun. 27, 2024	Radiation (03CH01-SZ)
Bilog Antenna	TeseQ	CBL6112D	35407	30MHz~2GHz	Sep. 28, 2021	May 22, 2023~ Jun. 28, 2023	Sep. 27, 2023	Radiation (03CH01-SZ)
Double Ridge Horn Antenna	ETS-Lindgren	3117	00119436	1GHz~18GHz	Jul. 07, 2022	May 22, 2023~ Jun. 28, 2023	Jul. 06, 2023	Radiation (03CH01-SZ)
SHF-EHF Horn	com-power	AH-840	101071	18GHz~40GHz	Apr. 08, 2023	May 22, 2023~ Jun. 28, 2023	Apr. 07, 2024	Radiation (03CH01-SZ)
LF Amplifier	Burgeon	BPA-530	102209	0.01~3000Mhz	Apr. 04, 2023	May 22, 2023~ Jun. 28, 2023	Apr. 03, 2024	Radiation (03CH01-SZ)
HF Amplifier	MITEQ	AMF-7D-0010 1800-30-10P-R	1943528	1GHz~18GHz	Oct. 19, 2022	May 22, 2023~ Jun. 28, 2023	Oct. 18, 2023	Radiation (03CH01-SZ)
HF Amplifier	KEYSIGHT	83017A	MY53270105	0.5GHz~26.5GHz	Oct. 19, 2022	May 22, 2023~ Jun. 28, 2023	Oct. 18, 2023	Radiation (03CH01-SZ)
HF Amplifier	MITEQ	TTA1840-35-HG	1871923	18GHz~40GHz	Jul. 06, 2022	May 22, 2023~ Jun. 28, 2023	Jul. 05, 2023	Radiation (03CH01-SZ)
AC Power Source	Chroma	61601	616010001985	N/A	Nov. 10, 2022	May 22, 2023~ Jun. 28, 2023	Nov. 09, 2023	Radiation (03CH01-SZ)
Turn Table	EM	EM1000	N/A	0~360 degree	NCR	May 22, 2023~ Jun. 28, 2023	NCR	Radiation (03CH01-SZ)
Antenna Mast	EM	EM1000	N/A	1 m~4 m	NCR	May 22, 2023~ Jun. 28, 2023	NCR	Radiation (03CH01-SZ)

NCR: No Calibration Required



5 Measurement Uncertainty

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI 63.10-2013. All the measurement uncertainty value were shown with a coverage K=2 to indicate 95% level of confidence. The measurement data show herein meets or exceeds the CISPR measurement uncertainty values specified in CISPR 16-4-2 and can be compared directly to specified limit to determine compliance.

Uncertainty of Conducted Measurement

Test Item	Uncertainty
Conducted Power	±1.34 dB
Conducted Emissions	±1.34 dB
Occupied Channel Bandwidth	±0.012 %

Uncertainty of Conducted Emission Measurement (150 kHz ~ 30 MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	2.7 dB
---	--------

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	4.2 dB
---	--------

Uncertainty of Radiated Emission Measurement (1000 MHz ~ 18000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	5.0 dB
---	--------

Uncertainty of Radiated Emission Measurement (18000 MHz ~ 40000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	4.3 dB
---	--------

----- THE END -----



Appendix A. Conducted Test Results

Appendix A. Test Result of Conducted Test Items

Test Engineer:	Guohng Zhang	Temperature:	21~25	°C
Test Date:	2023/4/23~2023/4/24	Relative Humidity:	51~54	%

TEST RESULTS DATA***20dB and 99% Occupied Bandwidth and Hopping Channel Separation***

Mod.	Data Rate	NTX	CH.	Freq. (MHz)	20db BW (MHz)	99% Bandwidth (MHz)	Hopping Channel Separation Measurement (MHz)	Hopping Channel Separation Measurement Limit (MHz)	Pass/Fail
DH	1Mbps	1	0	2402	1.036	0.906	0.999	0.6908	Pass
DH	1Mbps	1	39	2441	1.030	0.906	1.003	0.6869	Pass
DH	1Mbps	1	78	2480	1.039	0.906	0.999	0.6927	Pass
2DH	2Mbps	1	0	2402	1.276	1.164	0.999	0.8509	Pass
2DH	2Mbps	1	39	2441	1.285	1.169	0.994	0.8567	Pass
2DH	2Mbps	1	78	2480	1.285	1.166	0.999	0.8567	Pass
3DH	3Mbps	1	0	2402	1.276	1.164	0.999	0.8509	Pass
3DH	3Mbps	1	39	2441	1.285	1.169	1.003	0.8567	Pass
3DH	3Mbps	1	78	2480	1.276	1.166	1.003	0.8509	Pass

TEST RESULTS DATA***Dwell Time***

Mod.	Hopping Channel Number Rate	Hops Over Occupancy Time(hops)	Package Transfer Time (msec)	Dwell Time (sec)	Limits (sec)	Pass/Fail
Nomal	79	106.67	2.89	0.31	0.4	Pass
AFH	20	53.33	2.89	0.15	0.4	Pass

TEST RESULTS DATA***Peak Power Table***

DH	CH.	NTX	Peak Power (dBm)	Power Limit (dBm)	Test Result
DH5	0	1	7.60	20.97	Pass
	39	1	7.60	20.97	Pass
	78	1	7.40	20.97	Pass
2DH5	0	1	6.80	20.97	Pass
	39	1	6.80	20.97	Pass
	78	1	6.40	20.97	Pass
3DH5	0	1	6.80	20.97	Pass
	39	1	6.80	20.97	Pass
	78	1	6.60	20.97	Pass

TEST RESULTS DATA***Average Power Table
(Reporting Only)***

DH	CH.	NTX	Average Power (dBm)	Duty Factor (dB)
DH5	0	1	7.20	1.14
	39	1	7.20	1.14
	78	1	7.10	1.14
2DH5	0	1	4.60	1.14
	39	1	4.60	1.14
	78	1	4.50	1.14
3DH5	0	1	4.60	1.14
	39	1	4.60	1.14
	78	1	4.40	1.14


TEST RESULTS DATA***Number of Hopping Frequency***

Number of Hopping (Channel)	Adaptive Frequency Hopping (Channel)	Limits (Channel)	Pass/Fail
79	20	> 15	Pass




Appendix B. AC Conducted Emission Test Results

Test Engineer :	Lily Qiu	Temperature :	22~24°C
		Relative Humidity :	44~50%
Test Voltage :	120Vac / 60Hz	Phase :	Line
Remark :	All emissions not reported here are more than 10 dB below the prescribed limit.		



Site : CO01-SZ
 Condition: FCC 15C_QP LISN_20230420_L LINE
 Project : 340708
 Mode : Mode 1
 IMEI : 358957940006314

	Freq	Level	Over Limit	Limit Line	Read Level	LISN Factor	Cable Loss	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	dB	
1	0.15	38.60	-17.31	55.91	18.00	10.47	10.13	Average
2	0.15	50.70	-15.21	65.91	30.10	10.47	10.13	QP
3	0.23	34.84	-17.73	52.57	14.30	10.39	10.15	Average
4	0.23	46.14	-16.43	62.57	25.60	10.39	10.15	QP
5	0.30	30.92	-19.23	50.15	10.41	10.36	10.15	Average
6	0.30	42.02	-18.13	60.15	21.51	10.36	10.15	QP
7	0.38	35.35	-12.95	48.30	14.90	10.29	10.16	Average
8	0.38	45.45	-12.85	58.30	25.00	10.29	10.16	QP
9	0.45	36.23	-10.62	46.85	15.80	10.27	10.16	Average
10	0.45	43.93	-12.92	56.85	23.50	10.27	10.16	QP
11	0.53	33.32	-12.68	46.00	12.90	10.26	10.16	Average
12	0.53	40.22	-15.78	56.00	19.80	10.26	10.16	QP
13	0.61	33.83	-12.17	46.00	13.40	10.27	10.16	Average
14	0.61	43.03	-12.97	56.00	22.60	10.27	10.16	QP
15	0.68	35.91	-10.09	46.00	15.50	10.25	10.16	Average
16	0.68	43.41	-12.59	56.00	23.00	10.25	10.16	QP
17	0.75	35.41	-10.59	46.00	15.00	10.25	10.16	Average
18	0.75	42.81	-13.19	56.00	22.40	10.25	10.16	QP
19	0.83	36.00	-10.00	46.00	15.60	10.24	10.16	Average
20	0.83	43.50	-12.50	56.00	23.10	10.24	10.16	QP
21	0.91	34.59	-11.41	46.00	14.20	10.23	10.16	Average
22	0.91	42.99	-13.01	56.00	22.60	10.23	10.16	QP
23	0.98	37.80	-8.20	46.00	17.40	10.24	10.16	Average




Site : CO01-SZ
 Condition: FCC 15C_QP LISN_20230420_L LINE
 Project : 340708
 Mode : Mode 1
 IMEI : 358957940006314

	Freq	Level	Over Limit	Limit Line	Read Level	LISN Factor	Cable Loss	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	dB	
24	0.98	44.30	-11.70	56.00	23.90	10.24	10.16	QP
25	1.14	38.11	-7.89	46.00	17.71	10.23	10.17	Average
26	1.14	45.01	-10.99	56.00	24.61	10.23	10.17	QP
27	1.44	35.39	-10.61	46.00	15.00	10.19	10.20	Average
28	1.44	44.19	-11.81	56.00	23.80	10.19	10.20	QP
29 *	2.35	40.74	-5.26	46.00	20.40	10.09	10.25	Average
30	2.35	48.94	-7.06	56.00	28.60	10.09	10.25	QP
31	2.79	39.75	-6.25	46.00	19.41	10.07	10.27	Average
32	2.79	48.45	-7.55	56.00	28.11	10.07	10.27	QP
33	3.49	34.18	-11.82	46.00	13.81	10.07	10.30	Average
34	3.49	45.78	-10.22	56.00	25.41	10.07	10.30	QP
35	5.30	33.40	-16.60	50.00	13.00	10.05	10.35	Average
36	5.30	43.90	-16.10	60.00	23.50	10.05	10.35	QP
37	6.15	30.10	-19.90	50.00	9.70	10.04	10.36	Average
38	6.15	45.00	-15.00	60.00	24.60	10.04	10.36	QP
39	12.00	38.70	-11.30	50.00	18.40	9.87	10.43	Average
40	12.00	49.70	-10.30	60.00	29.40	9.87	10.43	QP
41	19.95	34.97	-15.03	50.00	14.50	9.91	10.56	Average
42	19.95	43.67	-16.33	60.00	23.20	9.91	10.56	QP




Test Engineer :	Lily Qiu	Temperature :	22~24°C
		Relative Humidity :	44~50%
Test Voltage :	120Vac / 60Hz	Phase :	Neutral
Remark :	All emissions not reported here are more than 10 dB below the prescribed limit.		



Site : CO01-SZ
 Condition: FCC 15C_QP LISN_20230420_N NEUTRAL
 Project : 340708
 Mode : Mode 1
 IMEI : 358957940006314

	Freq	Level	Over	Limit	Read	LISN	Cable	
	MHz	dBuV	Limit	Line	Level	Factor	Loss	Remark
			dB	dBuV	dBuV	dB	dB	
1	0.15	36.19	-19.68	55.87	15.60	10.46	10.13	Average
2	0.15	47.99	-17.88	65.87	27.40	10.46	10.13	QP
3	0.23	32.08	-20.40	52.48	11.60	10.33	10.15	Average
4	0.23	43.08	-19.40	62.48	22.60	10.33	10.15	QP
5	0.30	30.56	-19.68	50.24	10.10	10.31	10.15	Average
6	0.30	40.46	-19.78	60.24	20.00	10.31	10.15	QP
7	0.38	37.21	-11.09	48.30	16.80	10.25	10.16	Average
8	0.38	42.41	-15.89	58.30	22.00	10.25	10.16	QP
9	0.46	34.09	-12.67	46.76	13.70	10.23	10.16	Average
10	0.46	42.99	-13.77	56.76	22.60	10.23	10.16	QP
11	0.53	34.98	-11.02	46.00	14.60	10.22	10.16	Average
12	0.53	40.88	-15.12	56.00	20.50	10.22	10.16	QP
13	0.61	36.89	-9.11	46.00	16.50	10.23	10.16	Average
14	0.61	41.49	-14.51	56.00	21.10	10.23	10.16	QP
15	0.68	35.13	-10.87	46.00	14.70	10.27	10.16	Average
16	0.68	44.63	-11.37	56.00	24.20	10.27	10.16	QP
17	0.76	33.11	-12.89	46.00	12.70	10.25	10.16	Average
18	0.76	43.31	-12.69	56.00	22.90	10.25	10.16	QP
19	0.83	36.59	-9.41	46.00	16.20	10.23	10.16	Average
20	0.83	44.39	-11.61	56.00	24.00	10.23	10.16	QP
21	0.91	37.28	-8.72	46.00	16.90	10.22	10.16	Average
22	0.91	45.38	-10.62	56.00	25.00	10.22	10.16	QP
23	0.99	36.10	-9.90	46.00	15.70	10.24	10.16	Average



Site : CO01-SZ
 Condition: FCC 15C_QP LISN_20230420_N NEUTRAL
 Project : 340708
 Mode : Mode 1
 IMEI : 358957940006314

	Freq	Level	Over	Limit	Read	LISN	Cable	
	MHz	dBuV	Limit	Line	Level	Factor	Loss	Remark
			dB	dBuV	dBuV	dB	dB	
24	0.99	46.30	-9.70	56.00	25.90	10.24	10.16	QP
25	1.06	36.82	-9.18	46.00	16.40	10.25	10.17	Average
26	1.06	44.62	-11.38	56.00	24.20	10.25	10.17	QP
27	1.14	34.44	-11.56	46.00	14.00	10.27	10.17	Average
28	1.14	45.04	-10.96	56.00	24.60	10.27	10.17	QP
29	1.22	34.76	-11.24	46.00	14.30	10.28	10.18	Average
30	1.22	46.06	-9.94	56.00	25.60	10.28	10.18	QP
31	1.44	39.06	-6.94	46.00	18.60	10.26	10.20	Average
32	1.44	48.36	-7.64	56.00	27.90	10.26	10.20	QP
33	2.05	33.34	-12.66	46.00	12.91	10.20	10.23	Average
34	2.05	45.34	-10.66	56.00	24.91	10.20	10.23	QP
35	2.81	40.03	-5.97	46.00	19.61	10.15	10.27	Average
36 *	2.81	51.93	-4.07	56.00	31.51	10.15	10.27	QP
37	3.64	41.46	-4.54	46.00	21.00	10.15	10.31	Average
38	3.64	51.26	-4.74	56.00	30.80	10.15	10.31	QP
39	4.48	38.57	-7.43	46.00	18.10	10.13	10.34	Average
40	4.48	51.07	-4.93	56.00	30.60	10.13	10.34	QP
41	7.29	31.91	-18.09	50.00	11.49	10.05	10.37	Average
42	7.29	43.91	-16.09	60.00	23.49	10.05	10.37	QP
43	9.71	37.01	-12.99	50.00	16.60	10.03	10.38	Average
44	9.71	46.01	-13.99	60.00	25.60	10.03	10.38	QP
45	11.93	38.69	-11.31	50.00	18.30	9.96	10.43	Average
46	11.93	48.29	-11.71	60.00	27.90	9.96	10.43	QP
47	20.06	31.32	-18.68	50.00	11.00	9.76	10.56	Average
48	20.06	42.22	-17.78	60.00	21.90	9.76	10.56	QP

Note:

1. Level(dBμV) = Read Level(dBμV) + LISN Factor(dB) + Cable Loss(dB)
2. Over Limit(dB) = Level(dBμV) – Limit Line(dBμV)



Appendix C Radiated Spurious Emission Test Data

Test Engineer :	Zhicheng Li	Relative Humidity :	48~49%
		Temperature :	24~25°C

Radiated Spurious Emission Test Modes

Mode	Band (MHz)	Modulation	Channel	Frequency	Data Rate	Remark
Mode 1	2400-2483.5	Bluetooth BR_GFSK	00	2402	1DH5	-
Mode 2	2400-2483.5	Bluetooth BR_GFSK	39	2441	1DH5	-
Mode 3	2400-2483.5	Bluetooth BR_GFSK	78	2480	1DH5	-
Mode 4	2400-2483.5	Bluetooth BR_GFSK	78	2480	1DH5	LF

Summary of each worse mode

Mode	Modulation	Ch.	Freq. (MHz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Pol.	Peak Avg.	Result	Remark
1	Bluetooth BR_GFSK	00	2336.04	50.49	74.00	-23.51	H	PEAK	Pass	Band Edge
1	Bluetooth BR_GFSK	00	4804.00	46.53	74.00	-27.47	V	Peak	Pass	Harmonic
2	Bluetooth BR_GFSK	39	-	-	-	-	-	-	-	Band Edge
2	Bluetooth BR_GFSK	39	7323.00	47.94	74.00	-26.06	H	Peak	Pass	Harmonic
3	Bluetooth BR_GFSK	78	2483.89	52.71	74.00	-21.29	H	PEAK	Pass	Band Edge
3	Bluetooth BR_GFSK	78	7440.00	50.13	74.00	-23.87	V	Peak	Pass	Harmonic
4	Bluetooth BR_GFSK	78	491.72	41.91	46	-4.09	V	Peak	Pass	LF







Mode	1																																																																																																					
	Band Edge																																																																																																					
	2400-2483.5_Bluetooth BR_GFSK_CH00_2402MHz																																																																																																					
Pol.	Horizontal	Fundamental																																																																																																				
Peak	<p>Date: 2023-05-12</p> <p>Site : 03CH01-SZ Condition: PEAK_BE_74 3m HF_ANT(3117)_22 HORIZONTAL Mode : 1 Setting : 1DH5 Plane : X with Accessories : 358957940004483</p> <table border="1"> <thead> <tr> <th>Limit</th> <th>Read</th> <th>Ant</th> <th>Cable</th> <th>Preamp</th> <th>APos</th> <th>TPos</th> <th>Remark</th> </tr> <tr> <th>Freq</th> <th>Level</th> <th>Line</th> <th>Margin</th> <th>Level</th> <th>Factor</th> <th>Loss Factor</th> <th></th> </tr> <tr> <th>MHz</th> <th>dBuV/m</th> <th>dBuV/m</th> <th></th> <th>dBuV</th> <th>dB/m</th> <th>dB</th> <th>dB</th> <th>cm</th> <th>deg</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>2336.04</td> <td>50.49</td> <td>74.00</td> <td>-23.51</td> <td>42.81</td> <td>32.14</td> <td>7.61</td> <td>32.07</td> <td>361</td> <td>322</td> <td>PEAK</td> </tr> <tr> <td>2</td> <td>2336.04</td> <td>25.70</td> <td>54.00</td> <td>-28.30</td> <td>18.02</td> <td>32.14</td> <td>7.61</td> <td>32.07</td> <td>361</td> <td>322</td> <td>AVERAGE</td> </tr> </tbody> </table>	Limit	Read	Ant	Cable	Preamp	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss Factor		MHz	dBuV/m	dBuV/m		dBuV	dB/m	dB	dB	cm	deg	1	2336.04	50.49	74.00	-23.51	42.81	32.14	7.61	32.07	361	322	PEAK	2	2336.04	25.70	54.00	-28.30	18.02	32.14	7.61	32.07	361	322	AVERAGE	<p>Date: 2023-05-12</p> <p>Site : 03CH01-SZ Condition: PEAK_74 3m HF_ANT(3117)_22 HORIZONTAL Mode : 1 Setting : 1DH5 Plane : X with Accessories : 358957940004483</p> <table border="1"> <thead> <tr> <th>Limit</th> <th>Read</th> <th>Ant</th> <th>Cable</th> <th>Preamp</th> <th>APos</th> <th>TPos</th> <th>Remark</th> </tr> <tr> <th>Freq</th> <th>Level</th> <th>Line</th> <th>Margin</th> <th>Level</th> <th>Factor</th> <th>Loss Factor</th> <th></th> </tr> <tr> <th>MHz</th> <th>dBuV/m</th> <th>dBuV/m</th> <th></th> <th>dBuV</th> <th>dB/m</th> <th>dB</th> <th>dB</th> <th>cm</th> <th>deg</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>2402.00</td> <td>104.03</td> <td>74.00</td> <td>30.03</td> <td>96.04</td> <td>32.28</td> <td>7.79</td> <td>32.08</td> <td>361</td> <td>322</td> <td>PEAK</td> </tr> <tr> <td>2</td> <td>2402.00</td> <td>79.24</td> <td>74.00</td> <td>5.24</td> <td>71.25</td> <td>32.28</td> <td>7.79</td> <td>32.08</td> <td>361</td> <td>322</td> <td>AVERAGE</td> </tr> </tbody> </table>	Limit	Read	Ant	Cable	Preamp	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss Factor		MHz	dBuV/m	dBuV/m		dBuV	dB/m	dB	dB	cm	deg	1	2402.00	104.03	74.00	30.03	96.04	32.28	7.79	32.08	361	322	PEAK	2	2402.00	79.24	74.00	5.24	71.25	32.28	7.79	32.08	361	322	AVERAGE
Limit	Read	Ant	Cable	Preamp	APos	TPos	Remark																																																																																															
Freq	Level	Line	Margin	Level	Factor	Loss Factor																																																																																																
MHz	dBuV/m	dBuV/m		dBuV	dB/m	dB	dB	cm	deg																																																																																													
1	2336.04	50.49	74.00	-23.51	42.81	32.14	7.61	32.07	361	322	PEAK																																																																																											
2	2336.04	25.70	54.00	-28.30	18.02	32.14	7.61	32.07	361	322	AVERAGE																																																																																											
Limit	Read	Ant	Cable	Preamp	APos	TPos	Remark																																																																																															
Freq	Level	Line	Margin	Level	Factor	Loss Factor																																																																																																
MHz	dBuV/m	dBuV/m		dBuV	dB/m	dB	dB	cm	deg																																																																																													
1	2402.00	104.03	74.00	30.03	96.04	32.28	7.79	32.08	361	322	PEAK																																																																																											
2	2402.00	79.24	74.00	5.24	71.25	32.28	7.79	32.08	361	322	AVERAGE																																																																																											



Mode	1																																																																																																	
	Band Edge																																																																																																	
	2400-2483.5_Bluetooth BR_GFSK_CH00_2402MHz																																																																																																	
Pol.	Vertical	Fundamental																																																																																																
Peak	<p>Date: 2023-05-12</p> <p>Site : 03CH01-SZ Condition: PEAK_BE_74 3m HF_ANT(3117)_22 VERTICAL Mode : 1 Setting : 1DH5 Plane : X with Accessories : 358957940004483</p> <table border="1"> <thead> <tr> <th>Limit</th> <th>Read</th> <th>Ant</th> <th>Cable</th> <th>Preamp</th> <th>APos</th> <th>TPos</th> <th>Remark</th> </tr> <tr> <th>Freq</th> <th>Level</th> <th>Line</th> <th>Margin</th> <th>Level</th> <th>Factor</th> <th>Loss</th> <th>Factor</th> </tr> <tr> <th>MHz</th> <th>dBuV/m</th> <th>dBuV/m</th> <th>dB</th> <th>dB/m</th> <th>dB</th> <th>dB</th> <th>cm</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>2371.18</td> <td>50.36</td> <td>74.00</td> <td>-23.64</td> <td>42.50</td> <td>32.22</td> <td>7.71</td> <td>32.07</td> <td>100</td> <td>312</td> <td>PEAK</td> </tr> <tr> <td>2</td> <td>2371.18</td> <td>25.57</td> <td>54.00</td> <td>-28.43</td> <td>17.71</td> <td>32.22</td> <td>7.71</td> <td>32.07</td> <td>100</td> <td>312</td> <td>AVERAGE</td> </tr> </tbody> </table>	Limit	Read	Ant	Cable	Preamp	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	MHz	dBuV/m	dBuV/m	dB	dB/m	dB	dB	cm	1	2371.18	50.36	74.00	-23.64	42.50	32.22	7.71	32.07	100	312	PEAK	2	2371.18	25.57	54.00	-28.43	17.71	32.22	7.71	32.07	100	312	AVERAGE	<p>Date: 2023-05-12</p> <p>Site : 03CH01-SZ Condition: PEAK_74 3m HF_ANT(3117)_22 VERTICAL Mode : 1 Setting : 1DH5 Plane : X with Accessories : 358957940004483</p> <table border="1"> <thead> <tr> <th>Limit</th> <th>Read</th> <th>Ant</th> <th>Cable</th> <th>Preamp</th> <th>APos</th> <th>TPos</th> <th>Remark</th> </tr> <tr> <th>Freq</th> <th>Level</th> <th>Line</th> <th>Margin</th> <th>Level</th> <th>Factor</th> <th>Loss</th> <th>Factor</th> </tr> <tr> <th>MHz</th> <th>dBuV/m</th> <th>dBuV/m</th> <th>dB</th> <th>dB/m</th> <th>dB</th> <th>dB</th> <th>cm</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>2402.00</td> <td>97.19</td> <td>-----</td> <td>-----</td> <td>89.20</td> <td>32.28</td> <td>7.79</td> <td>32.08</td> <td>100</td> <td>312</td> <td>PEAK</td> </tr> <tr> <td>2</td> <td>2402.00</td> <td>72.40</td> <td>-----</td> <td>-----</td> <td>64.41</td> <td>32.28</td> <td>7.79</td> <td>32.08</td> <td>100</td> <td>312</td> <td>AVERAGE</td> </tr> </tbody> </table>	Limit	Read	Ant	Cable	Preamp	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	MHz	dBuV/m	dBuV/m	dB	dB/m	dB	dB	cm	1	2402.00	97.19	-----	-----	89.20	32.28	7.79	32.08	100	312	PEAK	2	2402.00	72.40	-----	-----	64.41	32.28	7.79	32.08	100	312	AVERAGE
Limit	Read	Ant	Cable	Preamp	APos	TPos	Remark																																																																																											
Freq	Level	Line	Margin	Level	Factor	Loss	Factor																																																																																											
MHz	dBuV/m	dBuV/m	dB	dB/m	dB	dB	cm																																																																																											
1	2371.18	50.36	74.00	-23.64	42.50	32.22	7.71	32.07	100	312	PEAK																																																																																							
2	2371.18	25.57	54.00	-28.43	17.71	32.22	7.71	32.07	100	312	AVERAGE																																																																																							
Limit	Read	Ant	Cable	Preamp	APos	TPos	Remark																																																																																											
Freq	Level	Line	Margin	Level	Factor	Loss	Factor																																																																																											
MHz	dBuV/m	dBuV/m	dB	dB/m	dB	dB	cm																																																																																											
1	2402.00	97.19	-----	-----	89.20	32.28	7.79	32.08	100	312	PEAK																																																																																							
2	2402.00	72.40	-----	-----	64.41	32.28	7.79	32.08	100	312	AVERAGE																																																																																							



Mode	1																																																																									
	Harmonic																																																																									
	2400-2483.5_Bluetooth BR_GFSK_CH00_2402MHz																																																																									
Pol.	Horizontal	Vertical																																																																								
Peak	 <p>Site : 03CH01-SZ Condition: PEAK_74_3m HF_ANT(3117)_22 HORIZONTAL Project : 340708 Mode : 1 IMEI : 358957940004483 Plane : X with Accessories : 1DH5</p> <table border="1"> <thead> <tr> <th>Limit</th> <th>Read</th> <th>Ant</th> <th>Cable</th> <th>Preamp</th> <th>Apos</th> <th>TPos</th> <th>Remark</th> </tr> <tr> <th>Freq</th> <th>Level</th> <th>Line</th> <th>Margin</th> <th>Level</th> <th>Factor</th> <th>Loss</th> <th>Factor</th> </tr> <tr> <th>MHz</th> <th>dBuV/m</th> <th>dBuV/m</th> <th>dB</th> <th>dBuV</th> <th>dB/m</th> <th>dB</th> <th>dB</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>4804.00</td> <td>45.38</td> <td>74.00</td> <td>-28.62</td> <td>51.07</td> <td>34.82</td> <td>11.07</td> <td>51.58</td> <td>---</td> <td>---</td> <td>Peak</td> </tr> </tbody> </table>	Limit	Read	Ant	Cable	Preamp	Apos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	1	4804.00	45.38	74.00	-28.62	51.07	34.82	11.07	51.58	---	---	Peak	 <p>Site : 03CH01-SZ Condition: PEAK_74_3m HF_ANT(3117)_22 VERTICAL Project : 340708 Mode : 1 IMEI : 358957940004483 Plane : X with Accessories : 1DH5</p> <table border="1"> <thead> <tr> <th>Limit</th> <th>Read</th> <th>Ant</th> <th>Cable</th> <th>Preamp</th> <th>Apos</th> <th>TPos</th> <th>Remark</th> </tr> <tr> <th>Freq</th> <th>Level</th> <th>Line</th> <th>Margin</th> <th>Level</th> <th>Factor</th> <th>Loss</th> <th>Factor</th> </tr> <tr> <th>MHz</th> <th>dBuV/m</th> <th>dBuV/m</th> <th>dB</th> <th>dBuV</th> <th>dB/m</th> <th>dB</th> <th>dB</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>4804.00</td> <td>46.53</td> <td>74.00</td> <td>-27.47</td> <td>52.22</td> <td>34.82</td> <td>11.07</td> <td>51.58</td> <td>---</td> <td>---</td> <td>Peak</td> </tr> </tbody> </table>	Limit	Read	Ant	Cable	Preamp	Apos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	1	4804.00	46.53	74.00	-27.47	52.22	34.82	11.07	51.58	---	---	Peak
Limit	Read	Ant	Cable	Preamp	Apos	TPos	Remark																																																																			
Freq	Level	Line	Margin	Level	Factor	Loss	Factor																																																																			
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB																																																																			
1	4804.00	45.38	74.00	-28.62	51.07	34.82	11.07	51.58	---	---	Peak																																																															
Limit	Read	Ant	Cable	Preamp	Apos	TPos	Remark																																																																			
Freq	Level	Line	Margin	Level	Factor	Loss	Factor																																																																			
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB																																																																			
1	4804.00	46.53	74.00	-27.47	52.22	34.82	11.07	51.58	---	---	Peak																																																															
Avg																																																																										



Mode	2																																																																							
	Harmonic																																																																							
	2400-2483.5_Bluetooth BR_GFSK_CH39_2441MHz																																																																							
Pol.	Horizontal	Vertical																																																																						
Peak Avg	<p>Site : 03CH01-SZ Condition: PEAK_74_3m HF_ANT(3117)_22 HORIZONTAL Project : 340708 Mode : 2 IMEI : 358957940004483 Plane : X with Accessories : 1DH5</p> <table border="1"> <thead> <tr> <th rowspan="2">Freq</th> <th rowspan="2">Level</th> <th colspan="2">Limit</th> <th rowspan="2">Read Level</th> <th rowspan="2">Ant Factor</th> <th rowspan="2">Cable Loss</th> <th rowspan="2">Preamp Factor</th> <th rowspan="2">APos</th> <th rowspan="2">TPos</th> <th rowspan="2">Remark</th> </tr> <tr> <th>dBuV/m</th> <th>dB</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>4882.00</td> <td>45.62</td> <td>74.00</td> <td>-28.38</td> <td>51.25</td> <td>34.85</td> <td>11.10</td> <td>51.58</td> <td>---</td> <td>Peak</td> </tr> <tr> <td>2</td> <td>7323.00</td> <td>47.94</td> <td>74.00</td> <td>-26.06</td> <td>49.69</td> <td>36.33</td> <td>13.09</td> <td>51.17</td> <td>---</td> <td>Peak</td> </tr> </tbody> </table>	Freq	Level	Limit		Read Level	Ant Factor	Cable Loss	Preamp Factor	APos	TPos	Remark	dBuV/m	dB	1	4882.00	45.62	74.00	-28.38	51.25	34.85	11.10	51.58	---	Peak	2	7323.00	47.94	74.00	-26.06	49.69	36.33	13.09	51.17	---	Peak	<p>Site : 03CH01-SZ Condition: PEAK_74_3m HF_ANT(3117)_22 VERTICAL Project : 340708 Mode : 2 IMEI : 358957940004483 Plane : X with Accessories : 1DH5</p> <table border="1"> <thead> <tr> <th rowspan="2">Freq</th> <th rowspan="2">Level</th> <th colspan="2">Limit</th> <th rowspan="2">Read Level</th> <th rowspan="2">Ant Factor</th> <th rowspan="2">Cable Loss</th> <th rowspan="2">Preamp Factor</th> <th rowspan="2">APos</th> <th rowspan="2">TPos</th> <th rowspan="2">Remark</th> </tr> <tr> <th>dBuV/m</th> <th>dB</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>4882.00</td> <td>46.91</td> <td>74.00</td> <td>-27.09</td> <td>52.54</td> <td>34.85</td> <td>11.10</td> <td>51.58</td> <td>---</td> <td>Peak</td> </tr> <tr> <td>2</td> <td>7323.00</td> <td>47.63</td> <td>74.00</td> <td>-26.37</td> <td>49.38</td> <td>36.33</td> <td>13.09</td> <td>51.17</td> <td>---</td> <td>Peak</td> </tr> </tbody> </table>	Freq	Level	Limit		Read Level	Ant Factor	Cable Loss	Preamp Factor	APos	TPos	Remark	dBuV/m	dB	1	4882.00	46.91	74.00	-27.09	52.54	34.85	11.10	51.58	---	Peak	2	7323.00	47.63	74.00	-26.37	49.38	36.33	13.09	51.17	---	Peak
	Freq			Level	Limit								Read Level	Ant Factor	Cable Loss	Preamp Factor	APos	TPos	Remark																																																					
dBuV/m		dB																																																																						
1	4882.00	45.62	74.00	-28.38	51.25	34.85	11.10	51.58	---	Peak																																																														
2	7323.00	47.94	74.00	-26.06	49.69	36.33	13.09	51.17	---	Peak																																																														
Freq	Level	Limit		Read Level	Ant Factor	Cable Loss	Preamp Factor	APos	TPos	Remark																																																														
		dBuV/m	dB																																																																					
1	4882.00	46.91	74.00	-27.09	52.54	34.85	11.10	51.58	---	Peak																																																														
2	7323.00	47.63	74.00	-26.37	49.38	36.33	13.09	51.17	---	Peak																																																														



		3																																																																																				
Mode		Band Edge																																																																																				
		2400-2483.5_Bluetooth BR_GFSK_CH78_2480MHz																																																																																				
Pol.	Horizontal	Fundamental																																																																																				
Peak	<p style="text-align: right;">Date: 2023-05-12</p> <p style="text-align: right;">PEAK_BE_74</p> <p>Site : 03CH01-SZ Condition: PEAK_BE_74 3m HF_ANT(3117)_22 HORIZONTAL Mode : 3 Setting : 1DH5 Plane : X with Accessories : 358957940004483</p> <table border="1"> <thead> <tr> <th>Limit</th> <th>Read</th> <th>Ant</th> <th>Cable</th> <th>Preamp</th> <th>APos</th> <th>TPos</th> <th>Remark</th> </tr> <tr> <th>Freq</th> <th>Level</th> <th>Line</th> <th>Margin</th> <th>Level</th> <th>Factor</th> <th>Loss</th> <th>Factor</th> </tr> <tr> <th>MHz</th> <th>dBuV/m</th> <th>dBuV/m</th> <th></th> <th>dBuV</th> <th>dB/m</th> <th>dB</th> <th>dB</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>2483.89</td> <td>52.71</td> <td>74.00</td> <td>-21.29</td> <td>44.47</td> <td>32.46</td> <td>7.88 32.10</td> <td>371 326 PEAK</td> </tr> <tr> <td>2</td> <td>2483.89</td> <td>27.92</td> <td>54.00</td> <td>-26.08</td> <td>19.68</td> <td>32.46</td> <td>7.88 32.10</td> <td>371 326 AVERAGE</td> </tr> </tbody> </table>	Limit	Read	Ant	Cable	Preamp	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	MHz	dBuV/m	dBuV/m		dBuV	dB/m	dB	dB	1	2483.89	52.71	74.00	-21.29	44.47	32.46	7.88 32.10	371 326 PEAK	2	2483.89	27.92	54.00	-26.08	19.68	32.46	7.88 32.10	371 326 AVERAGE	<p style="text-align: right;">Date: 2023-05-12</p> <p style="text-align: right;">PEAK_74</p> <p>Site : 03CH01-SZ Condition: PEAK_74 3m HF_ANT(3117)_22 HORIZONTAL Mode : 3 Setting : 1DH5 Plane : X with Accessories : 358957940004483</p> <table border="1"> <thead> <tr> <th>Limit</th> <th>Read</th> <th>Ant</th> <th>Cable</th> <th>Preamp</th> <th>APos</th> <th>TPos</th> <th>Remark</th> </tr> <tr> <th>Freq</th> <th>Level</th> <th>Line</th> <th>Margin</th> <th>Level</th> <th>Factor</th> <th>Loss</th> <th>Factor</th> </tr> <tr> <th>MHz</th> <th>dBuV/m</th> <th>dBuV/m</th> <th></th> <th>dBuV</th> <th>dB/m</th> <th>dB</th> <th>dB</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>2480.00</td> <td>103.49</td> <td>-----</td> <td>95.26</td> <td>32.46</td> <td>7.87</td> <td>32.10</td> <td>371 326 PEAK</td> </tr> <tr> <td>2</td> <td>2480.00</td> <td>78.70</td> <td>-----</td> <td>70.47</td> <td>32.46</td> <td>7.87</td> <td>32.10</td> <td>371 326 AVERAGE</td> </tr> </tbody> </table>	Limit	Read	Ant	Cable	Preamp	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	MHz	dBuV/m	dBuV/m		dBuV	dB/m	dB	dB	1	2480.00	103.49	-----	95.26	32.46	7.87	32.10	371 326 PEAK	2	2480.00	78.70	-----	70.47	32.46	7.87	32.10	371 326 AVERAGE
Limit	Read	Ant	Cable	Preamp	APos	TPos	Remark																																																																															
Freq	Level	Line	Margin	Level	Factor	Loss	Factor																																																																															
MHz	dBuV/m	dBuV/m		dBuV	dB/m	dB	dB																																																																															
1	2483.89	52.71	74.00	-21.29	44.47	32.46	7.88 32.10	371 326 PEAK																																																																														
2	2483.89	27.92	54.00	-26.08	19.68	32.46	7.88 32.10	371 326 AVERAGE																																																																														
Limit	Read	Ant	Cable	Preamp	APos	TPos	Remark																																																																															
Freq	Level	Line	Margin	Level	Factor	Loss	Factor																																																																															
MHz	dBuV/m	dBuV/m		dBuV	dB/m	dB	dB																																																																															
1	2480.00	103.49	-----	95.26	32.46	7.87	32.10	371 326 PEAK																																																																														
2	2480.00	78.70	-----	70.47	32.46	7.87	32.10	371 326 AVERAGE																																																																														



3																																																									
Band Edge																																																									
2400-2483.5_Bluetooth BR_GFSK_CH78_2480MHz																																																									
Pol.	Vertical																																																								
Peak	<div style="display: flex; justify-content: space-between;"> <div style="width: 48%;"> </div> <div style="width: 48%;"> </div> </div> <div style="margin-top: 10px;"> <p>Site : 03CH01-SZ Condition: PEAK_BE_74 3m HF_ANT(3117)_22 VERTICAL Mode : 3 Setting : 1DH5 Plane : X with Accessories : 358957940004483</p> </div> <table border="1" style="width: 100%; border-collapse: collapse; font-size: small;"> <thead> <tr> <th>Limit</th> <th>Read</th> <th>Ant</th> <th>Cable</th> <th>Preamp</th> <th>APos</th> <th>TPos</th> <th>Remark</th> </tr> <tr> <th>Freq</th> <th>Level</th> <th>Line</th> <th>Margin</th> <th>Level</th> <th>Factor</th> <th>Loss Factor</th> <th></th> </tr> <tr> <th>MHz</th> <th>dBuV/m</th> <th>dBuV/m</th> <th></th> <th>dBuV</th> <th>dB/m</th> <th>dB</th> <th>dB</th> </tr> <tr> <th></th> <th></th> <th></th> <th></th> <th></th> <th></th> <th>cm</th> <th>deg</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>2483.60</td> <td>50.65</td> <td>74.00</td> <td>-23.35</td> <td>42.41</td> <td>32.46</td> <td>7.88</td> <td>32.10</td> <td>109</td> <td>270</td> <td>PEAK</td> </tr> <tr> <td>2</td> <td>2483.60</td> <td>25.86</td> <td>54.00</td> <td>-28.14</td> <td>17.62</td> <td>32.46</td> <td>7.88</td> <td>32.10</td> <td>109</td> <td>270</td> <td>AVERAGE</td> </tr> </tbody> </table>	Limit	Read	Ant	Cable	Preamp	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss Factor		MHz	dBuV/m	dBuV/m		dBuV	dB/m	dB	dB							cm	deg	1	2483.60	50.65	74.00	-23.35	42.41	32.46	7.88	32.10	109	270	PEAK	2	2483.60	25.86	54.00	-28.14	17.62	32.46	7.88	32.10	109	270	AVERAGE
	Limit	Read	Ant	Cable	Preamp	APos	TPos	Remark																																																	
Freq	Level	Line	Margin	Level	Factor	Loss Factor																																																			
MHz	dBuV/m	dBuV/m		dBuV	dB/m	dB	dB																																																		
						cm	deg																																																		
1	2483.60	50.65	74.00	-23.35	42.41	32.46	7.88	32.10	109	270	PEAK																																														
2	2483.60	25.86	54.00	-28.14	17.62	32.46	7.88	32.10	109	270	AVERAGE																																														
	<div style="display: flex; justify-content: space-between;"> <div style="width: 48%;"> <p>Site : 03CH01-SZ Condition: PEAK_74 3m HF_ANT(3117)_22 VERTICAL Mode : 3 Setting : 1DH5 Plane : X with Accessories : 358957940004483</p> </div> <div style="width: 48%;"> </div> </div> <div style="margin-top: 10px;"> <p>Site : 03CH01-SZ Condition: PEAK_74 3m HF_ANT(3117)_22 VERTICAL Mode : 3 Setting : 1DH5 Plane : X with Accessories : 358957940004483</p> </div> <table border="1" style="width: 100%; border-collapse: collapse; font-size: small;"> <thead> <tr> <th>Limit</th> <th>Read</th> <th>Ant</th> <th>Cable</th> <th>Preamp</th> <th>APos</th> <th>TPos</th> <th>Remark</th> </tr> <tr> <th>Freq</th> <th>Level</th> <th>Line</th> <th>Margin</th> <th>Level</th> <th>Factor</th> <th>Loss Factor</th> <th></th> </tr> <tr> <th>MHz</th> <th>dBuV/m</th> <th>dBuV/m</th> <th></th> <th>dBuV</th> <th>dB/m</th> <th>dB</th> <th>dB</th> </tr> <tr> <th></th> <th></th> <th></th> <th></th> <th></th> <th></th> <th>cm</th> <th>deg</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>2480.00</td> <td>99.81</td> <td>75.02</td> <td>24.79</td> <td>91.58</td> <td>32.46</td> <td>7.87</td> <td>32.10</td> <td>109</td> <td>270</td> <td>PEAK</td> </tr> <tr> <td>2</td> <td>2480.00</td> <td>75.02</td> <td>75.02</td> <td>0.00</td> <td>66.79</td> <td>32.46</td> <td>7.87</td> <td>32.10</td> <td>109</td> <td>270</td> <td>AVERAGE</td> </tr> </tbody> </table>	Limit	Read	Ant	Cable	Preamp	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss Factor		MHz	dBuV/m	dBuV/m		dBuV	dB/m	dB	dB							cm	deg	1	2480.00	99.81	75.02	24.79	91.58	32.46	7.87	32.10	109	270	PEAK	2	2480.00	75.02	75.02	0.00	66.79	32.46	7.87	32.10	109	270	AVERAGE
Limit	Read	Ant	Cable	Preamp	APos	TPos	Remark																																																		
Freq	Level	Line	Margin	Level	Factor	Loss Factor																																																			
MHz	dBuV/m	dBuV/m		dBuV	dB/m	dB	dB																																																		
						cm	deg																																																		
1	2480.00	99.81	75.02	24.79	91.58	32.46	7.87	32.10	109	270	PEAK																																														
2	2480.00	75.02	75.02	0.00	66.79	32.46	7.87	32.10	109	270	AVERAGE																																														



Mode	3																																																																																	
	Harmonic																																																																																	
	2400-2483.5_Bluetooth BR_GFSK_CH78_2480MHz																																																																																	
Pol.	Horizontal	Vertical																																																																																
Peak Avg	<p>Site : 03CH01-SZ Condition: PEAK_74_3m HF_ANT(3117)_22 HORIZONTAL Project : 340708 Mode : 3 IMEI : 358957940004483 Plane : X with Accessories : 1DH5</p> <table border="1"> <thead> <tr> <th>Limit</th> <th>Read</th> <th>Ant</th> <th>Cable</th> <th>Preamp</th> <th>Apos</th> <th>TPos</th> <th>Remark</th> </tr> <tr> <th>Freq</th> <th>Level</th> <th>Line Margin</th> <th>Level Factor</th> <th>Loss Factor</th> <th>Loss Factor</th> <th></th> <th></th> </tr> <tr> <th>MHz</th> <th>dBuV/m</th> <th>dBuV/m</th> <th>dB</th> <th>dBuV</th> <th>dB/m</th> <th>dB</th> <th>cm deg</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>4960.00</td> <td>46.43</td> <td>74.00</td> <td>-27.57</td> <td>51.99</td> <td>34.88</td> <td>11.14 51.58 --- --- Peak</td> </tr> <tr> <td>2</td> <td>7440.00</td> <td>48.76</td> <td>74.00</td> <td>-25.24</td> <td>50.60</td> <td>36.38</td> <td>12.97 51.19 --- --- Peak</td> </tr> </tbody> </table>	Limit	Read	Ant	Cable	Preamp	Apos	TPos	Remark	Freq	Level	Line Margin	Level Factor	Loss Factor	Loss Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	cm deg	1	4960.00	46.43	74.00	-27.57	51.99	34.88	11.14 51.58 --- --- Peak	2	7440.00	48.76	74.00	-25.24	50.60	36.38	12.97 51.19 --- --- Peak	<p>Site : 03CH01-SZ Condition: PEAK_74_3m HF_ANT(3117)_22 VERTICAL Project : 340708 Mode : 3 IMEI : 358957940004483 Plane : X with Accessories : 1DH5</p> <table border="1"> <thead> <tr> <th>Limit</th> <th>Read</th> <th>Ant</th> <th>Cable</th> <th>Preamp</th> <th>Apos</th> <th>TPos</th> <th>Remark</th> </tr> <tr> <th>Freq</th> <th>Level</th> <th>Line Margin</th> <th>Level Factor</th> <th>Loss Factor</th> <th>Loss Factor</th> <th></th> <th></th> </tr> <tr> <th>MHz</th> <th>dBuV/m</th> <th>dBuV/m</th> <th>dB</th> <th>dBuV</th> <th>dB/m</th> <th>dB</th> <th>cm deg</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>4960.00</td> <td>46.07</td> <td>74.00</td> <td>-27.93</td> <td>51.63</td> <td>34.88</td> <td>11.14 51.58 --- --- Peak</td> </tr> <tr> <td>2</td> <td>7440.00</td> <td>50.13</td> <td>74.00</td> <td>-23.87</td> <td>51.97</td> <td>36.38</td> <td>12.97 51.19 --- --- Peak</td> </tr> </tbody> </table>	Limit	Read	Ant	Cable	Preamp	Apos	TPos	Remark	Freq	Level	Line Margin	Level Factor	Loss Factor	Loss Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	cm deg	1	4960.00	46.07	74.00	-27.93	51.63	34.88	11.14 51.58 --- --- Peak	2	7440.00	50.13	74.00	-23.87	51.97	36.38	12.97 51.19 --- --- Peak
	Limit	Read	Ant	Cable	Preamp	Apos	TPos	Remark																																																																										
Freq	Level	Line Margin	Level Factor	Loss Factor	Loss Factor																																																																													
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	cm deg																																																																											
1	4960.00	46.43	74.00	-27.57	51.99	34.88	11.14 51.58 --- --- Peak																																																																											
2	7440.00	48.76	74.00	-25.24	50.60	36.38	12.97 51.19 --- --- Peak																																																																											
Limit	Read	Ant	Cable	Preamp	Apos	TPos	Remark																																																																											
Freq	Level	Line Margin	Level Factor	Loss Factor	Loss Factor																																																																													
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	cm deg																																																																											
1	4960.00	46.07	74.00	-27.93	51.63	34.88	11.14 51.58 --- --- Peak																																																																											
2	7440.00	50.13	74.00	-23.87	51.97	36.38	12.97 51.19 --- --- Peak																																																																											




Mode	4																																																																																																																																																																									
	LF																																																																																																																																																																									
	2400-2483.5_Bluetooth BR_GFSK_CH78_2480MHz																																																																																																																																																																									
Pol.	Horizontal	Vertical																																																																																																																																																																								
QP/ Peak	<p>Date: 2023-05-22</p> <p>Site : 03CH01-SZ Condition: FCC CLASS-B 3m CBL6112D-47611 HORIZONTAL Project : 340708 Mode : 4 IMEI : 358957940004483 Plane : X with Accessories</p> <table border="1"> <thead> <tr> <th>Peak</th> <th>Freq (MHz)</th> <th>Level (dBuV/m)</th> <th>Limit (dBuV/m)</th> <th>Margin (dB)</th> <th>Read Level (dBuV)</th> <th>Ant Factor (dB/m)</th> <th>Cable Loss (dB)</th> <th>Preamp Loss (dB)</th> <th>APos (cm)</th> <th>TPos (deg)</th> <th>Remark</th> </tr> </thead> <tbody> <tr><td>1</td><td>51.34</td><td>24.87</td><td>40.00</td><td>-15.13</td><td>40.51</td><td>14.12</td><td>1.45</td><td>31.21</td><td>---</td><td>---</td><td>Peak</td></tr> <tr><td>2</td><td>133.79</td><td>26.99</td><td>43.50</td><td>-16.51</td><td>38.25</td><td>17.76</td><td>2.11</td><td>31.13</td><td>---</td><td>---</td><td>Peak</td></tr> <tr><td>3</td><td>231.76</td><td>26.20</td><td>46.00</td><td>-19.80</td><td>38.04</td><td>16.64</td><td>2.42</td><td>30.90</td><td>---</td><td>---</td><td>Peak</td></tr> <tr><td>4</td><td>436.43</td><td>29.62</td><td>46.00</td><td>-16.38</td><td>34.37</td><td>22.70</td><td>3.25</td><td>30.70</td><td>---</td><td>---</td><td>Peak</td></tr> <tr><td>5</td><td>491.72</td><td>32.18</td><td>46.00</td><td>-13.82</td><td>35.85</td><td>23.58</td><td>3.45</td><td>30.70</td><td>---</td><td>---</td><td>Peak</td></tr> <tr><td>6</td><td>818.61</td><td>29.56</td><td>46.00</td><td>-16.44</td><td>30.09</td><td>26.25</td><td>4.30</td><td>31.08</td><td>---</td><td>---</td><td>Peak</td></tr> </tbody> </table>	Peak	Freq (MHz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Read Level (dBuV)	Ant Factor (dB/m)	Cable Loss (dB)	Preamp Loss (dB)	APos (cm)	TPos (deg)	Remark	1	51.34	24.87	40.00	-15.13	40.51	14.12	1.45	31.21	---	---	Peak	2	133.79	26.99	43.50	-16.51	38.25	17.76	2.11	31.13	---	---	Peak	3	231.76	26.20	46.00	-19.80	38.04	16.64	2.42	30.90	---	---	Peak	4	436.43	29.62	46.00	-16.38	34.37	22.70	3.25	30.70	---	---	Peak	5	491.72	32.18	46.00	-13.82	35.85	23.58	3.45	30.70	---	---	Peak	6	818.61	29.56	46.00	-16.44	30.09	26.25	4.30	31.08	---	---	Peak	<p>Date: 2023-05-22</p> <p>Site : 03CH01-SZ Condition: FCC CLASS-B 3m CBL6112D-47611 VERTICAL Project : 340708 Mode : 4 IMEI : 358957940004483 Plane : X with Accessories</p> <table border="1"> <thead> <tr> <th>Peak</th> <th>Freq (MHz)</th> <th>Level (dBuV/m)</th> <th>Limit (dBuV/m)</th> <th>Margin (dB)</th> <th>Read Level (dBuV)</th> <th>Ant Factor (dB/m)</th> <th>Cable Loss (dB)</th> <th>Preamp Loss (dB)</th> <th>APos (cm)</th> <th>TPos (deg)</th> <th>Remark</th> </tr> </thead> <tbody> <tr><td>1</td><td>50.37</td><td>35.88</td><td>40.00</td><td>-4.12</td><td>51.35</td><td>14.30</td><td>1.43</td><td>31.20</td><td>---</td><td>---</td><td>Peak</td></tr> <tr><td>2</td><td>130.88</td><td>23.80</td><td>43.50</td><td>-19.70</td><td>34.91</td><td>17.94</td><td>2.09</td><td>31.14</td><td>---</td><td>---</td><td>Peak</td></tr> <tr><td>3</td><td>224.00</td><td>25.71</td><td>46.00</td><td>-20.29</td><td>38.49</td><td>15.74</td><td>2.38</td><td>30.90</td><td>---</td><td>---</td><td>Peak</td></tr> <tr><td>4</td><td>436.43</td><td>40.67</td><td>46.00</td><td>-5.33</td><td>45.42</td><td>22.70</td><td>3.25</td><td>30.70</td><td>---</td><td>---</td><td>Peak</td></tr> <tr><td>5</td><td>491.72</td><td>41.91</td><td>46.00</td><td>-4.09</td><td>45.58</td><td>23.58</td><td>3.45</td><td>30.70</td><td>---</td><td>---</td><td>Peak</td></tr> <tr><td>6</td><td>546.04</td><td>35.07</td><td>46.00</td><td>-10.93</td><td>37.55</td><td>24.90</td><td>3.60</td><td>30.98</td><td>---</td><td>---</td><td>Peak</td></tr> </tbody> </table>	Peak	Freq (MHz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Read Level (dBuV)	Ant Factor (dB/m)	Cable Loss (dB)	Preamp Loss (dB)	APos (cm)	TPos (deg)	Remark	1	50.37	35.88	40.00	-4.12	51.35	14.30	1.43	31.20	---	---	Peak	2	130.88	23.80	43.50	-19.70	34.91	17.94	2.09	31.14	---	---	Peak	3	224.00	25.71	46.00	-20.29	38.49	15.74	2.38	30.90	---	---	Peak	4	436.43	40.67	46.00	-5.33	45.42	22.70	3.25	30.70	---	---	Peak	5	491.72	41.91	46.00	-4.09	45.58	23.58	3.45	30.70	---	---	Peak	6	546.04	35.07	46.00	-10.93	37.55	24.90	3.60	30.98	---	---	Peak
Peak	Freq (MHz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Read Level (dBuV)	Ant Factor (dB/m)	Cable Loss (dB)	Preamp Loss (dB)	APos (cm)	TPos (deg)	Remark																																																																																																																																																															
1	51.34	24.87	40.00	-15.13	40.51	14.12	1.45	31.21	---	---	Peak																																																																																																																																																															
2	133.79	26.99	43.50	-16.51	38.25	17.76	2.11	31.13	---	---	Peak																																																																																																																																																															
3	231.76	26.20	46.00	-19.80	38.04	16.64	2.42	30.90	---	---	Peak																																																																																																																																																															
4	436.43	29.62	46.00	-16.38	34.37	22.70	3.25	30.70	---	---	Peak																																																																																																																																																															
5	491.72	32.18	46.00	-13.82	35.85	23.58	3.45	30.70	---	---	Peak																																																																																																																																																															
6	818.61	29.56	46.00	-16.44	30.09	26.25	4.30	31.08	---	---	Peak																																																																																																																																																															
Peak	Freq (MHz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Read Level (dBuV)	Ant Factor (dB/m)	Cable Loss (dB)	Preamp Loss (dB)	APos (cm)	TPos (deg)	Remark																																																																																																																																																															
1	50.37	35.88	40.00	-4.12	51.35	14.30	1.43	31.20	---	---	Peak																																																																																																																																																															
2	130.88	23.80	43.50	-19.70	34.91	17.94	2.09	31.14	---	---	Peak																																																																																																																																																															
3	224.00	25.71	46.00	-20.29	38.49	15.74	2.38	30.90	---	---	Peak																																																																																																																																																															
4	436.43	40.67	46.00	-5.33	45.42	22.70	3.25	30.70	---	---	Peak																																																																																																																																																															
5	491.72	41.91	46.00	-4.09	45.58	23.58	3.45	30.70	---	---	Peak																																																																																																																																																															
6	546.04	35.07	46.00	-10.93	37.55	24.90	3.60	30.98	---	---	Peak																																																																																																																																																															




Appendix D. Duty Cycle Plots

DH5 on time (One Pulse) Plot on Channel 39



DH5 on time (Count Pulses) Plot on Channel 39



Note:

1. Worst case Duty cycle = on time/100 milliseconds = $2 * 2.880 / 100 = 5.76 \%$
2. Worst case Duty cycle correction factor = $20 * \log(\text{Duty cycle}) = -24.79 \text{ dB}$
3. DH5 has the highest duty cycle worst case and is reported.