

Report No.: SEWM2203000022RG01

Rev.: 01 Page: 1 of 29

HAC (T-Coil) Test Report

Application No.: SEWM2203000022RG

Applicant: COOSEA GROUP (HK) COMPANY LIMITED **Manufacturer:** COOSEA GROUP (HK) COMPANY LIMITED

Product Name: Mobile Phone
Model No.(EUT): SL101AE
Trade Mark: Cricket

FCC ID: 2A28USL101AE

Standards: ANSI C63.19-2011 CFR 47 FCC Part 20

Date of Receipt: 2022-05-05

Date of Test: 2022-05-08 to 2022-05-17

Date of Issue: 2022-05-20
Test conclusion: PASS *

* In the configuration tested, the EUT detailed in this report complied with the standards specified above.

Authorized Signature:

Panta Sun

Wireless Laboratory Manager



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printer overleaf, available on request or accessible at http://www.sgs.com/en/Terms.and-Conditions.apx and for electronic forms and conditions for Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions/Terms-en-Document.aspx Attention is dorawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company, Any unauthorized alteration, forgery or faisification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) are refained for 30 days only.

| Suth of No. Float, No. T, Rursheng Road, Surbou Industrial Park, Surbou Area, Ohira (Alangsu) Pilot Free Trade Zone 215000 t (86—512) 62992980 www.sgs.group.com.c 中国 - 苏州 - 中国 (江苏) 自由贸易试验区苏州 Fi 区苏州工业园区润胜商 I 号的场 Fi 原南部 邮编: 215000 t (86—512) 62992980 sgs.china@sgs.com



Report No.: SEWM2203000022RG01

Rev.: 01 Page: 2 of 29

REVISION HISTORY

Revision Record				
Version	Chapter	Date	Modifier	Remark
01		2022-05-20		Original



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sas.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sas.com/en/Terms-and-Conditions appx and, for electronic format documents, at http://www.sas.com/en/Terms-and-Conditions for Electronic Document at http://www.sas.com/en/Terms-and-Conditions for Terms-a-Document ex. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues define therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company, Any unauthorized alteration, forgery or fallsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-75) 8307 1443,

South of No. 6 Plant, No. 1, Runsheng Road, Suchou Industrial Park, Suzhou Area, China (Jiangsu) Plot Free Trade Zone 215000 中国 - 苏州 - 中国(江苏)自由贸易试验区苏州片区苏州工业园区润胜裔1号约6号厂房南部 邮编: 215000 t (86–512) 62992980 www.sgsgroup.com.c t (86–512) 62992980 sgs.china@sgs.com



Report No.: SEWM2203000022RG01

Rev.: 01 Page: 3 of 29

Prepared by

TEST SUMMARY

Frequency Band	T-rating	
WCDMA II	Т3	
WCDMA IV	ТЗ	
WCDMA V	ТЗ	
LTE Band 2	T3	
LTE Band 4	T3	
LTE Band 5	T3	
LTE Band 12	T4	
LTE Band 14	Т3	
LTE Band 30	T3	
WI-FI (2.4GHz)	T3	
WI-FI (5GHz)	T3	
HAC Rate Category: T3		

Reviewed by

vell *wei*

Well Wei Nick Hu



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printe overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.spx and, for electronic format documents subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions/ferms-en-Document.aspx
Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to stransaction from exercising all their rights and obligations under the transaction document cannot be reproduce except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content of appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

South of No. 6 Plant, No. 1, Runsheng Road, Suchou Industrial Park, Suzhou Area, China (Jiangsu) Plot Free Trade Zone 215000 中国 - 苏州 - 中国(江苏)自由贸易试验区苏州片区苏州工业园区润胜裔1号约6号厂房南部 邮编: 215000



Report No.: SEWM2203000022RG01

Rev.: 01 Page: 4 of 29

CONTENTS

1	GEN	ERAL INFORMATION	5
	1.2 1.3 1.4 1.5 1.5.1 1.5.2		5 6 7 8
2	CALI	BRATION CERTIFICATE	10
3	HAC	(T-COIL) MEASUREMENT SYSTEM	11
	3.2 3.3 3.4 3.5 3.6 3.7	Measurement System Diagram for SPEAG Robotic T-Coil Measurement Set-up System Calibration Audio Magnetic Probe AM1DV3 Test Arch Phone Holder AMCC- Audio Magnetic Calibration Coil AMMI - Audio Magnetic Measurement Instrument	12 13 14 14 15
4	MEA	SUREMENT UNCERTAINTY EVALUATION	16
5	HAC	(T-COIL) MEASUREMENT	17
	5.2	T-Coil Performance Requirements	19
6	T-CO	IL TESTING FOR CMRS VOICE	22
		General DescriptionUMTS Tests Results	
7	T-CO	IL TESTING FOR CMRS IP VOICE	23
	7.2	VoLTE Tests Results VoWiFi Tests Results T-Coil testing for OTT VoIP Application	25
8	EQUI	PMENT LIST	29
9	CALI	BRATION CERTIFICATE	29
1() PHO	TOGRAPHS	29
Α	PPENDI)	(A: DETAILED TEST RESULTS	29
Α	PPENDI)	(B: CALIBRATION CERTIFICATE	29
Α	PPENDI)	(C: PHOTOGRAPHS	29



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sas.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sas.com/en/Terms-and-Conditions appx and, for electronic format documents, at http://www.sas.com/en/Terms-and-Conditions for Electronic Document at http://www.sas.com/en/Terms-and-Conditions for Terms-a-Document ex. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues define therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company, Any unauthorized alteration, forgery or fallsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-75) 8307 1443,

South of No. 6 Pfart, No. 1, Runsheng Road, Suchou Industrial Park, Suchou Area, China (Jiangsu) Pilot Fee Trade Zone 中国 - 苏州 - 中国(江苏)自由贸易试验区苏州片区苏州工业园区润胜路1号约6号厂房南部 邮编: 215000 t (86–512) 62992980 www.sgsgroup.com. t (86–512) 62992980 sgs.china@sgs.com



Report No.: SEWM2203000022RG01

Rev.: 01 Page: 5 of 29

1 General Information

1.1 Introduction

The purpose of this standard is to establish categories for hearing aids and for WD (wireless communications devices) that can indicate to health care practitioners and hearing aid users which hearing aids are compatible with which WD, and to provide tests that can be used to assess the electromagnetic characteristics of hearing aids and WD and assign them to these categories. The various parameters required, in order to demonstrate compatibility and accessibility are measured. The design of the standard is such that when a hearing aid and WD achieve one of the categories specified, as measured by the methodology of this standard, the indicated performance is realized.

In order to provide for the usability of a hearing aid with a WD, several factors must be coordinated:

- a) Radio frequency (RF) measurements of the near-field electric and magnetic fields emitted by a WD to categorize these emissions for correlation with the RF immunity of a hearing aid.
- b) Magnetic field measurements of a WD emitted via the audio transducer associated with the T-coil mode of the hearing aid, for assessment of hearing aid performance.
- c) Measurements with the hearing aid and a simulation of the categorized WD T-coil emissions to assess the hearing aid RF immunity in the T-coil mode.

The WD radio frequency (RF) and audio band emissions are measured.

Hence, the following are measurements made for the WD:

- a) RF E-Field emissions
- b) T-coil mode, magnetic signal strength in the audio band
- c) T-coil mode, magnetic signal and noise articulation index
- d) T-coil mode, magnetic signal frequency response through the audio band

Corresponding to the WD measurements, the hearing aid is measured for:

- a) RF immunity in microphone mode
- b) RF immunity in T-coil mode

1.2 Details of Client

Applicant:	COOSEA GROUP (HK) COMPANY LIMITED
Address:	UNIT 5-6 16/F MULTIFIELD PLAZA 3-7A PRAT AVENUE TSIMSHATSUI KL, HONG KONG, CHINA
Manufacturer:	COOSEA GROUP (HK) COMPANY LIMITED
Address:	UNIT 5-6 16/F MULTIFIELD PLAZA 3-7A PRAT AVENUE TSIMSHATSUI KL, HONG KONG, CHINA

1.3 Test Location

Company:	SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd.
Address:	South of No. 6 Plant, No. 1, Runsheng Road, Suzhou Industrial Park, Suzhou Area, China (Jiangsu) Pilot Free Trade Zone
Post code:	215000
Test Engineer:	Nature Shen, Leon Xu



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.apx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.apx. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction document. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

**Attention: To check the authenticity of testing /inspection report & certificate_please contact us at telephone: (86-755) \$3071443.

South of No. 6 Plant, No. 1, Runsheng Road, Suchou Industrial Park, Suzhou Area, China (Liangsu) Pilot Free Trade Zone 215000 中国 - 苏州 - 中国(江苏)自由贸易试验区苏州片区苏州工业园区润胜路1号的6号厂房南部 邮编: 215000

(86–512) 62992980 sgs.china@sgs.com



Report No.: SEWM2203000022RG01

Rev.: 01 Page: 6 of 29

1.4 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

• A2LA (Certificate No. 6336.01)

SGS-CSTC STANDARDS TECHNICAL SERVICES (SUZHOU) CO., LTD. is accredited by the American Association for Laboratory Accreditation(A2LA). Certificate No. 6336.01.

• Innovation, Science and Economic Development Canada

SGS-CSTC STANDARDS TECHNICAL SERVICES (SUZHOU) CO., LTD. has been recognized by ISED as an accredited testing laboratory.

CAB identifier: CN0120.

IC#: 27594.

• FCC -Designation Number: CN1312

SGS-CSTC STANDARDS TECHNICAL SERVICES (SUZHOU) CO., LTD. has been recognized as an accredited testing laboratory.



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.ags.com/en/Terms-and-Conditions.agx; and, for electronic Documents at http://www.ags.com/en/Terms-and-Conditions/Terms-e-Document as public to Terms and Conditions for Telectronic Document as http://www.ags.com/en/Terms-and-Conditions/Terms-e-Document as public to the state of the stat



Report No.: SEWM2203000022RG01

Rev.: 01 Page: 7 of 29

1.5 General Description of EUT

Device Type :	portable device			
Exposure Category:	uncontrolled environment / general population			
Product Name:	Mobile Phone			
Model No.(EUT):	SL101AE			
Trade Mark:	Cricket			
FCC ID:	2A28USL101AE			
Product Phase:	Identical Prototype			
IMEI:	355171430009902			
Hardware Version:	V1.0			
Software Version:	SL101AEC10004			
Antenna Type:	Integrated			
Device Operating Configuration	· ·			
Modulation Mode:	WCDMA: QPSK, HSPA+(16QAM); LTE: QPSK,16QAM WIFI: DSSS, OFDM; BT: GFSK, π/4DQPSK,8DPSK			
Power Class:	· .	trol "all up"(WCDMA Bands)		
1 ower class.	<u> </u>	trol Max Power(LTE Band)		
	Band	Tx (MHz)	Rx (MHz)	
	WCDMA Band II	1850 -1910	1930 - 1990	
	WCDMA Band IV	1710 -1755	2110 - 2155	
	WCDMA Band V	824 - 849	869 - 894	
	LTE Band 2	1850 - 1910	1930 - 1990	
	LTE Band 4	1710 - 1755	2110 - 2155	
	LTE Band 5	824 - 849	869 - 894	
Frequency Bands:	LTE Band 12	699 - 716	729 - 746	
Trequency Barras.	LTE Band 14	788 - 798	758 - 768	
	LTE Band 30	2305 - 2315	2350 - 2360	
	Bluetooth	2402~2480	2402~2480	
	Wi-Fi 2.4G	2412~2462	2412~2462	
		5150~5250	5150~5250	
	Wi-Fi 5G	5250~5350	5250~5350	
	VVI-1130	5470~5725	5470~5725	
		5725~5850	5725~5850	
RF Cable:	□ Provided	□ Provided by the aplicant □ Provided by the laboratory		
	Model:	BL-A36CT		
Battary Information:	Normal Voltage:	3.8V		
Battery Information:	Rated capacity:	2450mAh		
	Manufacturer:	Shenzhen Aerospace Electronic Co.,Ltd.		



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sas.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sas.com/en/Terms-and-Conditions appx and, for electronic format documents, at http://www.sas.com/en/Terms-and-Conditions for Electronic Document at http://www.sas.com/en/Terms-and-Conditions for Terms-a-Document ex. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues define therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company, Any unauthorized alteration, forgery or fallsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-75) 8307 1443,

South of No. 6 Plant, No. 1, Runsheng Road, Suchou Industrial Park, Suzhou Area, China (Jiangsu) Plot Free Trade Zone
中国 - 苏州 - 中国(江苏)自由贸易试验区苏州片区苏州工业园区润胜路(号的6号厂房南部 邮编: 215000


t (86–512) 62992980 www.sgsgroup.com. t (86–512) 62992980 sgs.china@sgs.com



Report No.: SEWM2203000022RG01

Rev.: 01 Page: 8 of 29

1.5.1 DUT Antenna Locations(Front view)



Bottom Side

Antenna	Support TX Band
Ant 0	WCDMA B2/4/5,LTE B2/B4/B5/B12/B14/B30
Ant 2	WIFI 2.4G /BT
Ant 3	WIFI 5G



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not excerate parties to a transaction from exercising all their rights and obligations under the transaction document. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawfull and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone (86-755) \$3071443.

South of No. 6 Plant, No. 1, Runsheng Road, Suchou Industrial Park, Suzhou Area, China (Jiangsu) Plot Free Trade Zone
中国 - 苏州 - 中国(江苏)自由贸易试验区苏州片区苏州工业园区润胜路(号的6号厂房南部 邮编: 215000

t (86–512) 62992980 www.sgsgroup.com.ci t (86–512) 62992980 sgs.china@sgs.com



Report No.: SEWM2203000022RG01

Rev.: 01 Page: 9 of 29

1.5.2 List of air interfaces/frequency bands

Air Interface	Band (MHz)	Туре	ANSI C63.19 Tested	Simultaneous Transmitter	Name of Voice Service	Power Reduction
	Band II	O	Yes	BT, Wi-Fi	CMRS Voice	NA
WCDMA	Band IV					
VVCDIVIA	Band V					
	HSPA	DT	No	BT, Wi-Fi	NA	NA
	Band 2		Yes	BT, Wi-Fi	VoLTE Google Duo*	NA
	Band 4	VD				
LTE	Band 5					
(FDD)	Band 12					
	Band 14					
	Band 30					
	2450	VD	Yes	WWAN	VOWIFI Google Duo*	NA
	5200					NA
Wi-Fi	5300					NA
	5500					NA
	5800					NA
BT	2450	DT	No	WWAN	NA	NA

VO: Legacy Cellular Voice Service from Table 7.1 in 7.4.2.1 of ANSI C63.19-2011

DT: Digital Transport (no voice)

VD: IP Voice Service over Digital Transport

For protocols not listed in Table 7.1 of ANSI C63.19-2011 or the ANSI C63.19-2011 VoLTE interpretation,

the average speech level of -20 dBm0 should be used.



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not excerate parties to a transaction from exercising all their rights and obligations under the transaction document. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawfull and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone (86-755) \$3071443.

South of No. 6 Pfart, No. 1, Runsheng Read, Suchou Industrial Park, Suchou Area, China (Jangsu) Pilot Free Trade Zone 215000 中国 - 苏州 - 中国(江苏)自由贸易试验区苏州片区苏州工业园区润胜路1号的6号厂房南部 邮编: 215000

t (86–512) 62992980

www.sgsgroup.com.cn sgs.china@sgs.com



Report No.: SEWM2203000022RG01

Rev.: 01 Page: 10 of 29

1.6 Test Specification

Identity	Document Title
CFR 47 FCC Part 20	§20.19 Hearing aid-compatible mobile handsets.
ANSI C63.19-2011	American National Standard for Methods of Measurement of Compatibility between Wireless Communication Devices
KDB 285076 D01	HAC Guidance v05r01
KDB 285076 D02	T-Coil testing v03
KDB 285076 D03	HAC FAQ v01r01

2 Calibration certificate

Temperature	Min. = 18°C, Max. = 25 °C
Relative humidity	Min. = 30%, Max. = 70%

Table 1: The Ambient Conditions





Report No.: SEWM2203000022RG01

Rev.: 01 Page: 11 of 29

3 HAC (T-Coil) Measurement System

3.1 Measurement System Diagram for SPEAG Robotic




Fig. 1. The SPEAG Robotic Diagram

The DASY5 system for performing compliance tests consists of the following items:

- A standard high precision 6-axis robot (Stabile RX family) with controller, teach pendant and software. An arm extension is for accommodating the data acquisition electronics (DAE).
- An Audio Magnetic probe.
- A data acquisition electronics (DAE) which performs the signal amplification, signal multiplexing, AD-conversion, offset measurements, mechanical surface detection, collision detection, etc. The unit is battery powered with standard or rechargeable batteries. The signal is optically transmitted to the EOC.
- The Electro-optical converter (EOC) performs the conversion between optical and electrical of the signals for the digital communication to the DAE and for the analog signal from the optical surface detection. The EOC is connected to the measurement server.
- The function of the measurement server is to perform the time critical tasks such as signal filtering, control of the robot operation and fast movement interrupts.
- A probe alignment unit which improves the (absolute) accuracy of the probe positioning.
- · A computer operating Windows 7.
- · DASY5 software.
- Remote control with teach pendant and additional circuitry for robot safety such as warning lamps, etc.
- The Test Arch SAM phantom
- The device holder for handheld mobile phones.
- Validation dipole kits allowing to validate the proper functioning of the system.



Inless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed worleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions/Terms-en/Cocuments. Usually the terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions/Terms-en/Cocuments.. It is the second of the second in the second of the second in the second i

South of No. 6 Plant, No. 1, Runsheng Road, Suthou Industrial Park, Suzhou Area, China (Jiangsu) Plot Free Trade Zone 中国 - 苏州 - 中国(江苏)自由贸易试验区苏州片区苏州工业园区润胜路(号的6号厂房南部 邮编: 215000

t (86–512) 62992980



Report No.: SEWM2203000022RG01

Rev.: 01 Page: 12 of 29

3.2 T-Coil Measurement Set-up




Fig. 2. T-coil signal measurement test setup

The sequence of the measurement is T-Coil testing procedure over a wireless communication device:

- 1. Confirm Geometry & signal check. Probe phantom alignment and check of accuracy.
- 2. Background noise measurement in the area of the WD.
- 3. Perform 50x50mm area scan with narrow band signal to determine ABM1, ABM2 and SNR for axial and radial orientation positions.
- 4. For Axial position, perform optimal SNR point measurement with a broadband signal determine Frequency Response
- 5. Define the all applicable input audio level according to ANSI C63.19-2011 and KDB 285076 D02v03.

Note.

- #. The EUT do not use the special HAC SW.
- #. Setting the maximum volume for EUT during the measurement.
- #. For the measurement, it don't use the "post-test measurement processing of results".
- #. Per KDB 285076 D01v05, handsets that that have the ability to support concurrent connections using simultaneous transmissions shall be independently tested for each air interface/band given in ANSI C63.19-2011. At the present time ANSI C63.19 does not provide simultaneous transmission test procedures.



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.apx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.apx. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction document. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

**Attention: To check the authenticity of testing /inspection report & certificate_please contact us at telephone: (86-755) \$3071443.

South of No. 6 Pfart, No. 1, Runsheng Road, Suchou Industrial Park, Suchou Area, China (Jiangsu) Pilot Free Trade Zone 215000 中国 - 苏州 - 中国(江苏)自由贸易试验区苏州片区苏州工业园区润胜路1号的6号厂房南部 邮编: 215000

t (86–512) 62992980 www.sgsgroup.com.c t (86–512) 62992980 sgs.china@sgs.com



Report No.: SEWM2203000022RG01

Rev.: 01

13 of 29 Page:

3.3 System Calibration

For correct and calibrated measurement of the voltages and ABM field, DASY will perform a calibration job as below.

In phase 1, the audio output is switched off, and a 200 mVpp symmetric rectangular signal of 1 kHz is generated and internally connected directly to both channels of the sampling unit (Coil in, Probe in).

In phase 2, the audio output is off, and a 20 mVpp symmetric 100 Hz signal is internally connected. The signals during phases 1 and 2 are available at the output on the rear panel of the AMMI. However, the output must not be loaded, in order to avoid influencing the calibration. An RMS voltmeter would indicate 100 mVRMS during the first phase and 10 mVRMS during the second phase. After the first two phases, the two input channels are both calibrated for absolute measurements of voltages. The resulting factors are displayed above the multi-meter window.

After phases 1 and 2, the input channels are calibrated to measure exact voltages. This is required to use the inputs for measuring voltages with their peak and RMS value.

In phase 3, a multi-sine signal covering each third-octave band from 50 Hz to 10 kHz is generated and applied to both audio outputs. The probe should be positioned in the center of the AMCC and aligned in the z-direction, the field orientation of the AMCC. The "Coil In" channel is measuring the voltage over the AMCC internal shunt, which is proportional to the magnetic field in the AMCC. At the same time, the "Probe In" channel samples the amplified

signal picked up by the probe coil and provides it to a numerical integrator. The ratio of the two voltages in each third-octave filter leads to the spectral representation over the frequency band of interest. The Coil signal is scaled in dBV, and the Probe signal is first integrated and normalized to show dB A/m. The ratio probe-to-coil at the frequency of 1 kHz is the sensitivity which will be used in the consecutive T-Coil jobs.



otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions/Terms-en-Document.aspx, is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document that information contained hereon reflects the Company's findings at the time of its intervion only and within the limits of instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a on from exercising all their rights and obligations under the transaction documents. This document common the reproduced in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or need fithis document is unlawful and offenders may be prosecuted to the fullest extent of the .Unless otherwise stated the hown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.



Report No.: SEWM2203000022RG01

Rev.: 01 Page: 14 of 29

3.4 Audio Magnetic Probe AM1DV3

Description	Active single sensor probe for both axial and radial measurement scans- Fully RF shielded, compatible with DAE, with adapted probe cup	1
Dynamic Range	0.1 KHz to 20 KHz	
Sensitivity	<-50dB A/m @ 1KHz	
Internal Amp	20dB	4
Dimensions	300X18mm	
		AM1DV3 Audio Probe

3.5 Test Arch

Description	Enables easy and well defined positioning of the phone and validation dipoles as well as simple teaching of the robot.	
	length: 370 mm width: 370 mm height: 370 mm	Test Arch

3.6 Phone Holder

Supports accurate and reliable positioning of any phone Effect on near field <+/- 0.5 dB	
	Phone Holder



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not excerate parties to a transaction from exercising all their rights and obligations under the transaction document. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawfull and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone (86-755) \$3071443.

South of No. 6 Pfart, No. 1, Runsheng Read, Suchou Industrial Park, Suchou Area, China (Jangsu) Pilot Free Trade Zone 215000 中国 - 苏州 - 中国(江苏)自由贸易试验区苏州片区苏州工业园区润胜路1号的6号厂房南部 邮编: 215000

00 t (86–512) 629929

www.sgsgroup.com.cn sgs.china@sgs.com



Report No.: SEWM2203000022RG01

Rev.: 01 Page: 15 of 29

3.7 AMCC- Audio Magnetic Calibration Coil

Allows calibration of the complete measurement setup, the two horizontal coils create a homogeneous magnetic field in the z direction. Refer to Appendix 5 for more detail on AMCC coil



3.8 AMMI - Audio Magnetic Measurement Instrument

Description	-USB interface to PC - Probe signal digitization and power supply- Test signal generation for wireless device (via base station simulator)- Autocalibration and interfaces to AMCC for complete setup-calibration	AMMI AMMI
Data Rate	48 KHz / 24bit	
Dynamic Range	85 dB	
Dimensions:	19" X 65 X 270mm	





Report No.: SEWM2203000022RG01

Rev.: 01 Page: 16 of 29

4 Measurement uncertainty evaluation

4 Measure	inent unc	citallity eve	aiuatioi				
Error Description	Uncertainty Value (%)	Probability Dist.	Divisor	ci ABM1	ci ABM2	Standard Uncertainty ABM1 (%)	Standard Uncertainty ABM2 (%)
Related to probe sensitivity						,	
Reference level	±3.0	R	$\sqrt{3}$	1	1	±3.0	±3.0
AMCC geometry	±0.4	R	$\sqrt{3}$	1	1	±0.2	±0.2
AMCC current	±0.6	R	$\sqrt{3}$	1	1	±0.4	±0.4
Probe positioning during calibration	±0.2	R	$\sqrt{3}$	1	1	±0.1	±0.1
Noise distribution	±0.7	R	$\sqrt{3}$	0.0143	1	±0.0	±0.4
Frequency slope	±5.9	R	$\sqrt{3}$	0.1	1	±0.3	±3.5
Related to probe system							
Repeatability / drift	±1.0	R	$\sqrt{3}$	1	1	±0.6	±0.6
Linearity / dynamic range	±0.6	N	1	1	1	±0.4	±0.4
Audio noise	±1.0	R	$\sqrt{3}$	0.1	1	±0.1	±0.6
Probe angle	±2.3	R	$\sqrt{3}$	1	1	±1.4	±1.4
Spectral Processing	±0.9	R	$\sqrt{3}$	1	1	±0.5	±0.5
Integration time	±0.6	N	1	1	5	±0.6	±3.0
Field distribution	±0.2	R	$\sqrt{3}$	1	1	±0.1	±0.1
Test signal							
Reference signal spectrum response	±0.6	R	$\sqrt{3}$	0	1	±0.0	±0.4
Positioning							
Probe positioning	±1.9	R	$\sqrt{3}$	1	1	±1.1	±1.1
Phantom Thickness	±0.9	R	$\sqrt{3}$	1	1	±0.5	±0.5
DUT positioning	±1.9	R	$\sqrt{3}$	1	1	±1.1	±1.1
External Contributions							
RF interference	±0.0	R	$\sqrt{3}$	1	0.3	±0.0	±0.0
Test Signal Variation	±2.0	R	$\sqrt{3}$	1	1	±1.2	±1.2
Combined Std. Uncertainty (ABM Field)		$u_c' = \sqrt{\sum_{i=1}^{20}}$	$c_i^2 u_i^2$			±4.1	±6.2
Expanded Std. Uncertainty (K=2)						±8.2	±12.4

Table 2: Measurement uncertainties for T-Coil



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company, Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@gs.com

South of No. 6 Plant, No. 1, Runsheng Road, Suchou Industrial Park, Suzhou Area, China (Jiangsu) Plot Free Trade Zone 中国 - 苏州 - 中国(江苏)自由贸易试验区苏州片区苏州工业园区润胜路1号约6号厂房南部 邮编: 215000

t (86–512) 62992980 t (86–512) 62992980

www.sgsgroup.com.cn sgs.china@sgs.com



Report No.: SEWM2203000022RG01

Rev.: 01 Page: 17 of 29

HAC (T-Coil) Measurement 5

5.1 T-Coil Performance Requirements

In order to be rated for T-Coil use, a WD shall meet the requirements for signal level and signal quality contained in this part.

1) T-Coil coupling field intensity

When measured as specified in ANSI C63.19, the T-Coil signal shall be ≥ -18 dB (A/m) at 1 kHz, in a 1/3 octave band filter for all orientations.

2) Frequency response

The frequency response of the axial component of the magnetic field, measured in 1/3 octave bands, shall follow the response curve specified in this sub-clause, over the frequency range 300 Hz to 3000 Hz. Figure 1 and Figure 2 provide the boundaries for the specified frequency.

These response curves are for true field strength measurements of the T-Coil signal. Thus the 6 dB/octave probe response has been corrected from the raw readings.




Figure 1—Magnetic field frequency response for WDs with a field ≤ -15 dB (A/m) at 1 kHz



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.ags.com/en/Terms-and-Conditions.agx; and, for electronic Documents at http://www.ags.com/en/Terms-and-Conditions/Terms-e-Document as public to Terms and Conditions for Telectronic Document as http://www.ags.com/en/Terms-and-Conditions/Terms-e-Document as public to the state of the stat

South of No. 6 Plant, No. 1, Runsheng Road, Suzhou Industrial Park, Suzhou Area, China (Jiangsu) Pilot Free Trade Zone 215000 中国•苏州•中国(江苏)自由贸易试验区苏州片区苏州工业园区润胜路1号的6号厂房南部 邮编: 215000



Report No.: SEWM2203000022RG01

Rev.: 01 Page: 18 of 29




Figure 2 —Magnetic field frequency response for WDs with a field that exceeds -15dB(A/m) at 1 kHz

3) Signal quality

This part provides the signal quality requirement for the intended T-Coil signal from a WD. Only the RF immunity of the hearing aid is measured in T-Coil mode. It is assumed that a hearing aid can have no immunity to an interference signal in the audio band, which is the intended reception band for this mode. So, the only criteria that can be measured is the RF immunity in T-Coil mode. This is measured using the same procedure as for the audio coupling mode and at the same levels.

The worst signal quality of the three T-Coil signal measurements shall be used to determine the T-Coil mode category per Table 3

Category	Telephone parameters WD signal quality [(signal + noise) – to – noise ratio in decibels]
Category T1	0 dB to 10 dB
Category T2	10 dB to 20 dB
Category T3	20 dB to 30 dB
Category T4	> 30 dB

Table 3: T-Coil signal quality categories



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.ags.com/en/Terms-and-Conditions.agx; and, for electronic Documents at http://www.ags.com/en/Terms-and-Conditions/Terms-e-Document as public to Terms and Conditions for Telectronic Document as http://www.ags.com/en/Terms-and-Conditions/Terms-e-Document as public to the state of the stat

South of No. 6 Pfart, No. 1, Runsheng Road, Suchou Industrial Park, Suchou Area, China (Jiangsu) Pilot Free Trade Zone 215000 中国 - 苏州 - 中国(江苏)自由贸易试验区苏州片区苏州工业园区润胜路1号的6号厂房南部 邮编: 215000

t (86–512) 62992980 t (86–512) 62992980



Report No.: SEWM2203000022RG01

Rev.: 01 Page: 19 of 29

5.2 T-Coil measurement points and reference plane

Figure 3 illustrate the references and reference plane that shall be used in a typical EUT emissions measurement. The principle of this section is applied to EUT with similar geometry. Please refer to Appendix C for the setup photographs.

- ◆ The area is 5 cm by 5 cm.
- The area is centered on the audio frequency output transducer of the EUT.
- ♦ The area is in a reference plane, which is defined as the planar area that contains the highest point in the area of the phone that normally rests against the user's ear. It is parallel to the centerline of the receiver area of the phone and is defined by the points of the receiver-end of the EUT handset, which, in normal handset use, rest against the ear.
- ◆ The measurement plane is parallel to, and 10 mm in front of, the reference plane.




Figure 3 Axis and planes for WD audio frequency magnetic field measurements



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.ags.com/en/Terms-and-Conditions.agx; and, for electronic Documents at http://www.ags.com/en/Terms-and-Conditions/Terms-e-Document as public to Terms and Conditions for Telectronic Document as http://www.ags.com/en/Terms-and-Conditions/Terms-e-Document as public to the state of the stat

South of No. 6 Pfart, No. 1, Runsheng Road, Suchou Industrial Park, Suchou Area, China (Jiangsu) Pilot Free Trade Zone 215000 中国 - 苏州 - 中国(江苏)自由贸易试验区苏州片区苏州工业园区润胜路1号的6号厂房南部 邮编: 215000

t (86–512) 62992980 www.sgsgroup.com. t (86–512) 62992980 sgs.china@sgs.com



Report No.: SEWM2203000022RG01

Rev.: 01 20 of 29 Page:

5.3 T-Coil Measurement Procedure

According to ANSI C63.19-2011, section 7.4:

This section describes the procedures used to measure the ABM (T-Coil) performance of the WD. In addition to measuring the absolute signal levels, the A-weighted magnitude of the unintended signal shall also be determined. To assure that the required signal quality is measured, the measurement of the intended signal and the measurement of the unintended signal must be made at the same location for each measurement position. In addition, the RF field strength at each measurement location must be at or below that required for the assigned category.

Measurements shall not include undesired properties from the WD's RF field; therefore, use of a coaxial connection to a base station simulator or nonradiating load might be necessary. However, even with a coaxial connection to a base station simulator or nonradiating load, there might still be RF leakage from the WD, which can interfere with the desired measurement. Premeasurement checks should be made to avoid this possibility. All measurements shall be performed with the WD operating on battery power with an appropriate normal speech audio signal input level given in ANSI C63.19-2011 Table 7.1. If the device display can be turned off during a phone call, then that may be done during the measurement as well.

Measurements shall be performed at two locations specified in ANSI C63.19-2011 A.3, with the correct probe orientation for aparticular location, in a multistage sequence by first measuring the field intensity of the desired T-Coil signal (ABM1) that is useful to a hearing aid T-Coil. The undesired magnetic components (ABM2) shall be examined for each probe orientation to determine the possible effects from the WD display and battery current paths that might disrupt the desired T-Coil signal. The undesired magnetic signal (ABM2) must be measured at the same location as the desired ABM or T-Coil signal (ABM1), and the ratio of desired to undesired ABM signals must be calculated. For the perpendicular field location, only the ABM1 frequency response shall be determined in a third measurement stage.

The following steps summarize the basic test flow for determining ABM1 and ABM2. These steps assume that a sine-wave or narrowband 1/3 octave signal can be used for the measurement of ABM1.

- a) A validation of the test setup and instrumentation may be performed using a TMFS or Helmholtz coil. Measure the emissions and confirm that they are within the specified tolerance.
- b) Position the WD in the test setup and connect the WD RF connector to a base station simulator or a nonradiating load as shown in ANSI C63.19-2011 Figure 7.1 or Figure 7.2. Confirm that the equipment that requires calibration has been calibrated and that the noise level meets the requirements of ANSI C63.19-2011 clause 7.3.1.
- c) The drive level to the WD is set such that the reference input level specified in ANSI C63.19-2011Table 7.1 is input to the base station simulator (or manufacturer's test mode equivalent) in the 1 kHz, 1/3 octave band. This drive level shall be used for the T-Coil signal test (ABM1) at f = 1 kHz. Either a sine wave at 1025 Hz or a voicelike signal, band-limited to the 1 kHz 1/3 octave, as defined in C63.19-2011 clause 7.4.2, shall be used for the reference audio signal. If interference is found at 1025 Hz, an alternative nearby reference audio signal frequency may be used.47 The same drive level shall be used for the ABM1 frequency response measurements at each 1/3 octave band center frequency. The WD volume control may be set at any level up to maximum, provided that a signal at any frequency at maximum modulation would not result in clipping or signal overload.
- d) Determine the magnetic measurement locations for the WD device (A.3), if not already specified by the manufacturer, as described in C63.19-2011 clause 7.4.4.1.1 and 7.4.4.2.
- e) At each measurement location, measure and record the desired T-Coil magnetic signals (ABM1 at fi) as specified in C63.19-2011 clause 7.4.4.2 in each ISO 266-1975 R10 standard 1/3 octave band. The desired audio band input frequency (fi) shall be centered in each 1/3 octave band maintaining the same drive level as determined in item c) and the reading taken for that band.
- f) Equivalent methods of determining the frequency response may also be employed, such as fast Fourier transform (FFT) analysis using noise excitation or input-output comparison using simulated speech. The full-band integrated or half-band integrated probe output, as specified in D.9, may be used, as long as the appropriate calibration curve is applied to the measured result, so as to yield an accurate measurement of the field magnitude. (The resulting measurement shall be an accurate measurement in dB A/m.)



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sag.com/en/Terms-and-Conditions.aspx.and. for electronic Documents at <a href="http://www.sag.com/en/Terms-en/Conditions/Terms-en/Co

South of No. 6 Plant, No. 1, Runsheng Road, Suzhou Industrial Park, Suzhou Area, China (Jiangsu) Pilot Free Trade Zone 215000 中国•苏州•中国(江苏)自由贸易试验区苏州片区苏州工业园区润胜路1号的6号厂房南部 邮编: 215000



Report No.: SEWM2203000022RG01

Rev.: 01 Page: 21 of 29

g) All measurements of the desired signal shall be shown to be of the desired signal and not of an undesired signal. This may be shown by turning the desired signal ON and OFF with the probe measuring the same location. If the scanning method is used, the scans shall show that all measurement points selected for the ABM1 measurement meet the ambient and test system noise criteria in C63.19-2011 clause 7.3.1.

- h) At the measurement location for each orientation, measure and record the undesired broadband audio magnetic signal (ABM2) as specified in C63.19-2011 clause 7.4.4.4 with no audio signal applied (or digital zero applied, if appropriate) using A-weighting49 and the half-band integrator. Calculate the ratio of the desired to undesired signal strength (i.e., signal quality).
- g) Determine the category that properly classifies the signal quality, based on C63.19-2011 Table 8.5.



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.ags.com/en/Terms-and-Conditions.agx; and, for electronic Documents at http://www.ags.com/en/Terms-and-Conditions/Terms-e-Document as public to Terms and Conditions for Telectronic Document as http://www.ags.com/en/Terms-and-Conditions/Terms-e-Document as public to the state of the stat

South of No. 6 Pfart, No. 1, Runsheng Road, Suchou Industrial Park, Suchou Area, China (Jiangsu) Pilot Free Trade Zone 215000 中国 - 苏州 - 中国(江苏)自由贸易试验区苏州片区苏州工业园区润胜路1号的6号厂房南部 邮编: 215000

(86–512) 62992980 www.sgsgroup.com. (86–512) 62992980 sgs.china@sgs.com



Report No.: SEWM2203000022RG01

Rev.: 01 Page: 22 of 29

6 T-Coil testing for CMRS Voice

6.1 General Description

1. Codec Investigation:

For a voice service/air interface, investigate the variations of codec configurations (WB, NB bit rate) and document the parameters (ABM1, ABM2, S+N/N, frequency response) for that voice service. It is only necessary to document this for one channel/band, the following worst investigation codec would be remarked to be used for the testing for the handset.

2. Air Interface Investigation:

- a. Use the worst-case codec test and document a limited set of bands/channel/bandwidths. Observe the effect of changing the band and bandwidth to ensure that there are no unexpected variations. Using the knowledge of the observed variations, it is necessary to report only a set band/channel/bandwidth for each orientation for a voice service/air interface.
- b. According to the ANSI C63.19 2011 section 7.3.2, test middle channel of each frequency band for HAC testing for each orientation to determine worst HAC T-Coil rating.

6.2 UMTS Tests Results

Codec Investigation:

Band Test Mode		Test Ch./Freq.	Probe Position	ABM1 (dBA/m)	ABM2	Signal Quality	T Rating	Freq. Response Variation	Frequency Response	Codec Setting
			Position	(UDA/III)	(ubA/III)	(dB)		(dB)	Response	
	AMR Voice	4182/836.4	Axial (Z)	-8.30	-41.53	33.23	T4	1.54	PASS	4.75kbps
WCDMA Band V	AMR Voice	4182/836.4	Axial (Z)	-10.29	-41.76	31.47	T4	0.79	PASS	7.95kbps
	AMR Voice	4182/836.4	Axial (Z)	-7.69	-38.91	31.22	T4	1.80	PASS	12.2kbps

Remark: According to codec investigation, the worst codec is 12.2kbps

Air Interface Investigation:

Band	Test Mode	Test Ch./Freq.	Probe Position	ABM1 (dBA/m)	ABM2 (dBA/m)	Signal Quality (dB)	T Rating	Freq. Response Variation (dB)	Frequency Response	Codec Setting
WCDMA	AMR	9400/1900	Axial (Z)	-9.45	-41.28	31.83	T4	1.45	PASS	12.2kbps
Band II	Voice	9400/1900	Transversal (Y)	-16.64	-41.21	24.57	T3	/	/	12.2kbps
WCDMA	AMR	1412/1732.	Axial (Z)	-6.18	-38.17	31.99	T4	2.00	PASS	10 Olaha a
Band IV	Voice	4	Transversal (Y)	-15.20	-40.79	25.59	Т3	/	/	12.2kbps
WCDMA	AMR	4402/026 4	Axial (Z)	-7.69	-38.91	31.22	T4	1.80	PASS	12.2kbps
Band V	4182/836		Transversal (Y)	-14.64	-40.71	26.07	Т3	/	/	12.28005

Remark:

- 1. Phone Condition: Mute on; Backlight off; Max Volume
- 2. The detail frequency response results please refer to appendix A.



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.apx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.apx. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction document. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

South of No. 6 Pfart, No. 1, Runsheng Road, Suchou Industrial Park, Suchou Area, China (Jiangsu) Pilot Free Trade Zone 中国 - 苏州 - 中国(江苏)自由贸易试验区苏州片区苏州工业园区润胜路1号的6号厂房南部 邮编: 215000

(86–512) 62992980 www.sgsgroup.com.ci (86–512) 62992980 sgs.china@sgs.com



Report No.: SEWM2203000022RG01

Rev.: 01 Page: 23 of 29

7 T-Coil testing for CMRS IP Voice

7.1 VoLTE Tests Results

1. Codec Investigation:

For a voice service/air interface, investigate the variations of codec configurations (WB, NB bit rate) and document the parameters (ABM1, ABM2, S+N/N, frequency response) for that voice service. It is only necessary to document this for one channel / band, the following worst investigation codec would be remarked to be used for the testing for the handset.

2. Air Interface Investigation:

- a. Use the worst-case codec test and document a limited set of bands / channel / bandwidths. Observe the effect of changing the band and bandwidth to ensure that there are no unexpected variations. Using the knowledge of the observed variations, it is necessary to report only a set band/channel/bandwidth for each orientation for a voice service/air interface and the following worst configure would be remarked to be used for the testing for the handset.
- b. Select LTE FDD one frequency band to do measurement at the worst SNR single point position was additionally performed with varying the BWs/Modulations/RB size to verify the variation to find out worst configuration, the observed variation is very little to be within 1.5 dB which is much less than the margin from the rating threshold.
- c. According to the ANSI C63.19 2011 section 7.3.2, test middle channel of each frequency band for HAC testing for each orientation to determine worst HAC T-Coil rating.

Codec Investigation:

Codec inve	onganon.									
LTE FDD Band	Test Mode	Test Ch./Freq.	Probe Position	ABM1 (dBA/m)	ABM2 (dBA/m)	Signal Quality (dB)		Freq. Response Variation (dB)	Frequency Response	Codec Setting
	20M QPSK 1RB_0	18900/1880	Axial (Z)	-5.27	-43.45	38.18	T4	1.71	PASS	WB AMR 6.60kbps
	20M QPSK 1RB_0	18900/1880	Axial (Z)	-4.09	-42.96	38.87	T4	0.82	PASS	WB AMR 12.65kbps
	20M QPSK 1RB_0	18900/1880	Axial (Z)	-3.56	-43.63	40.07	T4	0.62	PASS	NB AMR 4.75kbps
LTE Band 2	20M QPSK 1RB_0	18900/1880	Axial (Z)	-6.55	-46.02	39.47	T4	1.49	PASS	NB AMR 12.2kbps
LIE Band 2	20M QPSK 1RB_0	18900/1880	Axial (Z)	-6.40	-33.22	26.82	T3	1.18	PASS	WB EVS 5.90kbps
	20M QPSK 1RB_0	18900/1880	Axial (Z)	-3.78	-30.90	27.12	T3	0.85	PASS	WB EVS 13.2kbps
	20M QPSK 1RB_0	18900/1880	Axial (Z)	-3.90	-30.28	26.38	Т3	2.00	PASS	NB EVS 5.90kbps
	20M QPSK 1RB_0	18900/1880	Axial (Z)	-4.69	-34.15	29.46	T3	2.00	PASS	NB EVS 9.60kbps

Remark: According to codec investigation, the worst codec is NB EVS 5.90kbps

Air Interface Investigation:

LTE FDD

LIEFUU							
LTE FDD Band	Test Mode	Test Ch./Freq.	Probe Position	ABM1 (dBA/m)	ABM2 (dBA/m)	Signal Quality (dB)	T Rating
	20M QPSK 1RB_0	18900/1880	Axial (Z)	-3.09	-27.98	24.89	Т3
	20M QPSK 1RB_50	18900/1880	Axial (Z)	-3.00	-27.50	24.50	Т3
	20M QPSK 1RB_99	18900/1880	Axial (Z)	-2.97	-27.12	24.15	Т3
LTE Band 2	20M QPSK 50RB_0	18900/1880	Axial (Z)	-2.82	-27.49	24.67	Т3
LIE Ballu Z	20M QPSK 50RB_25	18900/1880	Axial (Z)	-2.78	-27.03	24.25	Т3
	20M QPSK 50RB_50	18900/1880	Axial (Z)	-2.86	-27.09	24.23	Т3
	20M QPSK 100RB_0	18900/1880	Axial (Z)	-2.66	-28.59	25.93	Т3
	20M 16QAM 100RB_0	18900/1880	Axial (Z)	-2.77	-30.58	27.81	Т3



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.appx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions/Terms-a-Document.appx. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawfull and offenders may be prosecuted to the fullest extend of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

**Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) \$3071443.

South of No. 6 Pfart, No. 1, Runsheng Road, Suchou Industrial Park, Suchou Area, China (Jangsu) Pilot Free Trade Zone 215000 中国 - 苏州 - 中国(江苏)自由贸易试验区苏州片区苏州工业园区润胜路1号的6号厂房南部 邮编: 215000

t (86–512) 62992980



Report No.: SEWM2203000022RG01

Rev.: 01

Page: 24 of 29

	15M QPSK 1RB_74	18900/1880	Axial (Z)	-3.02	-28.68	25.66	Т3
Γ	10M QPSK 1RB_49	18900/1880	Axial (Z)	-2.95	-27.86	24.91	Т3
Γ	5M QPSK 1RB_24	18900/1880	Axial (Z)	-2.96	-29.37	26.41	Т3
Γ	3M QPSK 1RB_14	18900/1880	Axial (Z)	-3.05	-28.74	25.69	Т3
	1.4M QPSK 1RB_5	18900/1880	Axial (Z)	-3.03	-28.24	25.21	Т3

Remark:

- Select Worst worst codec Bandwidth/Modulation/RB Size from LTE FDD Test results to do LTE FDD
- 2. Select Worst Bandwidth/Modulation/RB Size from LTE FDD Test results to do LTE FDD

Air interface:

LTE FDD Band	Test Mode	Test Ch./Freq.	Probe Position	ABM1 (dBA/m)	ABM2 (dBA/m)	Signal Quality (dB)	T Rating	Freq. Response Variation (dB)	Frequency Response	Codec Setting	
LTE Band 2	20M QPSK 1RB 99	18900/1880	Axial (Z)	-8.35	-32.71	24.36	Т3	1.42	PASS	NB EVS 5.90kbps	
LTE Ballu 2	20101 QPSK 1RB_99	16900/1660	Transversal (Y)	-8.51	-32.13	23.62	Т3	/	/	NB E V S 5.90KBPS	
LTE Band 4	20M QPSK 1RB 99	20175/1732.5	Axial (Z)	-8.26	-32.81	24.55	Т3	2.00	PASS	NB EVS 5.90kbps	
LTE Ballu 4	20W QF3K TKB_99	20175/1732.5	Transversal (Y)	-8.75	-32.48	23.73	Т3	/	/	NB E V3 3.90kbps	
LTE Band 5	10M ODSK 1DD 40	10M QPSK 1RB 49 2052	20E2E/926 E	Axial (Z)	-3.28	-37.71	34.43	T4	1.91	PASS	NB EVS 5.90kbps
LTE Ballu 5	TOWN QPSK TRB_49	20525/836.5	Transversal (Y)	-8.43	-36.53	28.10	Т3	/	/	NB E V S 5.90KBPS	
LTE Band 12	10M QPSK 1RB 49	23095/707.5	Axial (Z)	-3.32	-39.64	36.32	T4	2.00	PASS	NB EVS 5.90kbps	
LTE Ballu 12	TOWN QPSK TRB_49	23095/707.5	Transversal (Y)	-10.21	-41.25	31.04	T4	/	/	NB E V 3 5.90Kbps	
LTE Band 14	10M QPSK 1RB 49	23330/793	Axial (Z)	0.20	-36.63	36.83	T4	1.60	PASS	NB EVS 5.90kbps	
LTE Bana TT	TOWN QUE ON THE _ TO	200007700	Transversal (Y)	-10.00	-38.70	28.70	Т3	/	/	NB E VS 5.90kbps	
LTE Band 30	10M QPSK 1RB 49	27710/2310	Axial (Z)	0.10	-36.19	36.29	T4	2.00	PASS	NB EVS E 00kbpc	
LTE Ballu 30	TOWN QF3K TRB_49	21110/2310	Transversal (Y)	-8.31	-37.35	29.04	T3	/	1	NB EVS 5.90kbps	

Remark:

- 1. Phone Condition: Mute on; Backlight off; Max Volume
- 2. The detail frequency response results please refer to appendix A.



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.ags.com/en/Terms-and-Conditions.agx; and, for electronic Documents at http://www.ags.com/en/Terms-and-Conditions/Terms-e-Document as public to Terms and Conditions for Telectronic Document as http://www.ags.com/en/Terms-and-Conditions/Terms-e-Document as public to the state of the stat

South of No. 6 Pfart, No. 1, Runsheng Read, Suchou Industrial Park, Suchou Area, China (Jangsu) Pilot Free Trade Zone 215000 中国 - 苏州 - 中国(江苏)自由贸易试验区苏州片区苏州工业园区润胜路1号的6号厂房南部 邮编: 215000

(86–512) 62992980 www.sgsgroup.com.c (86–512) 62992980 sgs.china@sgs.com



Report No.: SEWM2203000022RG01

Rev.: 01 Page: 25 of 29

7.2 VoWiFi Tests Results

1. Codec Investigation:

For a voice service/air interface, investigate the variations of codec configurations (WB, NB bit rate) and document the parameters (ABM1, ABM2, S+N/N, frequency response) for that voice service. It is only necessary to document this for one channel/band, the following worst investigation codec would be remarked to be used for the testing for the handset.

2. Air Interface Investigation:

a. Use the worst-case codec test and document a limited set of bands/channel/bandwidths. Observe the effect of changing the band and bandwidth to ensure that there are no unexpected variations. Using the knowledge of the observed variations, it is necessary to report only a set band/channel/bandwidth for each orientation for a voice service/air interface and the following worst configure would be remarked to be used for the testing for the handset.

b. Select WLAN 2.4GHz and WLAN5GHz one frequency band to do measurement at the worst SNR position was additionally performed with varying the BWs/Modulations/data rate to verify the variation to find out worst configuration, the observed variation is very little to be within 1 dB which is much less than the margin from the rating threshold.

c. According to the ANSI C63.19 2011 section 7.3.2, test middle channel of each frequency band for HAC testing

for each orientation to determine worst HAC T-Coil rating.

Band	Test Mode	Test Ch./Freq.	Probe Position	ABM1 (dBA/m)	ABM2 (dBA/m)	Signal Quality (dB)	T Rating	Freq. Response Variation (dB)	Frequency Response	Codec Setting
	802.11b	6/2437	Axial (Z)	-5.67	-40.19	34.52	T4	1.82	PASS	WB AMR 6.60kbps
	802.11b	6/2437	Axial (Z)	-8.47	-44.75	36.28	T4	0.82	PASS	WB AMR 12.65kbps
	802.11b	6/2437	Axial (Z)	-6.51	-40.22	33.71	T4	1.92	PASS	NB AMR 4.75kbps
WiFi	802.11b	6/2437	Axial (Z)	-7.91	-46.25	38.34	T4	2.00	PASS	NB AMR 12.2kbps
2.4G	802.11b	6/2437	Axial (Z)	-6.33	-32.87	26.54	T3	1.28	PASS	WB EVS 5.90kbps
	802.11b	6/2437	Axial (Z)	-1.04	-30.26	29.22	Т3	1.04	PASS	WB EVS 13.20kbps
	802.11b	6/2437	Axial (Z)	-2.99	-29.36	26.37	T3	2.00	PASS	NB EVS 5.90kbps
	802.11b	6/2437	Axial (Z)	-0.09	-27.62	27.53	T3	1.46	PASS	NB EVS 9.60kbps

Remark: According to codec investigation, the worst codec is NB EVS 5.90kbps.

Air Interface Investigation:

Band	Test Mode	Test Ch./Freq.	Probe Position	ABM1 (dBA/m)	ABM2 (dBA/m)	Signal Quality (dB)	T Rating	Codec Setting
	802.11b	6/2437	Axial (Z)	-3.34	-28.22	24.88	Т3	1Mbps
	802.11b	6/2437	Axial (Z)	-3.20	-29.43	26.23	Т3	11Mbps
	802.11g	6/2437	Axial (Z)	-3.09	-29.36	26.27	T3	6Mbps
M/:F: 0.40	802.11g	6/2437	Axial (Z)	-3.26	-28.50	25.24	T3	54Mbps
WiFi 2.4G	802.11n-HT20	6/2437	Axial (Z)	-2.70	-30.71	28.01	T3	MCS0
	802.11n-HT20	6/2437	Axial (Z)	-3.21	-28.42	25.21	T3	MCS7
	802.11n-HT40	6/2437	Axial (Z)	-3.12	-31.33	28.21	T3	MCS0
	802.11n-HT40	6/2437	Axial (Z)	-3.22	-29.79	26.57	T3	MCS7
	802.11a	40/5200	Axial (Z)	-3.07	-27.77	24.70	T3	6Mbps
	802.11a	40/5200	Axial (Z)	-2.97	-27.93	24.96	T3	54Mbps
WiFi 5G	802.11n-HT20	40/5200	Axial (Z)	-3.00	-30.55	27.55	T3	MCS0
	802.11n-HT20	40/5200	Axial (Z)	-3.06	-28.61	25.55	T3	MCS7
	802.11n-HT40	38/5190	Axial (Z)	-2.98	-28.54	25.56	T3	MCS0
	802.11n-HT40	38/5190	Axial (Z)	-2.88	-27.93	25.05	T3	MCS7



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx.and, for electronic Documents at http://www.sgs.com/en/Terms-and-Conditions/Terms-en/Document.aspx.Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction document cannot be reproduced except in full, without prior written approval of the Company, Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawfull and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention:To check the authenticity of testing /inspection report & certificate_please contact us at telephone (86-755) \$3071443.

South of No. 6 Pfart, No. 1, Runsheng Road, Suchou Industrial Park, Suchou Area, China (Jiangsu) Pilot Free Trade Zone 中国 - 苏州 - 中国(江苏)自由贸易试验区苏州片区苏州工业园区润胜路1号的6号厂房南部 邮编: 215000

t (86–512) 62992980



Report No.: SEWM2203000022RG01

Rev.: 01

Page: 26 of 29

			- 0			-	
802.11ac-VHT20	40/5200	Axial (Z)	-3.16	-30.58	27.42	Т3	MCS0
802.11ac-VHT20	40/5200	Axial (Z)	-2.95	-28.97	26.02	T3	MCS8
802.11ac-VHT40	38/5190	Axial (Z)	-3.05	-28.08	25.03	Т3	MCS0
802.11ac-VHT40	38/5190	Axial (Z)	-2.86	-28.42	25.56	T3	MCS8
802.11ac-VHT80	50/5250	Axial (Z)	-3.09	-27.84	24.75	T3	MCS0
802.11ac-VHT80	50/5250	Axial (Z)	-3.33	-29.27	25.94	T3	MCS8

Remark: According to codec investigation, WiFi 2.4G the worst codec is **802.11b 1Mbps**, WiFi 5G the worst codec is **802.11a 6Mbps**.

Air interface:

Band	Test Mode	Test Ch./Freq.	Probe Position	ABM1 (dBA/m)	ABM2 (dBA/m)	Signal Quality (dB)	T Rating	Freq. Response Variation (dB)	Frequency Response	Codec Setting
WiFi 2.4G	802.11b	6/2437	Axial (Z)	-2.99	-29.36	26.37	Т3	2.00	PASS	1Mbps
VII 1 2.4G	002.110	0/2437	Transversal (Y)	-10.73	-36.68	25.95	T3	/	/	rivips
WiEi EC	WiFi 5G 802.11a	40/5200	Axial (Z)	-1.10	-36.57	35.47	T4	2.00	PASS	6Mbps
WIFI 3G			Transversal (Y)	-7.97	-37.84	29.87	T3	/	/	
WiFi 5G	802.11a	60/5300	Axial (Z)	-11.07	-36.99	25.92	Т3	0.67	PASS	- 6Mbps
WIFI 5G	WIF1 5G 802.11a		Transversal (Y)	-8.86	-33.33	24.47	Т3	/	/	
WiFi 5G	W.E. 20	124/5620	Axial (Z)	-1.59	-27.92	26.33	Т3	2.00	PASS	GMbpo
WIFI 5G 80	802.11a		Transversal (Y)	-10.75	-37.21	26.46	Т3	/	/	- 6Mbps
WiFi 5G	802.11a	157/5785	Axial (Z)	-4.18	-41.94	37.76	T4	1.40	PASS	6Mbps
VVII 13G	802.11a		Transversal (Y)	-8.80	-39.24	30.44	T4	/	/	

Remark:

- 1. Phone Condition: Mute on; Backlight off; Max Volume
- 2. The detail frequency response results please refer to appendix A.



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.ags.com/en/Terms-and-Conditions.agx; and, for electronic Documents at http://www.ags.com/en/Terms-and-Conditions/Terms-e-Document as public to Terms and Conditions for Telectronic Document as http://www.ags.com/en/Terms-and-Conditions/Terms-e-Document as public to the state of the stat

South of No. 6 Pfart, No. 1, Runsheng Read, Suchou Industrial Park, Suchou Area, China (Jangsu) Pilot Free Trade Zone 215000 中国 - 苏州 - 中国(江苏)自由贸易试验区苏州片区苏州工业园区润胜路1号的6号厂房南部 邮编: 215000

t (86–512) 62992980 www.sgsgroup.com. t (86–512) 62992980 sgs.china@sgs.com



Report No.: SEWM2203000022RG01

Rev.: 01 Page: 27 of 29

7.3 T-Coil testing for OTT VoIP Application

- 1. According to the ANSI C63.19 2011 section 7.3.2, test middle channel of each frequency band for HAC testing for each orientation to determine worst HAC T-Coil rating.
- 2. The google Duo VoIP application are pre-installed on this device. According to KDB 285076 D02, all air interfaces via a data connection with VoIP application need to be considered HAC testing.
- 3. The Google Duo only support OPUS audio codec and support 6kbps to 75kbps bitrate.
- 4. The test setup used for OTT VoIP call is the DUT connect to the CMW500 and via the data application unit on CMW500 connection to the Internet, the Auxiliary EUT is connected to the WiFi access point, the channel/Modulation/Frequency bands/data rate is configured on the CMW500 for the DUT unit. For the Auxiliary VoIP unit which is used to configure the audio codec rate and determine the audio input level of 20dBm0 based on the KDB 285076 D02v03 requirement.
- 5. Codec Investigation: For a voice service/air interface, investigate the variations of codec configurations (WB, NB bit rate) and document the parameters (ABM1, ABM2, S+N/N, frequency response) for that voice service. It is only necessary to document this for one channel/band, the following tests results which the worst case codec would be remarked to be used for the testing for the handset.
- 6. Air Interface Investigation:
- a. Use the worst-case codec test and document a limited set of bands/channel/bandwidths. Observe the effect of changing the band and bandwidth to ensure that there are no unexpected variations. Using the knowledge of the observed variations, it is necessary to report only a set band/channel/bandwidth for each orientation for a voice service/air interface.

Codec Investigation:

LTE FDD:

LTE FDD Band	Test Mode	Test Ch./Freq.	Probe Position	ABM1 (dBA/m)	ABM2 (dBA/m)	Signal Quality (dB)	T Rating	Freq. Response Variation (dB)	Frequency Response	Codec Setting
LTE Band 2	20M QPSK 1RB_99	18900/1880	Axial (Z)	1.88	-45.51	47.39	T4	1.11	PASS	OPUS 6kbps
LTE Band 2	20M QPSK 1RB_99	18900/1880	Axial (Z)	4.86	-43.06	47.92	T4	0.34	PASS	OPUS 40kbps
LTE Band 2	20M QPSK 1RB_99	18900/1880	Axial (Z)	2.38	-46.57	48.95	T4	0.54	PASS	OPUS 75kbps

Remark: According to codec investigation, the worst codec bitrate is **OPUS 6kbps**.

WIFI:

Band	Test Mode	Test Ch./Freq.	Probe Position	ABM1 (dBA/m)		Signal Quality (dB)	T Rating	Freq. Response Variation (dB)	Frequency Response	Codec Setting
		6/2437	Axial (Z)	0.88	-40.53	41.41	T4	1.16	PASS	6Mbps,OPUS 6kbps
WiFi 2.4G	802.11b	6/2437	Axial (Z)	3.62	-42.62	46.24	T4	0.74	PASS	6Mbps,OPUS 40kbps
		6/2437	Axial (Z)	3.75	-42.74	46.49	T4	0.42	PASS	6Mbps,OPUS 75kbps
WiFi 5G	802.11a	60/5300	Axial (Z)	0.66	-44.83	45.49	T4	1.37	PASS	6Mbps,OPUS 6kbps
		60/5300	Axial (Z)	2.51	-43.60	46.11	T4	0.56	PASS	6Mbps,OPUS 40kbps
		60/5300	Axial (Z)	5.75	-41.34	47.09	T4	0.48	PASS	6Mbps,OPUS 75kbps

Remark: According to codec investigation, WiFi 2.4G the worst codec is **OPUS 6kbps**, WiFi 5G the worst codec is **OPUS 6kbps**



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.appx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions/Terms-a-Document.appx. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention:To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) \$3071443.

South of No. 6 Pfart, No. 1, Runsheng Road, Suchou Industrial Park, Suchou Area, China (Jiangsu) Pilot Free Trade Zone 中国 - 苏州 - 中国(江苏)自由贸易试验区苏州片区苏州工业园区润胜路1号的6号厂房南部 邮编: 215000

t (86–512) 62992980



Report No.: SEWM2203000022RG01

Rev.: 01 Page: 28 of 29

Air interface:

LTE FDD Band	Test Mode	Test Ch./Freq.	Probe Position	ABM1 (dBA/m)	ABM2 (dBA/m)	Signal Quality (dB)	T Rating	Freq. Response Variation (dB)	Frequency Response	Codec Setting
	LTE Band 2 20M QPSK 1RB_99	18900/1880	Axial (Z)	1.88	-45.51	47.39	T4	1.11	PASS	OPUS 6kbps
LTE Band 2			Transversal (Y)	-3.68	-40.20	36.52	T4	/	/	
		6/2437	Axial (Z)	0.88	-40.53	41.41	T4	1.16	PASS	6Mbps,OPUS
WiFi 2.4G	WiFi 2.4G 802.11b		Transversal (Y)	-4.85	-37.37	32.52	T4	/	/	6kbps
WiFi 5G	802.11a	60/5300	Axial (Z)	0.66	-44.83	45.49	T4	1.37	PASS	6Mbps,OPUS
			Transversal (Y)	-3.93	-39.41	35.48	T4	/	/	6kbps

Remark:

1. Phone Condition: Mute on; Backlight off; Max Volume

2. The detail frequency response results please refer to appendix A.



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not excerate parties to a transaction from exercising all their rights and obligations under the transaction document. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawfull and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone (86-755) \$3071443.



Report No.: SEWM2203000022RG01

Rev.: 01 Page: 29 of 29

8 Equipment list

	Equipment	Manufacturer	Model	Serial Number	Calibration Date	Due date of calibration
	Software	SPEAG	DASY52 52.10.4	NA	NCR	NCR
	DAE	SPEAG	DAE4	1327	2021-11-05	2022-11-04
	Audio Magnetic 1D Field Probe	SPEAG	AM1DV3	3115	2021-06-01	2022-05-31
\boxtimes	Test Arch SD HAC	SPEAG	NA	NA	NCR	NCR
\boxtimes	Audio Magnetic Measuring Instrument	SPEAG	АММІ	1028	NCR	NCR
\boxtimes	Audio Magnetic	SPEAG	AMCC	1143	N/A	N/A
\boxtimes	Universal Radio Communication Tester	R&S	CMW500	169633	2022-02-14	2023-02-13
\boxtimes	Humidity and Temperature Indicator	MingGao	MingGao	NA	2021-06-16	2022-06-15

Note:

- 1. All the equipments are within the valid period when the tests are performed.
- 2. NCR: "No-Calibration Required".

9 Calibration certificate

Please see the Appendix B

10 Photographs

Please see the Appendix C

Appendix A: Detailed Test Results

Appendix B: Calibration certificate

Appendix C: Photographs

---END---



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printe overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic Documents subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions/Terms-en-Document.aspx Attention is advarw to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduce except in full, without prior written approval of the Company, Any unauthorized alteration. Torgety or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are tetalined for 30 days only.