



FCC RF EXPOSURE REPORT

FCC ID: 2A29YPM4204454

Project No. : 2108C034A
Equipment : Premium ONU
Brand Name : 
Test Model : PM4254
Series Model : N/A
Applicant : Radisys Corporation
Address : 8900 NE Walker Road, Suite 130 Hillsboro, OR 97006, USA
Manufacturer : Radisys Corporation
Address : 8900 NE Walker Road, Suite 130 Hillsboro, OR 97006, USA
Factory : Shenzhen Xinfu Electronics Co., Ltd.
Address : 3rd Floor, No.57, Baoli Road, Buji Street, Longgang District, Shenzhen, China
Date of Receipt : Sep. 02, 2021
Date of Test : Sep. 03, 2021 ~ Sep. 25, 2021
Issued Date : Oct. 25, 2021
Report Version : R02
Test Sample : Engineering Sample No.: DG2021090228
Standard(s) : FCC Guidelines for Human Exposure IEEE C95.1 & FCC Part 2.1091
FCC Title 47 Part 2.1091, OET Bulletin 65 Supplement C

The above equipment has been tested and found compliance with the requirement of the relative standards by BTL Inc.



Prepared by : Chella Zheng



Approved by : Ethan Ma



TESTING CERT #5123.02

Add: No. 3 Jinshagang 1st Rd. Shixia, Dalang Town, Dongguan City, Guangdong, People's Republic of China

Tel: +86-769-8318-3000

Web: www.newbtl.com

REPORT ISSUED HISTORY

| Report Version | Description | Issued Date |
|----------------|-------------------------|---------------|
| R00 | Original Issue | Sep. 30, 2021 |
| R01 | Removed a series model. | Oct. 19, 2021 |
| R02 | Removed a series model. | Oct. 25, 2021 |

1. TEST FACILITY

The test facilities used to collect the test data in this report is at the location of No. 3 Jinshagang 1st Rd. Shixia, Dalang Town, Dongguan City, Guangdong, People's Republic of China.

BTL's Test Firm Registration Number for FCC: 357015

BTL's Designation Number for FCC: CN1240

2. MPE CALCULATION METHOD

Calculation Method of RF Safety Distance:

$$S = \frac{PG}{4\pi^2} = \frac{EIRP}{4\pi^2}$$

where:

S = power density



P = power input to the antenna

G = power gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the center of radiation of the antenna

Antenna Specification:



For 2.4GHz:

| Ant. | Brand | P/N | Antenna Type | Connector | Gain (dBi) |
|------|--|--------------|--------------|----------------|------------|
| 1 |  | NB180-D220BX | Internal | Mini Connector | 2.92 |
| 2 |  | NB180-D220BX | Internal | Mini Connector | 2.92 |

Note:

- This EUT supports CDD, and all antennas have the same gain, Directional gain = $G_{ANT} + \text{Array Gain}$. For power measurements, Array Gain=0dB ($N_{ANT} \leq 4$), so the Directional gain=2.92. For power spectral density measurements, $N_{ANT}=2$, $N_{SS} = 1$. So the Directional gain= $G_{ANT} + \text{Array Gain} = G_{ANT} + 10\log(N_{ANT}/N_{SS})\text{dBi} = 2.92 + 10\log(2/1)\text{dBi} = 5.93$.
- The antenna gain is provided by the manufacturer.

For 5GHz:

| Ant. | Brand | P/N | Antenna Type | Connector | Gain (dBi) |
|------|---|--------------|--------------|----------------|------------|
| 1 |  | NB280-D120GX | Internal | Mini Connector | 4.36 |
| 2 |  | NB280-D180GX | Internal | Mini Connector | 3.05 |

Note:

- This EUT supports CDD, and all antenna gains are not equal, so Directional gain= $10\log[(10^{G1/20} + 10^{G2/20} + \dots + 10^{GN/20})^2/N]\text{dBi}$, that is Directional gain= $10\log[(10^{4.36/20} + 10^{3.05/20})^2/2]\text{dBi} = 6.74$. So, the UNII-1, UNII-3 output power limit is $30 - (6.74 - 6) = 29.26$. The UNII-1 power spectral density limit is $17 - (6.74 - 6) = 16.26$, the UNII-3 power spectral density limit is $30 - (6.74 - 6) = 29.26$.
- The antenna gain is provided by the manufacturer.

Table for Antenna Configuration:

For 2.4 GHz:

| Operating Mode | TX Mode | 2TX |
|--------------------|---------|---------------------|
| IEEE 802.11b | | V (Ant. 1 + Ant. 2) |
| IEEE 802.11g | | V (Ant. 1 + Ant. 2) |
| IEEE 802.11n(HT20) | | V (Ant. 1 + Ant. 2) |
| IEEE 802.11n(HT40) | | V (Ant. 1 + Ant. 2) |

For 5GHz:

| Operating Mode | TX Mode | 2TX |
|----------------------|---------|---------------------|
| IEEE 802.11a | | V (Ant. 1 + Ant. 2) |
| IEEE 802.11n(HT20) | | V (Ant. 1 + Ant. 2) |
| IEEE 802.11n(HT40) | | V (Ant. 1 + Ant. 2) |
| IEEE 802.11ac(VHT20) | | V (Ant. 1 + Ant. 2) |
| IEEE 802.11ac(VHT40) | | V (Ant. 1 + Ant. 2) |
| IEEE 802.11ac(VHT80) | | V (Ant. 1 + Ant. 2) |

3. TEST RESULTS

For 2.4GHz:

| Antenna Gain (dBi) | Antenna Gain (numeric) | Max. Output Power (dBm) | Max. Output Power (mW) | Power Density (S) (mW/cm ²) | Limit of Power Density (S) (mW/cm ²) | Test Result |
|--------------------|------------------------|-------------------------|------------------------|---|--|-------------|
| 2.92 | 1.9588 | 28.68 | 737.9042 | 0.28771 | 1 | Complies |

For 5GHz:

| Antenna Gain (dBi) | Antenna Gain (numeric) | Max. Output Power (dBm) | Max. Output Power (mW) | Power Density (S) (mW/cm ²) | Limit of Power Density (S) (mW/cm ²) | Test Result |
|--------------------|------------------------|-------------------------|------------------------|---|--|-------------|
| 6.74 | 4.7206 | 19.19 | 82.9851 | 0.07797 | 1 | Complies |

For the max simultaneous transmission MPE:

| Power Density (S) (mW/cm ²) | Power Density (S) (mW/cm ²) | Total | Limit of Power Density (S) (mW/cm ²) | Test Result |
|---|---|---------|--|-------------|
| 2.4GHz | 5GHz | | | |
| 0.28771 | 0.07797 | 0.36568 | 1 | Complies |

Note: The calculated distance is 20 cm.

End of Test Report