

Test report No:
 NIE: 67283RRF.001

Test Report

USA FCC Part 15.247, 15.209 CANADA RSS-247, RSS-Gen

Radio Frequency Devices. Operation within the bands 902 - 928 MHz, 2400 - 2483.5 MHz, and 5725 - 5850 MHz.

Digital Transmission Systems (DTSs), Frequency Hopping Systems (FHSs) and Licence-Exempt Local Area Network (LE-LAN) Devices.

General Requirements and Information for the Certification of Radio Apparatus.

(*) Identification of item tested	Charging dock with Bluetooth beacon transmitter
(*) Trademark	Navigil
(*) Model and /or type reference	BC
Other identification of the product	HW version: C SW version: 1.0 FCC ID: 2A2AY-N5BC IC: ---
(*) Features	Bluetooth beacon transmitter.
Applicant	Navigil USA Corp. 3739 Pinehurst Drive, Holiday, FL 34691, USA
Test method requested, standard	USA FCC Part 15.247 (10-1-19) Edition: Operation within the bands 902 - 928 MHz, 2400 -2483.5 MHz, and 5725 - 5850 MHz. USA FCC Part 15.209 (10-1-19) Edition: Radiated emission limits; general requirements. CANADA RSS-247 Issue 2 (February 2017). CANADA RSS-Gen Issue 5 Amendment 1 (March 2019). Guidance for Performing Compliance Measurements on Digital Transmission System, Frequency Hopping Spread Spectrum System, and Hybrid Systems Devices Operating Under Section 15.247 of the FCC Rules. 558074 D01 Meas Guidance v05r02 dated April 2, 2019. ANSI C63.10-2013: American National Standard for Testing Unlicensed Wireless Devices.
Summary	IN COMPLIANCE
Approved by (name / position & signature)	Jose Manuel Gómez Galván Industrial & Automotive EMC Lab Manager
Date of issue	2021-08-18
Report template No	FDT08_23 (*) "Data provided by the client"

Index

Competences and guarantees	3
General conditions	3
Uncertainty	3
Data provided by the client.....	3
Usage of samples	4
Test sample description	5
Identification of the client.....	6
Testing period and place.....	6
Document history	6
Environmental conditions	6
Remarks and comments	7
Testing verdicts.....	8
Summary	8
Appendix A: Test results. Bluetooth Low Energy 1Mbps	9

Competences and guarantees

DEKRA Testing and Certification S.A.U. is a testing laboratory accredited by the National Accreditation Body (ENAC -Entidad Nacional de Acreditación), to perform the tests indicated in the Certificate No. 51/LE 147.

DEKRA Testing and Certification is a FCC-recognized accredited testing laboratory with appropriate scope of accreditation that include testing performed in this test report.

DEKRA Testing and Certification is an ISED-recognized accredited testing laboratory with appropriate scope of accreditation that include testing performed in this test report.

In order to assure the traceability to other national and international laboratories, DEKRA Testing and Certification S.A.U. has a calibration and maintenance program for its measurement equipment.

DEKRA Testing and Certification S.A.U. guarantees the reliability of the data presented in this report, which is the result of the measurements and the tests performed to the item under test on the date and under the conditions stated on the report and, it is based on the knowledge and technical facilities available at DEKRA Testing and Certification S.A.U. at the time of performance of the test.

DEKRA Testing and Certification S.A.U. is liable to the client for the maintenance of the confidentiality of all information related to the item under test and the results of the test.

The results presented in this Test Report apply only to the particular item under test established in this document.

IMPORTANT: No parts of this report may be reproduced or quoted out of context, in any form or by any means, except in full, without the previous written permission of DEKRA Testing and Certification S.A.U.

General conditions

1. This report is only referred to the item that has undergone the test.
2. This report does not constitute or imply on its own an approval of the product by the Certification Bodies or competent Authorities.
3. This document is only valid if complete; no partial reproduction can be made without previous written permission of DEKRA Testing and Certification S.A.U.
4. This test report cannot be used partially or in full for publicity and/or promotional purposes without previous written permission of DEKRA Testing and Certification S.A.U. and the Accreditation Bodies.

Uncertainty

Uncertainty (factor $k=2$) was calculated according to the DEKRA Testing and Certification S.A.U. internal document PODT000.

Data provided by the client

The following data has been provided by the client:

1. Information relating to the description of the sample ("Identification of the item tested", "Trademark", "Model and/or type reference tested").
2. The sample of the model S4DS1 is a Charging dock for the Navigil 580 watch. The dock has also internal Bluetooth beacon transmitter.

DEKRA Testing and Certification S.A.U. declines any responsibility with respect to the information provided by the client and that may affect the validity of result.

Usage of samples

Samples undergoing test have been selected by: The client.

- Sample S/01 is composed of the following elements:

Control Nº	Description	Model	Serial Nº	Date of reception
67283/003	Charging dock	BC	1000003845S	2021/04/22
67283/006	USB Cable	--	--	2021/04/22
67283/008	AC/DC Adapter	SWI5-5N-I38		2021/04/22

Sample S/01 has undergone the following test(s): All Radiated tests indicated in Appendix A.

- Sample S/02 is composed of the following elements:

Control Nº	Description	Model	Serial Nº	Date of reception
67283/004	Charging dock	BC	1000003844S	2021/04/22
67283/006	USB Cable	--	--	2021/04/22
67283/008	AC/DC Adapter	SWI5-5N-I38		2021/04/22

Sample S/02 has undergone the following test(s): All Conducted tests indicated in Appendix A.

Test sample description

Ports..... :	Port name and description		Cable				
			Specified max length [m]	Attached during test	Shielded	Coupled to patient ⁽³⁾	
	<i>Power supply</i>		3	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	
Supplementary information to the ports..... :	USB 5VDC power supply from provided AC wall charger. Connected to the watch via charging dock.						
Rated power supply	Voltage and Frequency		Reference poles				
			L1	L2	L3	N	PE
	<input type="checkbox"/>	AC:	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
<input checked="" type="checkbox"/>	DC: 5V from AC wall charger						
Rated Power							
Clock frequencies..... :							
Other parameters							
Software version							
Hardware version							
Dimensions in cm (W x H x D)							
Mounting position	<input checked="" type="checkbox"/>	Table top equipment					
	<input type="checkbox"/>	Wall/Ceiling mounted equipment					
	<input type="checkbox"/>	Floor standing equipment					
	<input type="checkbox"/>	Hand-held equipment					
	<input type="checkbox"/>	Other:					
Modules/parts..... :	Module/parts of test item		Type		Manufacturer		
Accessories (not part of the test item)	Description		Type		Manufacturer		
	AC Wall charger		SWI5-5-I38		CUI Inc.		
Documents as provided by the applicant	Description		File name		Issue date		
	---		---		---		

⁽³⁾ Only applicable to medical equipments

Identification of the client

Navigil Oy
Karaportti 5, 02610 Espoo, FINLAND

Testing period and place

Test Location	DEKRA Testing and Certification S.A.U.
Date (start)	2021-05-03
Date (finish)	2021-05-12

Document history

Report number	Date	Description
67283RRF.001	2021-08-18	First release.

Environmental conditions

In the control chamber, the following limits were not exceeded during the test:

Temperature	Min. = 15 °C Max. = 35 °C
Relative humidity	Min. = 20 % Max. = 75 %

In the semianechoic chamber, the following limits were not exceeded during the test.

Temperature	Min. = 15 °C Max. = 35 °C
Relative humidity	Min. = 20 % Max. = 75 %

In the chamber for conducted measurements, the following limits were not exceeded during the test:

Temperature	Min. = 15 °C Max. = 35 °C
Relative humidity	Min. = 20 % Max. = 75 %

Remarks and comments

The tests have been performed by the technical personnel: Miguel Manuel López, Alfonso Gutiérrez and Verónica García.

Used instrumentation:

Conducted Measurements:

	Last Calibration	Due Calibration
1. Shielded room ETS LINDGREN S101	N.A.	N.A.
2. Signal and Spectrum Analyzer 10Hz-40GHz Rohde and Schwarz FSV40	2021/02	2023/02
3. Extension for OPEN SWITCH UNIT OSP- B157WX Up to 40GHz ROHDE AND SCHWARZ	2019/10	2021/10
4. OPEN SWITCH UNIT UP TO 6 GHz OSP- B157W8 ROHDE AND SCHWARZ	2019/09	2021/09

Radiated Measurements:

	Last Calibration	Due Calibration
1. Semianechoic Absorber Lined Chamber ETS LINDGREN FACT 3 200 STP	N.A.	N.A.
2. Shielded Room ETS LINDGREN S101	N.A.	N.A.
3. Hybrid Bilog Antenna 30 MHz - 6 GHz ETS LINDGREN 3142E	2020/10	2023/10
4. Pre-amplifier G>40dB 10MHz-6GHz Bonn Elektronik BLNA 0160-01N	2021/03	2022/03
5. EMI Test Receiver 7 GHz ROHDE AND SCHWARZ ESR7	2019/10	2021/10
6. Horn antenna 1-18 GHz SCHWARZBECK BBHA 9120 D	2020/08	2023/08
7. Pre-amplifier, G>30 dB ,1-18 GHz BONN ELEKTRONIK BLMA 0118-3A	2020/10	2021/10
8. Signal and spectrum analyzer 10Hz-40GHz Rhode and Schwarz FSV40	2019/10	2021/10
9. Broadband Horn antenna 18 - 40 GHz SCHWARZBECK MESS-ELEKTRONIK BBHA 9170	2020/05	2023/05
10. Pre-amplifier G>30dB 18-40 GHz BONN ELEKTRONIK BLMA 1840-3G	2019/11	2021/11

Testing verdicts

Not applicable:	N/A
Pass:	P
Fail:	F
Not measured:	N/M

Summary

Bluetooth Low Energy 1Mbps:

FCC PART 15 PARAGRAPH / RSS-247			
Requirement – Test case		Verdict	Remark
Section 15.247 (a) (2) / RSS-247 5.2. (a)	6 dB Bandwidth	P	
Section 15.247 (b) / RSS-247 5.4. (d)	Maximum output power and antenna gain	P	
Section 15.247 (d) / RSS-247 5.5.	Band-edge emissions compliance (Transmitter)	P	
Section 15.247 (e) / RSS-247 5.2. (b)	Power spectral density	P	
Section 15.247 (d) / RSS-247 5.5.	Emission limitations radiated (Transmitter)	P	
<u>Supplementary information and remarks:</u> None.			

Appendix A: Test results. Bluetooth Low Energy 1Mbps

INDEX

TEST CONDITIONS.....	11
Occupied Bandwidth.....	14
FCC Section 15.247 (a) (2) / RSS-247 5.2 (a) 6 dB Bandwidth	16
FCC Section 15.247 (b) / RSS-247 5.4 (d) Maximum output power and antenna gain.....	18
FCC Section 15.247 (d) / RSS-247 5.5. Band-edge emissions compliance (Transmitter)	21
FCC Section 15.247 (e) / RSS-247 5.2. (b) Power spectral density.....	23
FCC Section 15.247 (d) / RSS-247 5.5. Emission limitations radiated (Transmitter).....	25

TEST CONDITIONS

POWER SUPPLY (V):

V nominal:	5 Vdc.
Type of Power Supply:	AC/DC wall charger.

ANTENNA:

Type of Antenna:	Internal.
Maximum Declared Antenna Gain:	+1.0 dBi

TEST FREQUENCIES:

Low Channel:	2402 MHz
Middle Channel:	2440 MHz
High Channel:	2480 MHz

CONDUCTED MEASUREMENTS:

The equipment under test was set up in a shielded room and it is connected to the spectrum analyzer using a low loss RF cable. The reading of the spectrum analyser is corrected taking into account the cable loss.



The AC supply voltage is applied using an external calibrated power supply with a multimeter.

RADIATED MEASUREMENTS:

All radiated tests were performed in a semi-anechoic chamber. The measurement antenna (Bilog antenna for the range between 30 MHz to 1000 MHz) and 1 GHz-17 GHz Double ridge horn antenna is situated at a distance of 3 m and a distance of 1m for the frequency range 17 GHz-26 GHz (17 GHz-40 GHz horn antenna).


For radiated emissions in the range 17 GHz-26 GHz that is performed at a distance closer than the specified distance, an inverse proportionality factor of 20 dB per decade is used to normalize the measured data for determining compliance.

The equipment under test was set up on a non-conductive platform above the ground plane and the situation and orientation was varied to find the maximum radiated emission. It was also rotated 360° and the antenna height (Bilog antenna and Double ridge horn antenna) was varied from 1 to 4 meters to find the maximum radiated emission.


A resolution bandwidth/video bandwidth of 100 kHz/300 kHz was used for frequencies below 1 GHz and 1MHz/3MHz for frequencies above 1 GHz.

Measurements were made in both horizontal and vertical planes of polarization.


Radiated measurements setup from 30 MHz to 1 GHz:



Radiated measurements setup from 1 GHz to 17 GHz:



Radiated measurements setup $f > 17$ GHz:



Occupied Bandwidth


RESULTS:

- **1M modulation:**

	Low Channel 2402 MHz	Middle Channel 2440 MHz	High Channel 2480 MHz
99% bandwidth (MHz)	1.025	1.025	1.025
Measurement uncertainty (%)	<± 1.40		


Verdict: PASS

- Low Channel:




- Middle Channel:

99% Bandwidth



- High Channel:

99% Bandwidth



FCC 15.247 (a) (2) / RSS-247 5.2 (a) 6 dB Bandwidth

SPECIFICATION:

The minimum 6 dB bandwidth shall be at least 500 kHz.


RESULTS:

- **1M modulation:**

	Low Channel 2402 MHz	Middle Channel 2440 MHz	High Channel 2480 MHz
6 dB Spectrum Bandwidth (kHz)	732.674	732.674	732.674
Measurement uncertainty (%)	<± 1.40		


Verdict: PASS

- Low Channel:




- Middle Channel:

6 dB Bandwidth



- High Channel:

6 dB Bandwidth



FCC 15.247 (b) / RSS-247 5.4 (d) Maximum output power and antenna gain

SPECIFICATION:

For systems using digital modulation in the 2400-2483.5 MHz band: 1 watt (30 dBm).
The e.i.r.p. shall not exceed 4 W (36 dBm) (Canada).

RESULTS:

The maximum peak conducted output power level in the fundamental emission was measured using the method according to point 11.9.1.1 "RBW \geq DTS bandwidth" of ANSI C.63.10-2013.

The EIRP power (dBm) is calculated by adding the declared maximum antenna gain to the measured conducted power.

Maximum Declared Antenna Gain: +1.0 dBi


- **1M modulation:**

	Low Channel 2402 MHz	Middle Channel 2440 MHz	High Channel 2480 MHz
Maximum Conducted Power (dBm)	0.2	-0.7	-0.7
Maximum EIRP Power (dBm)	1.2	0.3	0.3
Measurement uncertainty (dB)	< \pm 0.99		


The maximum directional gain of the antenna is less than 6 dBi and therefore the maximum output power is not required to be reduced from the stated values

Verdict: PASS


- Low Channel:



- Middle Channel:



- High Channel:



FCC 15.247 (d) / RSS-247 5.5. Band-edge emissions compliance (Transmitter)


SPECIFICATION:

In any 100 kHz bandwidths outside the frequency band in which the intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, the attenuation required under this paragraph shall be 30 dB instead of 20 dB.

RESULTS:

- **1M modulation:**

- Low Channel:




Measurement uncertainty (dB) $\leq \pm 0.89$

Verdict: PASS

- High Channel:

Band Edge



— Limit — SumLevel × Fail

Measurement uncertainty (dB) $< \pm 0.89$

Verdict: PASS

FCC 15.247 (e) / RSS-247 5.2. (b) Power spectral density

SPECIFICATION:

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

RESULTS:


The maximum power spectral density level in the fundamental emission was measured using the method according to point 11.10.2." Method PKPSD (peak PSD)" of ANSI C.63.10-2013.

- **1M modulation:**

	Low Channel 2402 MHz	Middle Channel 2440 MHz	High Channel 2480 MHz
Power Spectral Density (dBm)	-8.627	-9.408	-9.316
Measurement uncertainty (dB)	<±0.99		


Verdict: PASS

- Low Channel:




- Middle Channel:

Peak Power Spectral Density



- High Channel:

Peak Power Spectral Density



FCC 15.247 (d) / RSS-247 5.5. Emission limitations radiated (Transmitter)

SPECIFICATION:

Radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c) / RSS-Gen):

Frequency Range (MHz)	Field strength ($\mu\text{V/m}$)	Field strength ($\text{dB}\mu\text{V/m}$)	Measurement distance (m)
0.009-0.490	2400/F(kHz)	-	300
0.490-1.705	24000/F(kHz)	-	30
1.705 - 30.0	30	-	30
30 - 88	100	40	3
88 - 216	150	43.5	3
216 - 960	200	46	3
960 - 25000	500	54	3

The emission limits shown in the above table are based on measurements employing CISPR quasi-peak detector except for the frequency bands 9-90 kHz, 110-490 kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector.

For average radiated emission measurements above 1000 MHz, there is also a limit corresponding to 20 dB above the indicated values in the table is specified when measuring with peak detector function.

RSS-247: Attenuation below the general field strength limits specified in RSS-Gen is not required.

RESULTS:

The situation and orientation was varied to find the maximum radiated emission. It was also rotated 360° and the antenna height was varied from 1 to 4 meters to find the maximum radiated emission.

Measurements were made in both horizontal and vertical planes of polarization.

All tests were performed in a semi-anechoic chamber at a distance of 3 m for the frequency range 30 MHz-17 GHz and at distance of 1m for the frequency range 17 GHz-26 GHz.

The field strength is calculated by adding correction factor to the measured level from the spectrum analyzer. This correction factor includes antenna factor, cable loss and pre-amplifiers gain.

Frequency range 30 MHz - 1 GHz:

The spurious frequencies do not depend neither on the operating channel nor the modulation mode.

No spurious frequencies were detected at less than 20 dB below the limit.

Measurement Uncertainty (dB): 30 MHz $\leq f \leq$ 1 GHz: $\leq \pm 5.08$

Frequency range 1 - 26 GHz:

The results in the next tables show the maximum measured levels in the 1-26 GHz range including the restricted bands 2.31-2.39 GHz and 2.4835-2.5 GHz.

Spurious frequencies with peak levels above the average limit (54 dB μ V/m at 3 m) are measured with average detector for checking compliance with the average limit.

- LOW CHANNEL. Spurious frequencies closest to the limit:

Spurious frequency (GHz)	Emission Level (dB μ V/m)	Polarization	Detector
2.3279	57.25	H	Peak
	44.57		Avg
2.4882	59.74	H	Peak
	45.24		Avg
4.8035	52.61	V	Peak
7.2060	57.62	H	Peak
	48.76		Avg
9.6085	50.36	V	Peak
12.0115	53.38	V	Peak
14.4135	55.00	V	Peak
	41.75		Avg
16.816	55.59	V	Peak
	42.13		Avg

- MIDDLE CHANNEL. Spurious frequencies closest to the limit:

Spurious frequency (GHz)	Emission Level (dB μ V/m)	Polarization	Detector
2.3858	57.47	H	Peak
	44.50		Avg
2.4877	57.97	H	Peak
	45.28		Avg
4.8795	56.32	V	Peak
	47.82		Avg
7.3195	59.56	H	Peak
	49.89		Avg
9.7610	51.59	V	Peak
12.2010	51.69	V	Peak
14.6390	55.02	V	Peak
	42.37		Avg

- HIGH CHANNEL. Spurious frequencies closest to the limit:


Spurious frequency (GHz)	Emission Level (dB μ V/m)	Polarization	Detector
2.4845	62.37	H	Peak
	45.44		Avg
4.9595	57.74	V	Peak
	49.39		Avg
7.4390	61.93	H	Peak
	50.60		Avg
9.9190	52.16	V	Peak
12.3995	55.29	V	Peak
	42.84		Avg
14.8795	51.54	V	Peak

Measurement Uncertainty (dB): 1 GHz \leq f \leq 3 GHz: \leq ± 4.11
 3 GHz < f \leq 17 GHz: \leq ± 5.13
 17 GHz < f \leq 26 GHz: \leq ± 4.82

Verdict: PASS


FREQUENCY RANGE 30 MHz - 1 GHz:

The spurious frequencies detected do not depend neither on the operating channel nor the modulation mode.




FREQUENCY RANGE 1 - 3 GHz:

- Low Channel:




The peak above the limit is the carrier frequency.

- Middle Channel:



The peak above the limit is the carrier frequency.


- High Channel:




The peak above the limit is the carrier frequency.

FREQUENCY RANGE 3 - 17 GHz:


- Low Channel:



- Middle Channel:




- High Channel:




FREQUENCY RANGE 17 - 26 GHz:

The spurious frequencies detected do not depend on the operating channel.




RESTRICTED BAND 2.31-2.39 GHz:

- Low Channel:




- Middle Channel:



- High Channel:


Full Spectrum




- | | | | |
|---|--------------------------------|---|---------------------------------|
| — | Preview Result 2V-AVG | — | Preview Result 1V-PK+ |
| — | Preview Result 2H-AVG | — | Preview Result 1H-PK+ |
| — | FCC 15.247 Restricted Bands PK | — | FCC 15.247 Restricted Bands AVG |
| ◆ | Final_Result PK+ | ◆ | Final_Result AVG |

RESTRICTED BAND 2.4835-2.5 GHz:

- Low Channel:



- Middle Channel:



- High Channel:

Full Spectrum

