# **RF Exposure Evaluation Statement**

Product Name: TWS wireless Bluetooth headset

Model No.: HE-044/ HE-044A/HE-044B/HE-024/HE-048/HE-025/HE-066/

HE-069/HE-065/T7/HE-

070/071/072/073/074/075/076/077/078/079/080/081/082/083/084/085/086/087/088/089/090/ 091/092/093/094/095/096/097/098/099

## FCC ID: 2A2BYHE-044

# 1.1 RF Exposure Compliance Requirement

### 1.1.1 Standard Requirement

According to KDB447498D01 General RF Exposure Guidance v06

Standalone SAR test exclusion considerations

Unless specifically required by the published RF exposure KDB procedures, standalone 1-g head or body and 10-g extremity SAR evaluation for general population exposure conditions, by measurement or numerical simulation, is not required when the corresponding SAR Exclusion Threshold condition, listed below, is satisfied.

#### 1.1.2 Limits

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances  $\leq$  50 mm are determined by:

[(max. power of channel, including tune-up tolerance, mW)/(min. test separation distance, mm)] ·

 $[\sqrt{f}(GHz)] \le 3.0$  for 1-g SAR and  $\le 7.5$  for 10-g extremity SAR, where

f(GHz) is the RF channel transmit frequency in GHz

Power and distance are rounded to the nearest mW and mm before calculation<sup>17</sup>

The result is rounded to one decimal place for comparison

The test exclusions are applicable only when the minimum test separation distance is  $\leq$  50 mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion

#### 1.1.3 EUT RF Exposure

Operational Mode: EDR ( $\pi$ /4 DQPSK worst case)						
	Maximum		Maximum tune-up Power			
Channel	Peak Conducted Output Power	Tune up tolerance (dB)	(dBm)	(mW)	Calculated value	Exclusion threshold
	(dBm)					
2402MHZ	-6.828	±1	-5.828	0.26	0.08	
2441MHz	-7.255	±1	-6.255	0.24	0.07	3.0
2480MHz	-7.047	±1	-6.047	0.25	0.08	
Conclusion: the calculated value $\leq$ 3.0, SAR is exempted.						