


Pi/4 DQPSK Low Channel





Pi/4 DQPSK Middle Channel



Page: 52 of 69 No.: BCTC/RF-EMC-007 Edition: A.3








No.: BCTC/RF-EMC-007 Page: 53 of 69 / / / / Edition: A.3



8DPSK Middle Channel







No.: BCTC/RF-EMC-007 Page: 54 of 69 / / / Edition; A.3



13. NUMBER OF HOPPING FREQUENCY

13.1 Block Diagram Of Test Setup

EUT	SPECTRUM	
	ANALYZER	

13.2 Limit

Frequency hopping systems in the 2400-2483.5 MHz band shall use at least 15 channels.

13.3 Test procedure

- 1. Remove the antenna from the EUT and then connect a low RF cable from the antenna port to the spectrum.
- 2. Set the spectrum analyzer: RBW = 100kHz. VBW = 300kHz. Sweep = auto; Detector Function = Peak. Trace = Max hold.
- 3. Allow the trace to stabilize. It may prove necessary to break the span up to sections. in order to clearly show all of the hopping frequencies. The limit is specified in one of the subparagraphs of this Section.
- 4. Set the spectrum analyzer: Start Frequency = 2.4GHz, Stop Frequency = 2.4835GHz. Sweep=auto;

No.: BCTC/RF-EMC-007 Page: 55 of 69 / / / Edition:, A.3




13.4 Test Result

Test Plots:


79 Channels in total GFSK






No.: BCTC/RF-EMC-007 Page: 56 of 69 / / / Edition: A.3







No.: BCTC/RF-EMC-007



14. DWELL TIME

14.1 Block Diagram Of Test Setup

EUT	SPECTRUM	
	ANALYZER	

14.2 Limit

Frequency hopping systems in the 2400-2483.5 MHz band shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used.

14.3 Test procedure

- 1. Remove the antenna from the EUT and then connect a low RF cable from the antenna port to the spectrum.
- 2. Set spectrum analyzer span = 0. Centred on a hopping channel;
- 3. Set RBW = 1MHz and VBW = 3MHz.Sweep = as necessary to capture the entire dwell time per hopping channel. Set the EUT for DH5, DH3 and DH1 packet transmitting.
- 4. Use the marker-delta function to determine the dwell time. If this value varies with different modes of operation (e.g., data rate, modulation format, etc.), repeat this test for each variation. The limit is specified in one of the subparagraphs of this Section. Submit this plot(s).

No.: BCTC/RF-EMC-007 Page: 58 of 69 / / Edition:, A.3



14.4 Test Result

DH5 Packet permit maximum 1600 / 79 / 6 hops per second in each channel (5 time slots RX, 1 time slot TX).


DH3 Packet permit maximum 1600 / 79 / 4 hops per second in each channel (3 time slots RX, 1 time slot TX).

DH1 Packet permit maximum 1600 / 79 /2 hops per second in each channel (1 time slot RX, 1 time slot TX). So, the Dwell Time can be calculated as follows:

DH5:1600/79/6*0.4*79*(MkrDelta)/1000 DH3:1600/79/4*0.4*79*(MkrDelta)/1000 DH1:1600/79/2*0.4*79*(MkrDelta)/1000 Remark: Mkr Delta is once pulse time.

Modulation	Channel Data	Packet	pulse time(ms)	Dwell Time(s)	Limits(s)
GFSK	Middle	DH1	0.404	0.129	0.4
		DH3	1.668	0.267	0.4
		DH5	2.910	0.310	0.4
Pi/4DQPSK	Middle	2DH1	0.408	0.131	0.4
		2DH3	1.668	0.267	0.4
		2DH5	2.910	0.310	0.4
8DPSK	Middle	3DH1	0.408	0.131	0.4
		3DH3	1.662	0.266	0.4 /
		3DH5	2.920	0.311	0.4


Test Plots
GFSK DH1 Middle Channel



No.: BCTC/RF-EMC-007 Page: 59 of 69 / / / / Edition: A.S




#VBW 3.0 MHz




No.: BCTC/RF-EMC-007 Page: 60 of 69 / / / | Edition A.S



Pi/4DQPSK DH1 Middle Channel




Pi/4DQPSK DH3 Middle Channel




No.: BCTC/RF-EMC-007 Page: 61 of 69 / / / Edition: A.3



Pi/4DQPSK DH5 Middle Channel




8DPSK DH1 Middle Channel




No.: BCTC/RF-EMC-007 Page: 62 of 69 / / / | Edition: A.3



8DPSK DH3 Middle Channel



8DPSK DH5 Middle Channel



No.: BCTC/RF-EMC-007 Page: 63 of 69 / / / | Edition: A.3



ANTENNA REQUIREMENT

Report No.: BCTC2106515615E


15.1 Limit

15.203 requirement: For intentional device, according to 15.203: an intentional radiator shall

be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

15.2 Test Result

The EUT antenna is FPC antenna, fulfill the requirement of this section.



No.: BCTC/RF-EMC-007



16. EUT PHOTOGRAPHS

Report No.: BCTC2106515615E

EUT Photo 1



EUT Photo 2



No.: BCTC/RF-EMC-007 Page: 65 of 69 / / / Edition: A.S





EUT Photo 3



EUT Photo 4




No.: BCTC/RF-EMC-007 Page: 66 of 69 / / / Edition: A.3



17. EUT TEST SETUP PHOTOGRAPHS

Conducted emissions







No.: BCTC/RF-EMC-007



Radiated Measurement Photos





No.: BCTC/RF-EMC-007 Page: 68 of 69 / / / Edition: A.3



STATEMENT

- 1. The equipment lists are traceable to the national reference standards.
- 2. The test report can not be partially copied unless prior written approval is issued from our lab.
- 3. The test report is invalid without stamp of laboratory.
- 4. The test report is invalid without signature of person(s) testing and authorizing.
- 5. The test process and test result is only related to the Unit Under Test.
- 6. The quality system of our laboratory is in accordance with ISO/IEC17025.

7.If there is any objection to report, the client should inform issuing laboratory within 15 days from the date of receiving test report.

Address:

1-2/F., Building B, Pengzhou Industrial Park, No.158, Fuyuan 1st Road, Tangwei, Fuhai Subdistrict, Bao'an District, Shenzhen, Guangdong, China

TEL: 400-788-9558

P.C.: 518103

FAX: 0755-33229357

Website: http://www.chnbctc.com.

E-Mail: bctc@bctc-lab.com.cn

**** END ****

No.: BCTC/RF-EMC-007 Page: 69 of 69 / / / / Edition: A.3