



Maximum Permissible Exposure Evaluation

FCC ID: 2A2GJ-HT-N5262

1. Client Information

Applicant	:	Heltec Automation Technology Co., Ltd
Address	:	1f, No.54,56,58, Zirui North Street, Gaoxin District, Chengdu, China.
Manufacturer	:	Heltec Automation Technology Co., Ltd
Address	:	1f, No.54,56,58, Zirui North Street, Gaoxin District, Chengdu, China.

2. General Description of EUT

EUT Name	:	Mesh Node
Models No.	:	HT-n5262, HT-n5262G, HT-n5262S, HT-n5262M, HT-n5362, HT-n5462, HT-n7062, HT-n9162, HT-n2162, HT-n5200
Model Difference	:	All these models are identical in the same PCB, layout and electrical circuit, the only difference is Different sales areas, different name.
Sample ID	:	HC-C-202408-0104-01-03-1#&HC-C-202408-0104-01-03-2#
Product Description	:	Operation Frequency: LORA: 902.3MHz~914.9MHz(125KHz) 903MHz~914.2MHz(500KHz) Bluetooth LE 5.0: 2402MHz~2480MHz
Power Rating	:	USB INPUT: DC 5V
Software Version	:	----
Hardware Version	:	----
Connecting I/O Port(S)	:	Please refer to the User's Manual
Remark	:	the MPE report used the EUT-2(HC-C-202408-0104-01-03-2#).

MPE Calculations for FCC

1. Antenna Gain:

Antenna	Brand	Model Name	Type	Antenna Gain(dBi)
LORA	N/A	N/A	Spring	1.1

Antenna	Brand	Model Name	Type	Antenna Gain(dBi)
Bluetooth LE	N/A	N/A	Ceramic	2.12

2. EUT Operation Condition:

Software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.

3. Exposure Evaluation:

Equation from page 18 of OET Bulletin 65, Edition 97-01

$$S = (PG) / 4\pi R^2$$

Where

S: power density

P: power input to the antenna

G: power gain of the antenna in the direction of interest relative to an isotropic radiator.

R: distance to the center of radiation of the antenna

4. Simultaneous transmission MPE Considerations

According to KDB447498: All transmitters and antennas in the host must be either evaluated for MPE compliance, by measurement or computational modeling, or qualify for the standalone MPE test exclusion in section 7.1. Simultaneous transmission MPE test exclusion applies when the sum of the MPE ratios for all simultaneous transmitting antennas incorporated in a host device, based on the calculated/estimated, numerically modeled or measured field strengths or power density, is ≤ 1.0 .

This means that:

$$\sum \text{ of MPE ratios } \leq 1.0$$



5. Standalone MPE Evaluation:

LORA(DSS) Worst Maximum MPE Result									
Mode	N _{TX}	Freq. (MHz)	Conducted Power(max) (dBm)	Turn-up Power (dB)	Max tune up power (dBm) [P]	ANT Gain (dBi) [G]	Distance (cm) [R]	Power Density (mW/cm ²) [S]	Limit of Power Density (mW/cm ²) (S)
LORA	1	902.3	12.279	12±1	13	1.1	20	0.00511	0.6015
		908.9	12.188	12±1	13	1.1	20	0.00511	0.6015
		914.9	12.162	12±1	13	1.1	20	0.00511	0.6015

Note:

 N_{TX}= Number of Transmit Antennas

RF Output power specifies that Maximum Conducted Peak Output Power.

LORA(DTS) Worst Maximum MPE Result									
Mode	N _{TX}	Freq. (MHz)	Conducted Power(max) (dBm)	Turn-up Power (dB)	Max tune up power (dBm) [P]	ANT Gain (dBi) [G]	Distance (cm) [R]	Power Density (mW/cm ²) [S]	Limit of Power Density (mW/cm ²) (S)
LORA	1	903	12.356	12±1	13	1.1	20	0.00511	0.6015
		907.8	12.602	12±1	13	1.1	20	0.00511	0.6015
		914.2	12.510	12±1	13	1.1	20	0.00511	0.6015

Note:

 N_{TX}= Number of Transmit Antennas

RF Output power specifies that Maximum Conducted Peak Output Power.

Bluetooth LE Worst Maximum MPE Result									
Mode	N _{TX}	Freq. (MHz)	Conducted Power(max) (dBm)	Turn-up Power (dB)	Max tune up power (dBm) [P]	ANT Gain (dBi) [G]	Distance (cm) [R]	Power Density (mW/cm ²) [S]	
1M	1	2402	3.047	3±1	4	2.12	20	0.00081	
		2440	4.539	4±1	5	2.12	20	0.00103	
		2480	4.000	4±1	5	2.12	20	0.00103	

Note:

 N_{TX}= Number of Transmit Antennas

RF Output power specifies that Maximum Conducted Peak Output Power.

Remark:

- Output power including turn-up tolerance;
- Output power was adjust to duty cycle at 100% if measured duty cycle less than 98%;
- MPE evaluate distance is 20cm from user manual provide by manufacturer.
- Only the worst power was evaluated for each wireless function



6. Conclusion:

As specified in Table 1B of 47 CFR 1.1310- Limits for Maximum Permissible Exposure (MPE),

Limits for General Population/ Uncontrolled Exposure

Frequency Range (MHz)	Power density (mW/ cm ²)
300-1,500	F/1500
1,500-100,000	1.0

7. Summary simultaneous transmission information

The sample supports two antennas for LORA Antenna and Bluetooth LE Antenna.

The LORA Antenna and Bluetooth LE Antenna can transmit simultaneous.

The LORA and Bluetooth LE with two different Antenna.

According to KDB447498 for Transmitters used in mobile exposure conditions for simultaneous transmission operations;

Σ of MPE ratios ≤ 1.0

8. Summary simultaneous transmission results

LORA ANT. + Bluetooth LE ANT. Maximum Simultaneous transmission MPE Ratios is

$0.00850+0.00103=0.00953 \leq 1.0$.

9. Conclusion:

The measurement results comply with the FCC Limit per 47 CFR 2.1091 for the uncontrolled RF Exposure of mobile device.

-----END OF THE REPORT-----

