

## RF EXPOSURE

#### 1. Regulation

According to §15.247(i), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy levels in excess of the Commission's guidelines. See § 1.1307(b)(1) of this Chapter.

Limits for Maximum Permissive Exposure: RF exposure is calculated.

Frequency Range	Electric Field Strength [V/m]	Magnetic Field Strength [A/m]	Power Density [mW/cm <sup>2</sup> ]	Averaging Time [minute]	
Limits for General Population / Uncontrolled Exposure					
0.3 ~ 1.34	614	1.63	*(100)	30	
1.34 ~ 30	824/f	2.19/f	*(180/f2)	30	
30 ~ 300	27.5	0.073	0.2	30	
300 ~ 1 500	1	1	f/1 500	30	
1 500 ~ 15 000	1	1	1	30	

f=frequency in MHz, \*= plane-wave equivalent power density

## **MPE (Maximum Permissive Exposure) Prediction**

Predication of MPE limit at a given distance: Equation from page 18 of OET Bulletin 65, Edition 97-01

$$S = PG/4\pi R^2 \quad \left( \Rightarrow R = \sqrt{PG/4\pi S} \right)$$

S = power density [mW/cm<sup>2</sup>]

P = Power input to antenna [mW]

G = Power gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the center of radiation of the antenna [cm]

#### 2. RF Exposure Compliance Issue

The information should be included in the user's manual:

This appliance and its antenna must not be co-located or operation in conjunction with any other antenna or transmitter. A minimum separation distance of 20 cm must be maintained between the antenna and the person for this appliance to satisfy the RF exposure requirements.



# **MPE Calculations: Wifi + BLE + LTE**

The EUT will only be used with a separation of 20 centimeters or greater between the antenna and the body of the The MPE calculation for this exposure is shown below.

#### Simultaneous MPE

Wifi+BLE+LTE

- Total (%) =	- NOTE		
[ Wifi Result(mW/cm2) / Limit(mW/cm2) ]+[ LTE Result(mW/cm2) / Limit(mW/cm2) ]+[ BLE Result(mW/cm2) / Limit(mW/cm2) ] * 100	Wifi+BT+LTE  Wifi = <u>0. 032</u> mW/cm2		
= [ <u>0.032 000</u> / 1 ] +	BLE= <u>0. 110</u> mW/cm2		
[ <u>0.110 000</u> / 1 ] +	LTE= <u>0. 080</u> mW/cm2		
[ <u>0.080 490</u> / 1 ] * 100 = <u>22.249</u> %	Distance to the center of the radiation of the antenna ( $\underline{20}$ cm) Limit : $\leq$ 100 %		

### **RF Exposure Compliance Issue**

Therefore, EUT is not required the SAR Evaluation.