APPENDIX REPORT

Project No.	SHT2106054104EW	Radio Specification	Bluetooth BLE
Test sample No.	YPHT21060541011	Model No.	VP880
Start test date	2021-07-02	Finish date	2021-07-02
Temperature	24.6°C	Humidity	39%
Test Engineer	Hailey Chen	Auditor	Xiaodong Zhao

Appendix clause	Test item	Result
A	Peak Output Power	PASS
B	Power Spectral Density	PASS
C	6 dB Bandwidth	PASS
D	99% Occupied Bandwidth	PASS
E	Duty cycle	PASS
F	Band edge and Spurious Emissions (conducted)	PASS

Appendix A：Peak Output Power

Type	Channel	Output power (dBm)	Average Output power (dBm)	Limit (dBm)	Result
BT-BLE	00	-6.78	-6.79	≤ 30.00	Pass
	19	-7.97	-7.98		
	39	-7.11	-7.14		

CH00	
CH19	
CH39	

Appendix B：Power Spectral Density

Type	Channel	Power Spectral Density(dBm/3KHz)	Limit (dBm/3KHz)	Result
BT-BLE	00	-22.07	≤8.00	Pass
	19	-23.06		
	39	-22.30		

CH00	
CH19	
CH39	

Appendix C：6dB bandwidth

Type	Channel	6dB Bandwidth(kHz)	Limit (kHz)	Result
BT-BLE	00	772.00	≥500	Pass
	19	768.00		
	39	770.00		

CH00	
CH19	
CH39	

Appendix D：99% Occupied Bandwidth

Type	Channel	99% Occupied Bandwidth(MHz)	Limit (kHz)	Result
BT-BLE	00	1.06	-	Pass
	19	1.06		
	39	1.06		

CH00	
CH19	
CH39	

Appendix E：Duty cycle

Test Frequency（MHz）	$T_{on\ time}$ for single burst (ms)	T_{period} (ms)	Duty cycle	$1/T_{on\ time}$ (kHz)
2440	0.39	0.62	62.9%	2.6



Appendix F：Band edge and Spurious Emissions (conducted)

Test Item:	Band edge
CH00	
CH39	

Test Item:	SE
CH00 Reference level	
CH00 30MHz~1000MHz	
CH00 1GHz~26GHz	

CH19 Reference level	
CH19 30MHz~1000MHz	
CH19 1GHz~26GHz	

CH39 Reference level	
CH39 30MHz~1000MHz	
CH39 1GHz~26GHz	

--------End of Report--------