

FCC ID: 2A2JY-Q8W

Portable device

According to §15.247(e)(i) and §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission’s guidelines.

According to KDB447498 D01 General RF Exposure Guidance V06

The 1-g SAR and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot \sqrt{f(\text{GHz})} \leq 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR, where:

- f(GHz) is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison

When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion.

BLE:

Antenna Type: PCB Antenna

Antenna Gain: 3.64 dBi

Modulation	Channel Freq. (GHz)	Conduct ed power (dBm)	Conducte d power (mW)	Tune-up power (dBm)	Max tune-up power (dBm)	Max tune-up power (mW)	Distance (mm)	Result calculatio n	1g SAR Exclusion threshold	SAR test exclusion
GFSK(1M)	2.402	-0.58	0.875	0±1	1.0	1.259	<5	0.39023	3.00	YES
	2.440	-0.69	0.853	0±1	1.0	1.259	<5	0.39330	3.00	YES
	2.480	-1.06	0.783	-1±1	0.0	1.000	<5	0.31496	3.00	YES
GFSK(2M)	2.402	-0.56	0.879	0±1	1.0	1.259	<5	0.39023	3.00	YES
	2.440	-0.69	0.853	0±1	1.0	1.259	<5	0.39330	3.00	YES
	2.480	-1.09	0.778	-1±1	0.0	1.000	<5	0.31496	3.00	YES

Conclusion:

For the max result : $0.39330 \leq 3.0$ for 1-g SAR, No SAR is required.

Signature:

Date: 2023-05-06

NAME AND TITLE (Please print or type): Alex /Manager

COMPANY (Please print or type): Shenzhen NTEK Testing Technology Co., Ltd./ 1/F, Building E, Fenda Science Park, Sanwei Community, Xixiang Street Bao’an District, Shenzhen 518126 P.R. China