

Hangzhou Kitchen Idea Technology Co., Ltd

MPE ASSESSMENT REPORT

Report Type:

FCC MPE assessment report

Model:

K3113, K3118

REPORT NUMBER:

230600955HAN-002

ISSUE DATE:

November 10, 2023

DOCUMENT CONTROL NUMBER:

TTRFFCCMPE-01_V1 © 2018 Intertek





Intertek Testing Services Shanghai Building No.86, 1198 Qinzhou Road (North) Caohejing Development Zone Shanghai 200233, China

> Telephone: 86 21 6127 8200 www.intertek.com

Report no.: 230600955HAN-002

Applicant: Hangzhou Kitchen Idea Technology Co., Ltd

Room 2501, Huaye Building, 511 Jianye Road, Changhe Subdistrict,

Binjiang District, Hangzhou, Zhejiang, China

Manufacturer: Same As Applicant

Factory: Shaoxing Kitchen Idea Electrical Appliances Manufacturing Co., Ltd.

West of 2nd Floor, South of Qisheng Road, Paojiang Industrial Zone,

Shaoxing City, Zhejiang Province, China

PRODUCT NAME: Cooking food processor

TYPE/MODEL: K3113, K3118

FCC ID: 2A2KP-K3118

IC: 30295-K3118

SUMMARY:

The equipment complies with the requirements according to the following standard(s) or Specification:

KDB447498 D01 General RF Exposure Guidance v06 FCC Part2.1091, FCC Part2.1093 FCC Part1.1307(b)

PREPARED BY:	REVIEWED BY:		
	J.K.W		
Alex Wu	Wakeyou Wang		
Project Engineer	Reviewer		

This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to permit copying or distribution of this report and then only in its entirety. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results in this report are relevant only to the sample tested. This report by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.





Revision History

Report No.	Version	Description	Issued Date
230600955HAN-002	Rev. 01	Initial issue of report	November 10, 2023





1 GENERAL INFORMATION

1.1 Description of Equipment Under Test (EUT)

Product name:	Cooking food processor
Type/Model:	K3113, K3118
Description of EUT:	The products covered by this report are portable Cooking food processor, which are intended for household and indoor use only and adopt thermal cut out, thermal link, fuse and NTC to safeguard. All models use same motors and have similar appearance. K3118 use 3L Capacity Cup, while K3113 use 2L Capacity Cup. All models use the same WIFI RF module. Therefore, we selected the K3113 to do all tests.
Rating:	110-120V~ or 120V~, 60Hz, Motor: 700W, Heating: 900W
EUT type:	☐ Tabletop ☐ Floor standing
Brand name:	/
Software Version:	/
Hardware Version:	/
Sample received date:	1230103-19-001
Date of test:	September 15-October 15, 2023





1.2 Technical Specification

Frequency Band:	2400MHz ~ 2483.5MHz			
Support Standards:	IEEE 802.11b, IEEE 802.11g, IEEE 802.11n(HT20),			
	IEEE 802.11n(HT40)			
Type of Modulation:	IEEE 802.11b: DSSS (CCK, DQPSK, DBPSK)			
	IEEE 802.11g: OFDM (64-QAM, 16-QAM, QPSK, BPSK)			
	IEEE 802.11n(HT20): OFDM (64-QAM, 16-QAM, QPSK, BPSK)			
	IEEE 802.11n(HT40): OFDM (64-QAM, 16-QAM, QPSK, BPSK)			
Operating Frequency:	2412MHz to 2462MHz for IEEE 802.11b/g/n(HT20)			
	2422MHz to 2452MHz for IEEE 802.11n(HT40)			
Channel Number:	11 Channels for 802.11b, 802.11g and 802.11n(HT20)			
	7 Channels for 802.11n(HT40)			
Channel Separation:	5 MHz			
Antenna:	PCB Antenna,			
	2.24dBi Gain			





1.3 Description of Test Facility

Name:	Intertek Testing Services Shanghai
Address:	Building 86, No. 1198 Qinzhou Road (North), Shanghai 200233, P.R. China
Telephone:	86 21 61278200
Telefax:	86 21 54262353

The test facility is recognized, certified, or accredited by these	CNAS Accreditation Lab Registration No. CNAS L0139
organizations:	FCC Accredited Lab Designation Number: CN0175
	IC Registration Lab CAB identifier.: CN0014
	VCCI Registration Lab Member No: 3598 (Registration No.: R-14243, G-10845, C-14723, T-12252)
	A2LA Accreditation Lab Certificate Number: 3309.02





2 MPE Assessment

Test result: Pass

2.1 MPE Assessment Limit

Mobile device exposure for standalone operations:

Frequency range	E-field strength (V/m)	H-field strength (A/m)	B-field (uT)	Equivalent plane wave power density S_{eq} (W/m²)
0-1 Hz	-	3,2 × 10 ⁴	4 × 10 ⁴	-
1-8 Hz	10 000	$3,2 \times 10^4/f^2$	$4 \times 10^4/f^2$	-
8-25 Hz	10 000	4 000/f	5 000/f	-
0,025-0,8 kHz	250/f	4/f	5/f	-
0,8-3 kHz	250/f	5	6,25	-
3-150 kHz	87	5	6,25	-
0,15-1 MHz	87	0,73/f	0,92/f	-
1-10 MHz	87/f ^{1/2}	0,73/f	0,92/f	-
10-400 MHz	28	0,073	0,092	2
400-2 000 MHz	1,375 f ^{1/2}	0,0037 f ^{1/2}	0,0046 f ^{1/2}	f/200
2-300 GHz	61	0,16	0,20	10

Mobile device exposure for simultaneous transmission operations: the sum of the MPE ratios for all simultaneously transmitting antennas incorporated in a host device is ≤ 1.0



2.2 Assessment Results

Power density (S) is calculated according to the formula:

 $S = PG / (4\pi R^2)$

Where $S = power density in mW/cm^2$

P = Radiated transmit power in mW

G = numeric gain of transmit antenna

R = distance (cm)

As we can see from the test report 230600955HAN-001:

The calculations in the table below use the highest gain of antenna for client EUT. These calculations represent worst case in terms of the exposure levels.

Mode	Frequency band	ERP	Antenna Gain	R	S	Limits
	(MHz)	dBm	dBi	(cm)	(mW/cm ²)	(mW/cm ²)
WIFI	2400-2483.5	12.78	1.5	20	0.006	1

Note: 1 mW/cm² from 1.310 Table 1

For the device can support simultaneous transmission, according to 447498 D01 General RF Exposure Guidance v06





Appendix I

Definition below must be outlined in the User Manual:

To satisfy FCC RF exposure requirements, a separation distance of 20 cm or more should be maintained between the antenna of this device and persons during device operation. To ensure compliance, operations at closer than this distance is not recommended.