

Safety Human Exposure

1 Radio Frequency Exposure Compliance

1.1 Electromagnetic Fields

RESULT:

Pass

Test Specification

Test standard

: CFR47 FCC Part 2: Section 2.1091
CFR47 FCC Part 1: Section 1.1310
FCC KDB Publication 447498 v06
FCC KDB Publication 865664 D01 v01r04
FCC KDB Publication 865664 D02 v01r02
RSS-102 Issue 5 March 2015

1.1.1 RF Exposure Compliance Requirement for FCC (FCC ID: 2A2LR-LF01)

FCC requirement: Systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess limit for maximum permissible exposure. In accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091 this device has been defined as a mobile device whereby a distance of 20cm normally can be maintained between the user and the device.

MPE Calculation Method according to KDB 447498 v06

Power Density: $S_{(mW/cm^2)} = PG/4\pi R^2$ or $EIRP/4\pi R^2$

Where:

S = power density (mW/cm²)

P = power input to the antenna (mW)

G = power gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the center of radiation of the antenna (cm)

The nominal maximum conducted output power specified:

Wi-Fi 802.11 b/g/n: 22.70 dBm

From the peak RF output power, the minimum mobile separation distance, d=20 cm, as well as the antenna gain (Max. 3.45 dBi for Wi-Fi 802.11 b/g/n), the RF power density can be calculated as below:

For Wi-Fi 802.11 b/g/n: $S_{(mW/cm^2)} = PG/4\pi R^2 = 0.082 \text{ mW/cm}^2$

Limits for Maximum Permissible Exposure (MPE) according to FCC Part 1.1310:

1.0 mW/cm²

1.1.2 RF Exposure Compliance Requirement for IC (IC: 27494-LF01)

The EUT shall comply with the requirement of RSS-102 section 2.5.2.

Exemption from Routine Evaluation Limits – RF Exposure Evaluation

RF exposure evaluation is required if the separation distance between the user and/or bystander and the device's radiating element is greater than 20 cm, except when the device operates as follows:

at or above 300 MHz and below 6 GHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than $1.31 \times 10^{-2} f^{0.6834}$ W (adjusted for tune-up tolerance), where f is in MHz;

- RF exposure evaluation exempted power for Wi-Fi 802.11 b/g/n: 2.670 W

The nominal maximum conducted output power specified:

Wi-Fi 802.11 b/g/n: 22.70 dBm

Antenna Gain: 3.45 dBi for Wi-Fi 802.11 b/g/n

The Max. e.i.r.p. for Wi-Fi 802.11 b/g/n: 26.15 dBm = 0.412 W

The e.i.r.p. for Wi-Fi 802.11 b/g/n is less than the RF exposure evaluation exempted power. So RF exposure evaluation is not required.

“RF Radiation Exposure Statement Caution: This Transmitter must be installed to provide a separation distance of at least 20 cm from all persons.”