



Shenzhen Global Test Service Co.,Ltd.

No.7-101 and 8A-104, Building 7 and 8, DCC Cultural and Creative Garden, No.98, Pingxin North Road, Shangmugu Community, Pinghu Street, Longgang District, Shenzhen, Guangdong

FCC PART 15 SUBPART C TEST REPORT

FCC PART 15.247

Report Reference No.: **GTS20210715018-1-1**

FCC ID.: **2A2MNHCD-1215L1CON**

Compiled by

(position+printed name+signature) : File administrators Jimmy Wang

Supervised by

(position+printed name+signature) : Test Engineer Aaron Tan



Approved by

(position+printed name+signature) : Manager Jason Hu

Date of issue: Jul. 15, 2021

Representative Laboratory Name : **Shenzhen Global Test Service Co., Ltd.**

Address: No.7-101 and 8A-104, Building 7 and 8, DCC Cultural and Creative Garden, No.98, Pingxin North Road, Shangmugu Community, Pinghu Street, Longgang District, Shenzhen, Guangdong

Applicant's name : **HEBEI HUACHUANGDA TECHNOLOGY CO., LTD**

Address : Southeast corner of the intersection of Maosui Street and Shaofeng Road, Xinxing Park, Jize County, Handan City, Hebei Province, China

Test specification :

Standard : **FCC Part 15.247**

Shenzhen Global Test Service Co.,Ltd. All rights reserved.

This publication may be reproduced in whole or in part for non-commercial purposes as long as the Shenzhen Global Test Service Co.,Ltd. is acknowledged as copyright owner and source of the material. Shenzhen Global Test Service Co.,Ltd. takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.

Test item description : **Controller**

Trade Mark : **HCD 华创达**

Manufacturer : **HEBEI HUACHUANGDA TECHNOLOGY CO., LTD**

Model/Type reference : **HCD-1215L1CON**

Listed Models : **N/A**

Modulation : **GFSK**

Frequency : **From 2402MHz to 2480MHz**

Ratings : **DC 12.6V From External circuit**

Result : **PASS**

TEST REPORT

Equipment under Test : Controller

Model /Type : HCD-1215L1CON

Listed Models : N/A

Applicant : HEBEI HUACHUANGDA TECHNOLOGY CO., LTD

Address : Southeast corner of the intersection of Maosui Street and Shaofeng Road, Xinxing Park, Jize County, Handan City, Hebei Province,China

Manufacturer : HEBEI HUACHUANGDA TECHNOLOGY CO., LTD

Address : Southeast corner of the intersection of Maosui Street and Shaofeng Road, Xinxing Park, Jize County, Handan City, Hebei Province,China

| | |
|---------------------|-------------|
| Test Result: | PASS |
|---------------------|-------------|

The test report merely corresponds to the test sample.

It is not permitted to copy extracts of these test result without the written permission of the test laboratory.

Contents

| | | |
|----------|---|----|
| <u>1</u> | <u>TEST STANDARDS</u> | 4 |
| <u>2</u> | <u>SUMMARY</u> | 5 |
| 2.1 | General Remarks | 5 |
| 2.2 | Product Description | 5 |
| 2.3 | Equipment Under Test | 5 |
| 2.4 | Short description of the Equipment under Test (EUT) | 5 |
| 2.5 | EUT operation mode | 6 |
| 2.6 | Block Diagram of Test Setup | 6 |
| 2.7 | Related Submittal(s) / Grant (s) | 6 |
| 2.8 | Modifications | 6 |
| <u>3</u> | <u>TEST ENVIRONMENT</u> | 7 |
| 3.1 | Address of the test laboratory | 7 |
| 3.2 | Test Facility | 7 |
| 3.3 | Environmental conditions | 7 |
| 3.4 | Summary of measurement results | 8 |
| 3.5 | Statement of the measurement uncertainty | 8 |
| 3.6 | Equipments Used during the Test | 9 |
| <u>4</u> | <u>TEST CONDITIONS AND RESULTS</u> | 10 |
| 4.1 | AC Power Conducted Emission | 10 |
| 4.2 | Radiated Emissions and Band Edge | 13 |
| 4.3 | Maximum Peak Output Power | 19 |
| 4.4 | Power Spectral Density | 20 |
| 4.5 | 6dB Bandwidth | 22 |
| 4.6 | Out-of-band Emissions | 24 |
| 4.7 | Antenna Requirement | 29 |
| <u>5</u> | <u>TEST SETUP PHOTOS OF THE EUT</u> | 30 |
| <u>6</u> | <u>PHOTOS OF THE EUT</u> | 31 |

1 TEST STANDARDS

The tests were performed according to following standards:

[FCC Rules Part 15.247](#): Frequency Hopping, Direct Spread Spectrum and Hybrid Systems that are in operation within the bands of 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz.

[ANSI C63.10-2013](#): American National Standard for Testing Unlicensed Wireless Devices

[KDB558074 D01 V05r02](#): Guidance for Performing Compliance Measurements on Digital Transmission Systems (DTS) Operating Under §15.247

2 SUMMARY

2.1 General Remarks

| | | |
|--------------------------------|---|---------------|
| Date of receipt of test sample | : | Jun. 20, 2021 |
| Testing commenced on | : | Jun. 20, 2021 |
| Testing concluded on | : | Jul. 15, 2021 |

2.2 Product Description

| | |
|---|---|
| Product Description: | Controller |
| Model/Type reference: | HCD-1215L1CON |
| Power supply: | DC 12.6V From External circuit |
| Testing sample ID: | GTS20210715018-1-1-1#(Engineer sample), GTS20210715018-1-1-2#(Normal sample) |
| Adapter information (Auxiliary test supplied by test Lab) : | Model:KT-12610 Input:AC100-240V-50/60Hz, 0.23A Output:DC 12.6V,1000mA |
| Software version: | V1.0 |
| Hardware version: | V1.0 |
| Bluetooth BLE | |
| Supported type: | Bluetooth low Energy |
| Modulation: | GFSK |
| Operation frequency: | 2402MHz to 2480MHz |
| Channel number: | 40 |
| Channel separation: | 2 MHz |
| Antenna type: | PCB antenna |
| Antenna gain: | 0.0 dBi |

2.3 Equipment Under Test

Power supply system utilised

| | | | | | |
|----------------------|---|----------------------------------|----------------------------------|-----------------------|-------------|
| Power supply voltage | : | <input type="radio"/> | 230V / 50 Hz | <input type="radio"/> | 120V / 60Hz |
| | | <input type="radio"/> | 12 V DC | <input type="radio"/> | 24 V DC |
| | | <input checked="" type="radio"/> | Other (specified in blank below) | | |

DC 12.6V From External circuit

2.4 Short description of the Equipment under Test (EUT)

This is a Controller

For more details, refer to the user's manual of the EUT.


2.5 EUT operation mode

The Applicant provides communication tools software(Engineer mode) to control the EUT for staying in continuous transmitting (Duty Cycle more than 98%) and receiving mode for testing .There are 40 channels provided to the EUT and Channel 00/19/39 were selected to test.

Operation Frequency:

| Channel | Frequency (MHz) |
|-----------|-----------------|
| 00 | 2402 |
| 01 | 2404 |
| 02 | 2406 |
| : | : |
| 19 | 2440 |
| : | : |
| 37 | 2476 |
| 38 | 2478 |
| 39 | 2480 |

2.6 Block Diagram of Test Setup



2.7 Related Submittal(s) / Grant (s)

This submittal(s) (test report) is intended for the device filing to comply with Section 15.247 of the FCC Part 15, Subpart C Rules.

2.8 Modifications

No modifications were implemented to meet testing criteria.

3 TEST ENVIRONMENT

3.1 Address of the test laboratory

Shenzhen Global Test Service Co.,Ltd.

No.7-101 and 8A-104, Building 7 and 8, DCC Cultural and Creative Garden, No.98, Pingxin North Road, Shangmugu Community, Pinghu Street, Longgang District, Shenzhen, Guangdong

The 3m-Semi anechoic test site fulfils CISPR 16-1-4 according to ANSI C63.4:2014 and CISPR 16-1-4:2010 SVSWR requirement for radiated emission above 1GHz.

3.2 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

FCC-Registration No.: 165725, FCC Designation Number is CN1234.

Shenzhen Global Test Service Co.,Ltd EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files.

A2LA-Lab Cert. No.: 4758.01

Shenzhen Global Test Service Co.,Ltd. EMC Laboratory has been accredited by A2LA for technical competence in the field of electrical testing, and proved to be in compliance with ISO/IEC 17025: 2005 General Requirements for the Competence of Testing and Calibration Laboratories and any additional program requirements in the identified field of testing.

CNAS-Lab Code: L8169

Shenzhen Global Test Service Co.,Ltd. has been assessed and proved to be in compliance with CNAS-CL01 Accreditation Criteria for Testing and Calibration Laboratories (identical to ISO/IEC 17025: 2005 General Requirements) for the Competence of Testing and Calibration Laboratories. Date of Registration: Dec. 11, 2015. Valid time is until Dec. 10, 2024.

3.3 Environmental conditions

During the measurement the environmental conditions were within the listed ranges:

Radiated Emission:

| | |
|-----------------------|--------------|
| Temperature: | 23 ° C |
| Humidity: | 48 % |
| Atmospheric pressure: | 950-1050mbar |

AC Main Conducted testing:

| | |
|-----------------------|--------------|
| Temperature: | 24 ° C |
| Humidity: | 45 % |
| Atmospheric pressure: | 950-1050mbar |

Conducted testing:

| | |
|-----------------------|--------------|
| Temperature: | 24 ° C |
| Humidity: | 45 % |
| Atmospheric pressure: | 950-1050mbar |

3.4 Summary of measurement results

| Test Specification clause | Test case | Test Mode | Test Channel | Recorded In Report | Test result | |
|---------------------------|---|-----------|---|--------------------|---|----------|
| §15.247(e) | Power spectral density | BLE 1Mpbs | <input checked="" type="checkbox"/> Lowest <input checked="" type="checkbox"/> Middle <input checked="" type="checkbox"/> Highest | BLE 1Mpbs | <input checked="" type="checkbox"/> Lowest <input checked="" type="checkbox"/> Middle <input checked="" type="checkbox"/> Highest | complies |
| §15.247(a)(2) | Spectrum bandwidth – 6 dB bandwidth | BLE 1Mpbs | <input checked="" type="checkbox"/> Lowest <input checked="" type="checkbox"/> Middle <input checked="" type="checkbox"/> Highest | BLE 1Mpbs | <input checked="" type="checkbox"/> Lowest <input checked="" type="checkbox"/> Middle <input checked="" type="checkbox"/> Highest | complies |
| §15.247(b)(3) | Maximum Peak output power | BLE 1Mpbs | <input checked="" type="checkbox"/> Lowest <input checked="" type="checkbox"/> Middle <input checked="" type="checkbox"/> Highest | BLE 1Mpbs | <input checked="" type="checkbox"/> Lowest <input checked="" type="checkbox"/> Middle <input checked="" type="checkbox"/> Highest | complies |
| §15.247(d) | Band edge compliance conducted | BLE 1Mpbs | <input checked="" type="checkbox"/> Lowest <input checked="" type="checkbox"/> Highest | BLE 1Mpbs | <input checked="" type="checkbox"/> Lowest <input checked="" type="checkbox"/> Highest | complies |
| §15.205 | Band edge compliance radiated | BLE 1Mpbs | <input checked="" type="checkbox"/> Lowest <input checked="" type="checkbox"/> Highest | BLE 1Mpbs | <input checked="" type="checkbox"/> Lowest <input checked="" type="checkbox"/> Highest | complies |
| §15.247(d) | TX spurious emissions conducted | BLE 1Mpbs | <input checked="" type="checkbox"/> Lowest <input checked="" type="checkbox"/> Middle <input checked="" type="checkbox"/> Highest | BLE 1Mpbs | <input checked="" type="checkbox"/> Lowest <input checked="" type="checkbox"/> Middle <input checked="" type="checkbox"/> Highest | complies |
| §15.247(d) | TX spurious emissions radiated | BLE 1Mpbs | <input checked="" type="checkbox"/> Lowest <input checked="" type="checkbox"/> Middle <input checked="" type="checkbox"/> Highest | BLE 1Mpbs | <input checked="" type="checkbox"/> Lowest <input checked="" type="checkbox"/> Middle <input checked="" type="checkbox"/> Highest | complies |
| §15.209(a) | TX spurious Emissions radiated Below 1GHz | BLE 1Mpbs | -/- | BLE 1Mpbs | -/- | complies |
| §15.107(a) §15.207 | Conducted Emissions < 30 MHz | BLE 1Mpbs | -/- | BLE 1Mpbs | -/- | complies |

Remark:

1. The measurement uncertainty is not included in the test result.
2. We tested all test mode and recorded worst case in report

3.5 Statement of the measurement uncertainty

The data and results referenced in this document are true and accurate. The reader is cautioned that there may be errors within the calibration limits of the equipment and facilities. The measurement uncertainty was calculated for all measurements listed in this test report acc. to CISPR 16 - 4 „Specification for radio disturbance and immunity measuring apparatus and methods – Part 4: Uncertainty in EMC Measurements“ and is documented in the Shenzhen Global Test Service Co.,Ltd quality system acc. to DIN EN ISO/IEC 17025. Furthermore, component and process variability of devices similar to that tested may result in additional deviation. The manufacturer has the sole responsibility of continued compliance of the device.

Hereafter the best measurement capability for Shenzhen GTS laboratory is reported:

| Test | Range | Measurement Uncertainty | Notes |
|-----------------------|------------|-------------------------|-------|
| Radiated Emission | 30~1000MHz | 4.10 dB | (1) |
| Radiated Emission | 1~18GHz | 4.32 dB | (1) |
| Radiated Emission | 18~40GHz | 5.54 dB | (1) |
| Conducted Disturbance | 0.15~30MHz | 3.12 dB | (1) |

(1) This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

3.6 Equipments Used during the Test


| Test Equipment | Manufacturer | Model No. | Serial No. | Calibration Date | Calibration Due Date |
|----------------------------|-----------------------------------|-----------------------|-----------------|------------------|----------------------|
| LISN | R&S | ENV216 | 3560.6550.08 | 2020/09/19 | 2021/09/18 |
| LISN | R&S | ESH2-Z5 | 893606/008 | 2020/09/19 | 2021/09/18 |
| EMI Test Receiver | R&S | ESPI3 | 101841-cd | 2020/09/19 | 2021/09/18 |
| EMI Test Receiver | R&S | ESCI7 | 101102 | 2020/09/19 | 2021/09/18 |
| Spectrum Analyzer | Agilent | N9020A | MY48010425 | 2020/09/19 | 2021/09/18 |
| Spectrum Analyzer | R&S | FSV40 | 100019 | 2020/09/19 | 2021/09/18 |
| Vector Signal generator | Agilent | N5181A | MY49060502 | 2020/09/19 | 2021/09/18 |
| Signal generator | Agilent | E4421B | 3610AO1069 | 2020/09/19 | 2021/09/18 |
| Climate Chamber | ESPEC | EL-10KA | A20120523 | 2020/09/19 | 2021/09/18 |
| Control | EM Electronics | control EM 1000 | N/A | N/A | N/A |
| Horn Antenna | Schwarzbeck | BBHA 9120D | 01622 | 2020/09/19 | 2021/09/18 |
| Active Loop Antenna | Beijing Da Ze Technology Co.,Ltd. | ZN30900C | 15006 | 2020/10/11 | 2021/10/10 |
| Bilog Antenna | Schwarzbeck | VULB9163 | 000976 | 2021/05/25 | 2022/05/24 |
| Broadband Horn Antenna | SCHWARZBECK | BBHA 9170 | 791 | 2020/09/19 | 2021/09/18 |
| Amplifier | Schwarzbeck | BBV 9743 | #202 | 2020/09/19 | 2021/09/18 |
| Amplifier | Schwarzbeck | BBV9179 | 9719-025 | 2020/09/19 | 2021/09/18 |
| Amplifier | EMCI | EMC051845B | 980355 | 2020/09/19 | 2021/09/18 |
| Temperature/Humidity Meter | Gangxing | CTH-608 | 02 | 2020/09/19 | 2021/09/18 |
| High-Pass Filter | K&L | 9SH10-2700/X12750-O/O | KL142031 | 2020/09/19 | 2021/09/18 |
| High-Pass Filter | K&L | 41H10-1375/U12750-O/O | KL142032 | 2020/09/19 | 2021/09/18 |
| RF Cable(below 1GHz) | HUBER+SUHNER | RG214 | RE01 | 2020/09/19 | 2021/09/18 |
| RF Cable(above 1GHz) | HUBER+SUHNER | RG214 | RE02 | 2020/09/19 | 2021/09/18 |
| Data acquisition card | Agilent | U2531A | TW53323507 | 2020/09/19 | 2021/09/18 |
| Power Sensor | Agilent | U2021XA | MY5365004 | 2020/09/19 | 2021/09/18 |
| Test Control Unit | Tonscend | JS0806-1 | 178060067 | 2021/06/19 | 2022/06/18 |
| Automated filter bank | Tonscend | JS0806-F | 19F8060177 | 2021/06/19 | 2022/06/18 |
| EMI Test Software | Tonscend | JS1120-1 | Ver 2.6.8.0518 | / | / |
| EMI Test Software | Tonscend | JS1120-3 | Ver 2.5.77.0418 | / | / |
| EMI Test Software | Tonscend | JS32-CE | Ver 2.5 | / | / |
| EMI Test Software | Tonscend | JS32-RE | Ver 2.5.1.8 | / | / |

Note: The Cal.Interval was one year.

4 TEST CONDITIONS AND RESULTS

4.1 AC Power Conducted Emission

TEST CONFIGURATION



TEST PROCEDURE

- 1 The equipment was set up as per the test configuration to simulate typical actual usage per the user's manual. The EUT is a tabletop system, a wooden table with a height of 0.8 meters is used and is placed on the ground plane as per ANSI C63.10-2013.
- 2 Support equipment, if needed, was placed as per ANSI C63.10-2013
- 3 All I/O cables were positioned to simulate typical actual usage as per ANSI C63.10-2013
- 4 The EUT received DC 12V power from adapter, the adapter received AC120V/60Hz and AC 240V/60Hz power through a Line Impedance Stabilization Network (LISN) which supplied power source and was grounded to the ground plane.
- 5 All support equipments received AC power from a second LISN, if any.
- 6 The EUT test program was started. Emissions were measured on each current carrying line of the EUT using a spectrum Analyzer / Receiver connected to the LISN powering the EUT. The LISN has two monitoring points: Line 1 (Hot Side) and Line 2 (Neutral Side). Two scans were taken: one with Line 1 connected to Analyzer / Receiver and Line 2 connected to a 50 ohm load; the second scan had Line 1 connected to a 50 ohm load and Line 2 connected to the Analyzer / Receiver.
- 7 Analyzer / Receiver scanned from 150 KHz to 30MHz for emissions in each of the test modes.
- 8 During the above scans, the emissions were maximized by cable manipulation.

AC Power Conducted Emission Limit

For intentional device, according to § 15.207(a) AC Power Conducted Emission Limits is as following :


| Frequency range (MHz) | Limit (dBuV) | |
|-----------------------|--------------|-----------|
| | Quasi-peak | Average |
| 0.15-0.5 | 66 to 56* | 56 to 46* |
| 0.5-5 | 56 | 46 |
| 5-30 | 60 | 50 |


* Decreases with the logarithm of the frequency.

TEST RESULTS

Remark:

1. All modes of GFSK, $\Pi/4$ DQPSK were test at Low, Middle, and High channel; only the worst result of GFSK Middle Channel was reported as below:
2. Both 120 VAC, 50/60 Hz and 240 VAC, 50/60 Hz power supply have been tested, only the worst result of 120 VAC, 60 Hz was reported as below:
3. Remark: Result=Reading value+Factor, and Margin=Limit- Result







4.2 Radiated Emissions and Band Edge

TEST CONFIGURATION


Frequency range 9 KHz – 30MHz



Frequency range 30MHz – 1000MHz



Frequency range above 1GHz-25GHz



TEST PROCEDURE

1. The EUT was placed on a turn table which is 0.8m above ground plane when testing frequency range 9 KHz –1GHz; the EUT was placed on a turn table which is 1.5m above ground plane when testing frequency range 1GHz – 25GHz.
2. Maximum procedure was performed by raising the receiving antenna from 1m to 4m and rotating the turn table from 0°C to 360°C to acquire the highest emissions from EUT.
3. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
4. Repeat above procedures until all frequency measurements have been completed.
5. The EUT minimum operation frequency was 32.768KHz and maximum operation frequency was 2480MHz. so radiated emission test frequency band from 9KHz to 25GHz.
6. The distance between test antenna and EUT as following table states:

| Test Frequency range | Test Antenna Type | Test Distance |
|----------------------|----------------------------|---------------|
| 9KHz-30MHz | Active Loop Antenna | 3 |
| 30MHz-1GHz | Ultra-Broadband Antenna | 3 |
| 1GHz-18GHz | Double Ridged Horn Antenna | 3 |
| 18GHz-25GHz | Horn Antenna | 1 |

7. Setting test receiver/spectrum as following table states:

| Test Frequency range | Test Receiver/Spectrum Setting | Detector |
|----------------------|---|----------|
| 9KHz-150KHz | RBW=200Hz/VBW=3KHz, Sweep time=Auto | QP |
| 150KHz-30MHz | RBW=9KHz/VBW=100KHz, Sweep time=Auto | QP |
| 30MHz-1GHz | RBW=120KHz/VBW=1000KHz, Sweep time=Auto | QP |
| 1GHz-40GHz | Peak Value: RBW=1MHz/VBW=3MHz, Sweep time=Auto Average Value: RBW=1MHz/VBW=10Hz, Sweep time=Auto | Peak |

Field Strength Calculation

The field strength is calculated by adding the Antenna Factor and Cable Factor and subtracting the Amplifier Gain and Duty Cycle Correction Factor(if any) from the measured reading. The basic equation with a sample calculation is as follows:

$$FS = RA + AF + CL - AG$$

| | |
|---------------------------|--|
| Where FS = Field Strength | CL = Cable Attenuation Factor (Cable Loss) |
| RA = Reading Amplitude | AG = Amplifier Gain |
| AF = Antenna Factor | |

$$Transd=AF + CL - AG$$

RADIATION LIMIT

For intentional device, according to § 15.209(a), the general requirement of field strength of radiated emission from intentional radiators at a distance of 3 meters shall not exceed the following table. According to § 15.247(d), in any 100kHz bandwidth outside the frequency band in which the EUT is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of desired power.


The pre-test have done for the EUT in three axes and found the worst emission at position shown in test setup photos.

| Frequency (MHz) | Distance (Meters) | Radiated (dB μ V/m) | Radiated (μ V/m) |
|-----------------|-------------------|----------------------------------|-----------------------|
| 0.009-0.49 | 3 | 20log(2400/F(KHz))+40log(300/3) | 2400/F(KHz) |
| 0.49-1.705 | 3 | 20log(24000/F(KHz))+ 40log(30/3) | 24000/F(KHz) |
| 1.705-30 | 3 | 20log(30)+ 40log(30/3) | 30 |
| 30-88 | 3 | 40.0 | 100 |
| 88-216 | 3 | 43.5 | 150 |
| 216-960 | 3 | 46.0 | 200 |
| Above 960 | 3 | 54.0 | 500 |

TEST RESULTS

Remark:


1. This test was performed with EUT in X, Y, Z position and the worse case was found when EUT in X position.
2. Both modes of BLE 1Mbps were tested at Low, Middle, and High channel and recorded worst mode at BLE 1Mbps.
3. Radiated emission test from 9 KHz to 10th harmonic of fundamental was verified, and no emission found except system noise floor in 9 KHz to 30MHz and not recorded in this report.

For 30MHz-1GHz**Suspected List**

| NO. | Frequency [MHz] | Reading [dB μ V/m] | Factor [dB] | Result [dB μ V/m] | Limit [dB μ V/m] | Margin [dB] | Height [cm] | Angle [°] | Detector | Polarity | Remark |
|-----|-----------------|------------------------|-------------|-----------------------|----------------------|-------------|-------------|-----------|----------|-----------|--------|
| 1 | 62.0100 | 34.63 | -8.75 | 25.88 | 40.00 | 14.12 | 100 | 170 | PK | Horizonta | PASS |
| 2 | 159.4950 | 33.45 | -11.53 | 21.92 | 43.50 | 21.58 | 100 | 10 | PK | Horizonta | PASS |
| 3 | 172.5900 | 42.32 | -11.27 | 31.05 | 43.50 | 12.45 | 100 | 210 | PK | Horizonta | PASS |
| 4 | 188.1100 | 35.24 | -10.07 | 25.17 | 43.50 | 18.33 | 100 | 210 | PK | Horizonta | PASS |
| 5 | 243.4000 | 38.14 | -8.41 | 29.73 | 46.00 | 16.27 | 100 | 350 | PK | Horizonta | PASS |
| 6 | 269.1050 | 31.54 | -8.31 | 23.23 | 46.00 | 22.77 | 100 | 180 | PK | Horizonta | PASS |

Note: 1. Result (dB μ V/m) = Reading(dB μ V/m) + Factor (dB) .

2. Factor (dB) = Antenna Factor (dB/m) + Cable loss (dB) - Pre Amplifier gain (dB).



For 1GHz to 25GHz

GFSK (above 1GHz)

| Frequency(MHz): | | 2402 | | Polarity: | | HORIZONTAL | | |
|-----------------|-------------------------|----------------|-------------|------------------|-----------------------|-------------------|--------------------|--------------------------|
| Frequency (MHz) | Emission Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Raw Value (dBuV) | Antenna Factor (dB/m) | Cable Factor (dB) | Pre-amplifier (dB) | Correction Factor (dB/m) |
| 4804.00 | 58.18 | PK | 74 | 15.82 | 56.28 | 31.42 | 6.98 | 36.5 |
| 4804.00 | 42.69 | AV | 54 | 11.31 | 40.79 | 31.42 | 6.98 | 36.5 |
| 7206.00 | 54.63 | PK | 74 | 19.37 | 44.03 | 37.03 | 8.87 | 35.3 |
| 7206.00 | 41.45 | AV | 54 | 12.55 | 30.85 | 37.03 | 8.87 | 35.3 |

| Frequency(MHz): | | 2402 | | Polarity: | | VERTICAL | | |
|-----------------|-------------------------|----------------|-------------|------------------|-----------------------|-------------------|--------------------|--------------------------|
| Frequency (MHz) | Emission Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Raw Value (dBuV) | Antenna Factor (dB/m) | Cable Factor (dB) | Pre-amplifier (dB) | Correction Factor (dB/m) |
| 4804.00 | 58.43 | PK | 74 | 15.57 | 56.53 | 31.42 | 6.98 | 36.5 |
| 4804.00 | 42.75 | AV | 54 | 11.25 | 40.85 | 31.42 | 6.98 | 36.5 |
| 7206.00 | 56.32 | PK | 74 | 17.68 | 45.72 | 37.03 | 8.87 | 35.3 |
| 7206.00 | 42.09 | AV | 54 | 11.91 | 31.49 | 37.03 | 8.87 | 35.3 |

| Frequency(MHz): | | 2440 | | Polarity: | | HORIZONTAL | | |
|-----------------|-------------------------|----------------|-------------|------------------|-----------------------|-------------------|--------------------|--------------------------|
| Frequency (MHz) | Emission Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Raw Value (dBuV) | Antenna Factor (dB/m) | Cable Factor (dB) | Pre-amplifier (dB) | Correction Factor (dB/m) |
| 4880.00 | 58.74 | PK | 74 | 15.26 | 56.68 | 30.98 | 7.58 | 36.5 |
| 4880.00 | 43.88 | AV | 54 | 10.12 | 41.82 | 30.98 | 7.58 | 36.5 |
| 7320.00 | 56.39 | PK | 74 | 17.61 | 45.47 | 37.66 | 8.56 | 35.3 |
| 7320.00 | 42.21 | AV | 54 | 11.79 | 31.29 | 37.66 | 8.56 | 35.3 |

| Frequency(MHz): | | 2440 | | Polarity: | | VERTICAL | | |
|-----------------|-------------------------|----------------|-------------|------------------|-----------------------|-------------------|--------------------|--------------------------|
| Frequency (MHz) | Emission Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Raw Value (dBuV) | Antenna Factor (dB/m) | Cable Factor (dB) | Pre-amplifier (dB) | Correction Factor (dB/m) |
| 4880.00 | 58.89 | PK | 74 | 15.11 | 56.83 | 30.98 | 7.58 | 36.5 |
| 4880.00 | 43.97 | AV | 54 | 10.03 | 41.91 | 30.98 | 7.58 | 36.5 |
| 7320.00 | 56.78 | PK | 74 | 17.22 | 45.86 | 37.66 | 8.56 | 35.3 |
| 7320.00 | 42.40 | AV | 54 | 11.60 | 31.48 | 37.66 | 8.56 | 35.3 |

| Frequency(MHz): | | 2480 | | Polarity: | | HORIZONTAL | | |
|-----------------|-------------------------|----------------|-------------|------------------|-----------------------|-------------------|--------------------|--------------------------|
| Frequency (MHz) | Emission Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Raw Value (dBuV) | Antenna Factor (dB/m) | Cable Factor (dB) | Pre-amplifier (dB) | Correction Factor (dB/m) |
| 4960.00 | 59.25 | PK | 74 | 14.75 | 56.18 | 31.47 | 7.8 | 36.2 |
| 4960.00 | 43.12 | AV | 54 | 10.88 | 40.05 | 31.47 | 7.8 | 36.2 |
| 7440.00 | 56.67 | PK | 74 | 17.33 | 44.93 | 38.32 | 8.72 | 35.3 |
| 7440.00 | 41.40 | PK | 54 | 12.60 | 29.66 | 38.32 | 8.72 | 35.3 |

| Frequency(MHz): | | 2480 | | Polarity: | | VERTICAL | | |
|-----------------|-------------------------|----------------|-------------|------------------|-----------------------|-------------------|--------------------|--------------------------|
| Frequency (MHz) | Emission Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Raw Value (dBuV) | Antenna Factor (dB/m) | Cable Factor (dB) | Pre-amplifier (dB) | Correction Factor (dB/m) |
| 4960.00 | 59.81 | PK | 74 | 14.19 | 56.74 | 31.47 | 7.8 | 36.2 |
| 4960.00 | 43.80 | AV | 54 | 10.20 | 40.73 | 31.47 | 7.8 | 36.2 |
| 7440.00 | 56.43 | PK | 74 | 17.57 | 44.69 | 38.32 | 8.72 | 35.3 |
| 7440.00 | 41.49 | PK | 54 | 12.51 | 29.75 | 38.32 | 8.72 | 35.3 |

REMARKS:

1. Emission level (dBuV/m) =Raw Value (dBuV)+Correction Factor (dB/m)
2. Correction Factor (dB/m) = Antenna Factor (dB/m)+Cable Factor (dB)- Pre-amplifier
3. Margin value = Limit value- Emission level.
4. -- Mean the PK detector measured value is below average limit.
5. The other emission levels were very low against the limit.

Results of Band Edges Test (Radiated)**GFSK**

| Frequency(MHz): | | 2402 | | Polarity: | | HORIZONTAL | | |
|------------------------|-------------------------|----------------|-------------|------------------|-----------------------|-------------------|--------------------|--------------------------|
| Frequency (MHz) | Emission Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Raw Value (dBuV) | Antenna Factor (dB/m) | Cable Factor (dB) | Pre-amplifier (dB) | Correction Factor (dB/m) |
| 2390.00 | 58.33 | PK | 74 | 15.67 | 63.74 | 27.49 | 3.32 | 36.22 |
| 2390.00 | 40.57 | AV | 54 | 13.43 | 45.98 | 27.49 | 3.32 | 36.22 |
| Frequency(MHz): | | 2402 | | Polarity: | | VERTICAL | | |
| Frequency (MHz) | Emission Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Raw Value (dBuV) | Antenna Factor (dB/m) | Cable Factor (dB) | Pre-amplifier (dB) | Correction Factor (dB/m) |
| 2390.00 | 58.55 | PK | 74 | 15.45 | 63.96 | 27.49 | 3.32 | 36.22 |
| 2390.00 | 39.88 | AV | 54 | 14.12 | 45.29 | 27.49 | 3.32 | 36.22 |
| Frequency(MHz): | | 2480 | | Polarity: | | HORIZONTAL | | |
| Frequency (MHz) | Emission Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Raw Value (dBuV) | Antenna Factor (dB/m) | Cable Factor (dB) | Pre-amplifier (dB) | Correction Factor (dB/m) |
| 2483.50 | 57.67 | PK | 74 | 16.33 | 63.18 | 27.45 | 3.38 | 36.34 |
| 2483.50 | 39.17 | AV | 54 | 14.83 | 44.68 | 27.45 | 3.38 | 36.34 |
| Frequency(MHz): | | 2480 | | Polarity: | | VERTICAL | | |
| Frequency (MHz) | Emission Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Raw Value (dBuV) | Antenna Factor (dB/m) | Cable Factor (dB) | Pre-amplifier (dB) | Correction Factor (dB/m) |
| 2483.50 | 57.88 | PK | 74 | 16.12 | 63.39 | 27.45 | 3.38 | 36.34 |
| 2483.50 | 39.36 | AV | 54 | 14.64 | 44.87 | 27.45 | 3.38 | 36.34 |

REMARKS:

1. Emission level (dBuV/m) =Raw Value (dBuV)+Correction Factor (dB/m)
2. Correction Factor (dB/m) = Antenna Factor (dB/m)+Cable Factor (dB)- Pre-amplifier
3. Margin value = Limit value- Emission level.
4. -- Mean the PK detector measured value is below average limit.

4.3 Maximum Peak Output Power


Limit

The Maximum Peak Output Power Measurement is 30dBm.

Test Procedure

Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the power sensor.

Test Configuration



Test Results

| Type | Channel | Output power (dBm) | Limit (dBm) | Result |
|------------|---------|--------------------|-------------|--------|
| GFSK 1Mbps | 00 | -4.739 | 30.00 | Pass |
| | 19 | -4.972 | | |
| | 39 | -5.163 | | |

Note: 1.The test results including the cable loss.

4.4 Power Spectral Density


Limit

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

Test Procedure

1. Use this procedure when the maximum peak conducted output power in the fundamental emission is used to demonstrate compliance.
2. Set the RBW \geq 3 kHz.
3. Set the VBW $\geq 3 \times$ RBW.
4. Set the span to 1.5 times the DTS channel bandwidth.
5. Detector = peak.
6. Sweep time = auto couple.
7. Trace mode = max hold.
8. Allow trace to fully stabilize.
9. Use the peak marker function to determine the maximum power level.
10. If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.
11. The resulting peak PSD level must be 8dBm.

Test Configuration



Test Results


| Type | Channel | Power Spectral Density (dBm/3KHz) | Limit (dBm/3KHz) | Result |
|------------|---------|-----------------------------------|------------------|--------|
| GFSK 1Mbps | 00 | -22.644 | 8.00 | Pass |
| | 19 | -22.995 | | |
| | 39 | -23.673 | | |

Test plot as follows:


BLE GFSK 1Mbps



CH00



CH19



CH39

4.5 6dB Bandwidth


Limit

For digital modulation systems, the minimum 6 dB bandwidth shall be at least 500 kHz

Test Procedure

The transmitter output was connected to the spectrum analyzer through an attenuator. The bandwidth of the fundamental frequency was measured by spectrum analyzer with 100 KHz RBW and 300 KHz VBW. The 6dB bandwidth is defined as the total spectrum the power of which is higher than peak power minus 6dB.

Test Configuration



Test Results

| Type | Channel | 6dB Bandwidth (MHz) | Limit (KHz) | Result |
|------------|---------|---------------------|-------------|--------|
| GFSK 1Mbps | 00 | 0.5317 | ≥500 | Pass |
| | 19 | 0.5297 | | |
| | 39 | 0.5312 | | |

Test plot as follows:



4.6 Out-of-band Emissions


Limit

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required.

Test Procedure

Connect the transmitter output to spectrum analyzer using a low loss RF cable, and set the spectrum analyzer to RBW=100 kHz, VBW= 300 kHz, peak detector , and max hold. Measurements utilizing these setting are made of the in-band reference level, bandedge and out-of-band emissions.


Test Configuration



Test Results

Remark: The measurement frequency range is from 30MHz to the 10th harmonic of the fundamental frequency. The lowest, middle and highest channels are tested to verify the spurious emissions and bandage measurement data.

Test plot as follows:



Test Mode: GFSK Test channel : 19

Test Mode: GFSK

Display Line -25.19 dBm

Ref Offset 1.5 dB
Ref 10.00 dBm

Center 2.440000 GHz #Res BW 100 kHz #VBW 300 kHz Sweep 1.000 ms (1001 pts)

Mkr1 2.439 739 GHz -5.194 dBm

10 dB/div Log

RF 50 Ω AC SENSE:PULSE ALIGN AUTO 03:32:16 PM Jul 10, 2021

PNO: Wide Trig: Free Run Avg Type: Log-Pwr Avg Hold: >100/100

IFGain:Low Atten: 20 dB

TYPE M W W W W DET P N N N N

Test channel : 19

Stop Freq 3.000000000 GHz

Ref Offset 1.5 dB
Ref 10.00 dBm

Start 0.030 GHz #Res BW 100 kHz #VBW 300 kHz Sweep 283.9 ms (1001 pts)

Mkr1 2.439 7 GHz -5.169 dBm

10 dB/div Log

RF 50 Ω AC SENSE:PULSE ALIGN AUTO 03:32:28 PM Jul 10, 2021

PNO: Fast Trig: Free Run Avg Type: Log-Pwr Avg Hold: 1/100

IFGain:Low Atten: 20 dB

TYPE M W W W W DET P N N N N

30M Hz~3GHz

Marker 1 24.1640000000000 GHz

Ref Offset 1.5 dB
Ref 10.00 dBm

Start 3.00 GHz #Res BW 100 kHz #VBW 300 kHz Sweep 2.103 s (1001 pts)

Mkr1 24.164 GHz -54.484 dBm

10 dB/div Log


RF 50 Ω AC SENSE:PULSE ALIGN AUTO 03:32:44 PM Jul 10, 2021


PNO: Fast Trig: Free Run Avg Type: Log-Pwr Avg Hold: 2/100

IFGain:Low Atten: 20 dB

TYPE M W W W W DET P N N N N

Display
Annotation
Title
Graticule
Display Line
System Display
Frequency
Auto Tune
Center Freq
1.515000000 GHz
Start Freq
30.000000 MHz
Stop Freq
3.000000000 GHz
CF Step
297.000000 MHz
Freq Offset
0 Hz
Scale Type
Log Lin
Peak Search
Next Peak
Next Pk Right
Next Pk Left
Marker Delta
Mkr→CF
Mkr→Ref Lvl
More
1 of 2



Band-edge Measurements for RF Conducted Emissions:

Left bandedge

Right bandedge

4.7 Antenna Requirement

Standard Applicable

For intentional device, according to FCC 47 CFR Section 15.203:

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited


FCC CFR Title 47 Part 15 Subpart C Section 15.247(c) (1) (I):

(i) Systems operating in the 2400-2483.5 MHz band that is used exclusively for fixed. Point-to-point operations may employ transmitting antennas with directional gain greater than 6dBi provided the maximum conducted output power of the intentional radiator is reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6dBi.



Antenna Connected Construction

The maximum gain of antenna was 0.00dBi.

5 Test Setup Photos of the EUT



6 Photos of the EUT



***** End of Report *****