

EcoFlow DELTA 3 Plus

Portable Power Station
Station électronique portable

Model / Modèle: EF-DL-H10-4
Capacity / Capacité: 1024Wh 51.2V \approx 20Ah
Charge Temperature / Température de recharge: 0 – 45°C (32 – 113°F)
Discharge Temperature / Température d'utilisation: -10 – 45°C (14 – 113°F)
AC Input / Entrée CA : 100-120V– 15A 50/60Hz (Duration time < 3h when current exceeds 12A)
Solar / Car Input / Entrée solaire / Entrée de voiture: 11-60V 15A 1000W Max (500W Max per port)
Total Output Power / Puissance de sortie totale: 1800W
AC Output(Discharge Only) / Sortie CA (décharge uniquement): 120V– 60Hz 1800W total
AC Output(Bypass MODE) / Sortie CA (mode Bypass): 100-120V– 50/60Hz total 13A
12V Output / Sortie 12V: 12.6V \approx 10A/3A/3A 126W Max
5V \approx 2.4A 9V \approx 2A 12V \approx 3A 36W Max per port total 72W
USB-A Fast Charge Output / Port USB A de charge rapide (x2): 5V/9/12/15/20/28V \approx 5A 140W Max per port total 280W
FCC ID: 2A2P9-DELTA3721
IC: 27618-DELTA3721

This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions:
 (1) This device may not cause harmful interference, and
 (2) This device must accept any interference received, including interference that may cause undesired operation.

Made in China EcoFlow Inc. www.ecoflow.com
 CAN ICES-003(A) / NMB-003(A)

FC **SGS ENERGY EFFICIENCY** **Bluetooth** **801593**

EcoFlow DELTA 3

Portable Power Station
Station électronique portable

Model / Modèle: EF-DL-H10-3
Capacity / Capacité: 1024Wh 51.2V \approx 20Ah
Charge Temperature / Température de recharge: 0 – 45°C (32 – 113°F)
Discharge Temperature / Température d'utilisation: -10 – 45°C (14 – 113°F)
AC Input / Entrée CA : 100-120V– 15A 50/60Hz (Duration time < 3h when current exceeds 12A)
Solar / Car Input / Entrée solaire / Entrée de voiture: 11-60V 15A 500W Max
Total Output Power / Puissance de sortie totale: 1800W
AC Output(Discharge Only) / Sortie CA (décharge uniquement): 120V– 60Hz 1800W total
AC Output(Bypass MODE) / Sortie CA (mode Bypass): 100-120V– 50/60Hz total 13A
12V Output / Sortie 12V: 12.6V \approx 10A/3A/3A 126W Max
5V \approx 2.4A 9V \approx 2A 12V \approx 1.5A 18W Max per port total 36W
USB-A Fast Charge Output / Port USB A de charge rapide (x2): 5V/9/12/15/20V \approx 5A 100W Max per port total 200W
FCC ID: 2A2P9-DELTA3721
IC: 27618-DELTA3721

This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions:
 (1) This device may not cause harmful interference, and
 (2) This device must accept any interference received, including interference that may cause undesired operation.

Made in China EcoFlow Inc. www.ecoflow.com
 CAN ICES-003(A) / NMB-003(A)

FC **SGS ENERGY EFFICIENCY** **Bluetooth** **801593**



Label location

Note: Product Label applied using permanent adhesive. It is user-accessible and non-detachable.