



Shenzhen Huaxia Testing Technology Co., Ltd

1F., Block A of Tongsheng Technology Building, Huahui Road, Dalang Street, Longhua District, Shenzhen, China

Telephone: +86-755-26648640
Fax: +86-755-26648637
Website: www.cqa-cert.com

Report Template Version: V04
Report Template Revision Date: 2018-07-06

RF Exposure Evaluation Report

Report No.: CQASZ20210500692E-02
Applicant: Ekoo Electronic Co., Ltd
Address of Applicant: B09, Block B, F2, Bldg.B, Runfeng Pioneer Park, No.973, Minzhi Avenue, Minzhi St., Longhua, Shenzhen, CHINA 518000
Equipment Under Test (EUT):
EUT Name: 2.1 Soundbar System
Model No.: D41AH-7, D40CH-8, HW-T150, HW-T350
Test Model No.: HW-T150
Brand Name: ANFLAG
FCC ID: 2A2PN-HW-T150
Standards: 47 CFR Part 1.1307
47 CFR Part 2.1091
KDB447498D01 General RF Exposure Guidance v06
Date of Receipt: 2021-5-19
Date of Test: 2021-5-19 to 2021-8-10
Date of Issue: 2021-8-10
Test Result: **PASS***

*In the configuration tested, the EUT complied with the standards specified above

Tested By: _____ *Lewis Zhou*

(Lewis Zhou)

Reviewed By: _____ *Rock Huang*

(Rock Huang)

Approved By: _____ *Jack Ai*

(Jack Ai)



1 Version

Revision History Of Report

Report No.	Version	Description	Issue Date
CQASZ20210500692E-02	Rev.01	Initial report	2021-8-10

2 Contents

	Page
1 VERSION	2
2 CONTENTS	3
.....	3
3 GENERAL INFORMATION	4
3.1 CLIENT INFORMATION.....	4
3.2 GENERAL DESCRIPTION OF EUT.....	4
4 RF EXPOSURE EVALUATION	5
4.1 RF EXPOSURE COMPLIANCE REQUIREMENT.....	5
4.1.1 <i>Limits</i>	5
4.1.2 <i>Test Procedure</i>	5
4.1.3 <i>EUT RF Exposure</i>	6

3 General Information

3.1 Client Information

Applicant:	Ekoo Electronic Co., Ltd
Address of Applicant:	B09, Block B, F2, Bldg.B, Runfeng Pioneer Park,No.973, Minzhi Avenue, Minzhi St.,Longhua, Shenzhen, CHINA 518000
Manufacturer:	Ekoo Electronic Co., Ltd
Address of Manufacturer:	B09, Block B, F2, Bldg.B, Runfeng Pioneer Park,No.973, Minzhi Avenue, Minzhi St.,Longhua, Shenzhen, CHINA 518000
Factory:	SHENZHEN MENGXIANG TECHNOLOGY CO.,LTD.
Address of Factory:	Shenzhen New District of Longhua City,Dalang street,Tong Fu village industrial zone,16 building 3floor

3.2 General Description of EUT

Product Name:	2.1 Soundbar System
Model No.:	D41AH-7, D40CH-8, HW-T150, HW-T350
Test Model No.:	HW-T150
Trade Mark:	ANFLAG
Hardware Version:	V1.0
Software Version:	V5.0
Operation Frequency:	2402MHz~2480MHz
Bluetooth Version:	V5.0
Modulation Technique:	Frequency Hopping Spread Spectrum(FHSS)
Modulation Type:	GFSK, π/4DQPSK, 8DPSK
Transfer Rate:	1Mbps/2Mbps/3Mbps
Number of Channel:	79
Hopping Channel Type:	Adaptive Frequency Hopping systems
Product Type:	<input type="checkbox"/> Mobile <input type="checkbox"/> Portable <input checked="" type="checkbox"/> Fix Location
Test Software of EUT:	BT Tool
Antenna Type:	PCB antenna
Antenna Gain:	0dBi
Power Supply:	AC ADAPTER Model No:CW1804000US INPUT: 100-240V~ 50/60Hz 1.2A MAX OUTPUT:18V $\overline{=}$ 4000mA

Model No.: D41AH-7, D40CH-8, HW-T150, HW-T350

Only the model HW-T150 was tested, since the electrical circuit design, layout, components used and internal wiring were identical for the above models, with difference being color of appearance and model name.

4 RF Exposure Evaluation

4.1 RF Exposure Compliance Requirement

4.1.1 Limits

According to FCC Part1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in part1.1307(b)

TABLE 1—LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(A) Limits for Occupational/Controlled Exposures				
0.3–3.0	614	1.63	*(100)	6
3.0–30	1842/f	4.89/f	*(900/f ²)	6
30–300	61.4	0.163	1.0	6
300–1500	f/300	6
1500–100,000	5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3–1.34	614	1.63	*(100)	30
1.34–30	824/f	2.19/f	*(180/f ²)	30
30–300	27.5	0.073	0.2	30
300–1500	f/1500	30
1500–100,000	1.0	30

F= Frequency in MHz

Friis Formula

Friis transmission formula: $P_d = (P_{out} * G) / (4 * \pi * R^2)$

Where

P_d = power density in mW/cm²

P_{out} = output power to antenna in mW

G = gain of antenna in linear scale

π = 3.1416

R = distance between observation point and center of the radiator in cm

P_d is the limit of MPE, 1 mW/cm². If we know the maximum gain of the antenna and the total power input to the antenna, through the calculation, we will know the distance r where the MPE limit is reached.

4.1.2 Test Procedure

Software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.

4.1.3 EUT RF Exposure

Antenna Gain: 0dBi

Antenna Gain: The maximum Gain measured in fully anechoic chamber is 1 in linear scale.

Output Power Into Antenna & RF Exposure Evaluation Distance:

Measurement Data

GFSK mode				
Test channel	Peak Output Power (dBm)	Tune up tolerance (dBm)	Maximum tune-up Power	
			(dBm)	(mW)
Lowest(2402MHz)	-5.380	-6±1	-5	0.316
Middle(2441MHz)	-5.930	-6.51	-5.5	0.282
Highest(2480MHz)	-6.110	-7±1	-6	0.251
π/4DQPSK mode				
Test channel	Peak Output Power (dBm)	Tune up tolerance (dBm)	Maximum tune-up Power	
			(dBm)	(mW)
Lowest(2402MHz)	-3.190	-4±1	-3	0.501
Middle(2441MHz)	-3.750	-4.5±1	-3.5	0.447
Highest(2480MHz)	-3.870	-4.5±1	-3.5	0.447
8DPSK mode				
Test channel	Peak Output Power (dBm)	Tune up tolerance (dBm)	Maximum tune-up Power	
			(dBm)	(mW)
Lowest(2402MHz)	-2.700	-3.5±1	-2.5	0.562
Middle(2441MHz)	-3.260	-4±1	-3	0.501
Highest(2480MHz)	-3.460	-4±1	-3	0.501

The worst case:

Maximum tune-up Power (mW)	Antenna Gain (dBi)	Power Density at R = 20 cm (mW/cm ²)	Limit	Result
0.562	0	0.0001	1.0	PASS

Note: 1) Refer to report No. CQASZ20210500692E-01 for EUT test Max Conducted Peak Output Power value.

2) $P_d = (P_{out} * G) / (4 * \pi * R^2) = (0.562 * 1) / (4 * 3.1416 * 20^2) = 0.0001$