# RF Exposure Report

FCC ID: 2A2PN-V8PRO

**Report No.** : SSP24010168-3E

**Applicant** : Ekoo Electronic Co., Ltd

**Product Name** : Robot Vacuum Cleaner

Model Name : V8 Pro

**Test Standard**: FCC CFR 47 PART 1.1307(b)

**Date of Issue** : 2024-03-20



#### Shenzhen CCUT Quality Technology Co., Ltd.

1F, Building 35, Changxing Technology Industrial Park, Yutang Street, Guangming District, Shenzhen, Guangdong, China; (Tel.:+86-755-23406590 website: www.ccuttest.com)

This test report is limited to the above client company and the product model only. It may not be duplicated without prior permitted by Shenzhen CCUT Quality Technology Co., Ltd.

FCC Test Report Page 1 of 7

APPROVE

### **Test Report Basic Information**

Applicant..... Ekoo Electronic Co., Ltd

B09, Block B, F2, Bldg.B, Runfeng Pioneer Park, No.973, Minzhi Avenue,

Address of Applicant...... Minzhi St., Longhua, Shenzhen, China

Manufacturer..... Ekoo Electronic Co., Ltd

B09, Block B, F2, Bldg.B, Runfeng Pioneer Park, No.973, Minzhi Avenue,

Address of Manufacturer......: Minzhi St., Longhua, Shenzhen, China

Product Name ...... Robot Vacuum Cleaner

Brand Name...... Huniture

Main Model..... V8 Pro

Series Models...... V8, V8 SE, Mars02, Mars02 Pro, Mars02 Nex

FCC CFR 47 PART 1.1307(b)

**Test Standard**...... KDB 447498 D01 v06

Test Result...... PASS

Tested By ...... Larrix Lua (Lorzix Luo)

Reviewed By (Lieber Ouvang)

Authorized Signatory...... (Lahm Peng)

Note: This test report is limited to the above client company and the product model only. It may not be duplicated without prior permitted by Shenzhen CCUT Quality Technology Co., Ltd.. All test data presented in this test report is only applicable to presented test sample.

FCC Test Report Page 2 of 7

## **CONTENTS**

1. General Information	5
1.1 Product Information	
1.2 Test Facilities	
2. RF Exposure	e
2.1 Standard and Limit	
2.2 Test Data and Results	_

## **Revision History**

Revision	Issue Date	Description	Revised By
V1.0	2024-03-20	Initial Release	Lahm Peng

FCC Test Report Page 4 of 7

### 1. General Information

#### 1.1 Product Information

Product Name:	Robot Vacuum Cleaner
Trade Name:	Huniture
Main Model:	V8 Pro
Series Models:	V8, V8 SE, Mars02, Mars02 Pro, Mars02 Nex
Rated Voltage:	DC 14.4V by battery, DC 20V Charging from Charging Dock
Dayyor Adaptor	Model: SAW12G-200-0600U
Power Adapter:	Input: 100-240V~50/60Hz 0.5A, Output: DC 20V/600mA
Battery:	DC 14.4V, 2600mAh
Hardware Version:	V1.0
Software Version:	V1.0

Report No: SSP24010168-3E

Note 1: The test data is gathered from a production sample, provided by the manufacturer.

Note 2: The color of appearance and model name of series models listed are different from the main model, but the circuit and the electronic construction are the same, declared by the manufacturer.

Wireless Specification				
Wireless Standard:	Bluetooth BLE, 802.11b/g/n			
Operating Frequency:	BT: 2402MHz ~2480MHz, 2.4GWiFi: 2412 MHz ~2462 MHz			
RF Output Power:	BLE: 1.65dBm, 2.4GWiFi: 15.55dBm			
Antenna Gain:	3.46dBi			
Type of Antenna:	FPCB Antenna			
Type of Device:	☐ Portable Device ☐ Modular Device			

### 1.2 Test Facilities

	Shenzhen CCUT Quality Technology Co., Ltd.				
Laboratory Name:	1F, Building 35, Changxing Technology Industrial Park, Yutang Street,				
	Guangming District, Shenzhen, Guangdong, China				
CNAS Laboratory No.:	L18863				
A2LA Certificate No.:	6893.01				
FCC Registration No:	583813				
ISED Registration No.:	CN0164				
	•				

All measurement facilities used to collect the measurement data are located at 1F, Building 35, Changxing Technology Industrial Park, Yutang Street, Guangming District, Shenzhen, Guangdong, China.

FCC Test Report Page 5 of 7

## 2. RF Exposure

#### 2.1 Standard and Limit

The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in 1.1307(b)

Report No: SSP24010168-3E

Limits for Maximum Permissible Exposure (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm2)	Averaging time (minutes)		
	(A) Limits f	or Occupational/Controlle	d Exposures			
0.3-3.0	614	1.63	*(100)	6		
3.0-30	1842/f	4.89/f	*(900/f2)	6		
30-300	61.4	0.163	1.0	6		
300-1500			f/300	6		
1500-100,000			5	6		
	(B) Limits for General Population/Uncontrolled Exposure					
0.3-1.34	614	1.63	*(100)	30		
1.34-30	824/f	2.19/f	*(180/f2)	30		
30-300	27.5	0.073	0.2	30		
300-1500			f/1500	30		
1500-100,000			1.0	30		

f = frequency in MHz

Friis transmission formula: Pd = (Pout\*G)/(4\*pi\*r2)

#### Where

Pd = power density in mW/cm2, Pout = output power to antenna in mW;

G = gain of antenna in linear scale, Pi = 3.1416;

R = distance between observation point and center of the radiator in cm

Pd id the limit of MPE, 1 mW/cm2. If we know the maximum gain of the antenna and the total power input to the antenna, through the calculation, we will know the distance r where the MPE limit is reached.

#### **Test Procedure**

Software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.

FCC Test Report Page 6 of 7

## 2.2 Test Data and Results

## For BLE

Mode	Output power to antenna (dBm)	Tune-up Power(dBm)	Max Tune-up Power(dBm)	Output power to antenna (mW)	Power Density at R=20cm (mW/cm2)	Limit (mW/cm2)	Result
GFSK	1.65	1(±1)	2	1.58	0.0007	1.0	PASS

### For 2.4G WiFi

Mode	Output power to antenna (dBm)	Tune-up Power(dBm)	Max Tune-up Power(dBm)	Output power to antenna (mW)	Power Density at R=20cm (mW/cm2)	Limit (mW/cm2)	Result
802.11b	15.55	15(±1)	16	39.81	0.0176	1.0	PASS

Remark: antenna gain=3.46dBi

FCC Test Report Page 7 of 7