

## RF EXPOSURE EVALUATION

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency(RF) Radiation as specified in §1.1307(b)

FCC ID: 2A2PW149658

### EUT Specification

<b>EUT</b>	Outdoor Access Point
<b>Frequency band (Operating)</b>	<input type="checkbox"/> BT: 2.402GHz ~ 2.480GHz <input checked="" type="checkbox"/> BLE: 2.402GHz ~ 2.480GHz <input checked="" type="checkbox"/> WIFI: 2.412GHz ~ 2.462GHz <input checked="" type="checkbox"/> WIFI: 5.180GHz ~ 5.240GHz <input checked="" type="checkbox"/> WIFI: 5.260GHz ~ 5.320GHz <input checked="" type="checkbox"/> WIFI: 5.500GHz ~ 5.700GHz <input checked="" type="checkbox"/> WIFI: 5.745GHz ~ 5.825GHz
<b>Device category</b>	<input type="checkbox"/> Portable (<20cm separation) <input checked="" type="checkbox"/> Mobile (>20cm separation)
<b>Exposure classification</b>	<input type="checkbox"/> Occupational/Controlled exposure (S = 5mW/cm <sup>2</sup> ) <input checked="" type="checkbox"/> General Population/Uncontrolled exposure (S=1mW/cm <sup>2</sup> )
<b>Antenna diversity</b>	<input type="checkbox"/> Single antenna <input checked="" type="checkbox"/> Multiple antennas <input type="checkbox"/> Tx diversity <input type="checkbox"/> Rx diversity <input type="checkbox"/> Tx/Rx diversity
<b>Max. output power (peak power)</b>	BLE BLE 1M: 2.25 dBm 2.4G WIFI IEEE 802.11b: 10.61 dBm IEEE 802.11g: 9.47 dBm IEEE 802.11n HT20: 11.68 dBm IEEE 802.11n HT40: 10.86 dBm IEEE 802.11ax HE20: 12.01 dBm IEEE 802.11ax HE40: 11.3 dBm 5G WIFI U-NII-1 IEEE 802.11a: 7.71 dBm IEEE 802.11n HT20: 7.67 dBm IEEE 802.11n HT40: 7.59 dBm IEEE 802.11ac VHT20: 7.4 dBm IEEE 802.11ac VHT40: 7.49 dBm IEEE 802.11ac VHT80: 7.23 dBm IEEE 802.11ax HE20: 7.61 dBm

	<p>IEEE 802.11ax HE40: 7.66 dBm  IEEE 802.11ax HE80: 7.33 dBm  U-NII-2A  IEEE 802.11a: 8.08 dBm  IEEE 802.11n HT20: 8.34 dBm  IEEE 802.11n HT40: 8.09 dBm  IEEE 802.11ac VHT20: 7.54 dBm  IEEE 802.11ac VHT40: 8.05 dBm  IEEE 802.11ac VHT80: 6.84 dBm  IEEE 802.11ax HE20: 7.78 dBm  IEEE 802.11ax HE40: 8.22 dBm  IEEE 802.11ax HE80: 6.91 dBm  U-NII-2C  IEEE 802.11a: 8.23 dBm  IEEE 802.11n HT20: 7.48 dBm  IEEE 802.11n HT40: 6.62 dBm  IEEE 802.11ac VHT20: 7.33 dBm  IEEE 802.11ac VHT40: 6.55 dBm  IEEE 802.11ac VHT80: 7.2 dBm  IEEE 802.11ax HE20: 7.66 dBm  IEEE 802.11ax HE40: 6.77 dBm  IEEE 802.11ax HE80: 7.3 dBm  U-NII-3  IEEE 802.11a: 6.6 dBm  IEEE 802.11n HT20: 9.3 dBm  IEEE 802.11n HT40: 9.1 dBm  IEEE 802.11ac VHT20: 9.23 dBm  IEEE 802.11ac VHT40: 9 dBm  IEEE 802.11ac VHT80: 9.04 dBm  IEEE 802.11ax HE20: 9.56 dBm  IEEE 802.11ax HE40: 9.19 dBm  IEEE 802.11ax HE80: 9.37 dBm</p>
<b>Antenna gain (Max)</b>	<p>BLE: 4.5dBi  2.4G WIFI  9 dBi for antenna 1  9 dBi for antenna 2  5G WIFI  9 dBi for antenna 1  9 dBi for antenna 2</p>
<b>Evaluation applied</b>	<p><input checked="" type="checkbox"/>MPE Evaluation  <input type="checkbox"/>SAR Evaluation</p>

Limits for Maximum Permissible Exposure(MPE)

Frequency Range(MHz)	Electric Field Strength(V/m)	Magnetic Field Strength(A/m)	Power Density(mW/cm <sup>2</sup> )	Average Time
<b>(A) Limits for Occupational/Control Exposures</b>				
300-1500	--	--	F/300	6
1500-100000	--	--	5	6
<b>(B) Limits for General Population/Uncontrol Exposures</b>				
300-1500	--	--	F/1500	6
1500-100000	--	--	1	30

**Friis transmission formula:  $P_d=(P_{out}*G)/(4*\pi*R^2)$**

Where

$P_d$ = Power density in mW/cm<sup>2</sup>,  $P_{out}$ =output power to antenna in mW.

G= gain of antenna in linear scale,  $\pi=3.1416$

R= distance between observation point and center of the radiator in cm=20cm

$P_d$  the limit of MPE, 1mW/cm<sup>2</sup>. If we know the maximum gain of the antenna and total power input to the antenna, through the calculation, we will know the distance where the MPE limit is reached.

For multiple RF sources: Multiple RF sources are exempt if:

in the case of fixed RF sources operating in the same time-averaging period, or of multiple mobile or portable RF sources within a device operating in the same time averaging period, if the sum of the fractional contributions to the applicable thresholds is less than or equal to 1 as indicated in the following equation

$$\sum_{k=1}^c \frac{Evaluated_k}{Exposure Limit_k} \leq 1$$

$Evaluated_k$ : the maximum reported SAR or MPE of fixed, mobile, or portable RF source k either in the device or at the transmitter site from an existing evaluation at the location of exposure.

$Exposure Limit_k$ : either the general population/uncontrolled maximum permissible exposure (MPE) or specific Absorption rate (SAR) limit for each fixed, mobile, or portable RF source k.

## Measurement Result

### BLE:

Mode	Max Measured Power (dBm)	Tune up tolerance (dBm)	Max tune up conducted power(dBm)	Output Peak power (mW)	Ant. Gain (dBi)	Ant. Gain (numeric)	Power density at 20cm (mW/ cm <sup>2</sup> )	Power density Limits (mW/ cm <sup>2</sup> )
BLE 1M	2.25	2 ± 1	3	1.995	4.5	2.818	0.00112	1

## 2.4G WIFI:

Mode	Max Measured Power (dBm)	Tune up tolerance (dBm)	Max tune up conducted power(dBm)	Output Peak power (mW)	Ant. Gain (dBi)	Ant. Gain (numeric)	Power density at 20cm (mW/cm <sup>2</sup> )	Power density Limits (mW/cm <sup>2</sup> )
802.11b	10.61	10±1	11	12.589	9	7.943	0.01989	1
802.11g	9.47	9±1	10	10.000	9	7.943	0.01580	1
802.11n HT20	11.68	11±1	12	15.849	9	7.943	0.02505	1
802.11n HT40	10.86	10±1	11	12.589	9	7.943	0.01989	1
802.11ax HE20	12.01	12±1	13	19.953	9	7.943	0.03153	1
802.11ax HE40	11.3	11±1	12	15.849	9	7.943	0.02505	1

**5G WIFI:**

U-NII-1

Mode	Max Measured Power (dBm)	Tune up tolerance (dBm)	Max tune up conducted power(dBm)	Output Peak power (mW)	Ant. Gain (dBi)	Ant. Gain (numeric)	Power density at 20cm (mW/cm <sup>2</sup> )	Power density Limits (mW/cm <sup>2</sup> )
802.11a	7.71	7±1	8	6.310	9	7.943	0.00997	1
802.11n HT20	7.67	7±1	8	6.310	9	7.943	0.00997	1
802.11n HT40	7.59	7±1	8	6.310	9	7.943	0.00997	1
802.11ac VHT20	7.4	7±1	8	6.310	9	7.943	0.00997	1
802.11ac VHT40	7.49	7±1	8	6.310	9	7.943	0.00997	1
802.11ac VHT80	7.23	7±1	8	6.310	9	7.943	0.00997	1
802.11ax HE20	7.61	7±1	8	6.310	9	7.943	0.00997	1
802.11ax HE40	7.66	7±1	8	6.310	9	7.943	0.00997	1
802.11ax HE80	7.33	7±1	8	6.310	9	7.943	0.00997	1

U-NII-2A

Mode	Max Measured Power (dBm)	Tune up tolerance (dBm)	Max tune up conducted power(dBm)	Output Peak power (mW)	Ant. Gain (dBi)	Ant. Gain (numeric)	Power density at 20cm (mW/cm <sup>2</sup> )	Power density Limits (mW/cm <sup>2</sup> )
802.11a	8.08	8±1	9	7.943	9	7.943	0.01255	1
802.11n HT20	8.34	8±1	9	7.943	9	7.943	0.01255	1
802.11n HT40	8.09	8±1	9	7.943	9	7.943	0.01255	1
802.11ac VHT20	7.54	7±1	8	6.310	9	7.943	0.00997	1
802.11ac VHT40	8.05	8±1	9	7.943	9	7.943	0.01255	1
802.11ac VHT80	6.84	6±1	7	5.012	9	7.943	0.00792	1
802.11ax HE20	7.78	7±1	8	6.310	9	7.943	0.00997	1
802.11ax HE40	8.22	8±1	9	7.943	9	7.943	0.01255	1
802.11ax HE80	6.91	6±1	7	5.012	9	7.943	0.00792	1

U-NII-2C

Mode	Max Measured Power (dBm)	Tune up tolerance (dBm)	Max tune up conducted power(dBm)	Output Peak power (mW)	Ant. Gain (dBi)	Ant. Gain (numeric)	Power density at 20cm (mW/cm <sup>2</sup> )	Power density Limits (mW/cm <sup>2</sup> )
802.11a	8.23	8±1	9	7.943	9	7.943	0.01255	1
802.11n HT20	7.48	7±1	8	6.310	9	7.943	0.00997	1
802.11n HT40	6.62	6±1	7	5.012	9	7.943	0.00792	1
802.11ac VHT20	7.33	7±1	8	6.310	9	7.943	0.00997	1
802.11ac VHT40	6.55	6±1	7	5.012	9	7.943	0.00792	1
802.11ac VHT80	7.2	7±1	8	6.310	9	7.943	0.00997	1
802.11ax HE20	7.66	7±1	8	6.310	9	7.943	0.00997	1
802.11ax HE40	6.77	6±1	7	5.012	9	7.943	0.00792	1
802.11ax HE80	7.3	7±1	8	6.310	9	7.943	0.00997	1



U-NII-3

Mode	Max Measured Power (dBm)	Tune up tolerance (dBm)	Max tune up conducted power(dBm)	Output Peak power (mW)	Ant. Gain (dBi)	Ant. Gain (numeric)	Power density at 20cm (mW/cm <sup>2</sup> )	Power density Limits (mW/cm <sup>2</sup> )
802.11a	6.6	6±1	7	5.012	9	7.943	0.00792	1
802.11n HT20	9.3	9±1	10	10.000	9	7.943	0.01580	1
802.11n HT40	9.1	9±1	10	10.000	9	7.943	0.01580	1
802.11ac VHT20	9.23	9±1	10	10.000	9	7.943	0.01580	1
802.11ac VHT40	9	9±1	10	10.000	9	7.943	0.01580	1
802.11ac VHT80	9.04	9±1	10	10.000	9	7.943	0.01580	1
802.11ax HE20	9.56	9±1	10	10.000	9	7.943	0.01580	1
802.11ax HE40	9.19	9±1	10	10.000	9	7.943	0.01580	1
802.11ax HE80	9.37	9±1	10	10.000	9	7.943	0.01580	1

Maximum Simultaneous transmission MPE Ratio for Bluetooth & 2.4G WIFI & 5G WIFI

Maximum MPE ratio (Bluetooth)	Maximum MPE ratio (2.4G WIFI)	Maximum MPE ratio (5G WIFI)	∑ MPE ratios	Limit	Results
0.00112	0.03153	0.01580	0.04845	1.000	Pass

Signature:



Shawn Wen

Date: 2024-3-13