

Specifications

Specification

client's name: **Shenzhen Gongjin Electronics Co., Ltd.**

CUSTOMER: _____

Customer part number: _____

CUSTOMER P/N: _____

Customer product name: _____

DESCRIPTION: _____

JieLei material number: _____

JL P/N: **C168-JL-6168**


JieLei product name: _____

PART NO: **NDS-5.8G antenna**

Version: _____

Revision: _____

approve	Review	prepared by
Frank	Wensen	Sean
2022.06.02	2022.06.02	2022.06.02



© 2020-2030 Fu Zhou Jie Lei Corporation. All rights reserved.

All content, materials, and programs in this document, including all code, text, graphics, and logos, unless otherwise noted, are the property of Jie Lei Corporation and cannot be reproduced or transmitted in any form or by any means, electronic or mechanical, for any purpose, without the express written permission of Jie Lei Corporation.

Jie Lei Corporation may have patents or pending patent applications, trademarks, copyrights, or other intellectual property rights covering subject matter in this document.

The furnishing of this document does not give you any license to these patents, trademarks, copyrights, or other intellectual property rights except expressly provided in any written license agreement from Jie Lei.



Table of contents

1. Product Performance.....2

2. Environmental Performance Test.....3

3. Mechanical Dimension Drawing.....5

4. BOM..... 8

5.QC Engineering Drawing.....9

6.Packing Specification.....10




Version description

date	Approval	version	description
2022-06-02		V1.0	first version


1. Product Performance

Electrical specifications/Electrical specifications	
Antenna type/Antenna type	5.8G antenna
Antenna number (see drawing)	0031071
Frequency range (MHz)/Frequency range(MHz)	5150~5850
Voltage standing wave ratio/VSWR	≤2.0@5150-5850MHz
input impedance (Ohm)/Impedance(Ohm)	50
Gain(dBi)/Peak Gain(dBi)	4.17@5150-5850MHz
Mechanical specifications/Mechanical specifications	
Antenna size (mm) /Dimensions(mm)	16.2*12.6*7
Connector Type/Connector Type	MHF RF Generation
Cable Type/Cable Type	1.13, L=103mm, black double tin wire
Operating Temperature (°C)/Operation Temperature(°C)	-40~70
Storage temperature (°C)/Storage Temperature(°C)	-20~85


2D/3D Radiation pattern 5G-ANT3

H (Theta=90)



E1 (Phi=0)




E2 (Phi=90)

2. Environmental Performance Test


NO	Item	Test Condition	Test Condition	Specification requirements Requirement 1.	in conclusion
1	Exterior Appearance	Visual inspection by eye Light:1.0 Lighting Lamp:200~300Lx Visual distance Space:0.3~0.6m	Visual Visual	<p>There should be no obvious scars, dents, cracks or deformation on the surface of plastic parts that would affect use.</p> <p>Plastic part: smooth and flat surface without discolor, broken, crack distortion defects is acceptable</p> <p>2. The surface of metal parts has no obvious mechanical damage and other defects.</p> <p>Metal part: No obvious mechanical damage and other defects on the surface</p> <p>3. The surface of the circuit board (or flexible circuit board) has no dirt, damage, oxidation, no obvious mechanical damage and other defects, and the silk screen is clear.</p> <p>PCB (or FPCB): The surface is free of dirt, damage, oxidation, no obvious mechanical damage and other defects, screen printing clear.</p> <p>4. The surface of the conductors is clean and has no defects such as damage.</p> <p>Wire:clearing surface without discolor,broken defects.</p>	<p>Pass</p> <p>Unsatisfied/Fail</p> <p>Not applicable/NA</p>
2	Terminal fixing force /Terminal Retention Force	Fix the connector or load cell and apply the specified pulling force in the direction of the connector axis at a speed not greater than 25mm/min. Apply axial pull out force at the speed rate of not more 25mm/min on the pin assembled in the housing.		<p>12NMIN _</p>	<p>Pass</p> <p>Unsatisfied/Fail</p> <p>Not applicable/NA</p>
3	Welding fixation force /Solder Retention Force	Apply axial pull out force at the speed rate of not more 25mm/min on the pin assembled in the housing. Refer to GB-T2423.17		<p>10NMIN _</p>	<p>Pass</p> <p>Unsatisfied/Fail</p> <p>Not applicable/NA</p>
4	Salt spray resistance test /Salt spray test	specification, 5% sodium chloride (NaCl) solution; pH value 6.5-7.2; temperature 35, test time 48H. Refer to GB-T2423.17, NAACL		<p>After drying at room temperature, check the appearance. There is no obvious corrosion or other abnormal phenomena on the surface of the sample or as required by the drawing specifications.</p> <p>After drying at room temperature, check appearance, the sample surface has no obvious corrosion and other abnormal phenomena or</p>	<p>Pass</p> <p>Unsatisfied/Fail</p> <p>Not applicable/NA</p>

		solution with 5% concentration, pH 6.5-7.2, temperature 35 °C, test time 48 hours.	according to the drawing specifications.	
5	High temperature test /High temperature test	Refer to GB-T2423.2 specification, temperature 70°C, test time 28 hours. Refer to GB-T2423.2, the temperature is 70 °C and the time is 28 hours.	After drying at room temperature, check the appearance to see if the sample has no deformation. Peeling, cracks, wrinkles, discoloration, fish scales. After drying at room temperature, check appearance, samples without deformation, stripping, cracks, wrinkles, different color, fish scale lines.	Pass Unqualified/Fail Not applicable/NA
6	Low temperature test /Low temperature test	Refer to GB-T2423.1 specification, temperature -40°C, test time 28 hours. Refer to GB-T2423.1, the temperature is -40 °C for 28 hours.	After drying at room temperature, check the appearance to see if the sample has no deformation. Peeling, cracks, wrinkles, discoloration, fish scales. After drying at room temperature, check appearance, samples without deformation, stripping, cracks, wrinkles, different color, fish scale lines.	Pass Unqualified/Fail Not applicable/NA
7	High temperature and high humidity measurement Try/High temperature and high humidity test	Refer to GB-T2423.3 specification, temperature 70°C, humidity 95%, test time 16 hours. Refer to GB-T2423.3 specification, temperature 70°C, humidity 95%, time 16H.	After drying at room temperature, check the appearance to see if the sample has no deformation. Peeling, cracks, wrinkles, discoloration, fish scales. After drying at room temperature, check appearance, samples without deformation, stripping, cracks, wrinkles, different color, fish scale lines.	Pass Unqualified/Fail Not applicable/NA
8	Temperature shock test Try /Temperature shock test	Refer to GB-T2423.3 specification, temperature -30°C, 1 hour, temperature 75°C, 1 hour, 22 cycles in total. Refer to GB-T2423.3 specification, temperature -30 °C, 1 hour, temperature 75°C, 1 hour, total 22 cycles.	After drying at room temperature, check the appearance to see if the sample has no deformation. Peeling, cracks, wrinkles, discoloration, fish scales. After drying at room temperature, check appearance, samples without deformation, stripping, cracks, wrinkles, different color, fish scale lines.	Pass Unqualified/Fail Not applicable/NA
9	Drop test /Drop test	One corner, three sides, six sides 1M high altitude Free fall. One corner, three edges, six sides, free fall at an altitude of 1M.	The electrical and mechanical properties are normal. Electrical and mechanical properties are normal.	Pass Unqualified/Fail Not applicable/NA
10	Simulated transportation vibration move	Tested according to ISTA standards. Testing according to ISTA standards	The electrical and mechanical properties are normal. Electrical and mechanical properties are normal.	Pass Unqualified/Fail Not applicable/NA

3. Mechanical Dimension Drawing



产品规格 Product Type		RF113/50 双锡线		
结构图 Structure Drawing				
结构特性 Structure Characteristics				
结构 Structure	项目 Item	标准值 Standard Value		
内导体 Inner Conductor	材质 Material	镀锡铜线 Tinned Copper Wire		
	结构 Construction(mm)	7/0.08		
	标称外径 Nom.Dia(mm)	0.24±0.02		
绝缘层 Insulation	材质 Material	聚全氟乙丙烯 FEP		
	标称外径 Nom.Dia(mm)	0.70±0.02		
外导体 Outer Conductor	材质 Material	镀锡铜线 Tinned Copper Wire 16*4/0.05		
	标称外径 Nom.Dia(mm)	0.92±0.05		
	编织覆盖率 Coverage Ratio(%)	90±5		
护套 Jacket	材质 Material	聚全氟乙丙烯 FEP		
	标称外径 Nom.Dia(mm)	1.13±0.05		
电气性能 Electrical Characteristics				
项目 Item	标准值 Standard Value	项目 Item	频率 Frequency	标准值 Standard Value
阻抗 Impedanc (Ω)	50±2	衰减 Attenuation@20°C (dB/m)	1GHz	2.20
电容 Capacitance(pF/m)	98		2GHz	3.10
速率 Velocity(%)	70		3GHz	3.80
驻波比 VSWR	≤1.30@DC-6GHz		4GHz	4.40
最大工作电压 Max.Operating Voltage(V)	1000		5GHz	4.90
最大工作频率 Max.Operating Frequency(GHz)	6		6GHz	5.40
可靠性 Dependability				
最小弯曲半径(单次)Min.Bending Radius/Single	mm	5		
最小弯曲半径(重复) Min.Bending Radius/Repeated	mm	10		
工作温度范围 Operating Temperature	°C	-55--+200		
包装 Packing				
包装方式 Packing Mode	纸盘 Papery Reel			
包装长度 The Length of Each Reel(m)	1000			
每盘段数 The Joints of Each Reel	≤5			
最小段长 Min. Segment Length(m)	≥10			
使用提示 Trips for Use				
存储环境 Storage Environment	Temperature: below 30°C, humidity :20-65%			
最佳保存周期 The Best Save Cycle	After 2 months, the tinning effect becomes worse after 2 months			
加工温度 Processing Temperature	It can withstand the high temperature of 260°C for a short time			
铁氟龙收缩 Teflon Shrink	Inherent properties of the material, insulation below 0.2mm, sheath			
护套窜动 Jacket Taaverse	below 0.3mm			



4. BOM

List of key raw materials for the built-in antenna							
serial number	Key raw material	Raw material material	Type of raw material	Full name of manufacturer	CQC and UL certification number		remark
1	Wire rod	Ditin copper	1.13		\		
2	metal	Nickel-plated iron	spcc	JY	\		
3	terminal	copper	C5191	CM	\		

Note:

- 1) Fill in "NA" for raw materials that do not contain;
- 2) If there are multiple suppliers of raw materials, they need to be reported, and only 2 suppliers can be reported (and changes are not allowed within 2 years).
- 3) It is necessary to ensure that the antennas supplied in bulk are consistent with the requirements of the sample and the acknowledgement letter, and the raw material specifications must meet the above requirements.