

Xiamen Joint Tech. Co., Ltd

MPE ASSESSMENT REPORT

Report Type:

FCC Part §2.1091, §2.1093 and §1.1307(b) assessment report

Model:

JNT-EVC10/xxAC/BD/F/G, JNT-EVC11/xxAC/BD/F/G

REPORT NUMBER:

210403626SHA-003

ISSUE DATE:

August 24, 2021

DOCUMENT CONTROL NUMBER:

TTRFFCCMPE-01_V1 © 2018 Intertek



Applicant: Xiamen Joint Tech. Co., Ltd
Building #1, No. 268 HouXiang Rd, Xinyang Industrial Park, Haicang District, XIAMEN Fujian

Manufacturer: Xiamen Joint Tech. Co., Ltd
Building #1, No. 268 HouXiang Rd, Xinyang Industrial Park, Haicang District, XIAMEN Fujian

Manufacturing Site: Xiamen Joint Tech. Co., Ltd
Building #1, No. 268 HouXiang Rd, Xinyang Industrial Park, Haicang District, XIAMEN Fujian

Product Name: Electric Vehicle AC Charger

Type/Model: JNT-EVC10/xxAC/BD/F/G, JNT-EVC11/xxAC/BD/F/G

FCC ID: 2A2RN-ACEVC

SUMMARY:

The equipment complies with the requirements according to the following standard(s) or Specification:

KDB447498 D01 General RF Exposure Guidance v06
FCC Part2.1091, FCC Part2.1093 FCC Part1.1307(b)

PREPARED BY:



Project Engineer
Dylan Tang

REVIEWED BY:



Reviewer
Daniel Zhao

This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to permit copying or distribution of this report and then only in its entirety. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results in this report are relevant only to the sample tested. This report by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.

Revision History

Report No.	Version	Description	Issued Date
210403626SHA-003	Rev. 01	Initial issue of report	August 24, 2021

1 GENERAL INFORMATION

1.1 Description of Equipment Under Test (EUT)

Product name:	Electric Vehicle AC Charger
Type/Model:	JNT-EVC10/xxAC/BD/F/G, JNT-EVC11/xxAC/BD/F/G "xx"denotes Wattage,can be 16=16A, 32=32A, 40=40A,48=48A. "B"denotes Outlet type,can be 01=type 1,02=type 2. "D"denotes Charging Outlet, can be C=cabel, S=socket. "F"denotes Colour, can be SR=Silver, RD=Red, BK=Black, BU=Blue or other colour. "G"denotes Function, can be WF=WiFi+BT, 4G=4G,RF=RFID, RF/4G= RFID+4G, RF/WF=RFID+WiFi, If blank, it means Plug and charge.
Description of EUT:	The EUT is Electric Vehicle AC Charger with RFID Function, it supports WIFI or LTE function, the wireless modular FCC ID is 2AC7Z-ESPWROOM32D and XMR202008EC25AFXD. Both module are selectable, but cannot be used at same. there have two models and they are same except the appearance and display screen. So choose JNT-EVC10/xxAC/BD/F/G to test as representative.
Rating:	200-240V ~ 60Hz
EUT type:	<input checked="" type="checkbox"/> Table top <input type="checkbox"/> Floor standing
Software Version:	V2.0
Hardware Version:	V200
Sample received date:	April 30, 2021
Date of test:	April 30, 2021 ~ August 20, 2021

1.2 Technical Specification

Frequency Range:	13.56 MHz ~ 13.56 MHz
------------------	-----------------------

TEST REPORT

1.3 Description of Test Facility

Name:	Intertek Testing Services Shanghai
Address:	Building 86, No. 1198 Qinzhou Road(North), Shanghai 200233, P.R. China
Telephone:	86 21 61278200
Telefax:	86 21 54262353

The test facility is recognized, certified, or accredited by these organizations:	CNAS Accreditation Lab Registration No. CNAS L0139
	FCC Accredited Lab Designation Number: CN1175
	IC Registration Lab CAB identifier.: CN0051
	VCCI Registration Lab Registration No.: R-14243, G-10845, C-14723, T-12252
	A2LA Accreditation Lab Certificate Number: 3309.02

2 MPE Assessment

Test result: Pass

2.1 MPE Assessment Limit

Mobile device exposure for standalone operations:

According to §1.1310, the limit for general population/uncontrolled exposures

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
0.3-1.34	614	1.63	*(100)	30
1.34-30	824/f	2.19/f	*(180/f ²)	30
30-300	27.5	0.073	0.2	30
300-1500	/	/	f/1500	30
1500-100,000	/	/	1.0	30

Note: Limit for 13.56MHz is 60.77 V/m

Mobile device exposure for simultaneous transmission operations: **the sum of the MPE ratios for all simultaneously transmitting antennas incorporated in a host device is ≤ 1.0**

TEST REPORT

2.2 Assessment Results

Power density (S) is calculated according to the formula:

$$S = PG / (4\pi R^2)$$

Where S = power density in mW/cm²

P = Radiated transmit power in mW

G = numeric gain of transmit antenna

R = distance (cm)

As we can see from the test report 210403626SHA-002:

$$91.22\text{dBuV/m} = 0.0364 \text{ V/m} < 60.77 \text{ V/m.}$$

The power for WIFI modular refer certificate of FCC ID: 2AC7Z-ESPWROOM32D

The power for LTE modular refer report of MPE, report No. R2007A0434-M1

The calculations in the table below use the highest gain of antenna for client EUT. These calculations represent worst case in terms of the exposure levels.

The calculations in the table below use the highest gain of antenna for client EUT. These calculations represent worst case in terms of the exposure levels.

Frequency band (MHz)	Power		Antenna Gain dBi	R (cm)	S (mW/cm ²)	Limits (mW/cm ²)
	dBm	mW				
2412 - 2462	18.01	63.241	3.70	20	0.0295	1
LTE Band 5	25.00	316.23	3.00	20	0.0318	0.55

Note: 1 mW/cm² from 1.310 Table 1.

RFID and WIFI Module can simultaneous transmitting, so the maximum rate of MPE is,
 $0.0364/60.77 + 0.0295/1 = 0.0301 \leq 1.0$.

RFID and LTE Module can simultaneous transmitting, so the maximum rate of MPE is,
 $0.0364/60.77 + 0.0318/0.55 = 0.058 \leq 1.0$.

Appendix I

Definition below must be outlined in the User Manual:

To satisfy FCC RF exposure requirements, a separation distance of 20 cm or more should be maintained between the antenna of this device and persons during device operation. To ensure compliance, operations at closer than this distance is not recommended.

*****END*****