



FCC Part 15C Test Report

FCC ID: 2A2RX-ELLIS

Applicant: FergTech, Inc.

Address: 28 Thorndal Circle, Darien, CT 06820

Manufacturer: Skyvision Technology Co., LTD

Address: F2,Block D ,Chengjian Industrial Park,FuYong Town,ShenZhen,China

EUT: WIFI Digital Signage

Trade Mark: ELLIS

Model Number: C13 Ver1

Date of Receipt: Jul. 20, 2021

Test Date: Jul. 20, 2021 – Aug. 12, 2021

Date of Report: Aug. 12, 2021

Prepared By: Shenzhen DL Testing Technology Co., Ltd.

Address: 101-201, Building C, Shuanghuan, No.8, Baoqing Road, Baolong Industrial Zone, Baolong Street, Longgang District, Shenzhen, Guangdong, China

Applicable Standards: FCC PART 15 C 15.407
ANSI C63.10:2013

Test Result: Pass

Report Number: DL-20210803031-2E

Prepared (Test Engineer): Pxing Huang

Reviewer (Supervisor): Jack Bu

Approved (Manager): Jade Yang



This test report is based on a single evaluation of one sample of above mentioned products. It is not permitted to be duplicated in extracts without written approval of Shenzhen DL Testing Technology Co., Ltd.



Table of Contents	Page
1 . SUMMARY OF TEST RESULTS	5
1.1 MEASUREMENT UNCERTAINTY	5
2 . GENERAL INFORMATION	6
2.1 GENERAL DESCRIPTION OF EUT	6
2.2 DESCRIPTION OF TEST MODES	8
2.3 BLOCK DIGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED	9
2.4 DESCRIPTION OF SUPPORT UNITS(CONDUCTED MODE)	9
2.5 TABLE OF PARAMETERS OF TEST SOFTWARE SETTING	9
2.6 EQUIPMENTS LIST FOR ALL TEST ITEMS	10
3 . EMC EMISSION TEST	11
3.1 CONDUCTED EMISSION MEASUREMENT	11
3.1.1 POWER LINE CONDUCTED EMISSION LIMITS	11
3.1.2 TEST PROCEDURE	11
3.1.3 DEVIATION FROM TEST STANDARD	11
3.1.4 TEST SETUP	12
3.1.5 EUT OPERATING CONDITIONS	12
3.1.6 TEST RESULTS	12
3.2 RADIATED EMISSION MEASUREMENT	15
3.2.1 RADIATED EMISSION LIMITS	15
3.2.2 TEST PROCEDURE	16
3.2.3 DEVIATION FROM TEST STANDARD	16
3.2.4 TEST SETUP	16
3.2.5 EUT OPERATING CONDITIONS	17
3.2.6 TEST RESULTS (BETWEEN 9KHZ – 30 MHZ)	18
3.2.7 TEST RESULTS (BETWEEN 30MHZ – 1GHZ)	19
3.2.8 TEST RESULTS (1GHZ~40GHZ)	21
3.3 RADIATED BAND EMISSION MEASUREMENT	33
3.3.1 TEST REQUIREMENT:	33
3.3.2 TEST PROCEDURE	33
3.3.3 DEVIATION FROM TEST STANDARD	33
3.3.4 TEST SETUP	33
3.3.5 EUT OPERATING CONDITIONS	33
4 . PEAK OUTPUT POWER	39
4.1 APPLIED PROCEDURES / LIMIT	39
4.1.1 TEST PROCEDURE	39
4.1.2 DEVIATION FROM STANDARD	39
4.1.3 TEST SETUP	39



Table of Contents	Page
4.1.4 EUT OPERATION CONDITIONS	39
4.1.5 TEST RESULTS	40
5 . POWER SPECTRAL DENSITY TEST	47
5.1 APPLIED PROCEDURES / LIMIT	47
5.1.1 TEST PROCEDURE	47
5.1.2 DEVIATION FROM STANDARD	47
5.1.3 TEST SETUP	47
5.1.4 EUT OPERATION CONDITIONS	47
5.1.5 TEST RESULTS	48
6 . 26DB BANDWIDTH TEST	55
6.1 APPLIED PROCEDURES / LIMIT	55
6.1.1 TEST PROCEDURE	55
6.1.2 DEVIATION FROM STANDARD	55
6.1.3 TEST SETUP	55
6.1.4 EUT OPERATION CONDITIONS	55
6.1.5 TEST RESULTS	56
7 . DUTY CYCLE TEST SIGNAL	63
7.1 APPLIED PROCEDURES / LIMIT	63
7.1.1 TEST PROCEDURE	63
7.1.2 DEVIATION FROM STANDARD	63
7.1.3 TEST SETUP	63
7.1.4 EUT OPERATION CONDITIONS	63
7.1.5 TEST RESULTS	64
8 . FREQUENCY STABILITY	67
8.1 APPLIED PROCEDURES / LIMIT	67
8.1.1 TEST PROCEDURE	67
8.1.2 DEVIATION FROM STANDARD	67
8.1.3 TEST SETUP	67
8.1.4 EUT OPERATION CONDITIONS	67
8.1.5 TEST RESULTS	68
9 . TRANSMISSION IN THE ABSENCE OF DATA	70
9.1 STANDARD REQUIREMENT	70
9.2 TEST RESULT	70
10 . ANTENNA REQUIREMENT	70
10.1 STANDARD REQUIREMENT	70
10.2 EUT ANTENNA	70
11 . TEST SEUUP PHOTO	71



Table of Contents	Page
12 . EUT PHOTO	73



1. SUMMARY OF TEST RESULTS

Test procedures according to the technical standards:

FCC Part15 (15.407) , Subpart C			
Standard Section	Test Item	Judgment	Remark
15.207	Conducted Emission	PASS	
15.407(b), 15.209	Radiated Spurious Emission	PASS	
15.407 (b)	Band Edge Emission	PASS	
15.407 (a)	Peak Output Power	PASS	
15.407 (a)	Power Spectral Density	PASS	
15.403(i) 15.407(e)	26dB bandwidth and 99%dB Bandwidth 6dB bandwidth and 99%dB Bandwidth	PASS	
15.407(g)	Frequency Stability	PASS	
15.407(c)	Transmission in case of Absence of Information	PASS	
15.203	Antenna Requirement	PASS	

NOTE:

(1)" N/A" denotes test is not applicable in this Test Report

1.1 MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement $y \pm U$, where expended uncertainty U is based on a standard uncertainty multiplied by a coverage factor of $k=2$ providing a level of confidence of approximately 95 %.

No.	Item	Uncertainty
1	Conducted Emission Test	$\pm 2.56\text{dB}$
2	RF power,conducted	$\pm 0.42\text{dB}$
3	Spurious emissions,conducted	$\pm 2.76\text{dB}$
4	All emissions,radiated(<1G)	$\pm 3.65\text{dB}$
5	All emissions,radiated(>1G)	$\pm 4.89\text{dB}$
6	Temperature	$\pm 0.5^{\circ}\text{C}$
7	Humidity	$\pm 2\%$



2. GENERAL INFORMATION

2.1 GENERAL DESCRIPTION OF EUT

Product Name:	WIFI Digital Signage
Trademark	ELLIS
Model No.:	C13 Ver1
Model Difference	N/A
Operation Frequency:	5180-5240, 5745-5825MHz(802.11a/n/ac(HT20)) 5190-5230, 5755-5795MHz(802.11n/ac(HT40)) 5210MHz , 5775MHz (802.11ac(HT80))
Channel numbers:	See channel list
Channel separation:	20MHz
Modulation technology:	64QAM, 16QAM, QPSK, BPSK for OFDM
Rate of Transmitter	802.11a: 6Mbps, 9Mbps, 12Mbps, 18Mbps, 24Mbps, 36Mbps, 48Mbps,54Mbps 802.11n: Up to 500Mbps
Antenna Type:	Internal antenna
Antenna gain:	2dBi
Power supply:	DC 12V from adapter
Adapter:	Model Number: THX-012300KU Input: 100-240V~ 50/60Hz 1.0A MAX Output: 12.0V === 3.0A 36.0W

Note:

- 1.For a more detailed features description, please refer to the manufacturer's specifications or the User's Manual.
- 2.The EUT's all information provided by client.



2. Channel List

Channel List for 802.11a/n(HT20)/ac(HT20)			
Channel	Frequency (MHz)	Channel	Frequency (MHz)
36	5180	44	5220
40	5200	48	5240

Channel List for 802.11a/n(HT20)/ac(HT20)			
Channel	Frequency (MHz)	Channel	Frequency (MHz)
149	5745	161	5805
153	5765	165	5825
157	5785		

Channel List for 802.11n(HT40)/ac(HT40)			
Channel	Frequency (MHz)	Channel	Frequency (MHz)
38	5190	46	5230

Channel List for 802.11n(HT40)/ac(HT40)			
Channel	Frequency (MHz)	Channel	Frequency (MHz)
151	5755	159	5795

Channel List for 802.11ac(HT80)			
Channel	Frequency (MHz)	Channel	Frequency (MHz)
42	5210	/	/

Channel List for 802.11ac(HT80)			
Channel	Frequency (MHz)	Channel	Frequency (MHz)
155	5775	/	/



2.2 DESCRIPTION OF TEST MODES

To investigate the maximum EMI emission characteristics generates from EUT, the test system was pre-scanning tested base on the consideration of following EUT operation mode or test configuration mode which possible have effect on EMI emission level. Each of these EUT operation mode(s) or test configuration mode(s) mentioned above was evaluated respectively.

Description			
Pretest Mode	Channel	Band 1	Band 4
Mode 1	802.11a/n/acHT20	CH36, CH44, CH48	CH149, CH157, CH165
Mode 2	802.11n/acHT40	CH38, CH46	CH151, CH159
Mode 3	802.11acHT80	CH42	CH155
Mode 4	Other	Link Mode	


For Radiated Emission			
Pretest Mode	Channel	Band 1	Band 4
Mode 1	802.11a/n/acHT20	CH36, CH44, CH48	CH149, CH157, CH165
Mode 2	802.11n/acHT40	CH38, CH46	CH151, CH159
Mode 3	802.11acHT80	CH42	CH155
Mode 4	Other	Link Mode	

Note: 1. The measurements are performed at the highest, middle, lowest available channels.
2. During the test, the duty cycle >98%, the test voltage was tuned from 85% to 115% of the nominal rated supply voltage, and found that the worst case was under the nominal rated supply condition. So the report just shows that condition's data.



2.3 BLOCK DIGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED

Radiated Spurious Emission Test



Conducted Spurious Emission Test



2.4 DESCRIPTION OF SUPPORT UNITS(CONDUCTED MODE)

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Item	Equipment	Model/Type No.	Series No.	Note

Item	Shielded Type	Ferrite Core	Length	Note

Note:

(1) For detachable type I/O cable should be specified the length in cm in 『Length』 column.

2.5 TABLE OF PARAMETERS OF TEST SOFTWARE SETTING

During testing, channel & power controlling software provided by the customer was used to control the operating channel as well as the output power level. The RF output power selection is for the setting of RF output power expected by the customer and is going to be fixed on the end product.

Max output power Setting				
Test software Version	Test program: AXDN-0002.0			
Mode	802.11a	802.11n HT20	802.11n HT40	802.11ac HT20/HT40/HT80
Data Rate	6Mbps	MSC0	MSC0	MSC0
Power Setting of Software	60	60	66	66



2.6 EQUIPMENTS LIST FOR ALL TEST ITEMS

Radiation test, Band-edge test and 6db bandwidth test equipment

Item	Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until
1	Spectrum Analyzer (9kHz-26.5GHz)	Agilent	E4408B	MY50140780	Dec. 07, 2020	Dec. 06, 2021
2	Test Receiver (9kHz-7GHz)	R&S	ESRP7	101393	Dec. 07, 2020	Dec. 06, 2021
3	Bilog Antenna (30MHz-1GHz)	R&S	VULB9162	00306	Dec. 07, 2020	Dec. 06, 2021
4	Horn Antenna (1GHz-18GHz)	Schwarzbeck	BBHA9120D	02139	Dec. 07, 2020	Dec. 06, 2021
5	Horn Antenna (18GHz-40GHz)	A.H. Systems	SAS-574	588	Dec. 07, 2020	Dec. 06, 2021
6	Amplifier (9KHz-6GHz)	Schwarzbeck	BBV9743B	00153	Dec. 07, 2020	Dec. 06, 2021
7	Amplifier (1GHz-18GHz)	EMEC	EM01G8GA	00270	Dec. 07, 2020	Dec. 06, 2021
8	Amplifier (18GHz-40GHz)	Quanjuda	DLE-161	97	Dec. 07, 2020	Dec. 06, 2021
9	Loop Antenna (9KHz-30MHz)	Schwarzbeck	FMZB1519B	00014	Dec. 07, 2020	Dec. 06, 2021
10	RF cables1 (9kHz-1GHz)	ChengYu	966	004	Dec. 07, 2020	Dec. 06, 2021
11	RF cables2 (1GHz-40GHz)	ChengYu	966	003	Dec. 07, 2020	Dec. 06, 2021
12	Antenna connector	Florida RF Labs	N/A	RF 01#	Dec. 07, 2020	Dec. 06, 2021
13	Power probe	KEYSIGHT	U2021XA	MY55210018	Dec. 07, 2020	Dec. 06, 2021
14	Signal Analyzer 9kHz-26.5GHz	Agilent	N9020A	MY55370280	Dec. 07, 2020	Dec. 06, 2021
15	Test Receiver 20kHz-40GHz	R&S	ESU 40	100376	Dec. 07, 2020	Dec. 06, 2021
16	D.C. Power Supply	LongWei	PS-305D	010964729	Dec. 07, 2020	Dec. 06, 2021

Conduction Test equipment

Item	Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until
1	843 Shielded Room	ChengYu	843 Room	843	Nov. 25, 2019	Nov. 24, 2022
2	EMI Receiver	R&S	ESR	101421	Dec. 07, 2020	Dec. 06, 2021
3	LISN	R&S	ENV216	102417	Dec. 07, 2020	Dec. 06, 2021
4	843 Cable 1#	ChengYu	CE Cable	001	Dec. 07, 2020	Dec. 06, 2021

Other

Item	Name	Manufacturer	Model	Software version
1	EMC Conduction Test System	FALA	EZ_EMCC	EMC-CON 3A1.1
2	EMC radiation test system	FALA	EZ_EMCC	FA-03A2
3	RF test system	MAIWEI	MTS8310	2.0.0.0
4	RF communication test system	MAIWEI	MTS8200	2.0.0.0



3. EMC EMISSION TEST

3.1 CONDUCTED EMISSION MEASUREMENT

3.1.1 POWER LINE CONDUCTED EMISSION Limits (Frequency Range 150KHz-30MHz)

FREQUENCY (MHz)	Limit (dBuV)		Standard
	Quasi-peak	Average	
0.15 -0.5	66 - 56 *	56 - 46 *	FCC
0.5 -5.0	56.00	46.00	FCC
5.0 -30.0	60.00	50.00	FCC

Note:

- (1) The tighter limit applies at the band edges.
- (2) The limit of " * " marked band means the limitation decreases linearly with the logarithm of the frequency in the range.

The following table is the setting of the receiver

Receiver Parameters	Setting
Attenuation	10 dB
Start Frequency	0.15 MHz
Stop Frequency	30 MHz
IF Bandwidth	9 kHz

3.1.2 TEST PROCEDURE


- a. The EUT was placed 0.8 meters from the horizontal ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipments powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
- b. Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
- c. I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
- d. LISN at least 80 cm from nearest part of EUT chassis.
- e. For the actual test configuration, please refer to the related Item –EUT Test Photos.

3.1.3 DEVIATION FROM TEST STANDARD

No deviation



3.1.4 TEST SETUP



Note: 1.Support units were connected to second LISN.

2.Both of LISNs (AMN) are 80 cm from EUT and at least 80 from other units and other metal planes


3.1.5 EUT OPERATING CONDITIONS

The EUT was configured for testing in a typical fashion (as a customer would normally use it). The EUT has been programmed to continuously transmit during test. This operating condition was tested and used to collect the included data.

3.1.6 TEST RESULTS



Temperature:	25 °C	Relative Humidity:	54%
Pressure:	1010hPa	Phase :	L
Test Voltage :	AC 120V/60Hz	Test Mode:	Mode 4




Remark:

Margin = Limit – Level, Correct Factor = Cable lose + LISN insertion loss, Level= Reading + Correct factor

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector	P/F	Remark
1	0.1547	44.75	10.58	55.33	65.74	10.41	QP	P	
2	0.1547	22.90	10.58	33.48	55.74	22.26	AVG	P	
3	0.3165	38.87	9.20	48.07	59.80	11.73	QP	P	
4	0.3165	27.36	9.20	36.56	49.80	13.24	AVG	P	
5	2.1838	32.30	9.78	42.08	56.00	13.92	QP	P	
6	2.1838	22.65	9.78	32.43	46.00	13.57	AVG	P	
7	4.0514	33.86	9.76	43.62	56.00	12.38	QP	P	
8	4.0514	26.24	9.76	36.00	46.00	10.00	AVG	P	
9	10.2885	34.41	10.01	44.42	60.00	15.58	QP	P	
10	10.2885	24.34	10.01	34.35	50.00	15.65	AVG	P	
11	17.6952	36.47	10.33	46.80	60.00	13.20	QP	P	
12 *	17.6952	32.79	10.33	43.12	50.00	6.88	AVG	P	



Temperature:	25 °C	Relative Humidity:	54%
Pressure:	1010hPa	Phase :	N
Test Voltage :	AC 120V/60Hz	Test Mode:	Mode 4



Remark:

Margin = Limit – Level, Correct Factor = Cable lose + LISN insertion loss, Level= Reading + Correct factor

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector	P/F	Remark
1	0.1572	45.93	10.31	56.24	65.61	9.37	QP	P	
2	0.1572	24.59	10.31	34.90	55.61	20.71	AVG	P	
3	0.3029	37.31	9.23	46.54	60.16	13.62	QP	P	
4	0.3029	19.02	9.23	28.25	50.16	21.91	AVG	P	
5	0.9374	33.88	9.53	43.41	56.00	12.59	QP	P	
6 *	0.9374	30.70	9.53	40.23	46.00	5.77	AVG	P	
7	4.0605	29.91	9.94	39.85	56.00	16.15	QP	P	
8	4.0605	23.03	9.94	32.97	46.00	13.03	AVG	P	
9	10.9365	37.80	10.22	48.02	60.00	11.98	QP	P	
10	10.9365	26.43	10.22	36.65	50.00	13.35	AVG	P	
11	17.7360	34.85	10.41	45.26	60.00	14.74	QP	P	
12	17.7360	30.23	10.41	40.64	50.00	9.36	AVG	P	



3.2 RADIATED EMISSION MEASUREMENT

3.2.1 RADIATED EMISSION LIMITS (Frequency Range 9kHz-1000MHz)

In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

Frequencies (MHz)	Field Strength (microvolt/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

LIMITS OF RADIATED EMISSION MEASUREMENT (Above 1000MHz)

FREQUENCY (MHz)	Limit (dBuV/m) (at 3M)	
	PEAK	AVERAGE
Above 1000	74	54

Notes:

- (1) The limit for radiated test was performed according to FCC PART 15C.
- (2) The tighter limit applies at the band edges.
- (3) Emission level (dBuV/m)=20log Emission level (uV/m).

Spectrum Parameter	Setting
Attenuation	Auto
Start Frequency	1000 MHz
Stop Frequency	25GHz
RB / VB (emission in restricted band)	1 MHz / 1 MHz for Peak, 1 MHz / 10Hz for Average

Receiver Parameter	Setting
Attenuation	Auto
Start ~ Stop Frequency	9kHz~150kHz / RB 200Hz for QP
Start ~ Stop Frequency	150kHz~30MHz / RB 9kHz for QP
Start ~ Stop Frequency	30MHz~1000MHz / RB 120kHz for QP



3.2.2 TEST PROCEDURE

Below 1GHz test procedure as below:

- The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.

Above 1GHz test procedure as below:

- Different between above is the test site, change from Semi- Anechoic Chamber to fully Anechoic Chamber and change form table 0.8 metre to 1.5 metre(Above 18GHz the distance is 1 meter and table is 1.5 metre).
- Test the EUT in the lowest channel, the middle channel, the Highest channel

Note:


Both horizontal and vertical antenna polarities were tested and performed pretest to three orthogonal axis. The worst case emissions were reported

3.2.3 DEVIATION FROM TEST STANDARD


No deviation

3.2.4 TEST SETUP


(A) Radiated Emission Test-Up Frequency Below 30MHz



(B) Radiated Emission Test-Up Frequency 30MHz~1GHz



(C) Radiated Emission Test-Up Frequency Above 1GHz



3.2.5 EUT OPERATING CONDITIONS

The EUT tested system was configured as the statements of 2.3 Unless otherwise a special operating condition is specified in the follows during the testing.

**3.2.6 TEST RESULTS (Between 9KHz – 30 MHz)**

Temperature:	20°C	Relative Humidity:	48%
Pressure:	1010 hPa	Test Voltage :	AC 120V/60Hz
Test Mode :	Mode 4	Polarization :	--

Freq.	Reading	Limit	Margin	State
(MHz)	(dBuV/m)	(dBuV/m)	(dB)	P/F
--	--	--	--	PASS
--	--	--	--	PASS

NOTE:


The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

Distance extrapolation factor = $40 \log(\text{specific distance/test distance})$ (dB);

Limit line = specific limits(dBuV) + distance extrapolation factor.

**3.2.7 TEST RESULTS (Between 30MHz – 1GHz)**

Temperature:	26℃	Relative Humidity:	54%
Pressure:	1010 hPa	Polarization :	Horizontal
Test Voltage :	AC 120V/60Hz		
Test Mode :	Mode 4		



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dB/m	Over dB	Detector
1		41.4215	45.79	-14.16	31.63	40.00	8.37	QP
2	*	63.9827	51.99	-15.40	36.59	40.00	3.41	QP
3	!	83.8155	54.42	-18.60	35.82	40.00	4.18	QP
4	!	157.0072	56.74	-18.72	38.02	43.50	5.48	QP
5	!	250.3009	55.53	-13.89	41.64	46.00	4.36	QP
6		383.9318	50.37	-11.15	39.22	46.00	6.78	QP

Remark:


Correct Factor = Cable loss + Antenna factor – Preamplifier;

Level = Reading Level + Correct Factor; Margin = Limit – Level;

Temperature:	26℃	Relative Humidity:	54%
--------------	-----	--------------------	-----



Pressure:	1010 hPa	Polarization :	Vertical
test voltage :	AC 120V/60Hz		
Test Mode :	Mode 4		



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dB/m	Over dB	Detector
1	!	41.1319	50.91	-14.18	36.73	40.00	3.27	QP
2	!	71.8319	52.94	-17.65	35.29	40.00	4.71	QP
3	*	128.1126	58.79	-18.30	40.49	43.50	3.01	QP
4	!	170.1947	58.01	-17.92	40.09	43.50	3.41	QP
5	!	447.9821	51.53	-9.54	41.99	46.00	4.01	QP
6	!	625.0778	47.60	-6.17	41.43	46.00	4.57	QP

Remark:

Correct Factor = Cable loss + Antenna factor – Preamplifier;

Level = Reading Level + Correct Factor; Margin = Limit – Level;

**3.2.8 TEST RESULTS (1ghz~40ghZ)**

802.11a band 1

Polar (H/V)	Frequency	Meter Reading	Pre- amplifier	Cable Loss	Antenna Factor	Emission Level	Limits	Margin	Detector Type
	(MHz)	(dBuV)	(dB)	(dB)	(dB/m)	(dBuV/m)	(dBuV/m)	(dB)	
operation frequency:5180									
V	10360	56.12	49.05	15.3	37.39	59.76	74	-14.24	PK
V	10360	45.34	49.05	15.3	37.39	48.98	54	-5.02	AV
V	15540	56.55	49.16	15.27	40.45	63.11	74	-10.89	PK
V	15540	43.1	49.16	15.27	40.45	49.66	54	-4.34	AV
H	10360	56.88	49.05	15.3	37.39	60.52	74	-13.48	PK
H	10360	45.44	49.05	15.3	37.39	49.08	54	-4.92	AV
H	15540	59.76	49.16	15.27	40.45	66.32	74	-7.68	PK
H	15540	43.67	49.16	15.27	40.45	50.23	54	-3.77	AV
operation frequency:5200									
V	10400	57.53	49.09	15.34	37.42	61.2	74	-12.80	PK
V	10400	45.15	49.09	15.34	37.42	48.82	54	-5.18	AV
V	15600	59.41	49.18	15.29	40.47	65.99	74	-8.01	PK
V	15600	43.46	49.18	15.29	40.47	50.04	54	-3.96	AV
H	10400	56.61	49.09	15.34	37.42	60.28	74	-13.72	PK
H	10400	45.25	49.09	15.34	37.42	48.92	54	-5.08	AV
H	15600	59.5	49.18	15.29	40.47	66.08	74	-7.92	PK
H	15600	43.57	49.18	15.29	40.47	50.15	54	-3.85	AV
operation frequency:5240									
V	10480	58.01	49.11	15.37	37.46	61.73	74	-12.27	PK
V	10480	45.55	49.11	15.37	37.46	49.27	54	-4.73	AV
V	15720	59.19	49.21	15.34	40.51	65.83	74	-8.17	PK
V	15720	43.34	49.21	15.34	40.51	49.98	54	-4.02	AV
H	10480	57.08	49.11	15.37	31.31	54.65	74	-19.35	PK
H	10480	45.65	49.11	15.37	31.31	43.22	54	-10.78	AV
H	15720	57.43	49.21	15.34	40.51	64.07	74	-9.93	PK
H	15720	42.37	49.21	15.34	40.51	49.01	54	-4.99	AV

Remark:

1. Emission Level = Meter Reading + Antenna Factor + Cable Loss – Pre-amplifier,
Margin= Emission Level - Limit
2. If peak below the average limit, the average emission was no test.
3. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.



802.11n HT20

Polar (H/V)	Frequency	Meter Reading	Pre- amplifier	Cable Loss	Antenna Factor	Emission Level	Limits	Margin	Detector Type
	(MHz)	(dBuV)	(dB)	(dB)	(dB/m)	(dBuV/m)	(dBuV/m)	(dB)	
operation frequency:5180									
V	10360	56.89	49.05	15.3	37.39	60.53	74	-13.47	PK
V	10360	45.72	49.05	15.3	37.39	49.36	54	-4.64	AV
V	15540	56.23	49.16	15.27	40.45	62.79	74	-11.21	PK
V	15540	43.39	49.16	15.27	40.45	49.95	54	-4.05	AV
H	10360	56.62	49.05	15.3	37.39	60.26	74	-13.74	PK
H	10360	45.67	49.05	15.3	37.39	49.31	54	-4.69	AV
H	15540	54.58	49.16	15.27	40.45	61.14	74	-12.86	PK
H	15540	44.39	49.16	15.27	40.45	50.95	54	-3.05	AV
operation frequency:5200									
V	10400	56.88	49.09	15.34	37.42	60.55	74	-13.45	PK
V	10400	44.95	49.09	15.34	37.42	48.62	54	-5.38	AV
V	15600	55.62	49.18	15.29	40.47	62.2	74	-11.80	PK
V	15600	43.45	49.18	15.29	40.47	50.03	54	-3.97	AV
H	10400	55.38	49.09	15.34	37.42	59.05	74	-14.95	PK
H	10400	43.68	49.09	15.34	37.42	47.35	54	-6.65	AV
H	15600	55.08	49.18	15.29	40.47	61.66	74	-12.34	PK
H	15600	43.46	49.18	15.29	40.47	50.04	54	-3.96	AV
operation frequency:5240									
V	10480	57.63	49.11	15.37	37.46	61.35	74	-12.65	PK
V	10480	44.68	49.11	15.37	37.46	48.4	54	-5.60	AV
V	15720	54.9	49.21	15.34	40.51	61.54	74	-12.46	PK
V	15720	43.46	49.21	15.34	40.51	50.1	54	-3.90	AV
H	10480	57.55	49.11	15.37	31.31	55.12	74	-18.88	PK
H	10480	44.79	49.11	15.37	31.31	42.36	54	-11.64	AV
H	15720	55.33	49.21	15.34	40.51	61.97	74	-12.03	PK
H	15720	44.08	49.21	15.34	40.51	50.72	54	-3.28	AV

Remark:

1. Emission Level = Meter Reading + Antenna Factor + Cable Loss – Pre-amplifier,
Margin= Emission Level - Limit
2. If peak below the average limit, the average emission was no test.
3. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.



802.11n HT40

Polar (H/V)	Frequency	Meter Reading	Pre- amplifier	Cable Loss	Antenna Factor	Emission Level	Limits	Margin	Detector Type
	(MHz)	(dBuV)	(dB)	(dB)	(dB/m)	(dBuV/m)	(dBuV/m)	(dB)	
operation frequency:5190									
V	10380	56.89	49.07	15.33	37.41	60.56	74	-13.44	PK
V	10380	45.72	49.07	15.33	37.41	49.39	54	-4.61	AV
V	15570	56.23	49.17	15.28	40.46	62.8	74	-11.20	PK
V	15570	43.39	49.17	15.28	40.46	49.96	54	-4.04	AV
H	10380	56.62	49.07	15.33	37.41	60.29	74	-13.71	PK
H	10380	45.67	49.07	15.33	37.41	49.34	54	-4.66	AV
H	15570	54.58	49.17	15.28	40.46	61.15	74	-12.85	PK
H	15570	44.39	49.17	15.28	40.46	50.96	54	-3.04	AV
operation frequency:5230									
V	10460	57.63	49.11	15.37	37.46	61.35	74	-12.65	PK
V	10460	44.68	49.11	15.37	37.46	48.4	54	-5.60	AV
V	15690	54.9	49.21	15.34	40.51	61.54	74	-12.46	PK
V	15690	43.46	49.21	15.34	40.51	50.1	54	-3.90	AV
H	10460	57.55	49.11	15.37	31.31	55.12	74	-18.88	PK
H	10460	44.79	49.11	15.37	31.31	42.36	54	-11.64	AV
H	15690	55.33	49.21	15.34	40.51	61.97	74	-12.03	PK
H	15690	44.08	49.21	15.34	40.51	50.72	54	-3.28	AV

Remark:

1. Emission Level = Meter Reading + Antenna Factor + Cable Loss – Pre-amplifier,
Margin= Emission Level - Limit
2. If peak below the average limit, the average emission was no test.
3. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.



802.11ac HT20

Polar (H/V)	Frequency	Meter Reading	Pre- amplifier	Cable Loss	Antenna Factor	Emission Level	Limits	Margin	Detector Type
	(MHz)	(dBuV)	(dB)	(dB)	(dB/m)	(dBuV/m)	(dBuV/m)	(dB)	
operation frequency:5180									
V	10360	56.89	49.05	15.3	37.39	60.53	74	-13.47	PK
V	10360	45.72	49.05	15.3	37.39	49.36	54	-4.64	AV
V	15540	56.23	49.16	15.27	40.45	62.79	74	-11.21	PK
V	15540	43.39	49.16	15.27	40.45	49.95	54	-4.05	AV
H	10360	56.62	49.05	15.3	37.39	60.26	74	-13.74	PK
H	10360	45.67	49.05	15.3	37.39	49.31	54	-4.69	AV
H	15540	54.58	49.16	15.27	40.45	61.14	74	-12.86	PK
H	15540	44.39	49.16	15.27	40.45	50.95	54	-3.05	AV
operation frequency:5200									
V	10400	56.88	49.09	15.34	37.42	60.55	74	-13.45	PK
V	10400	44.95	49.09	15.34	37.42	48.62	54	-5.38	AV
V	15600	55.62	49.18	15.29	40.47	62.2	74	-11.80	PK
V	15600	43.45	49.18	15.29	40.47	50.03	54	-3.97	AV
H	10400	55.38	49.09	15.34	37.42	59.05	74	-14.95	PK
H	10400	43.68	49.09	15.34	37.42	47.35	54	-6.65	AV
H	15600	55.08	49.18	15.29	40.47	61.66	74	-12.34	PK
H	15600	43.46	49.18	15.29	40.47	50.04	54	-3.96	AV
operation frequency:5240									
V	10480	57.63	49.11	15.37	37.46	61.35	74	-12.65	PK
V	10480	44.68	49.11	15.37	37.46	48.4	54	-5.60	AV
V	15720	54.9	49.21	15.34	40.51	61.54	74	-12.46	PK
V	15720	43.46	49.21	15.34	40.51	50.1	54	-3.90	AV
H	10480	57.55	49.11	15.37	31.31	55.12	74	-18.88	PK
H	10480	44.79	49.11	15.37	31.31	42.36	54	-11.64	AV
H	15720	55.33	49.21	15.34	40.51	61.97	74	-12.03	PK
H	15720	44.08	49.21	15.34	40.51	50.72	54	-3.28	AV

Remark:

1. Emission Level = Meter Reading + Antenna Factor + Cable Loss – Pre-amplifier,
Margin= Emission Level - Limit
2. If peak below the average limit, the average emission was no test.
3. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.



802.11ac HT40

Polar (H/V)	Frequency	Meter Reading	Pre- amplifier	Cable Loss	Antenna Factor	Emission Level	Limits	Margin	Detector Type
	(MHz)	(dBuV)	(dB)	(dB)	(dB/m)	(dBuV/m)	(dBuV/m)	(dB)	
operation frequency:5190									
V	10380	56.89	49.07	15.33	37.41	60.56	74	-13.44	PK
V	10380	45.72	49.07	15.33	37.41	49.39	54	-4.61	AV
V	15570	56.23	49.17	15.28	40.46	62.8	74	-11.20	PK
V	15570	43.39	49.17	15.28	40.46	49.96	54	-4.04	AV
H	10380	56.62	49.07	15.33	37.41	60.29	74	-13.71	PK
H	10380	45.67	49.07	15.33	37.41	49.34	54	-4.66	AV
H	15570	54.58	49.17	15.28	40.46	61.15	74	-12.85	PK
H	15570	44.39	49.17	15.28	40.46	50.96	54	-3.04	AV
operation frequency:5230									
V	10460	57.63	49.11	15.37	37.46	61.35	74	-12.65	PK
V	10460	44.68	49.11	15.37	37.46	48.4	54	-5.60	AV
V	15690	54.9	49.21	15.34	40.51	61.54	74	-12.46	PK
V	15690	43.46	49.21	15.34	40.51	50.1	54	-3.90	AV
H	10460	57.55	49.11	15.37	31.31	55.12	74	-18.88	PK
H	10460	44.79	49.11	15.37	31.31	42.36	54	-11.64	AV
H	15690	55.33	49.21	15.34	40.51	61.97	74	-12.03	PK
H	15690	44.08	49.21	15.34	40.51	50.72	54	-3.28	AV

Remark:

1. Emission Level = Meter Reading + Antenna Factor + Cable Loss – Pre-amplifier,
Margin= Emission Level - Limit
2. If peak below the average limit, the average emission was no test.
3. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

802.11ac HT80

Polar (H/V)	Frequency	Meter Reading	Pre- amplifier	Cable Loss	Antenna Factor	Emission Level	Limits	Margin	Detector Type
	(MHz)	(dBuV)	(dB)	(dB)	(dB/m)	(dBuV/m)	(dBuV/m)	(dB)	
operation frequency:5210									
V	10420	56.89	49.07	15.33	37.41	60.56	74	-13.44	PK
V	10420	45.72	49.07	15.33	37.41	49.39	54	-4.61	AV
V	15630	56.23	49.17	15.28	40.46	62.8	74	-11.20	PK
V	15630	43.39	49.17	15.28	40.46	49.96	54	-4.04	AV
H	10420	56.62	49.07	15.33	37.41	60.29	74	-13.71	PK
H	10420	45.67	49.07	15.33	37.41	49.34	54	-4.66	AV
H	15630	54.58	49.17	15.28	40.46	61.15	74	-12.85	PK
H	15630	44.39	49.17	15.28	40.46	50.96	54	-3.04	AV

Remark:

1. Emission Level = Meter Reading + Antenna Factor + Cable Loss – Pre-amplifier,
Margin= Emission Level - Limit
2. If peak below the average limit, the average emission was no test.
3. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.



802.11a band 4

Polar (H/V)	Frequency	Meter Reading	Pre- amplifier	Cable Loss	Antenna Factor	Emission Level	Limits	Margin	Detector Type
	(MHz)	(dBuV)	(dB)	(dB)	(dB/m)	(dBuV/m)	(dBuV/m)	(dB)	
operation frequency:5745									
V	11490	57.76	49.05	15.3	37.39	61.4	74	-12.60	PK
V	11490	45.34	49.05	15.3	37.39	48.98	54	-5.02	AV
V	17235	56.55	49.16	15.27	40.45	63.11	74	-10.89	PK
V	17235	43.8	49.16	15.27	40.45	50.36	54	-3.64	AV
H	11490	55.88	49.05	15.3	37.39	59.52	74	-14.48	PK
H	11490	45.44	49.05	15.3	37.39	49.08	54	-4.92	AV
H	17235	59.76	49.16	15.27	40.45	66.32	74	-7.68	PK
H	17235	43.67	49.16	15.27	40.45	50.23	54	-3.77	AV
operation frequency:5785									
V	11570	57.53	49.09	15.34	37.42	61.2	74	-12.80	PK
V	11570	45.15	49.09	15.34	37.42	48.82	54	-5.18	AV
V	17355	59.41	49.18	15.29	40.47	65.99	74	-8.01	PK
V	17355	43.46	49.18	15.29	40.47	50.04	54	-3.96	AV
H	11570	56.61	49.09	15.34	37.42	60.28	74	-13.72	PK
H	11570	45.25	49.09	15.34	37.42	48.92	54	-5.08	AV
H	17355	52.5	49.18	15.29	40.47	59.08	74	-14.92	PK
H	17355	43.57	49.18	15.29	40.47	50.15	54	-3.85	AV
operation frequency:5825									
V	11650	58.01	49.11	15.37	37.46	61.73	74	-12.27	PK
V	11650	45.55	49.11	15.37	37.46	49.27	54	-4.73	AV
V	17475	59.19	49.21	15.34	40.51	65.83	74	-8.17	PK
V	17475	43.34	49.21	15.34	40.51	49.98	54	-4.02	AV
H	11650	57.08	49.11	15.37	31.31	54.65	74	-19.35	PK
H	11650	45.65	49.11	15.37	31.31	43.22	54	-10.78	AV
H	17475	57.43	49.21	15.34	40.51	64.07	74	-9.93	PK
H	17475	45.37	49.21	15.34	40.51	52.01	54	-1.99	AV

Remark:

1. Emission Level = Meter Reading + Antenna Factor + Cable Loss – Pre-amplifier,
Margin= Emission Level - Limit
2. If peak below the average limit, the average emission was no test.
3. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.



802.11n HT20

Polar (H/V)	Frequency	Meter Reading	Pre- amplifier	Cable Loss	Antenna Factor	Emission Level	Limits	Margin	Detector Type
	(MHz)	(dBuV)	(dB)	(dB)	(dB/m)	(dBuV/m)	(dBuV/m)	(dB)	
operation frequency:5745									
V	11490	56.89	49.05	15.3	37.39	60.53	74	-13.47	PK
V	11490	45.72	49.05	15.3	37.39	49.36	54	-4.64	AV
V	17235	56.23	49.16	15.27	40.45	62.79	74	-11.21	PK
V	17235	43.39	49.16	15.27	40.45	49.95	54	-4.05	AV
H	11490	56.62	49.05	15.3	37.39	60.26	74	-13.74	PK
H	11490	45.67	49.05	15.3	37.39	49.31	54	-4.69	AV
H	17235	54.58	49.16	15.27	40.45	61.14	74	-12.86	PK
H	17235	44.39	49.16	15.27	40.45	50.95	54	-3.05	AV
operation frequency:5785									
V	11570	56.88	49.09	15.34	37.42	60.55	74	-13.45	PK
V	11570	44.95	49.09	15.34	37.42	48.62	54	-5.38	AV
V	17355	55.62	49.18	15.29	40.47	62.2	74	-11.80	PK
V	17355	43.45	49.18	15.29	40.47	50.03	54	-3.97	AV
H	11570	55.38	49.09	15.34	37.42	59.05	74	-14.95	PK
H	11570	43.68	49.09	15.34	37.42	47.35	54	-6.65	AV
H	17355	55.08	49.18	15.29	40.47	61.66	74	-12.34	PK
H	17355	43.46	49.18	15.29	40.47	50.04	54	-3.96	AV
operation frequency:5825									
V	11650	57.63	49.11	15.37	37.46	61.35	74	-12.65	PK
V	11650	44.68	49.11	15.37	37.46	48.4	54	-5.60	AV
V	17475	54.9	49.21	15.34	40.51	61.54	74	-12.46	PK
V	17475	43.46	49.21	15.34	40.51	50.1	54	-3.90	AV
H	11650	57.55	49.11	15.37	31.31	55.12	74	-18.88	PK
H	11650	44.79	49.11	15.37	31.31	42.36	54	-11.64	AV
H	17475	55.33	49.21	15.34	40.51	61.97	74	-12.03	PK
H	17475	44.08	49.21	15.34	40.51	50.72	54	-3.28	AV

Remark:

1. Emission Level = Meter Reading + Antenna Factor + Cable Loss – Pre-amplifier,
Margin= Emission Level - Limit
2. If peak below the average limit, the average emission was no test.
3. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.



802.11n HT40

Polar (H/V)	Frequency	Meter Reading	Pre- amplifier	Cable Loss	Antenna Factor	Emission Level	Limits	Margin	Detector Type
	(MHz)	(dBuV)	(dB)	(dB)	(dB/m)	(dBuV/m)	(dBuV/m)	(dB)	
operation frequency:5755									
V	11510	56.89	49.07	15.33	37.41	60.56	74	-13.44	PK
V	11510	45.72	49.07	15.33	37.41	49.39	54	-4.61	AV
V	17265	56.23	49.17	15.28	40.46	62.8	74	-11.20	PK
V	17265	43.39	49.17	15.28	40.46	49.96	54	-4.04	AV
H	11510	56.62	49.07	15.33	37.41	60.29	74	-13.71	PK
H	11510	45.67	49.07	15.33	37.41	49.34	54	-4.66	AV
H	17265	54.58	49.17	15.28	40.46	61.15	74	-12.85	PK
H	17265	44.39	49.17	15.28	40.46	50.96	54	-3.04	AV
operation frequency:5795									
V	11590	57.63	49.11	15.37	37.46	61.35	74	-12.65	PK
V	11590	44.68	49.11	15.37	37.46	48.4	54	-5.60	AV
V	17385	54.9	49.21	15.34	40.51	61.54	74	-12.46	PK
V	17385	43.46	49.21	15.34	40.51	50.1	54	-3.90	AV
H	11590	57.55	49.11	15.37	31.31	55.12	74	-18.88	PK
H	11590	44.79	49.11	15.37	31.31	42.36	54	-11.64	AV
H	17385	55.33	49.21	15.34	40.51	61.97	74	-12.03	PK
H	17385	44.08	49.21	15.34	40.51	50.72	54	-3.28	AV

Remark:

1. Emission Level = Meter Reading + Antenna Factor + Cable Loss – Pre-amplifier,
Margin= Emission Level - Limit
2. If peak below the average limit, the average emission was no test.
3. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.



802.11ac HT20

Polar (H/V)	Frequency	Meter Reading	Pre- amplifier	Cable Loss	Antenna Factor	Emission Level	Limits	Margin	Detector Type
	(MHz)	(dBuV)	(dB)	(dB)	(dB/m)	(dBuV/m)	(dBuV/m)	(dB)	
operation frequency:5745									
V	11490	56.89	49.05	15.3	37.39	60.53	74	-13.47	PK
V	11490	45.72	49.05	15.3	37.39	49.36	54	-4.64	AV
V	17235	56.23	49.16	15.27	40.45	62.79	74	-11.21	PK
V	17235	43.39	49.16	15.27	40.45	49.95	54	-4.05	AV
H	11490	56.62	49.05	15.3	37.39	60.26	74	-13.74	PK
H	11490	45.67	49.05	15.3	37.39	49.31	54	-4.69	AV
H	17235	54.58	49.16	15.27	40.45	61.14	74	-12.86	PK
H	17235	44.39	49.16	15.27	40.45	50.95	54	-3.05	AV
operation frequency:5785									
V	11570	56.88	49.09	15.34	37.42	60.55	74	-13.45	PK
V	11570	44.95	49.09	15.34	37.42	48.62	54	-5.38	AV
V	17355	55.62	49.18	15.29	40.47	62.2	74	-11.80	PK
V	17355	43.45	49.18	15.29	40.47	50.03	54	-3.97	AV
H	11570	55.38	49.09	15.34	37.42	59.05	74	-14.95	PK
H	11570	43.68	49.09	15.34	37.42	47.35	54	-6.65	AV
H	17355	55.08	49.18	15.29	40.47	61.66	74	-12.34	PK
H	17355	43.46	49.18	15.29	40.47	50.04	54	-3.96	AV
operation frequency:5825									
V	11650	57.63	49.11	15.37	37.46	61.35	74	-12.65	PK
V	11650	44.68	49.11	15.37	37.46	48.4	54	-5.60	AV
V	17475	54.9	49.21	15.34	40.51	61.54	74	-12.46	PK
V	17475	43.46	49.21	15.34	40.51	50.1	54	-3.90	AV
H	11650	57.55	49.11	15.37	31.31	55.12	74	-18.88	PK
H	11650	44.79	49.11	15.37	31.31	42.36	54	-11.64	AV
H	17475	55.33	49.21	15.34	40.51	61.97	74	-12.03	PK
H	17475	44.08	49.21	15.34	40.51	50.72	54	-3.28	AV

Remark:

1. Emission Level = Meter Reading + Antenna Factor + Cable Loss – Pre-amplifier,
Margin= Emission Level - Limit
2. If peak below the average limit, the average emission was no test.
3. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.



802.11ac HT40

Polar (H/V)	Frequency	Meter Reading	Pre- amplifier	Cable Loss	Antenna Factor	Emission Level	Limits	Margin	Detector Type
	(MHz)	(dBuV)	(dB)	(dB)	(dB/m)	(dBuV/m)	(dBuV/m)	(dB)	
operation frequency:5755									
V	11510	56.89	49.07	15.33	37.41	60.56	74	-13.44	PK
V	11510	45.72	49.07	15.33	37.41	49.39	54	-4.61	AV
V	17265	56.23	49.17	15.28	40.46	62.8	74	-11.20	PK
V	17265	43.39	49.17	15.28	40.46	49.96	54	-4.04	AV
H	11510	56.62	49.07	15.33	37.41	60.29	74	-13.71	PK
H	11510	45.67	49.07	15.33	37.41	49.34	54	-4.66	AV
H	17265	54.58	49.17	15.28	40.46	61.15	74	-12.85	PK
H	17265	44.39	49.17	15.28	40.46	50.96	54	-3.04	AV
operation frequency:5795									
V	11590	57.63	49.11	15.37	37.46	61.35	74	-12.65	PK
V	11590	44.68	49.11	15.37	37.46	48.4	54	-5.60	AV
V	17385	54.9	49.21	15.34	40.51	61.54	74	-12.46	PK
V	17385	43.46	49.21	15.34	40.51	50.1	54	-3.90	AV
H	11590	57.55	49.11	15.37	31.31	55.12	74	-18.88	PK
H	11590	44.79	49.11	15.37	31.31	42.36	54	-11.64	AV
H	17385	55.33	49.21	15.34	40.51	61.97	74	-12.03	PK
H	17385	44.08	49.21	15.34	40.51	50.72	54	-3.28	AV

Remark:

1. Emission Level = Meter Reading + Antenna Factor + Cable Loss – Pre-amplifier,
Margin= Emission Level - Limit
2. If peak below the average limit, the average emission was no test.
3. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

802.11ac HT80

Polar (H/V)	Frequency	Meter Reading	Pre- amplifier	Cable Loss	Antenna Factor	Emission Level	Limits	Margin	Detector Type
	(MHz)	(dBuV)	(dB)	(dB)	(dB/m)	(dBuV/m)	(dBuV/m)	(dB)	
operation frequency:5775									
V	11550	56.89	49.07	15.33	37.41	60.56	74	-13.44	PK
V	11550	45.72	49.07	15.33	37.41	49.39	54	-4.61	AV
V	17325	56.23	49.17	15.28	40.46	62.8	74	-11.20	PK
V	17325	43.39	49.17	15.28	40.46	49.96	54	-4.04	AV
H	11550	56.62	49.07	15.33	37.41	60.29	74	-13.71	PK
H	11550	45.67	49.07	15.33	37.41	49.34	54	-4.66	AV
H	17325	54.58	49.17	15.28	40.46	61.15	74	-12.85	PK
H	17325	44.39	49.17	15.28	40.46	50.96	54	-3.04	AV

Remark:

1. Emission Level = Meter Reading + Antenna Factor + Cable Loss – Pre-amplifier,
Margin= Emission Level - Limit
2. If peak below the average limit, the average emission was no test.
3. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.




For Conducted

During the test, pre-scan the all modulation, and found the 802.11a mode of Band 1 and Band 4 which it is worse case.

Test channel:

Band 1/Lowest channel



0.03Hz~40GHz

Test channel:


Band 1/Middle channel



0.03GHz~40GHz

Test channel:

Band 1/Highest channel




0.03GHz~40GHz



Test channel:


Band 4/Lowest channel



0.03Hz~40GHz

Test channel:


Band 4/Middle channel



0.03GHz~40GHz

Test channel:

Band 4/Highest channel



0.03GHz~40GHz



3.3 RADIATED BAND EMISSION MEASUREMENT

3.3.1 TEST REQUIREMENT:

FCC Part15 C Section 15.209 and 15.407

(1) For transmitters operating in the 5.15-5.25 GHz band: All emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.

(4) For transmitters operating in the 5.725-5.85 GHz band: All emissions within the frequency range from the band edge to 10 MHz above or below the band edge shall not exceed an e.i.r.p. of -17 dBm/MHz; for frequencies 10 MHz or greater above or below the band edge, emissions shall not exceed an e.i.r.p. of -27 dBm/MHz.

Spectrum Parameter	Setting	
Attenuation	Auto	
Start Frequency	5150MHz	5725MHz
Stop Frequency	5250MHz	5850MHz
RB / VB (emission in restricted band)	1 MHz / 1 MHz for Peak, 1 MHz / 10Hz for Average	

3.3.2 TEST PROCEDURE


Test method: FCC KDB 789033 G)& Parts 15.407(b)(4) & 15.209(a)

3.3.3 DEVIATION FROM TEST STANDARD

No deviation

3.3.4 TEST SETUP

Radiated Emission Test-Up Frequency Above 1GHz



3.3.5 EUT OPERATING CONDITIONS

The EUT tested system was configured as the statements of 2.3 Unless otherwise a special operating condition is specified in the follows during the testing.

**3.3.6 TEST RESULT**


Modulation	Test Frequency (MHz)	Max Level Frequency (MHz)	Max Level (dBμV/m)	EIRP (dBm)	Limit (dBm)	Result
802.11a	5180	5148.63	51.46	-43.74	-27.00	Pass
	5240	5255.34	53.74	-41.46	-27.00	Pass
	5745	5723.67	52.56	-42.64	-27.00	Pass
	5825	5853.16	51.85	-43.35	-27.00	Pass
802.11n(HT20)	5180	5146.86	52.52	-42.68	-27.00	Pass
	5240	5253.19	52.37	-42.83	-27.00	Pass
	5745	5723.51	51.45	-43.75	-27.00	Pass
	5825	5853.43	52.63	-42.57	-27.00	Pass
802.11n(HT40)	5190	5147.69	51.77	-43.43	-27.00	Pass
	5230	5253.42	52.36	-42.84	-27.00	Pass
	5755	5723.11	51.47	-43.73	-27.00	Pass
	5795	5853.61	51.64	-43.56	-27.00	Pass
802.11ac(HT20)	5180	5145.74	52.38	-42.82	-27.00	Pass
	5240	5256.23	52.25	-42.95	-27.00	Pass
	5745	5735.47	51.41	-43.79	-27.00	Pass
	5825	5849.37	52.39	-42.81	-27.00	Pass
802.11ac(HT40)	5190	5145.72	51.74	-43.46	-27.00	Pass
	5230	5252.38	52.38	-42.82	-27.00	Pass
	5755	5736.28	53.47	-41.73	-27.00	Pass
	5795	5856.49	52.49	-42.71	-27.00	Pass
802.11ac(HT80)	5210	5235.14	54.49	-40.71	-27.00	Pass
	5775	5769.48	51.38	-43.82	-27.00	Pass

Remark: 1. According to KDB 789033 D02 section H) d) (iii), for measurement above 1000MHz@3m distance, the limit of EIRP is calculated as follows: $EIRP[dBm] = E[dBμV/m] - 95.2$




For Conducted

802.11a




5180MHz




5240MHz

802.11n HT20




5180MHz




5240MHz

802.11n HT40





5190MHz



5230MHz





802.11ac HT20



5180MHz

5240MHz


802.11ac HT40



5190MHz

5230MHz


802.11ac HT80



5210MHz



802.11a




5745MHz



5825MHz

802.11n HT20




5745MHz



5825MHz

802.11n HT40




5755MHz



5795MHz




802.11ac HT20



5745MHz

5825MHz


802.11ac HT40



5755MHz

5795MHz

802.11ac HT80



5775MHz



4. PEAK OUTPUT POWER

4.1 APPLIED PROCEDURES / LIMIT

For mobile and portable client devices in the 5.15-5.25 GHz band, the maximum conducted output power over the frequency band of operation shall not exceed 250 mW provided the maximum antenna gain does not exceed 6 dBi.

For the band 5.725-5.85 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W.

4.1.1 TEST PROCEDURE

- The EUT was directly connected to the power meter and antenna output port as show in the block diagram below,
- Spectrum Setting : RBW > the 20 dB bandwidth of the emission being measured
Span = approximately 5 times the 20 dB bandwidth, centered on a hopping channel
VBW $\geq$ RBW
Sweep = auto
Detector function = peak
Trace = max hold

4.1.2 DEVIATION FROM STANDARD

No deviation.

4.1.3 TEST SETUP



4.1.4 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.

**4.1.5 TEST RESULTS**

Temperature:	25 °C	Relative Humidity:	60%
Pressure:	1012 hPa	Test Voltage :	AC 120V/60Hz

Band	Mode	Test Channel	Peak Output Power (dBm)	LIMIT (dBm)
Band 1	802.11a	Low	11.332	23.98
		Moddle	11.575	23.98
		High	11.11	23.98
	802.11n HT20	Low	9.33	23.98
		Moddle	9.462	23.98
		High	9.196	23.98
	802.11n HT40	Low	9.658	23.98
		High	10.612	23.98
	802.11ac HT20	Low	8.865	23.98
		Moddle	9.797	23.98
		High	9.553	23.98
	802.11ac HT40	Low	9.394	23.98
		High	10.441	23.98
	802.11ac HT80	/	7.196	23.98


Band	Mode	Test Channel	Peak Output Power (dBm)	LIMIT (dBm)
Band 4	802.11a	Low	9.846	30
		Moddle	10.789	30
		High	10.814	30
	802.11n HT20	Low	13.357	30
		Moddle	14.117	30
		High	14.041	30
	802.11n HT40	Low	12.597	30
		High	13.427	30
	802.11ac HT20	Low	13.044	30
		Moddle	13.938	30
		High	13.891	30
	802.11ac HT40	Low	12.33	30
		High	13.301	30
	802.11ac HT80	/	11.664	30



802.11a



802.11n HT20



5180MHz




5180MHz



5200MHz



5200MHz



5240MHz

5240MHz



802.11n HT40



802.11ac HT20



5190MHz



5180



5230MHz




5200


5240



802.11ac HT40



802.11ac HT80



5190MHz




5210

5230MHz



802.11a



802.11n HT20



5745MHz



5745MHz



5785MHz



5785MHz



5825MHz

5825MHz



802.11n HT40




802.11ac HT20



5755MHz



5745MHz



5795MHz

5785MHz




5825MHz



802.11ac HT40



802.11ac HT80



5755MHz



5775MHz

5795MHz



5. POWER SPECTRAL DENSITY TEST

5.1 APPLIED PROCEDURES / LIMIT

In addition, the maximum power spectral density shall not exceed 11 dBm in any 1 megahertz band.
In addition, the maximum power spectral density shall not exceed 30 dBm in any 500 kHz band.

Spectrum Parameters	Setting
Attenuation	Auto
Span Frequency	= the frequency band of operation
RB	RBW $\geq$ 1MHz for band 1 RBW $\geq$ 510KHz for band 4
VB	VBW $\geq$ 3RBW
Detector	Peak
Trace	Max Hold
Sweep Time	Auto

5.1.1 TEST PROCEDURE

1. Place the EUT on the table and set it in transmitting mode.
2. The testing follows FCC KDB 789033 D02.
3. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to Spectrum.
4. For U-NII1, U-NII-2A, U-NII-2C Band:
Set RBW=1MHz, VBW=3MHz, where span is enough to capture the entire bandwidth, Sweep time = Auto (601 pts), detector = sample, traces 100 sweeps of video averaging. (SA-2 with the omission of procedure x, the integration with 26dB EBW bandwidth)
For U-NII-3 Band:
Set RBW=510 kHz, VBW=3*RBW, where span is enough to capture the entire bandwidth, Sweep time = Auto (601 pts), detector = sample, traces 100 sweeps of video averaging. (SA-2 with the omission of procedure x, the integration with 26dB EBW bandwidth)
5. Use the cursor on spectrum to peak search the highest level of trace
6. Record the max. reading and add 10 log(1/duty cycle).
we test all antennas, the antenna 1 was worst mode and the data recording in the report.

5.1.2 DEVIATION FROM STANDARD

No deviation.

5.1.3 TEST SETUP



5.1.4 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.



5.1.5 TEST RESULTS

	Mode	Test Channel	Reading Level (dBm)	Duty factor (dB)	PSD (dBm)	Limit (dBm)	Result
Band1	802.11a	Low	1.111	0.13	1.241	11.00	PASS
		Moddle	0.94	0.13	1.07	11.00	PASS
		High	0.773	0.13	0.903	11.00	PASS
	802.11n20	Low	-1.171	0.13	-1.041	11.00	PASS
		Moddle	-0.991	0.13	-0.861	11.00	PASS
		High	-1.331	0.13	-1.201	11.00	PASS
	802.11n40	Low	-4.212	0.26	-3.952	11.00	PASS
		High	-3.132	0.26	-2.872	11.00	PASS
	802.11ac20	Low	-1.676	0.15	-1.526	11.00	PASS
		Moddle	-0.758	0.15	-0.608	11.00	PASS
		High	-0.735	0.15	-0.585	11.00	PASS
	802.11ac40	Low	-4.247	0.28	-3.967	11.00	PASS
		High	-3.422	0.28	-3.142	11.00	PASS
	802.11ac80	/	-8.589	0.52	-8.069	11.00	PASS

	Mode	Test Channel	Reading Level (dBm)	Duty factor (dB)	PSD (dBm)	Limit (dBm)	Result
Band4	802.11a	Low	-0.877	0.13	-0.747	30.00	PASS
		Moddle	-0.209	0.13	-0.079	30.00	PASS
		High	-0.475	0.13	-0.345	30.00	PASS
	802.11n20	Low	1.773	0.15	1.923	30.00	PASS
		Moddle	2.323	0.15	2.473	30.00	PASS
		High	2.049	0.15	2.199	30.00	PASS
	802.11n40	Low	-2.353	0.28	-2.073	30.00	PASS
		High	-1.473	0.28	-1.193	30.00	PASS
	802.11ac20	Low	1.82	0.13	1.95	30.00	PASS
		Moddle	2.414	0.13	2.544	30.00	PASS
		High	2.13	0.13	2.26	30.00	PASS
	802.11ac40	Low	-2.479	0.28	-2.199	30.00	PASS
		High	-1.576	0.28	-1.296	30.00	PASS
	802.11ac80	/	-5.048	0.52	-4.528	30.00	PASS




802.11a




802.11n HT20



5180MHz




5180MHz



5200MHz



5200MHz



5240MHz


5240MHz



802.11n HT40




802.11ac HT20




5190MHz



5180




5230MHz



5200

5240





802.11a



802.11n HT20



5745MHz



5745MHz



5785MHz



5785MHz



5825MHz

5825MHz



802.11n HT40



802.11ac HT20



5755MHz



5745MHz



5795MHz



5785MHz

5825MHz



802.11ac HT40



802.11ac HT80



5755MHz



5775MHz

5795MHz



6. 26DB BANDWIDTH TEST

6.1 APPLIED PROCEDURES / LIMIT

The 26 dB bandwidth is used to determine the conducted power limits.

There is no limit bandwidth for U-NII-1, U-NII-2-A and U-NII-2-C.

The minimum of 6dB Bandwidth measurement is 0.5 MHz for U-NII-3


6.1.1 TEST PROCEDURE

1. Set RBW = 300 kHz.
2. Set the video bandwidth (VBW) ≥ 3 RBW.
3. Detector = Peak.
4. Trace mode = max hold.
5. Sweep = auto couple.
6. Allow the trace to stabilize.
7. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 20 dB relative to the maximum level measured in the fundamental emission.

6.1.2 DEVIATION FROM STANDARD

No deviation.

6.1.3 TEST SETUP



6.1.4 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.3 Unless otherwise a special operating condition is specified in the follows during the testing.



6.1.5 TEST RESULTS

		Test Channel	26dB Bandwidth (MHz)	99% Bandwidth (MHz)	Result
Band 1	802.11a	Low	20.00	16.540	Pass
		Middle	20.11	16.501	Pass
		High	20.27	16.518	Pass
	802.11n HT20	Low	21.01	17.624	Pass
		Middle	20.67	17.614	Pass
		High	20.70	17.632	Pass
	802.11n HT40	Low	43.23	36.423	Pass
		High	43.60	36.435	Pass
	802.11ac HT20	Low	20.60	17.613	Pass
		Middle	20.76	17.614	Pass
		High	20.73	17.640	Pass
	802.11ac HT40	Low	43.29	36.387	Pass
		High	43.25	36.433	Pass
	802.11ac HT80	/	82.11	75.464	Pass

		Test Channel	6dB Bandwidth (MHz)	99% Bandwidth (MHz)	26dB Bandwidth Limit (MHz)	Result
Band 4	802.11a	Low	16.305	16.420	>0.5	Pass
		Middle	16.337	16.407	>0.5	Pass
		High	16.332	16.420	>0.5	Pass
	802.11n HT20	Low	16.933	17.596	>0.5	Pass
		Middle	17.281	17.597	>0.5	Pass
		High	17.276	17.631	>0.5	Pass
	802.11n HT40	Low	36.28	36.181	>0.5	Pass
		High	35.944	36.170	>0.5	Pass
	802.11ac HT20	Low	16.942	17.596	>0.5	Pass
		Middle	17.127	17.610	>0.5	Pass
		High	17.538	17.631	>0.5	Pass
	802.11ac HT40	Low	36.071	36.176	>0.5	Pass
		High	36.029	36.158	>0.5	Pass
	802.11ac HT80	/	75.155	75.299	>0.5	Pass



802.11a



802.11n HT20




5180MHz



5180MHz



5200MHz



5200MHz




5240MHz


5240MHz



802.11n HT40



802.11ac HT20




5190MHz



5180



5230MHz



5200


5240




802.11ac HT40



802.11ac HT80



5190MHz



5210

5230MHz




802.11a



802.11n HT20



5745MHz



5745MHz



5785MHz



5785MHz




5825MHz

5825MHz




802.11n HT40



802.11ac HT20



5755MHz



5745MHz



5795MHz

5785MHz



5825MHz



802.11ac HT40



802.11ac HT80



5755MHz



5775MHz

5795MHz



7. DUTY CYCLE TEST SIGNAL

7.1 APPLIED PROCEDURES / LIMIT

Pre-analysis Check: While conducting average power measurement, duty cycle of each mode shall be checked to ensure its duty cycle in order to compensate for the loss due to insufficient ratio of duty cycle. All duty cycle is pre-scanned, and result as obtained below shows only the most representative ones where duty cycle is conducted as the given transmission with given virtual operation that expresses the percentage.

7.1.1 TEST PROCEDURE

1. Set RBW = 8 MHz.
2. Set the video bandwidth (VBW) $\geq$ RBW.
3. Detector = Peak.
4. Sweep = auto couple.
5. Allow the trace to stabilize.
6. Span=0

7.1.2 DEVIATION FROM STANDARD

No deviation.

7.1.3 TEST SETUP



7.1.4 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.3 Unless otherwise a special operating condition is specified in the follows during the testing.





7.1.5 TEST RESULTS



Operation Mode		Duty Cycle(%)	Duty Fator (dB) $10 * \log (1/ \text{Duty cycle})$
Band 1	802.11a	97.06	0.13
	802.11n(HT20)	96.96	0.13
	802.11n(HT40)	94.16	0.26
	802.11ac(HT20)	96.68	0.15
	802.11ac(HT40)	93.78	0.28
	802.11ac(HT80)	88.67	0.52
Band 4	802.11a	97.09	0.13
	802.11n(HT20)	96.64	0.15
	802.11n(HT40)	93.86	0.28
	802.11ac(HT20)	97.00	0.13
	802.11ac(HT40)	93.86	0.28
	802.11ac(HT80)	88.80	0.52





802.11a



802.11n HT20




802.11n HT40








802.11ac HT20



802.11ac HT40



802.11ac HT80





8. FREQUENCY STABILITY

8.1 APPLIED PROCEDURES / LIMIT

Manufacturers of U-NII devices are responsible for ensuring frequency stability such that an emission is maintained within the band of operation under all conditions of normal operation as specified in the user's manual.


8.1.1 TEST PROCEDURE

1. The EUT was placed inside temperature chamber and powered and powered by nominal DC voltage.
2. Set EUT as normal operation.
3. Turn the EUT on and couple its output to spectrum.
4. Turn the EUT off and set the chamber to the highest temperature specified.
5. Allow sufficient time (approximately 30 min) for the temperature of the chamber to stabilize, turn the EUT and measure the operating frequency.
6. Repeat step with the temperature chamber set to the lowest temperature.

8.1.2 DEVIATION FROM STANDARD

No deviation.

8.1.3 TEST SETUP



8.1.4 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.3 Unless otherwise a special operating condition is specified in the follows during the testing.



8.1.5 TEST RESULTS

Test Voltage	Test Temp.	Measured Frequency (MHz)	Spectrum Frequency (MHz)			Δ Frequency (MHz)		
			802.11a	802.11n HT20	802.11ac HT20	802.11a	802.11n HT20	802.11ac HT20
132V	-20°C	5180.000	5180.0436	5180.0342	5180.0352	-0.0436	-0.0342	-0.0352
		5220.000	5220.0363	5220.0377	5220.0335	-0.0363	-0.0377	-0.0335
		5240.000	5240.0241	5240.0241	5240.0226	-0.0241	-0.0241	-0.0226
		5745.000	5745.0347	5745.0328	5745.0333	-0.0347	-0.0328	-0.0333
		5785.000	5785.0316	5785.0338	5785.0328	-0.0316	-0.0338	-0.0328
		5825.000	5825.0341	5825.0335	5825.0319	-0.0341	-0.0335	-0.0319
108V	-20°C	5180.000	5180.0236	5180.0285	5180.0263	-0.0236	-0.0285	-0.0263
		5220.000	5220.0334	5220.0352	5220.0334	-0.0334	-0.0352	-0.0334
		5240.000	5240.0241	5240.0236	5240.0245	-0.0241	-0.0236	-0.0245
		5745.000	5745.0236	5745.0252	5745.0263	-0.0236	-0.0252	-0.0263
		5785.000	5785.0357	5785.0336	5785.0338	-0.0357	-0.0336	-0.0338
		5825.000	5825.0417	5825.0438	5825.0425	-0.0417	-0.0438	-0.0425
120V	25°C	5180.000	5180.0526	5180.0541	5180.0563	-0.0526	-0.0541	-0.0563
		5220.000	5220.0247	5220.0285	5220.0241	-0.0247	-0.0285	-0.0241
		5240.000	5240.0396	5240.0348	5240.0368	-0.0396	-0.0348	-0.0368
		5745.000	5745.0317	5745.0358	5745.0339	-0.0317	-0.0358	-0.0339
		5785.000	5785.0429	5785.0426	5785.0438	-0.0429	-0.0426	-0.0438
		5825.000	5825.0285	5825.0257	5825.0248	-0.0285	-0.0257	-0.0248
132V	50°C	5180.000	5180.0336	5180.0348	5180.0327	-0.0336	-0.0348	-0.0327
		5220.000	5220.0239	5220.0228	5220.0266	-0.0239	-0.0228	-0.0266
		5240.000	5240.0327	5240.0338	5240.0347	-0.0327	-0.0338	-0.0347
		5745.000	5745.0652	5745.0638	5745.0636	-0.0652	-0.0638	-0.0636
		5785.000	5785.0438	5785.0452	5785.0445	-0.0438	-0.0452	-0.0445
		5825.000	5825.0626	5825.0637	5825.0638	-0.0626	-0.0637	-0.0638
108V	50°C	5180.000	5180.0325	5180.0336	5180.0328	-0.0325	-0.0336	-0.0328
		5220.000	5220.0264	5220.0252	5220.0238	-0.0264	-0.0252	-0.0238
		5240.000	5240.0315	5240.0363	5240.0385	-0.0315	-0.0363	-0.0385
		5745.000	5745.0474	5745.0449	5745.0448	-0.0474	-0.0449	-0.0448
		5785.000	5785.0226	5785.0252	5785.0245	-0.0226	-0.0252	-0.0245
		5825.000	5825.0736	5825.0752	5825.0717	-0.0736	-0.0752	-0.0717



Test Voltage	Test Temp.	Measured Frequency (MHz)	Spectrum Frequency (MHz)		Δ Frequency (MHz)	
			802.11n HT40	802.11ac HT40	802.11n HT40	802.11ac HT40
132V	-20℃	5190.000	5190.0252	5190.0237	-0.0252	-0.0237
		5230.000	5230.0315	5230.0329	-0.0315	-0.0329
		5755.000	5755.0526	5755.0534	-0.0526	-0.0534
		5795.000	5795.0633	5795.0685	-0.0633	-0.0685
108V		5190.000	5190.0296	5190.0245	-0.0296	-0.0245
		5230.000	5230.0318	5230.0325	-0.0318	-0.0325
		5755.000	5755.0241	5755.0233	-0.0241	-0.0233
		5795.000	5795.0453	5795.0458	-0.0453	-0.0458
120V	25℃	5190.000	5190.0241	5190.0246	-0.0241	-0.0246
		5230.000	5230.0636	5230.0682	-0.0636	-0.0682
		5755.000	5755.0245	5755.0274	-0.0245	-0.0274
		5795.000	5795.0536	5795.0517	-0.0536	-0.0517
132V	50℃	5190.000	5190.0652	5190.0639	-0.0652	-0.0639
		5230.000	5230.0534	5230.0528	-0.0534	-0.0528
		5755.000	5755.0441	5755.0433	-0.0441	-0.0433
		5795.000	5795.0336	5795.0348	-0.0336	-0.0348
108V	50℃	5190.000	5190.0529	5190.0537	-0.0529	-0.0537
		5230.000	5230.0349	5230.0352	-0.0349	-0.0352
		5755.000	5755.0341	5755.0326	-0.0341	-0.0326
		5795.000	5795.0426	5795.0437	-0.0426	-0.0437

Test Voltage	Test Temp.	Measured Frequency (MHz)	Spectrum Frequency (MHz)	Δ Frequency (MHz)
			802.11ac HT80	802.11ac HT80
132V	-20℃	5210.000	5210.0128	-0.0128
		5775.000	5775.0185	-0.0185
108V		5210.000	5210.0296	-0.0296
		5775.000	5775.0341	-0.0341
230V	25℃	5210.000	5210.0418	-0.0418
		5775.000	5775.0486	-0.0486
132V	50℃	5210.000	5210.0385	-0.0385
		5775.000	5775.0284	-0.0284
108V	50℃	5210.000	5210.0374	-0.0374
		5775.000	5775.0536	-0.0536



9. TRANSMISSION IN THE ABSENCE OF DATA

9.1 STANDARD REQUIREMENT

According to §15.407(c)

The device shall automatically discontinue transmission in case of either absence of information to transmit or operational failure. These provisions are not intended to preclude the transmission of control or signaling information or the use of repetitive codes used by certain digital technologies to complete frame or burst intervals. Applicants shall include in their application for equipment authorization a description of how this requirement is met.

9.2 TEST RESULT

No non-compliance noted:
Refer to the theory of operation.

10. ANTENNA REQUIREMENT

10.1 STANDARD REQUIREMENT

15.203 requirement: For intentional device, according to 15.203: an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.



10.2 EUT ANTENNA

The EUT antenna is internal antenna,. It comply with the standard requirement.




11. TEST SEUUP PHOTO

Radiated Measurement Photos







Conducted Measurement Photos









12. EUT PHOTO






















***** END OF REPORT *****