



F2 Labs
16740 Peters Road
Middlefield, Ohio 44062
United States of America
www.f2labs.com

CERTIFICATION TEST REPORT

Manufacturer: VICEDO MARTI, S.L.
C/ AVILA, 2
Ibi (ALICANTE) - 03440
SPAIN

Applicant: Same as Above

Product Name: VICEDO MARTI MANNEQUIN

Product Description: Mannequin Torso for CPR Training

Model(s): VM-BABY MANNEQUIN*
**Denotes actual model tested as representative of product family that includes models VM-BABY MANNEQUIN and VM-ADULT MANNEQUIN.*

FCC ID: 2A2SDCPRTY1

Testing Commenced: 2021-07-27

Testing Ended: 2021-11-09

Summary of Test Results: In Compliance

The EUT complies with the EMC requirements when manufactured identically as the unit tested in this report, including any required modifications and/or manufacturer's statement. Any changes to the design or build of this unit subsequent to this testing may deem it non-compliant.

Standards:

- ❖ FCC Part 15 Subpart C, Section 15.249
- ❖ FCC Part 15 Subpart C, Section 15.215(c) – Additional provisions to the general radiated emission limitations
- ❖ FCC Part 15 Subpart A, Section 15.31(e) – Measurement Standards



Order Number: F2P25939

Applicant: VICEDO MARTI, S.L.
Model(s): VM-BABY MANNEQUIN

Evaluation Conducted by:

Julius Chiller, EMC/Wireless Engineer

Report Reviewed by:

Ken Littell, Vice President of EMC

F2 Labs
26501 Ridge Road
Damascus, MD 20872
Ph 301.253.4500

F2 Labs
16740 Peters Road
Middlefield, OH 44062
Ph 440.632.5541

F2 Labs
8583 Zionsville Road
Indianapolis, IN 46268
Ph 317.610.0611

This test report may be reproduced in full; partial reproduction only may be made with the written consent of F2 Labs. The results in this report apply only to the equipment tested.

TABLE OF CONTENTS

Section	Title	Page
1	ADMINISTRATIVE INFORMATION	4
2	SUMMARY OF TEST RESULTS/MODIFICATIONS	7
3	TABLE OF MEASURED RESULTS	8
4	ENGINEERING STATEMENT	9
5	EUT INFORMATION AND DATA	10
6	LIST OF MEASUREMENT INSTRUMENTATION	11
7	OCCUPIED BANDWIDTH	12
8	FIELD STRENGTH OF EMISSIONS	19
9	PHOTOGRAPHS - TEST SETUPS	30



Order Number: F2P25939

Applicant: VICEDO MARTI, S.L.
Model(s): VM-BABY MANNEQUIN

1 ADMINISTRATIVE INFORMATION

1.1 Measurement Location:

F2 Labs in Middlefield, Ohio. Site description and attenuation data are on file with the FCC's Sampling and Measurement Branch at the FCC Laboratory in Columbia, MD.

1.2 Measurement Procedure:

All measurements were performed according to the 2013 version of ANSI C63.10 and recommended FCC procedure of measurement of DXT operating under Section 15.249. A list of the measurement equipment can be found in Section 6.

1.3 Uncertainty Budget:

The uncertainty in EMC measurements arises from several factors which affect the results, some associated with environmental conditions in the measurement room, the test equipment being used, and the measurement techniques adopted.

The measurement uncertainty budgets detailed below are calculated from the test and calibration data and are expressed with a 95% confidence factor using a coverage factor of $k=2$. The Uncertainty for a laboratory is referred to as U_{lab} . For Radiated and Conducted Emissions, the Expanded Uncertainty is compared to the U_{cispr} values to determine if a specific margin is required to deem compliance.

U_{lab}

Measurement Range	Combined Uncertainty	Expanded Uncertainty
Radiated Emissions <1 GHz @ 3m	2.54	5.07dB
Radiated Emissions <1 GHz @ 10m	2.55	5.09dB
Radiated Emissions 1 GHz to 2.7 GHz	1.81	3.62dB
Radiated Emissions 2.7 GHz to 18 GHz	1.55	3.10dB
AC Power Line Conducted Emissions, 150kHz to 30 MHz	1.38	2.76dB
AC Power Line Conducted Emissions, 9kHz to 150kHz	1.66	3.32dB

U_{cispr}

Measurement Range	Expanded Uncertainty
Radiated Emissions <1 GHz @ 3m	5.2dB
Radiated Emissions <1 GHz @ 10m	5.2dB
Radiated Emissions 1 GHz to 2.7 GHz	Under Consideration
Radiated Emissions 2.7 GHz to 18 GHz	Under Consideration
AC Power Line Conducted Emissions, 150kHz to 30 MHz	3.6dB
AC Power Line Conducted Emissions, 9kHz to 150kHz	4.0dB

If U_{lab} is less than or equal to U_{cispr} , then:

- compliance is deemed to occur if no measured disturbance exceeds the disturbance limit;
- non-compliance is deemed to occur if any measured disturbance exceeds the disturbance limit.

If U_{lab} is greater than U_{cispr} in table 1, then:

- compliance is deemed to occur if no measured disturbance, increased by $(U_{lab} - U_{cispr})$, exceeds the disturbance limit;
- non-compliance is deemed to occur if any measured disturbance, increased by $(U_{lab} - U_{cispr})$, exceeds the disturbance limit.

Note: Only measurements listed in the tables above that relate to tests included in this Test Report are applicable.



Order Number: F2P25939

Applicant: VICEDO MARTI, S.L.
Model(s): VM-BABY MANNEQUIN

1.4 Document History:

Document Number	Description	Issue Date	Approved By
F2P25939-01E	First Issue	2021-11-10	K. Littell



Order Number: F2P25939

Applicant: VICEDO MARTI, S.L.
Model(s): VM-BABY MANNEQUIN

2 SUMMARY OF TEST RESULTS

Test Name	Standard(s)	Results
99% Occupied Bandwidth	CFR 47 Part 15.215(c)	Complies
-20dB Occupied Bandwidth	CFR 47 Part 15.215(c)	Complies
Field Strength of Emissions	CFR 47 Part 15.249(a)(d)	Complies
Variation of the Input Power	CFR 47 Part 15.231(e)	Complies*

*Requirements met by using new batteries.

Modifications Made to the Equipment
None

3 TABLE OF MEASURED RESULTS

Test	Low Channel 2407 MHz	Mid Channel 2427 MHz	High Channel 2447 MHz
Average Field Strength of Fundamental	79.6 dB μ V/m, 9.55 mV/m	79.3 dB μ V/m, 9.22 mV/m	78.2 dB μ V/m, 8.12 mV/m
Average Limit for Fundamental	50 millivolts/meter (93.97 dB μ V/m)	50 millivolts/meter (93.97 dB μ V/m)	50 millivolts/meter (93.97 dB μ V/m)
Peak Field Strength of Fundamental	80.1 dB μ V/m 10.1 mV/m	80.3 dB μ V/m 10.3 mV/m	80.4 dB μ V/m 10.5 mV/m
Peak Limit for Fundamental	113.97 dB μ V/m	113.97 dB μ V/m	113.97 dB μ V/m
-20dB Occupied Bandwidth	1.023 MHz	1.009 MHz	1.017 MHz
99% Occupied Bandwidth (MHz)	0.929 MHz	0.928 MHz	0.934 MHz

The -20dB bandwidth of the emission shall be contained within the frequency band designated in the rule section under which the equipment is operated.



Order Number: F2P25939

Applicant: VICEDO MARTI, S.L.
Model(s): VM-BABY MANNEQUIN

4 ENGINEERING STATEMENT

This report has been prepared on behalf of VICEDO MARTI, S.L. to provide documentation for the testing described herein. This equipment has been tested and found to comply with part 15.249 of the FCC Rules using ANSI C63.10 2013 standard. The test results found in this test report relate only to the items tested.



Order Number: F2P25939

Applicant: VICEDO MARTI, S.L.
Model(s): VM-BABY MANNEQUIN

5 EUT INFORMATION AND DATA

5.1 Equipment Under Test:

Product: VICEDO MARTI MANNEQUIN

Model(s): VM-BABY MANNEQUIN*

**Denotes actual model tested as representative of product family that includes models VM-BABY MANNEQUIN and VM-ADULT MANNEQUIN.*

Serial No.: v1.02

Firmware: ViMa_Body_FW_rev1.12 / ViMa_Mon_FW_rev1.03

Hardware: MIR-01_HW_rev1.02 / MIR-01_HW_rev1.05

FCC ID: 2A2SDCPRTY1

5.2 Trade Name:

VICEDO MARTI, S.L.

5.3 Power Supply:

Battery-Operated (9V)

5.4 Applicable Rules:

CFR 47, Part 15.249, subpart C

5.5 Equipment Category:

Radio Transmitter-DXT

5.6 Antenna:

Integral Antenna, 2.5dBi Gain

5.7 Accessories:

Device	Manufacturer	Model Number	Serial Number
Battery*	Interstate	9V	N/A
Laptop*	Dell	Latitude E6500	JWM6XH1

**Indicates F2 Labs-supplied equipment.*

5.8 Test Item Condition:

The equipment to be tested was received in good condition.

5.9 Testing Algorithm:

EUT was set to operate on three channels (low, mid and high) using GFSK modulation in the 2.4 GHz band.



Order Number: F2P25939

Applicant: VICEDO MARTI, S.L.
Model(s): VM-BABY MANNEQUIN

6 LIST OF MEASUREMENT INSTRUMENTATION

Equipment Type	Asset Number	Manufacturer	Model	Serial Number	Calibration Due Date
Shielded Chamber	CL166-E	Albatross Projects	B83117-DF435-T261	US140023	2022-03-09
Temp/Hum. Recorder	CL232	Extech	445814	01	2022-03-04
Receiver	CL151	Rohde & Schwarz	ESU40	100319	2022-07-08
Low Loss Cable Set	--	Pasternack	PE3C0666-252 / PE3C066-50CM	None Spec.	2023-10-12
Horn Antenna 18-26.5 GHz	CL114	A.H. Systems, Inc.	SAS-572	237	2023-07-30
Pre-Amplifier	CL153	Keysight Tech.	83006A	MY39500791	2022-02-12
Pre-Amplifier	CL285	Com-Power	PAM-0207	322	2022-07-08
Active 18" Loop Antenna	CL163-Loop	A.H. Systems, Inc.	EHA-52B	100	2022-09-14
Antenna, JB3 Combination	CL175	Sunol Sciences	JB3	A030315	2022-09-14
Horn Antenna	CL098	Emco	3115	9809-5580	2022-01-08
Software:	Tile Version 3.4.B.3			Software Verified: 2021-07-27; 2021-10-26	
Software:	EMC 32, Version 8.53.0			Software Verified: 2021-07-27	



Order Number: F2P25939

Applicant: VICEDO MARTI, S.L.
Model(s): VM-BABY MANNEQUIN

7 FCC PART 15.215(e), OCCUPIED BANDWIDTH

7.1 Requirements:


Intentional radiators operating under the alternative provisions to the general emission limits, as contained in §§15.217 through 15.257 and in Subpart E of this part, must be designed to ensure that the -20dB bandwidth of the emission, or whatever bandwidth may otherwise be specified in the specific rule section under which the equipment operates, is contained within the frequency band designated in the rule section under which the equipment is operated. The requirement to contain the designated bandwidth of the emission within the specified frequency band includes the effects from frequency sweeping, frequency hopping and other modulation techniques that may be employed as well as the frequency stability of the transmitter over expected variations in temperature and supply voltage.


Bandwidth measurements were made at the low (2.407 GHz), mid (2.427 GHz) and upper (2.447 GHz) frequencies. The bandwidth was measured using the analyzer's marker function.


7.2 Occupied Bandwidth Test Data

Test Date(s):	2021-07-27; 2021-11-09	Test Engineer(s):	J. Chiller
Standards:	CFR 47 Part 15.215(c)	Air Temperature:	22.3°C
		Relative Humidity:	39%


-20dB, Low Channel




-20dB, Mid Channel

-20dB, High Channel


99%, Low Channel



99%, Mid Channel



99%, High Channel



8 FIELD STRENGTH OF EMISSIONS FROM INTENTIONAL RADIATORS

(a) Except as provided in paragraph (b) of this section, the field strength of emissions from intentional radiators operated within these frequency bands shall comply with the following:

Fundamental Frequency	Field Strength of Fundamental (millivolts/meter)	Field Strength of Harmonics (microvolts/meter)
902-928 MHz	50	500
2400-2483.5 MHz	50	500
5725-5875 MHz	50	500
24.0-24.25 GHz	250	2500

(d) Emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 50dB below the level of the fundamental or to the general radiated emission limits in §15.209, whichever is the lesser attenuation.


NOTE: During the pre-scan evaluation, the EUT was rotated in all possible directions to find the maximum emissions. The orthogonal position that showed the highest emissions was used. The antenna was raised between 1 and 4 meters and the EUT turntable was rotated 360 degrees to maximize the emissions.

Scans were performed with just the PCB assembly for the mannequin; with just the PCB assembly for the monitor; with the child mannequin with monitor; and with the adult mannequin with monitor. There was no change whatsoever in the measurement results. This was done to prove a product family that any mannequin can be used with the monitor.


8.1 Test Data - Field Strength of Emissions from Intentional Radiators

Test Date(s):	2021-07-27; 2021-11-09	Test Engineer(s):	J. Chiller
Standards:	CFR 47 Part 15.249(a)	Air Temperature:	21.5°C
		Relative Humidity:	47%

Band Edge: Low



Band Edge: High




Band Edge and Field Strength of the Fundamentals
MaxPeak

Frequency (MHz)	Antenna Polarization	Bandwidth (kHz)	Antenna Height (cm)	Azimuth (deg)	Reading (dB μ V)	Cable Loss & Antenna Factor (dB)	Emission (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)
2400.00	H	1000.00	150.00	145.00	36.6	5.8	42.40	74.0	-31.6
2400.00	V	1000.00	150.00	97.00	36.3	5.8	42.10	74.0	-31.9
2407.00	V	1000.00	150.00	97.00	71.0	5.8	76.80	114.0	-37.2
2407.00	H	1000.00	150.00	145.00	74.3	5.8	80.10	114.0	-33.9
2427.00	H	1000.00	150.00	153.00	74.5	5.8	80.30	114.0	-33.7
2427.00	V	1000.00	150.00	50.00	70.8	5.8	76.60	114.0	-37.4
2447.00	V	1000.00	150.00	61.00	69.8	5.7	75.50	114.0	-38.5
2447.00	H	1000.00	150.00	154.00	74.7	5.7	80.40	114.0	-33.6
2483.50	V	1000.00	150.00	97.00	36.2	5.8	42.00	74.0	-32.0
2483.50	H	1000.00	150.00	154.00	36.1	5.8	41.90	74.0	-32.1

AVG

Frequency (MHz)	Antenna Polarization	Bandwidth (kHz)	Height (cm)	Reading (dB μ V)	Cable Loss & Antenna Factor (dB)	Emission (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)
2400.000000	H	1000.00	150.00	23.1	5.8	28.90	54.0	-25.1
2400.000000	V	1000.00	150.00	23.1	5.8	28.90	54.0	-25.1
2407.000000	V	1000.00	150.00	69.0	5.8	74.80	94.0	-19.2
2407.000000	H	1000.00	150.00	73.8	5.8	79.60	94.0	-14.4
2427.000000	H	1000.00	150.00	73.5	5.8	79.30	94.0	-14.7
2427.000000	V	1000.00	150.00	68.9	5.8	74.70	94.0	-19.3
2447.000000	V	1000.00	150.00	69.0	5.7	74.70	94.0	-19.3
2447.000000	H	1000.00	150.00	72.5	5.7	78.20	94.0	-15.8
2483.500000	V	1000.00	150.00	23.1	5.8	28.90	54.0	-25.1
2483.500000	H	1000.00	150.00	23.1	5.8	28.90	54.0	-25.1



8.2 Test Data – Spurious Emissions


Notes: Plots are peak, max hold pre-scan data included only to determine what frequencies to investigate and measure. During the pre-scan evaluation, the EUT was rotated in all possible directions to find the maximum emissions. The orthogonal position that showed the highest emissions was used. At some frequencies, no emissions from the EUT were measurable over the ambient noise floor. The readings did not change with EUT on and EUT off.

At least 6 of the highest frequencies were measured per ANSI 63.4 in a 3-meter anechoic chamber. Frequencies below 1 GHz were measured using a quasi-peak detector. The antenna was raised between 1 and 4 meters and the EUT turntable was rotated 360 degrees to maximize the emissions. Some of the frequencies did not change with the EUT on or off. At those frequencies, the test distance was shortened to 1 meter and still no emissions from the EUT were visible or over the ambient or limit. Frequencies were scanned from 9kHz to 26 GHz and the highest emissions are listed below.


In the following plots, the black line indicates ambient noise and the red line indicates the measurement with the EUT on. Emissions to be found by the EUT were measured and listed in tables below.

Test Date(s):	2021-07-27; 2021-11-09	Test Engineer(s):	J. Chiller
Standards:	CFR 47 Part 15.249(d) / Part 15.209	Air Temperature:	22.5°C
		Relative Humidity:	39%

Characterization Scan, 9 kHz to 150 kHz






Characterization Scan, 150 kHz to 30 MHz







30 MHz to 1000 MHz
Note: Chart below includes data from all three channels.

Frequency (MHz)	Antenna Polarization	Antenna Height (cm)	Azimuth (degrees)	Reading (dB μ V)	Correction Factors (dB)	Emission (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)
31.360000	V	100.00	0.00	27.0	-2.2	24.80	40.0	-15.2
33.120000	H	100.00	336.00	25.7	-3.5	22.20	40.0	-17.8
48.040000	V	100.00	0.00	34.0	-13.6	20.40	40.0	-19.6
66.680000	V	100.00	0.00	29.2	-14.6	14.60	40.0	-25.4
79.840000	H	100.00	10.00	21.3	-14.7	6.60	40.0	-33.4
79.840000	H	100.00	0.00	21.1	-14.7	6.40	40.0	-33.6
79.840000	H	100.00	348.00	21.9	-14.7	7.20	40.0	-32.8
79.840000	V	100.00	0.00	21.9	-14.7	7.20	40.0	-32.8
100.040000	V	100.00	0.00	33.8	-12.0	21.80	43.5	-21.7
120.000000	V	100.00	0.00	35.1	-8.5	26.60	43.5	-16.9
143.880000	V	100.00	0.00	25.4	-9.1	16.30	43.5	-27.2
144.080000	H	100.00	357.00	29.5	-9.1	20.40	43.5	-23.1
144.080000	H	100.00	0.00	26.4	-9.1	17.30	43.5	-26.2
160.000000	V	100.00	0.00	33.1	-9.5	23.60	43.5	-19.9
192.000000	H	100.00	0.00	33.7	-10.0	23.70	43.5	-19.8
192.000000	H	100.00	357.00	35.2	-10.0	25.20	43.5	-18.3
288.040000	H	100.00	133.00	41.1	-7.6	33.50	46.0	-12.5
288.040000	H	100.00	357.00	28.7	-7.6	21.10	46.0	-24.9
288.040000	H	100.00	0.00	32.1	-7.6	24.50	46.0	-21.5
312.080000	H	100.00	357.00	27.4	-6.9	20.50	46.0	-25.5
336.120000	H	100.00	357.00	25.8	-6.3	19.50	46.0	-26.5




Low Channel, 30 MHz to 1000 MHz, Vertical**Low Channel, 30 MHz to 1000 MHz, Horizontal**

Mid Channel, 30 MHz to 1000 MHz, Vertical**Mid Channel, 30 MHz to 1000 MHz, Horizontal**


High Channel, 30 MHz to 1000 MHz, Vertical**High Channel, 30 MHz to 1000 MHz, Horizontal**



Note: No signals between 1-26 GHz, other than the fundamental frequency, are within 20dB of the limit.

Low Channel, 1 GHz to 18 GHz, Vertical



Low Channel, 1 GHz to 18 GHz, Horizontal



Low Channel, 18 GHz to 26 GHz, Vertical**Low Channel, 18 GHz to 26 GHz, Horizontal**

9 PHOTOGRAPHS - TEST SETUPS**Radiated Emissions: Less Than 1 GHz****Radiated Emissions: Greater Than 1 GHz; OBW**