



BLE 2M Ant1 2480 30~1000



BLE 2M Ant1 2480 1000~26500



## 8.5 RADIATED SPURIOUS EMISSION

### 8.5.1 Applicable Standard

According to FCC Part 15.247(d) and 15.209 and KDB 558074 D01 15.247 Meas Guidance v05r02.

### 8.5.2 Conformance Limit

According to FCC Part 15.247(d): radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

According to FCC Part 15.205, Restricted bands:

MHz	MHz	MHz	GHz
0.090-0.110	16.42-16.423	399.9-410	4.5-5.15
10.495-0.505	16.69475-16.69525	608-614	5.35-5.46
2.1735-2.1905	16.80425-16.80475	960-1240	7.25-7.75
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5
4.17725-4.17775	37.5-38.25	1435-1626.5	9.0-9.2
4.20725-4.20775	73-74.6	1645.5-1646.5	9.3-9.5
6.215-6.218	74.8-75.2	1660-1710	10.6-12.7
6.26775-6.26825	123-138	2200-2300	14.47-14.5
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2
8.362-8.366	156.52475-156.52525	2483.5-2500	17.7-21.4
8.37625-8.38675	156.7-156.9	2690-2900	22.01-23.12
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0
12.29-12.293	167.72-173.2	3332-3339	31.2-31.8
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5
12.57675-12.57725	322-335.4	3600-4400	(2)
13.36-13.41			

According to FCC Part 15.205, the level of any transmitter spurious emission in Restricted bands shall not exceed the level of the emission specified in the following table.

Restricted Frequency(MHz)	Field Strength (μV/m)	Field Strength (dBμV/m)	Measurement Distance
0.009-0.490	2400/F(KHz)	20 log (uV/m)	300
0.490-1.705	24000/F(KHz)	20 log (uV/m)	30
1.705-30	30	29.5	30
30-88	100	40	3
88-216	150	43.5	3
216-960	200	46	3
Above 960	500	54	3

### 8.5.3 Test Configuration

Test according to clause 7.2 radio frequency test setup 2.

### 8.5.4 Test Procedure

This test is required for any spurious emission that falls in a Restricted Band, as defined in Section 15.205. It must be performed with the highest gain of each type of antenna proposed for use with the EUT. Use the following spectrum analyzer settings:

The EUT was placed on a turn table which is 0.8m above ground plane.

Maximum procedure was performed on the highest emissions to ensure EUT compliance.

Span = wide enough to fully capture the emission being measured.

RBW = 1 MHz for  $f \geq 1$  GHz(1GHz to 25GHz), 100 kHz for  $f < 1$  GHz(30MHz to 1GHz).

VBW  $\geq$  RBW.

Sweep = auto.

Detector function = peak.

Trace = max hold.

Follow the guidelines in ANSI C63.10-2013 with respect to maximizing the emission by rotating the EUT, measuring the emission while the EUT is situated in three orthogonal planes (if appropriate), adjusting the measurement antenna height and polarization, etc. A pre-amp and a high pass filter are required for this test, in order to provide the measuring system with sufficient sensitivity. Allow the trace to stabilize. The peak reading of the emission, after being corrected by the antenna factor, cable loss, pre-amp gain, etc., is the peak field strength, which must comply with the limit specified in Section 15.35(b). Submit this data.

Now set the VBW to 10 Hz, while maintaining all of the other instrument settings. This peak level, once corrected, must comply with the limit specified in Section 15.209. If the dwell time per channel of the hopping signal is less than 100 ms, then the reading obtained with the 10 Hz VBW may be further adjusted by a “duty cycle correction factor”, derived from  $20\log(\text{dwell time}/100 \text{ ms})$ , in an effort to demonstrate compliance with the 15.209 limit. Submit this data.

Repeat above procedures until all frequency measured was complete.

### 8.5.5 Test Results

Temperature:	26° C
Relative Humidity:	54%
ATM Pressure:	1011 mbar

#### ■ Spurious Emission below 30MHz (9KHz to 30MHz)

Freq. (MHz)	Ant.Pol. H/V	Emission Level(dBuV/m)		Limit 3m(dBuV/m)		Over(dB)	
		PK	AV	PK	AV	PK	AV
--	--	--	--	--	--	--	--

Note: Data of measurement within this frequency range shown “ -- ” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.

■ Spurious Emission Above 1GHz (1GHz to 25GHz)

BLE mode have been tested, and the worst result was report as below:

Test mode: BLE(1M) Frequency: Channel 0: 2402MHz

Freq. (MHz)	Ant.Pol.	Emission Level(dBuV/m)		Limit 3m(dBuV/m)		Over(dB)	
	H/V	PK	AV	PK	AV	PK	AV
11375.1	V	59.24	46.21	74	54	14.76	7.79
14581.2	V	63.07	47.11	74	54	10.93	6.89
17489.7	V	68.44	46.67	74	54	5.56	7.33
11519.7	H	59.37	47.20	74	54	14.63	6.80
14615.3	H	63.30	46.97	74	54	10.70	7.03
17515.2	H	68.35	46.56	74	54	5.65	7.44

Test mode: BLE(1M) Frequency: Channel 19: 2440MHz

Freq. (MHz)	Ant.Pol.	Emission Level(dBuV/m)		Limit 3m(dBuV/m)		Over(dB)	
	H/V	PK	AV	PK	AV	PK	AV
11502.7	V	59.15	46.85	74	54	14.85	7.15
14623.8	V	62.47	46.76	74	54	11.53	7.24
17506.7	V	67.23	46.80	74	54	6.77	7.20
11477.2	H	59.23	49.07	74	54	14.77	4.93
14623.8	H	63.01	46.45	74	54	10.99	7.55
17498.2	H	67.58	47.45	74	54	6.42	6.55

Test mode: BLE(1M) Frequency: Channel 39: 2480MHz

Freq. (MHz)	Ant.Pol.	Emission Level(dBuV/m)		Limit 3m(dBuV/m)		Over(dB)	
	H/V	PK	AV	PK	AV	PK	AV
11553.7	V	59.04		74	54	14.96	
15159.5	V	63.51		74	54	10.49	
17498.2	V	68.43		74	54	5.57	
11511.2	H	59.51	47.35	74	54	14.49	6.65
14555.7	H	63.11	46.99	74	54	10.89	7.01
17498.2	H	67.87	47.44	74	54	6.13	6.56

- Note:**
- (1) All Readings are Peak Value (VBW=3MHz) and Average Value (VBW=10Hz).
  - (2) Emission Level= Reading Level+Correct Factor.
  - (3) Correct Factor= Ant\_F + Cab\_L - Preamp
  - (4) The reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.

■ Spurious Emission in Restricted Band 2310-2390MHz and 2483.5-2500MHz

Test mode: BLE(1M) Frequency: Channel 0: 2402MHz


Frequency (MHz)	Polarity	PK(dBuV/m) (VBW=3MHz)	Limit 3m (dBuV/m)	Margin (dB)	AV(dBuV/m) (VBW=10Hz)	Limit 3m (dBuV/m)	Margin (dB)
2315.64	H	44.11	74.00	29.89	43.08	54.00	10.92
2317.26	V	44.83	74.00	29.17	43.50	54.00	10.50

Test mode: BLE(1M) Frequency: Channel 39: 2480MHz


Frequency (MHz)	Polarity	PK(dBuV/m) (VBW=3MHz)	Limit 3m (dBuV/m)	Margin (dB)	AV(dBuV/m) (VBW=10Hz)	Limit 3m (dBuV/m)	Margin (dB)
2484.03	H	46.23	74.00	27.77	44.50	54.00	9.50
2484.26	V	45.86	74.00	28.14	42.56	54.00	11.44

- Note:**
- (1) All Readings are Peak Value (VBW=3MHz) and Average Value (VBW=10Hz).
  - (2) Emission Level= Reading Level+Correct Factor.
  - (3) Correct Factor= Ant\_F + Cab\_L - Preamp
  - (4) Data of measurement within this frequency range shown "--" in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.

Test Model Spurious Emission in Restricted Band 2310-2390MHz  
BLE  
Channel 0: 2402MHz H



Test Model Spurious Emission in Restricted Band 2310-2390MHz  
BLE  
Channel 0: 2402MHz V








■ Spurious Emission below 1GHz (30MHz to 1GHz)


All modes have been tested, and the worst result recorded was report as below:

Test mode: BLE(1M)      Frequency:      Channel 0: 2402MHz



Suspected Data List								
NO.	Freq. [MHz]	Reading [dBµV]	Factor [dB/m]	Level [dBµV/m]	Detector	Limit [dBµV/m]	Margin [dB]	Polarity
1	30.971	33.97	-18.47	15.50	PK	40.00	24.50	Vertical
2	67.8679	31.82	-19.66	12.16	PK	40.00	27.84	Vertical
3	102.822	31.01	-16.95	14.06	PK	43.50	29.44	Vertical
4	164.965	32.17	-19.29	12.88	PK	43.50	30.62	Vertical
5	402.852	32.98	-11.79	21.19	PK	46.00	24.81	Vertical
6	836.876	31.75	-3.94	27.81	PK	46.00	18.19	Vertical







### Suspected Data List

NO.	Freq. [MHz]	Reading [dBµV]	Factor [dB/m]	Level [dBµV/m]	Detector	Limit [dBµV/m]	Margin [dB]	Polarity
1	30.971	35.54	-18.47	17.07	PK	40.00	22.93	Horizontal
2	59.1291	30.91	-18.43	12.48	PK	40.00	27.52	Horizontal
3	110.590	31.09	-17.35	13.74	PK	43.50	29.76	Horizontal
4	248.468	31.06	-15.17	15.89	PK	46.00	30.11	Horizontal
5	375.665	31.48	-12.19	19.29	PK	46.00	26.71	Horizontal
6	914.554	31.01	-2.85	28.16	PK	46.00	17.84	Horizontal

Test mode: BLE(1M)      Frequency:      Channel 19: 2440MHz




Suspected Data List								
NO.	Freq. [MHz]	Reading [dBµV]	Factor [dB/m]	Level [dBµV/m]	Detector	Limit [dBµV/m]	Margin [dB]	Polarity
1	30.971	32.97	-18.47	14.50	PK	40.00	25.50	Vertical
2	49.4194	32.36	-17.25	15.11	PK	40.00	24.89	Vertical
3	105.735	31.29	-17.10	14.19	PK	43.50	29.31	Vertical
4	250.410	32.42	-15.17	17.25	PK	46.00	28.75	Vertical
5	544.614	32.17	-9.22	22.95	PK	46.00	23.05	Vertical
6	901.931	31.31	-2.82	28.49	PK	46.00	17.51	Vertical




Suspected Data List								
NO.	Freq. [MHz]	Reading [dBµV]	Factor [dB/m]	Level [dBµV/m]	Detector	Limit [dBµV/m]	Margin [dB]	Polarity
1	30.971	34.41	-18.47	15.94	PK	40.00	24.06	Horizontal
2	43.5936	32.16	-17.66	14.50	PK	40.00	25.50	Horizontal
3	56.2162	31.30	-18.04	13.26	PK	40.00	26.74	Horizontal
4	214.484	31.34	-17.12	14.22	PK	43.50	29.28	Horizontal
5	394.114	32.51	-11.81	20.70	PK	46.00	25.30	Horizontal
6	892.222	31.53	-2.86	28.67	PK	46.00	17.33	Horizontal

Test mode: BLE(1M)      Frequency:      Channel 39: 2480MHz



Suspected Data List								
NO.	Freq. [MHz]	Reading [dBµV]	Factor [dB/m]	Level [dBµV/m]	Detector	Limit [dBµV/m]	Margin [dB]	Polarity
1	30.971	32.08	-18.47	13.61	PK	40.00	26.39	Vertical
2	42.6226	32.36	-17.73	14.63	PK	40.00	25.37	Vertical
3	90.2002	32.79	-19.12	13.67	PK	43.50	29.83	Vertical
4	181.471	30.63	-18.30	12.33	PK	43.50	31.17	Vertical
5	391.201	32.73	-11.83	20.90	PK	46.00	25.10	Vertical
6	773.763	31.76	-4.87	26.89	PK	46.00	19.11	Vertical



### Suspected Data List

NO.	Freq. [MHz]	Reading [dBµV]	Factor [dB/m]	Level [dBµV/m]	Detector	Limit [dBµV/m]	Margin [dB]	Polarity
1	30.971	35.66	-18.47	17.19	PK	40.00	22.81	Horizontal
2	62.042	33.10	-18.84	14.26	PK	40.00	25.74	Horizontal
3	154.284	32.50	-19.70	12.80	PK	43.50	30.70	Horizontal
4	314.494	31.58	-14.14	17.44	PK	46.00	28.56	Horizontal
5	475.675	32.17	-10.06	22.11	PK	46.00	23.89	Horizontal
6	966.987	31.06	-2.11	28.95	PK	54.00	25.05	Horizontal

## 8.6 CONDUCTED EMISSIONS TEST

### 8.6.1 Applicable Standard

According to FCC Part 15.207(a)

### 8.6.2 Conformance Limit

Frequency(MHz)	Conducted Emission Limit	
	Quasi-peak	Average
0.15-0.5	66-56	56-46
0.5-5.0	56	46
5.0-30.0	60	50

Note: 1. The lower limit shall apply at the transition frequencies  
 2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50MHz.

### 8.6.3 Test Configuration

Test according to clause 7.3 conducted emission test setup


### 8.6.4 Test Procedure

The EUT was placed on a table which is 0.8m above ground plane.  
 Maximum procedure was performed on the highest emissions to ensure EUT compliance.  
 Repeat above procedures until all frequency measured were complete.

### 8.6.5 Test Results

**Pass**


The 120V & 240V voltage have been tested, and the worst result recorded was report as below:



Site Conduction #1 Phase: **L1** Temperature: 21.9

No. Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measurement dBuV	Limit dBuV	Over dB	Detector	Comment
1	0.4400	32.15	9.76	41.91	57.06	-15.15	QP	
2	0.4400	22.85	9.76	32.61	47.06	-14.45	AVG	
3	0.5000	34.06	9.67	43.73	56.00	-12.27	QP	
4	0.5000	23.99	9.67	33.66	46.00	-12.34	AVG	
5	0.9950	32.98	9.85	42.83	56.00	-13.17	QP	
6	0.9950	22.53	9.85	32.38	46.00	-13.62	AVG	
7 *	1.4350	35.19	9.78	44.97	56.00	-11.03	QP	
8	1.4350	22.31	9.78	32.09	46.00	-13.91	AVG	
9	1.9400	34.30	9.71	44.01	56.00	-11.99	QP	
10	1.9400	18.46	9.71	28.17	46.00	-17.83	AVG	
11	12.0050	34.66	9.98	44.64	60.00	-15.36	QP	
12	12.0050	17.65	9.98	27.63	50.00	-22.37	AVG	





Site Conduction #1 Phase: **N** Temperature: 21.9

No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Over dB	Detector	Comment
1		0.4400	33.03	9.76	42.79	57.06	-14.27	QP	
2		0.4400	23.09	9.76	32.85	47.06	-14.21	AVG	
3		0.4950	34.00	9.68	43.68	56.08	-12.40	QP	
4		0.4950	24.09	9.68	33.77	46.08	-12.31	AVG	
5		0.9900	34.17	9.84	44.01	56.00	-11.99	QP	
6		0.9900	23.32	9.84	33.16	46.00	-12.84	AVG	
7	*	1.3700	36.00	9.79	45.79	56.00	-10.21	QP	
8		1.3700	24.32	9.79	34.11	46.00	-11.89	AVG	
9		1.6800	34.90	9.75	44.65	56.00	-11.35	QP	
10		1.6800	22.07	9.75	31.82	46.00	-14.18	AVG	
11		12.1550	34.79	9.99	44.78	60.00	-15.22	QP	
12		12.1550	21.08	9.99	31.07	50.00	-18.93	AVG	

## 8.7 ANTENNA APPLICATION

### 8.7.1 Antenna Requirement

Standard	Requirement
FCC CRF Part 15.203	An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. This requirement does not apply to carrier current devices or to devices operated under the provisions of §15.211, §15.213, §15.217, §15.219, or §15.221. Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with §15.31(d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this part are not exceeded.

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. And according to FCC 47 CFR Section 15.247 (b), if transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

### 8.7.2 Result

#### PASS

The EUT is integrated antenna, the antenna gain is 1.05dBi.

- Antenna use a permanently attached antenna which is not replaceable.
- Not using a standard antenna jack or electrical connector for antenna replacement
- The antenna has to be professionally installed (please provide method of installation)

which in accordance to section 15.203, please refer to the internal photos.

Detail of factor for radiated emission:

Frequency(MHz)	Ant_F(dB)	Cab_L(dB)	Preamp(dB)	Correct Factor(dB)
0.009	20.6	0.03	\	20.63
0.15	20.7	0.1	\	20.8
1	20.9	0.15	\	21.05
10	20.1	0.28	\	20.38
30	18.8	0.45	\	19.25
30	11.7	0.62	27.9	-15.58
100	12.5	1.02	27.8	-14.28
300	12.9	1.91	27.5	-12.69
600	19.2	2.92	27	-4.88
800	21.1	3.54	26.6	-1.96
1000	22.3	4.17	26.2	0.27
1000	25.6	1.76	41.4	-14.04
3000	28.9	3.27	43.2	-11.03
5000	31.1	4.2	44.6	-9.3
8000	36.2	5.95	44.7	-2.55
10000	38.4	6.3	43.9	0.8
12000	38.5	7.14	42.3	3.34
15000	40.2	8.15	41.4	6.95
18000	45.4	9.02	41.3	13.12
18000	37.9	1.81	47.9	-8.19
21000	37.9	1.95	48.7	-8.85
25000	39.3	2.01	42.8	-1.49
28000	39.6	2.16	46.0	-4.24
31000	41.2	2.24	44.5	-1.06
34000	41.5	2.29	46.6	-2.81
37000	43.8	2.30	46.4	-0.3
40000	43.2	2.50	42.2	3.5

--- End of Report ---