

FCC TEST REPORT

FCC ID:2A2SV-CKS31W

Report No. : SSP25010053-2E

Applicant : Shenzhen Coolkit Technology Co., Ltd.

Product Name : CKS3-1-W

Model Name : CKS3-1-W-N16R8

Test Standard : FCC Part 15.247

Date of Issue : 2025-02-19




Shenzhen CCUT Quality Technology Co., Ltd.

1F, Building 35, Changxing Technology Industrial Park, Yutang Street, Guangming District, Shenzhen,
Guangdong, China; (Tel.:+86-755-23406590 website: www.ccuttest.com)

This test report is limited to the above client company and the product model only. It may not be duplicated without prior permitted by Shenzhen CCUT Quality Technology Co., Ltd.

Test Report Basic Information

Applicant:	Shenzhen Coolkit Technology Co., Ltd. B11,2nd Floor,T6 Art Zone,No.6 Tongfa Road,Xili Town,Shenzhen,GuangDong, Address of Applicant.....: China
Manufacturer:	Shenzhen Coolkit Technology Co., Ltd. B11,2nd Floor,T6 Art Zone,No.6 Tongfa Road,Xili Town,Shenzhen,GuangDong, Address of Manufacturer.....: China
Product Name:	CKS3-1-W
Brand Name:	Coolkit
Main Model:	CKS3-1-W-N16R8
Series Models:	See section 1.1 (Page 5)
Test Standard:	FCC Part 15 Subpart C KDB 558074 D01 15.247 Meas Guidance v05r02 ANSI C63.4-2014 ANSI C63.10-2013
Date of Test	2024-12-23 to 2025-01-20
Test Result:	PASS
Tested By	 (Lorzix Luo)
Reviewed By:	 (Lieber Ouyang)
Authorized Signatory:	 (Lahm Peng)
Note : This test report is limited to the above client company and the product model only. It may not be duplicated without prior permitted by Shenzhen CCUT Quality Technology Co., Ltd.. All test data presented in this test report is only applicable to presented test sample.	

CONTENTS

1. General Information	5
1.1 Product Information	5
1.2 Test Setup Information	6
1.3 Compliance Standards	7
1.4 Test Facilities	7
1.5 List of Measurement Instruments	8
1.6 Measurement Uncertainty	9
2. Summary of Test Results	10
3. Antenna Requirement	11
3.1 Standard and Limit	11
3.2 Test Result	11
4. Conducted Emissions	12
4.1 Standard and Limit	12
4.2 Test Procedure	12
4.3 Test Data and Results	13
5. Radiated Emissions	16
5.1 Standard and Limit	16
5.2 Test Procedure	16
5.3 Test Data and Results	18
6. Band-edge Emissions(Radiated)	23
6.1 Standard and Limit	23
6.2 Test Procedure	23
6.3 Test Data and Results	23
7. Maximum Conducted Output Power	25
7.1 Standard and Limit	25
7.2 Test Procedure	25
7.3 Test Data and Results	25
8. Occupied Bandwidth	26
8.1 Standard and Limit	26
8.2 Test Procedure	26
8.3 Test Data and Results	26
9. Maximum Power Spectral Density	31
9.1 Standard and Limit	31
9.2 Test Procedure	31
9.3 Test Data and Results	31
10. Band-edge Emission(Conducted)	36
10.1 Standard and Limit	36
10.2 Test Procedure	36
10.3 Test Data and Results	36
11. Conducted RF Spurious Emissions	42
11.1 Standard and Limit	42
11.2 Test Procedure	42
11.3 Test Data and Results	42

Revision History

Revision	Issue Date	Description	Revised By
V1.0	2025-02-19	Initial Release	Lahm Peng

1. General Information

1.1 Product Information

Product Name:	CKS3-1-W
Trade Name:	Cookit
Main Model:	CKS3-1-W-N16R8
Series Models:	CKS3-1-W-N4、CKS3-1-W-N8、CKS3-1-W-N16、CKS3-1-W-N4R2、 CKS3-1-W-N4R8、CKS3-1-W-N8R2、CKS3-1-W-N8R8、CKS3-1-W-N16R2
Rated Voltage:	3.0V-3.6V
Power Adapter:	N/A
Battery:	N/A
Hardware Version:	CK-ESP32S3-WR-01
Software Version:	N/A
Note 1: The test data is gathered from a production sample, provided by the manufacturer.	
Note 2: The color of appearance and model name of series models listed are different from the main model, but the circuit and the electronic construction are the same, declared by the manufacturer.	

Wireless Specification	
Wireless Standard:	802.11b/g/n
Operating Frequency:	2412MHz ~ 2462MHz for 802.11b/g/n(HT20)/ax(HT20) 2422MHz ~ 2452MHz for 802.11n(HT40)
RF Output Power:	11.72dBm
Number of Channel:	11
Channel Separation:	5MHz
Modulation:	CCK, OFDM, QPSK, BPSK, 16QAM, 64QAM, 1024QAM
Antenna Gain:	0.85dBi
Type of Antenna:	Integral Antenna
Type of Device:	☒ Portable Device ☐ Mobile Device ☒ Modular Device

1.2 Test Setup Information

List of Test Modes			
Test Mode	Description	Remark	
TM1	802.11b	2412MHz/2437MHz/2462MHz	
TM2	802.11g	2412MHz/2437MHz/2462MHz	
TM3	802.11n(H20)	2412MHz/2437MHz/2462MHz	
TM4	802.11n(H40)	2422MHz/2437MHz/2452MHz	
TM5	802.11ax(H20)	2412MHz/2437MHz/2462MHz	
List and Details of Auxiliary Cable			
Description	Length (cm)	Shielded/Unshielded	With/Without Ferrite
-	-	-	-
-	-	-	-
List and Details of Auxiliary Equipment			
Description	Manufacturer	Model	Serial Number
Adapter	EASTSUN	ES005-U120200XYC	ES2017103100047
USB TO TTL	Yeahbot	HW-597	-

List of Channels							
No. of Channel	Frequency (MHz)	No. of Channel	Frequency (MHz)	No. of Channel	Frequency (MHz)	No. of Channel	Frequency (MHz)
01	2412	05	2432	09	2452	13	--
02	2417	06	2437	10	2457	14	--
03	2422	07	2442	11	2462	15	--
04	2427	08	2447	12	--	16	--

1.3 Compliance Standards

Compliance Standards	
FCC Part 15 Subpart C	FEDERAL COMMUNICATIONS COMMISSION, RADIO FREQUENCY DEVICES, Intentional Radiators
All measurements contained in this report were conducted with all above standards	
According to standards for test methodology	
FCC Part 15 Subpart C	FEDERAL COMMUNICATIONS COMMISSION, RADIO FREQUENCY DEVICES, Intentional Radiators
KDB 558074 D01 15.247 Meas Guidance v05r02	GUIDANCE FOR COMPLIANCE MEASUREMENTS ON DIGITAL TRANSMISSION SYSTEM, FREQUENCY HOPPING SPREAD SPECTRUM SYSTEM, AND HYBRID SYSTEM DEVICES OPERATING UNDER SECTION 15.247 OF THE FCC RULES
ANSI C63.4-2014	American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the range of 9 kHz to 40 GHz.
ANSI C63.10-2013	American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices
Maintenance of compliance is the responsibility of the manufacturer or applicant. Any modification of the product, which result is lowering the emission, should be checked to ensure compliance has been maintained.	

1.4 Test Facilities

Laboratory Name:	Shenzhen CCUT Quality Technology Co., Ltd. 1F, Building 35, Changxing Technology Industrial Park, Yutang Street, Guangming District, Shenzhen, Guangdong, China
CNAS Laboratory No.:	L18863
A2LA Certificate No.:	6893.01
FCC Registration No:	583813
ISED Registration No.:	CN0164
All measurement facilities used to collect the measurement data are located at 1F, Building 35, Changxing Technology Industrial Park, Yutang Street, Guangming District, Shenzhen, Guangdong, China.	

1.5 List of Measurement Instruments

Description	Manufacturer	Model	Serial Number	Cal. Date	Due. Date
Conducted Emissions					
AMN	ROHDE&SCHWARZ	ENV216	101097	2024-08-07	2025-08-06
EMI Test Receiver	ROHDE&SCHWARZ	ESPI	100242	2024-08-07	2025-08-06
Test Cable	N/A	Cable 5	N/A	2024-08-07	2025-08-06
EMI Test Software	FARA	EZ-EMC	EMEC-3A1+	N/A	N/A
Radiated Emissions					
EMI Test Receiver	ROHDE&SCHWARZ	ESPI	100154	2024-08-07	2025-08-06
Spectrum Analyzer	KEYSIGHT	N9020A	MY48030972	2024-08-07	2025-08-06
Spectrum Analyzer	ROHDE&SCHWARZ	FSV40-N	101692	2024-08-07	2025-08-06
Amplifier	SCHWARZBECK	BBV 9743B	00251	2024-08-07	2025-08-06
Amplifier	HUABO	YXL0518-2.5-45	--	2024-08-07	2025-08-06
Amplifier	COM-MW	DLAN-18G-4G-02	10229104	2024-08-07	2025-08-06
Loop Antenna	DAZE	ZN30900C	21104	2024-08-03	2025-08-02
Broadband Antenna	SCHWARZBECK	VULB 9168	01320	2024-08-03	2025-08-02
Horn Antenna	SCHWARZBECK	BBHA 9120D	02553	2024-08-03	2025-08-02
Horn Antenna	COM-MW	ZLB7-18-40G-950	12221225	2024-08-03	2025-08-02
Attenuator	QUANJUDA	6dB	220731	2024-08-07	2025-08-06
Test Cable	N/A	Cable 1	N/A	2024-08-07	2025-08-06
Test Cable	N/A	Cable 2	N/A	2024-08-07	2025-08-06
Test Cable	N/A	Cable 3	N/A	2024-08-07	2025-08-06
Test Cable	N/A	Cable 4	N/A	2024-08-07	2025-08-06
Test Cable	N/A	Cable 8	N/A	2024-08-07	2025-08-06
Test Cable	N/A	Cable 9	N/A	2024-08-07	2025-08-06
EMI Test Software	FARA	EZ-EMC	FA-03A2 RE+	N/A	N/A
Conducted RF Testing					
RF Test System	MWRFTTest	MW100-RFCB	220418SQS-37	2024-08-07	2025-08-06
Spectrum Analyzer	KEYSIGHT	N9020A	ATO-90521	2024-08-07	2025-08-06
RF Test Software	MWRFTTest	MTS 8310	N/A	N/A	N/A

1.6 Measurement Uncertainty

Test Item	Conditions	Uncertainty
Conducted Emissions	9kHz ~ 30MHz	±1.64 dB
Radiated Emissions	9kHz ~ 30MHz	±2.88 dB
	30MHz ~ 1GHz	±3.32 dB
	1GHz ~ 18GHz	±3.50 dB
	18GHz ~ 40GHz	±3.66 dB
Conducted Output Power	9kHz ~ 26GHz	±0.50 dB
Occupied Bandwidth	9kHz ~ 26GHz	±4.0 %
Conducted Spurious Emission	9kHz ~ 26GHz	±1.32 dB
Power Spectrum Density	9kHz ~ 26GHz	±0.62 dB

2. Summary of Test Results

FCC Rule	Description of Test Item	Result
FCC Part 15.203	Antenna Requirement	Passed
FCC Part 15.247(i)	RF Exposure(see the RF exposure report)	Passed
FCC Part 15.207	Conducted Emissions	Passed
FCC Part 15.209, 15.247(d)	Radiated Emissions	Passed
FCC Part 15.247(d)	Band-edge Emissions(Radiated)	Passed
FCC Part 15.247(b)(3)	Maximum Peak conducted output power	Passed
FCC Part 15.247(a)(2)	Occupied Bandwidth	Passed
FCC Part 15.247(e)	Maximum Power Spectral Density	Passed
FCC Part 15.247(d)	Band-edge Emissions(Conducted)	Passed
FCC Part 15.247(d)	Conducted RF Spurious Emissions	Passed
Passed: The EUT complies with the essential requirements in the standard Failed: The EUT does not comply with the essential requirements in the standard N/A: Not applicable		

3. Antenna Requirement

3.1 Standard and Limit

According to FCC Part 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.

3.2 Test Result

This product has an integral antenna, fulfill the requirement of this section.

4. Conducted Emissions

4.1 Standard and Limit


According to the rule FCC Part 15.207, Conducted emissions limit, the limit for a wireless device as below:

Frequency of Emission (MHz)	Conducted emissions (dBuV)	
	Quasi-peak	Average
0.15-0.5	66 to 56	56 to 46
0.5-5	56	46
5-30	60	50

Note 1: Decreases with the logarithm of the frequency in the range 0.15 MHz to 0.5 MHz
 Note 2: The lower limit applies at the band edges

4.2 Test Procedure

Test is conducting under the description of ANSI C63.10 - 2013 section 6.2.



Test Setup Block Diagram

a) The EUT was configured for testing in a typical fashion (as a customer would normally use it). The EUT has been programmed to continuously transmit during test. This operating condition was tested and used to collect the included data.

b) The following is the setting of the receiver

Attenuation: 10dB

Start Frequency: 0.15MHz

Stop Frequency: 30MHz

IF Bandwidth: 9kHz

c) The EUT was placed 0.8 meters from the horizontal ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipment powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.

- d) Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
- e) I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
- f) LISN is at least 80 cm from nearest part of EUT chassis.
- g) For the actual test configuration, please refer to the related Item - photographs of the test setup.

4.3 Test Data and Results

Based on all tested data, the EUT complied with the FCC Part 15.207 standard limit for a wireless device, and with the worst case as below:

Remark: Level = Reading + Factor, Margin = Level - Limit


Test Plots and Data of Conducted Emissions

Tested Mode: TM1

Test Voltage: AC 120V/60Hz

Test Power Line: Neutral

Remark:



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector	P/F	Remark
1	0.2670	23.37	9.33	32.70	61.21	-28.51	QP	P	
2	0.2670	12.11	9.33	21.44	51.21	-29.77	AVG	P	
3 *	0.8430	27.12	9.40	36.52	56.00	-19.48	QP	P	
4	0.8430	14.01	9.40	23.41	46.00	-22.59	AVG	P	
5	2.0625	17.62	9.47	27.09	56.00	-28.91	QP	P	
6	2.0625	5.79	9.47	15.26	46.00	-30.74	AVG	P	
7	4.9920	12.03	9.57	21.60	56.00	-34.40	QP	P	
8	4.9920	-0.27	9.57	9.30	46.00	-36.70	AVG	P	
9	14.1405	9.87	9.53	19.40	60.00	-40.60	QP	P	
10	14.1405	-1.17	9.53	8.36	50.00	-41.64	AVG	P	
11	21.2280	9.61	10.00	19.61	60.00	-40.39	QP	P	
12	21.2280	-2.02	10.00	7.98	50.00	-42.02	AVG	P	


Test Plots and Data of Conducted Emissions

Tested Mode: TM1

Test Voltage: AC 120V/60Hz

Test Power Line: Live

Remark:



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector	P/F	Remark
1	0.2580	23.41	9.51	32.92	61.50	-28.58	QP	P	
2	0.2580	12.59	9.51	22.10	51.50	-29.40	AVG	P	
3	0.7440	21.73	9.59	31.32	56.00	-24.68	QP	P	
4	0.7440	10.60	9.59	20.19	46.00	-25.81	AVG	P	
5 *	1.3110	22.83	9.63	32.46	56.00	-23.54	QP	P	
6	1.3110	11.32	9.63	20.95	46.00	-25.05	AVG	P	
7	2.6700	13.49	9.68	23.17	56.00	-32.83	QP	P	
8	2.6700	1.83	9.68	11.51	46.00	-34.49	AVG	P	
9	5.8515	10.20	9.76	19.96	60.00	-40.04	QP	P	
10	5.8515	-1.74	9.76	8.02	50.00	-41.98	AVG	P	
11	13.5870	14.52	9.73	24.25	60.00	-35.75	QP	P	
12	13.5870	-2.29	9.73	7.44	50.00	-42.56	AVG	P	

5. Radiated Emissions

5.1 Standard and Limit

According to §15.247(d), In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in § 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in § 15.205(a), must also comply with the radiated emission limits specified in § 15.209(a) (see § 15.205(c)).

According to the rule FCC Part 15.209, Radiated emission limit for a wireless device as below:


Frequency of Emission (MHz)	Field Strength (micorvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(kHz)	300
0.490~1.705	24000/F(kHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3
Note: The more stringent limit applies at transition frequencies.		

The emission limit in this paragraph is based on measurement instrumentation employing an average detector. The provisions in §15.35 for limiting peak emissions apply. Spurious Radiated Emissions measurements starting below or at the lowest crystal frequency.


Note: Spurious Radiated Emissions measurements starting below or at the lowest crystal frequency.

5.2 Test Procedure


Test is conducting under the description of ANSI C63.10 - 2013 section 6.3 to 6.6.



Block Diagram of Radiated Emission Below 30MHz



Block Diagram of Radiated Emission From 30MHz to 1GHz



Block Diagram of Radiated Emission Above 1GHz

- a) The EUT is placed on a turntable, which is 0.8m above ground plane for test frequency range below 1GHz, and 1.5m above ground plane for test frequency range above 1GHz.
- b) EUT is set 3m away from the receiving antenna, which is varied from 1m to 4m to find out the highest emissions.
- c) Use the following spectrum analyzer settings:
Span = wide enough to fully capture the emission being measured
RBW = 1 MHz for $f \geq 1\text{GHz}$, 100 kHz for $f < 1\text{GHz}$, 10kHz for $f < 30\text{MHz}$
VBW $\geq$ RBW, Sweep = auto
Detector function = peak
Trace = max hold
- d) Follow the guidelines in ANSI C63.4-2014 with respect to maximizing the emission by rotating the EUT, adjusting the measurement antenna height and polarization, etc. The peak reading of the emission, after being corrected by the antenna factor, cable loss, pre-amp gain, etc., is the peak field strength, submit this data. Each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
- e) The peak level, once corrected, must comply with the limit specified in Section 15.209. Set the RBW = 1MHz, VBW = 10Hz, Detector = PK for AV value, while maintaining all of the other instrument settings.
- f) For the actual test configuration, please refer to the related item - EUT test photos.

5.3 Test Data and Results

Based on all tested data, the EUT complied with the FCC Part 15.247 standard limit for a wireless device, and with the worst case as below:


Remark: Level = Reading + Factor, Margin = Level - Limit

Radiated Emission Test Data (30MHz to 1GHz)

Tested Mode: TM1

Test Antenna Polarization: Horizontal

Remark:




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg.)	P/F	Remark
1	119.8555	42.92	-9.76	33.16	43.50	-10.34	QP	100	224	P	
2	179.3863	46.53	-10.44	36.09	43.50	-7.41	QP	100	234	P	
3 *	215.2675	51.61	-11.87	39.74	43.50	-3.76	QP	100	324	P	
4 !	319.9370	47.60	-7.27	40.33	46.00	-5.67	QP	100	231	P	
5 !	373.3110	47.70	-6.51	41.19	46.00	-4.81	QP	100	213	P	
6	694.4174	38.57	0.15	38.72	46.00	-7.28	QP	100	56	P	

Radiated Emission Test Data (30MHz to 1GHz)

Tested Mode: TM1

Test Antenna Polarization: Vertical

Remark:



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg.)	P/F	Remark
1	61.5617	40.79	-10.22	30.57	40.00	-9.43	QP	100	245	P	
2	143.3260	38.45	-8.06	30.39	43.50	-13.11	QP	100	351	P	
3	165.4866	36.88	-8.37	28.51	43.50	-14.99	QP	100	51	P	
4	210.7860	40.22	-11.90	28.32	43.50	-15.18	QP	100	124	P	
5	323.3201	44.11	-7.13	36.98	46.00	-9.02	QP	100	214	P	
6 *	361.7137	45.31	-6.95	38.36	46.00	-7.64	QP	100	123	P	

Radiated Emission Test Data (Above 1GHz)							
Frequency	Reading	Correct	Result	Limit	Margin	Polar	Detector
MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	H/V	PK/AV
Lowest Channel (2412MHz)							
Horizontal							
2400	49.55	-14.09	35.46	74	-38.54	H	PK
2400	41.56	-14.09	27.47	54	-26.53	H	AV
2810	45.42	-11.99	33.43	74	-40.57	H	PK
2840	40.39	-11.86	28.53	54	-25.47	H	AV
3535	46.57	-10.06	36.51	74	-37.49	H	PK
3595	38.57	-9.78	28.79	54	-25.21	H	AV
4330	45.44	-7.48	37.96	74	-36.04	H	PK
4365	40.37	-7.42	32.95	54	-21.05	H	AV
Vertical							
1700	40.72	-17.53	23.19	54	-30.81	V	AV
1750	47.77	-17.47	30.3	74	-43.7	V	PK
2480	54.43	-13.69	40.74	74	-33.26	V	PK
2480	45.88	-13.69	32.19	54	-21.81	V	AV
2965	46.95	-11.26	35.69	74	-38.31	V	PK
2980	40.33	-11.19	29.14	54	-24.86	V	AV
3870	47.05	-8.75	38.3	74	-35.7	V	PK
3930	39.61	-8.49	31.12	54	-22.88	V	AV
Middle Channel (2437MHz)							
Horizontal							
2435	52.93	-13.92	39.01	74	-34.99	H	PK
2435	48.05	-13.92	34.13	54	-19.87	H	AV
2815	39.75	-11.97	27.78	54	-26.22	H	AV
2860	45.48	-11.77	33.71	74	-40.29	H	PK
3255	47.02	-10.5	36.52	74	-37.48	H	PK
3260	37.71	-10.5	27.21	54	-26.79	H	AV
4075	37.97	-8.01	29.96	54	-24.04	H	AV
4110	46.03	-7.92	38.11	74	-35.89	H	PK
Vertical							
2175	46.27	-14.85	31.42	74	-42.58	V	PK
2185	41.14	-14.78	26.36	54	-27.64	V	AV
2435	46.79	-13.92	32.87	54	-21.13	V	AV
2440	51.43	-13.89	37.54	74	-36.46	V	PK
3115	45.68	-10.8	34.88	74	-39.12	V	PK
3175	37.73	-10.65	27.08	54	-26.92	V	AV

3905	45.62	-8.59	37.03	74	-36.97	V	PK
3940	40.73	-8.45	32.28	54	-21.72	V	AV
Highest Channel (2462MHz)							
Horizontal							
1910	40.3	-16.63	23.67	54	-30.33	H	AV
1930	47.45	-16.48	30.97	74	-43.03	H	PK
2460	50.32	-13.79	36.53	74	-37.47	H	PK
2460	45.95	-13.79	32.16	54	-21.84	H	AV
3190	45.62	-10.61	35.01	74	-38.99	H	PK
3220	39.37	-10.53	28.84	54	-25.16	H	AV
3635	45.58	-9.65	35.93	74	-38.07	H	PK
3680	39.66	-9.51	30.15	54	-23.85	H	AV
Vertical							
1945	40.78	-16.37	24.41	54	-29.59	V	AV
1980	47.6	-16.12	31.48	74	-42.52	V	PK
2425	58.36	-13.97	44.39	74	-29.61	V	PK
2425	48.74	-13.97	34.77	54	-19.23	V	AV
3285	47.29	-10.49	36.8	74	-37.2	V	PK
3340	40.4	-10.48	29.92	54	-24.08	V	AV
3640	46.74	-9.64	37.1	74	-36.9	V	PK
3640	40.68	-9.64	31.04	54	-22.96	V	AV

Note 1: this EUT was tested in 3 orthogonal positions and the worst case position data was reported.

Note 2: Testing is carried out with frequency rang 9kHz to the tenth harmonics. The measurements greater than 20dB below the limit from 9kHz to 30MHz.

Note 3: Other emissions are attenuated 20dB below the limits from 9kHz to 30MHz, so it does not recorded report, 18GHz-26GHz not recorded for no spurious point have a margin of less than 6 dB with respect to the limits.


6. Band-edge Emissions(Radiated)

6.1 Standard and Limit

According to §15.247(d), In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in § 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in § 15.205(a), must also comply with the radiated emission limits specified in § 15.209(a) (see § 15.205(c)).

6.2 Test Procedure

Test is conducting under the description of ANSI C63.10 - 2013 section 6.3 to 6.6 and section 6.10.



Test Setup Block Diagram

As the radiated emissions testing, set the Lowest and Highest Transmitting Channel, observed the outside band of 2310MHz to 2400MHz and 2483.5MHz to 2500MHz, than mark the higher-level emission for comparing with the FCC rules.

6.3 Test Data and Results

Based on all tested data, the EUT complied with the FCC Part 15.247 standard limit, and with the worst case as below:

Test Mode	Frequency	Limit	Result
	MHz	dBuV/m	
Lowest	2310.00	<54 dBuV/m	Pass
	2390.00	<54 dBuV/m	Pass
Highest	2483.50	<54 dBuV/m	Pass
	2500.00	<54 dBuV/m	Pass

Radiated Emission Test Data (Band edge emissions)							
Frequency	Reading	Correct	Result	Limit	Margin	Polar	Detector
MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	H/V	PK/AV
Lowest Channel (802.11b_2412MHz)							
2310	64.84	-21.34	43.5	74	-30.5	H	PK
2310	51.93	-21.34	30.59	54	-23.41	H	AV
2390	68.72	-20.96	47.76	74	-26.24	H	PK
2390	50.58	-20.96	29.62	54	-24.38	H	AV
2400	71.42	-20.91	50.51	74	-23.49	H	PK
2400	56.88	-20.91	35.97	54	-18.03	H	AV
2310	67.37	-21.34	46.03	74	-27.97	V	PK
2310	52.6	-21.34	31.26	54	-22.74	V	AV
2390	66.21	-20.96	45.25	74	-28.75	V	PK
2390	50.37	-20.96	29.41	54	-24.59	V	AV
2400	68.57	-20.91	47.66	74	-26.34	V	PK
2400	55.44	-20.91	34.53	54	-19.47	V	AV
Highest Channel (802.11b_2462MHz)							
2483.50	67.22	-20.51	46.71	74	-27.29	H	PK
2483.50	52.17	-20.51	31.66	54	-22.34	H	AV
2500	64.65	-20.43	44.22	74	-29.78	H	PK
2500	52.44	-20.43	32.01	54	-21.99	H	AV
2483.50	70.62	-20.51	50.11	74	-23.89	V	PK
2483.50	55.11	-20.51	34.6	54	-19.4	V	AV
2500	67.99	-20.43	47.56	74	-26.44	V	PK
2500	51.3	-20.43	30.87	54	-23.13	V	AV

Remark: Level = Reading + Factor, Margin = Level - Limit


7. Maximum Peak conducted output power

7.1 Standard and Limit

The Maximum Peak Output Power Measurement is 30dBm.

7.2 Test Procedure

Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the Power Meter.



Test Setup Block Diagram

7.3 Test Data and Results

Test Mode	Test Channel MHz	Peak Conducted Power (dBm)	Limit (dBm)	Test Result
802.11b	2412	7.57	30	Pass
	2437	7.96	30	Pass
	2462	6.7	30	Pass
802.11g	2412	6.94	30	Pass
	2437	7.26	30	Pass
	2462	7.82	30	Pass
802.11n(HT20)	2412	7.55	30	Pass
	2437	7.7	30	Pass
	2462	7.48	30	Pass
802.11n(HT40)	2422	7.34	30	Pass
	2437	7.68	30	Pass
	2452	7.2	30	Pass
802.11ax(HT40)	2412	6.98	30	Pass
	2437	7.76	30	Pass
	2462	7.52	30	Pass


8. DTS Bandwidth

8.1 Standard and Limit

According to 15.247(a)(2), Systems using digital modulation techniques may operate in the 902–928 MHz, 2400–2483.5 MHz, and 5725–5850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.

8.2 Test Procedure

The transmitter output was connected to the spectrum analyzer through an attenuator. The bandwidth of the fundamental frequency was measured by spectrum analyzer with 100 KHz RBW and 300 KHz VBW. The 6dB bandwidth is defined as the total spectrum the power of which is higher than peak power minus 6dB. Measured the 6dB bandwidth by related function of the spectrum analyzer.



Test Setup Block Diagram

8.3 Test Data and Results

Test Mode	Test Channel (MHz)	6dB Bandwidth (MHz)	Limit (MHz)	Test Result
802.11b	2412	9.075	0.5	Pass
	2437	9.068	0.5	Pass
	2462	9.082	0.5	Pass
802.11g	2412	16.282	0.5	Pass
	2437	15.899	0.5	Pass
	2462	16.013	0.5	Pass
802.11n(HT20)	2412	17.618	0.5	Pass
	2437	17.607	0.5	Pass
	2462	17.578	0.5	Pass
802.11n(HT40)	2422	35.059	0.5	Pass
	2437	35.075	0.5	Pass
	2452	35.14	0.5	Pass
802.11ax(HT20)	2412	17.888	0.5	Pass
	2437	18.623	0.5	Pass
	2462	17.772	0.5	Pass

802.11b

2412MHz



802.11g

2412MHz



2437MHz



2437MHz



2462MHz



2462MHz




802.11n(HT20)

2412MHz



802.11n(HT40)


2422MHz



2437MHz




2437MHz



2462MHz




2452MHz




802.11ax(HT20)

2412MHz



2437MHz



2462MHz




9. Maximum Power Spectral Density

9.1 Standard and Limit

According to FCC 15.247(e), For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8dBm in any 3 kHz band during any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of paragraph (b) of this section. The same method of determining the conducted output power shall be used to determine the power spectral density.

9.2 Test Procedure

- 1) Remove the antenna from the EUT and connect to the spectrum analyzer via a low loss RF cable.
- 2) Set the spectrum analyzer to any one measured frequency within its operating range.
- 3) Set RBW = 100kHz, VBW = 300kHz, Sweep = Auto, Detector = RMS.
- 4) Measure the highest amplitude appearing on spectral display and mark the value.
- 5) Repeat above procedures until all frequencies measured were complete.



Test Setup Block Diagram

9.3 Test Data and Results

Test Mode	Test Channel MHz	Power Spectral Density (dBm/100kHz)	Limit (dBm/3kHz)	Test Result
802.11b	2412	-0.38	8	Pass
	2437	-1.76	8	Pass
	2462	-0.9	8	Pass
802.11g	2412	-5.99	8	Pass
	2437	-7.86	8	Pass
	2462	-7.14	8	Pass
802.11n(HT20)	2412	-5.22	8	Pass
	2437	-5.78	8	Pass
	2462	-5.55	8	Pass
802.11n(HT40)	2422	-8.6	8	Pass
	2437	-8.85	8	Pass
	2452	-8.78	8	Pass
802.11ax(HT20)	2412	-7.25	8	Pass
	2437	-9.31	8	Pass
	2462	-7.88	8	Pass


802.11b

2412MHz



802.11g


2412MHz




2437MHz




2437MHz



2462MHz




2462MHz




802.11n(HT20)

2412MHz




802.11n(HT40)


2422MHz




2437MHz




2437MHz



2462MHz




2452MHz




802.11ax(HT20)


2412MHz



2437MHz



2462MHz



10. Band-edge Emission(Conducted)

10.1 Standard and Limit

According to §15.247(d), In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in § 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in § 15.205(a), must also comply with the radiated emission limits specified in § 15.209(a) (see § 15.205(c)).

10.2 Test Procedure

Test is conducting under the description of ANSI C63.10 - 2013 section 6.10.

- 1) Remove the antenna from the EUT and connect to the spectrum analyzer via a low loss RF cable.
- 2) Set the spectrum analyzer to any one measured frequency within its operating range.
- 3) Set RBW = 100kHz, VBW = 300kHz, Sweep = Auto, Detector = Peak.
- 4) Measure the highest amplitude appearing on spectral display and set it as a reference level.
- 5) Set a convenient frequency span including 100 kHz bandwidth from band edge.
- 6) Measure the emission and marking the edge frequency.
- 7) Repeat above procedures until all frequencies measured were complete.



Test Setup Block Diagram

10.3 Test Data and Results


Test Mode	Band-edge	Test Channel (MHz)	Max. Value (dBc)	Limit (dBc)	Test Result
802.11b	Lowest	2412	-51.86	-20	Pass
	Highest	2462	-52.97	-20	Pass
802.11g	Lowest	2412	-36.54	-20	Pass
	Highest	2462	-48.5	-20	Pass
802.11n(HT20)	Lowest	2412	-39.81	-20	Pass
	Highest	2462	-49.75	-20	Pass
802.11n(HT40)	Lowest	2422	-37.33	-20	Pass
	Highest	2452	-45.83	-20	Pass
802.11ax(HT20)	Lowest	2412	-37.95	-20	Pass
	Highest	2462	-46.79	-20	Pass

802.11b Lowest

Reference Power



Band-edge Emission




802.11b Highest

Reference Power



Band-edge Emission




802.11g Lowest

Reference Power




Band-edge Emission




802.11g Highest

Reference Power




Band-edge Emission




802.11n(HT20) Lowest

Reference Power




Band-edge Emission



802.11n(HT20) Highest

Reference Power



Band-edge Emission

