

FCC RF Test Report

For

System Monitoring Tablet

Model Number : K1002C-POE-K001
FCC ID : 2A2UHK1002C-POE
Date of Receipt : Septemebr 29, 2021
Date of Report : November 19, 2021

Prepared for

Rivertech Co., Ltd.

5F., No. 34, Songde Rd., Xinyi dist., Taipei city Taiwan(R.O.C)

Prepared by



Central Research Technology Co.

11, Lane 41, Fushuen St., Jungshan Chiu, Taipei 104, Taiwan



This report shall not be reproduced, except in full, without written approval of Central Research Technology Co.. It may be duplicated completely in its entirety for legal use with the permission of the applicant. The test result in this report is based on the information provided by manufacturer and applies only to the sample tested.

Verification of Compliance

Equipment under Test : System Monitoring Tablet
Model No. : K1002C-POE-K001
FCC ID : 2A2UHK1002C-POE
Applicant : Rivertech Co., Ltd.
Address : 5F., No. 34, Songde Rd., Xinyi dist., Taipei city Taiwan(R.O.C)
Applicable Standards : 47 CFR part 15, Subpart C
ANSI C63.10:2013
Date of Testing : October 13 ~ November 9, 2021
Deviation : The method, configuration and arrangement of the tests are following the requirement of customer and the applicable standards cited above.
Condition of Test Sample : Mass Production



We, **Central Research Technology Co.**, hereby certify that one sample of the designated product was tested in our facility during the period mentioned above. The test records, data evaluation and Equipment Under Test (EUT) configurations shown in the present report are true and accurate representation of the measurements of the sample's RF characteristics under the conditions herein specified.

The test results show that the EUT as described in the present report is in compliance with the requirements set forth in the standards mentioned above and apply to the tested sample identified in the present report only. The test report shall not be reproduced, except in its entirety, without the written approval of Central Research Technology Co.

PREPARED BY

:

Cathy Chen
(Cathy Chen/ Technical Manager)

, DATE :

November 19, 2021

APPROVED BY

:

Sam Chien
(Sam Chien /General Manager)

, DATE :

November 19, 2021

Contents

1	General Description	5
1.1	General Description of EUT	5
1.2	Applied standards	7
1.3	Test result	11
1.4	The Support Units	12
1.5	Layout of Setup	13
1.6	Test Instruments	14
1.7	Test Capability	17
1.8	Measurement Uncertainty	19
2	6dB Bandwidth	20
2.1	Applied standard	20
2.2	Measurement Procedure	20
2.3	Test configuration	20
2.4	Test Data	21
3	Maximum Peak Output Power	23
3.1	Applied standard	23
3.2	Measurement Procedure	23
3.3	Test configuration	23
3.4	Test Data	24
4	Power Spectral Density	26
4.1	Applied standard	26
4.2	Measurement Procedure	26
4.3	Test configuration	26
4.4	Test Data	27
5	Conducted Spurious emission	29
5.1	Applied standard	29
5.2	Measurement Procedure	29
5.3	Test configuration	29
5.4	Test Data	30
6	Radiated Spurious Emission.....	34
6.1	Applied standard	34
6.2	Measurement Procedure	35
6.3	Test configuration	36

6.4	Test Data	38
7	Line Conducted Emission Measurement	50
7.1	Limits for Emission Measurement	50
7.2	Test Procedures	錯誤! 尚未定義書籤。
7.3	Test Configurations	52
7.4	Test Data	53
Attachment 1 – Photographs of the Test Configuration		
Attachment 2 –External Photographs of EUT		
Attachment 3 –Internal Photographs of EUT		

1 General Description

1.1 General Description of EUT

Equipment under Test : System Monitoring Tablet
 Model No. : K1002C-POE-K001
 Power in : 120 Vac/60 Hz
 Frequency Range : 2402 MHz - 2480 MHz
 Modular Function : GFSK
 Channel No. : 40
 Antenna Spec : Brand/Mode No.: South Star/ SMB-K1002
 Type: FPCB Antenna
 Antenna Gain : 2.76dBi

Channel List:

Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
0	2402	10	2422	20	2442	30	2462
1	2404	11	2424	21	2444	31	2464
2	2406	12	2426	22	2446	32	2466
3	2408	13	2428	23	2448	33	2468
4	2410	14	2430	24	2450	34	2470
5	2412	15	2432	25	2452	35	2472
6	2414	16	2434	26	2454	36	2474
7	2416	17	2436	27	2456	37	2476
8	2418	18	2438	28	2458	38	2478
9	2420	19	2440	29	2460	39	2480

Test Mode

Test item	Operation Frequency
Conducted power test/ Radiated emission above 1 GHz	CH 0, CH 19, CH 39
Radiated emission below 1 GHz	Normal mode
Power line conducted emission	Normal mode

EUT Test step:

1. EUT turn on the power.
2. Enter engineer mode.
3. Adjust test mode, channel, setting power.
4. Press start testing.
5. EUT run test program and transmit signal.

1.2 Applied standards

(1) 6 dB Bandwidth

According to FCC 15.247(a)(2), the minimum 6 dB bandwidth shall be at least 500 kHz.

(2) Maximun Peak Output Power

According to FCC 15.247(b)(3), for systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: 1 Watt.

According to FCC 15.247(b) (4), the conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

(3) Conducted emission measurements

According to FCC 15.247(d), in any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph FCC 15.247(b)(3), the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in FCC 15.209(a) is not required. Radiated emissions which fall in the restricted bands, as defined in FCC 15.205(a), must also comply with the radiated emission limits specified in FCC 15.209(a).

(4) Power Spectral Density

According to FCC 15.247(e), for digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

(5) Radiated emission measurements

For intentional device, according to FCC 15.209, the general requirement of field strength of radiated emissions from intentional radiator at a distance of 3 meters shall not exceed the below table.

Frequency (MHz)	Measurement Distance (m)	Field Strength (uV/m)	Field Strength (dBuV/m)
0.009-0.490	300	2400/F(kHz)	
0.490-1.705	30	24000/F(kHz)	
1.705-30.0	3	30	29.5
30 – 88	3	100	40.0
88 – 216	3	150	43.5
216 – 960	3	200	46.0
above 1610	3	500	54.0

Note1 : At frequencies at or above 30 MHz, measurements may be performed at a distance other than what is specified provided: measurements are not made in the near field except where it can be shown that near field measurements are appropriate due to the characteristics of the device; and it can be demonstrated that the signal levels needed to be measured at the distance employed can be detected by the measurement equipment. When performing measurements at a distance other than that specified, the results shall be extrapolated to the specified distance using an extrapolation factor of 20 dB/decade (inverse linear-distance for field strength measurements; inverse-linear-distance-squared for power density measurements).

Note 2: At frequencies below 30 MHz, measurements may be performed at a distance closer than that specified in the regulations; however, an attempt should be made to avoid making measurements in the near field. Pending the development of an appropriate measurement procedure for measurements performed below 30 MHz, when performing measurements at a closer distance than specified, the results shall be extrapolated to the specified distance by either making measurements at a minimum of two distances on at least one radial to determine the proper extrapolation factor or by using the square of an inverse linear distance extrapolation factor (40 dB/decade)

(6) Conduction Emission Requirement

For intentional device, according to FCC 15.207(a), line conduction emission limit is as below table.

Frequency of Emission (MHz)	Conducted Limit (dBuV)	
	Quasi-peak	Average
0.15 – 0.5	66 to 56*	56 to 46*
0.5 - 5	56	46
5 - 30	60	50

* Decreases with the logarithm of the frequency.

(7) Restricted Band

Frequency (MHz)	Frequency (MHz)	Frequency (MHz)	Frequency (GHz)
0.090 - 0.110	16.42 - 16.423	399.9 - 410	4.5 - 5.15
¹ 0.495 - 0.505	16.69475 - 16.69525	608 - 614	5.35 - 5.46
2.1735 - 2.1905	16.80425 - 16.80475	960 - 1240	7.25 - 7.75
4.125 - 4.128	25.5 - 25.67	1300 - 1427	8.025 - 8.5
4.17725 - 4.17775	37.5 - 38.25	1435 - 1626.5	9.0 - 9.2
4.20725 - 4.20775	73 - 74.6	1645.5 - 1646.5	9.3 - 9.5
6.215 - 6.218	74.8 - 75.2	1660 - 1710	10.6 - 12.7
6.26775 - 6.26825	108 - 121.94	1718.8 - 1722.2	13.25 - 13.4
6.31175 - 6.31225	123 - 138	2200 - 2300	14.47 - 14.5
8.291 - 8.294	149.9 - 150.05	2310 - 2390	15.35 - 16.2
8.362 - 8.366	156.52475 - 156.52525	2483.5 - 2500	17.7 - 21.4
8.37625 - 8.38675	156.7 - 156.9	2690 - 2900	22.01 - 23.12
8.41425 - 8.41475	162.0125 - 167.17	3260 - 3267	23.6 - 24.0
12.29 - 12.293	167.72 - 173.2	3332 - 3339	31.2 - 31.8
12.51975 - 12.52025	240 - 285	3345.8 - 3358	36.43 - 36.5
12.57675 - 12.57725	322 - 335.4	3600 - 4400	(2)
13.36 - 13.41			

¹ Until February 1, 1999, this restricted band shall be 0.490-0.510 MHz.

² Above 38.6

1.3 Test result

Test Item	FCC standard section	Report section	Test result
6 dB bandwidth	FCC 15.247(a)(2)	2	PASS
Maximun Peak Output Power	FCC 15.247(b)(3)	3	PASS
Power Spectral Density	FCC 15.247(e)	4	PASS
Conducted spurious emission	FCC 15.247(d)	5	PASS
Radiated spurious emission	FCC 15.209	6	PASS
Power line conducted	FCC 15.207(a)	7	PASS


According to ANSI C63.10, determining compliance is based on the results of the compliance measurement, not taking into account measurement instrumentation uncertainty.

1.4 The Support Units


No.	Unit	Model No.	Trade Name	Power Code	Supported by lab.
1.	Adaptor	ICP30-120-2500	Cullpower		
2.	BT Speaker	XMYX03YM	Mi		√
3	Wireless Router	RT-AC51U	ASUS		√

1.5 Layout of Setup

Normal mode



Other Test



Connecting Cables :

No.	Cable	Length	Shielded	Core	Shielded Backshell	Supported by lab.	Note
A	Micro USB cable	0.35m	✓				
B	Power cable	1.2m		✓			

1.6 Test Instruments

Conducted Emission Test

Test Site and Equipment	Manufacturer	Model No. /Serial No.	Last Calibration Date	Calibration Due Date
Spectrum Alayzer	R&S	FSV40/ 101609	2021/10/18	2022/10/18
RFcable	JMCA	MWX/ C0150~C0153, C0161~C0163	2020/12/3	2021/12/3
Test software	R&S	EMC32/ V11.10.00	NCR	NCR
Test room	N/A	TR13	NCR	NCR

Note:

1. The calibrations are traceable to NML/ROC.
2. NCR:No Calibration Required.

Radiated Emission Test (Below 1GHz)

Test Site and Equipment	Manufacturer	Model No. /Serial No.	Last Calibration Date	Calibration Due Date
EMI Receiver	R&S	ESCS30/ 836858/020	2020/10/30	2021/10/30
Spectrum Alayzer	Agilent	E4407B/ MY45106795	2021/6/23	2022/6/23
Antenna	SCHWARZBECK & Mini-Circuits	VULB 9168 & BW-N5W5+/ VULB 9168-668 & 003	2021/5/6	2022/5/6
Pre-amplifer	Mini-circuit	ZKL-1R5+/ 004	2021/7/13	2022/1/13
RF cable	JYBAO	0214/ C0080-4 + C0080-1 + C0080- 2+RSU(CRC- 011/11)+C0080-3	2021/7/13	2022/1/13
Test software	Audix	e3/ V6.20110303a2	NCR	NCR
Semi-anechoic chamber	ETS. LINDGREN	TR11/ 906-A	2021/4/10	2022/4/10

Note:

1. The calibrations are traceable to NML/ROC.
2. NCR : No Calibration Required.
3. The calibration date of the semi-anechoic chamber listed above is the date of NSA measurement.

Radiated Emission Test (Above 1 GHz)

Test Site and Equipment	Manufacturer	Model No. /Serial No.	Last Calibration Date	Calibration Due Date
Antenna	EMCO	3117/ 0082847	2020/11/3	2021/11/3
Antenna	Com-Power	AH-840/ 101098	2020/12/31	2021/12/31
Pre-amplifier	MITEQ	TTA1800-30-HG- N-M/ 1904295	2020/10/28	2021/10/28
Pre-amplifier	MITEQ	TTA1840-35-HG/ 2034375	2021/9/9	2022/9/9
RFcable	Suhner	Sucoflex 106P / C0091	2021/10/4	2022/10/4
RFcable	JMCA	MWX241/B/ C0103~C0104	2021/4/9	2022/4/9
MXA signal analyzer	KeySight	N9020A/ MY54420147	2021/7/5	2022/7/5
Test software	Audix	e3/ V9 20150907c	NCR	NCR
Semi-anechoic chamber	ETS. LINDGREN	TR1/ 17627-B	2021/2/9	2022/2/9

Note:

1. The calibrations are traceable to NML/ROC.
2. NCR : No Calibration Required.
3. The calibration date of the chamber TR1 listed above is the date of site VSWR measurement.

For Power Line Conducted Measurement

Test Site and Equipment	Manufacturer	Model No./ Serial No.	Last Calibration Date	Calibration Due Date
Test Receiver	R&S	ESCI/ 100316/003	2021/4/9	2022/4/9
LISN	R&S	ESH2-Z5/ 880669/039	2021/4/23	2022/4/23
2 nd LISN	R&S	ESH2-Z5/ 836613/001	2021/9/6	2022/9/6
50Ω terminator	SHHNER	65 BNC-50-0-1/133 NE/004	2021/6/1	2022/6/1
RF Cable	JYBAO	0214/ C0113 + RSU + C0114	2021/8/18	2022/2/18
RF Cable	JYBAO	0214/ C0112 + RSU + C0114	2021/8/18	2022/2/18
Test Software	Audix	e3/ V6.20110303a2	NCR	NCR
TR20 shielded room	ETS LINDGREN	T R20/ 17873-2	NCR	NCR

Note:

1. The calibrations are traceable to NML/ROC.
2. NCR : No Calibration Required.

1.7 Test Capability

Test Facility

The test facility used for evaluating the conformance of the EUT with each standard in the present report meets what required in CISPR16 series and ANSI C63.4:2014 amended as per ANSI C63.4a:2017.

Test Room	Type of Test Room	Descriptions
TR1	10m semi-anechoic chamber	For the radiated emission measurement (below 1GHz)
TR1	3m fully-anechoic chamber	For the radiated emission measurement (above 1GHz)
TR11	3m semi-anechoic chamber	For the radiated emission measurement (below 1GHz)
TR13	Test Site	For the RF conducted emission measurement.
TR5	Shielding Room	For the conducted emission measurement.
TR20	Shielding Room	

Test Laboratory Competence Information

Central Research Technology Co. has been accredited / filed / authorized by the agencies listed in the following table.

Certificate	Nation	Agency	Code	Mark
Accreditation Certificate	USA	NVLAP	200575-0	ISO/IEC 17025
	USA	FCC	TW1104, TW0019	ISO/IEC 17025
	R.O.C. (Taiwan)	TAF	0905	ISO/IEC 17025
	R.O.C. (Taiwan)	BSMI	SL2-IN-E-0033, SL2-IS-E-0033, SL2-R1/R2-E-0033, SL2-A1-E-0033, SL2-L1-E-0033	ISO/IEC 17025
	Canada	ISED	TW0905	ISO/IEC 17025
Site Filing Document	Japan	VCCI	R-11527,C-11609,T-11441, G-10010,C-20010, G-10614, T-20009	Test facility list & NSA Data
Authorization Certificate	Germany	TUV	UA 50235497	ISO/IEC 17025

The copy of each certificate can be downloaded from our web site: www.crc-lab.com

1.8 Measurement Uncertainty

The assessed measurement uncertainty with a suitable coverage factor K to ensure 95% confidence level for the normal distribution are shown as below, the values are less than U_{Cispr} in table 1 of CISPR 16-4-2.

Test Item	Measurement Uncertainty	
Occupied bandwidth	1.2%	
Conducted emission	0.9 dB	
Radiated Emission: (9 kHz~30 MHz)	Horizontal 3.92dB ; Vertical 3.92dB	
Radiated Emission: (30 MHz~1000 MHz)	Horizontal 4.42dB ; Vertical 5.98dB	
Radiated Emission: (1 GHz~6 GHz)	Horizontal 4.60dB ; Vertical 4.48dB	
Radiated Emission: (6 GHz~18 GHz)	Horizontal 4.66dB ; Vertical 4.58dB	
Radiated Emission: (18 GHz~40 GHz)	Horizontal 4.74dB ; Vertical 4.76dB	
Line Conducted Emission	NSLK-8128-RC	2.48 dB
	ENV 4200	2.52 dB
	ESH2-Z5	2.20 dB

2 6dB Bandwidth

Result: Pass


2.1 Applied standard

According to According to FCC 15.247(a)(2), the minimum 6 dB bandwidth shall be at least 500 kHz.

2.2 Measurement Procedure

- a. The EUT was set up per the test configuration figured in the next section of this chapter to simulate the typical usage per the user's manual.
- b. A software provided by client enabled the EUT to transmit data at middle channel frequencies individually.
- c. Test procedures follow ANSI C63.10 Section 11.8.
- d. Spectrum analyzer setting: RBW=100 kHz, VBW=300 kHz, Max peak
- e. Measure the 6dB bandwidth and compare with the required limit.


2.3 Test configuration




2.4 Test Data**Test Mode : Continuous transmitter****Tester : Wayne****Ambient Temperature : 25°C****Relative Humidity : 51%****Test Date : 110/11/9**

Operating Frequency (MHz)	6 dB Bandwidth (MHz)	Limit (kHz)
2402	0.75	> 500
2440	0.75	> 500
2480	0.73	> 500


Channel 0 (2402MHz)



Channel 19 (2440MHz)



Channel 39 (2480MHz)



3 Maximum Peak Output Power

Result: Pass


3.1 Applied standard

According to FCC 15.247(b)(3), for systems using digital modulation in the 902–928 MHz, 2400–2483.5 MHz, and 5725–5850 MHz bands: 1 Watt.

3.2 Measurement Procedure

- a. The EUT was set up per the test configuration figured in the next section of this chapter to simulate the typical usage per the user's manual.
- b. Test procedures follow ANSI C63.10 section 11.9.1.1.
- c. Spectrum alayzer setting: RBW:1 MHz, VBW=3 MHz, Max peak
- d. Measurement the Maximum Peak Output Power and compare with the required limit.

3.3 Test configuration



3.4 Test Data


Test Mode : Continuous transmitter **Tester** : Wayne
Ambient Temperature : 25°C **Relative Humidity** : 51%
Test Date : 110/11/9

Operating Frequency (MHz)	output power (dBm)	Limit (dBm)	Margin (dB)
2402	5.5	30	24.5
2440	5.5	30	24.5
2480	5.2	30	24.8


Note:

1. $\text{Margin(dB)} = \text{Limit} - \text{output power}$


Channel 0 (2402MHz)



Channel 19 (2440MHz)



Channel 39 (2480MHz)



4 Power Spectral Density

Result: Pass


4.1 Applied standard

According to FCC 15.247(e), for digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

4.2 Measurement Procedure

- a. The EUT was set up per the test configuration figured in the next section of this chapter to simulate the typical usage per the user's manual.
- b. Test procedures follow ANSI C63.10 section 11.10.2.
- c. Spectrum analyzer setting: RBW:10 kHz, VBW=30 kHz, Max peak
- d. Measure the peak power spectral density and compare with the required limit.

4.3 Test configuration



4.4 Test Data


Test Mode : Continuous transmitter **Tester** : Wayne
Ambient Temperature : 25°C **Relative Humidity** : 51%
Test Date : 110/11/9

Operating Frequency (MHz)	Power Density (dBm/10 kHz)	Limit (dBm/3 kHz)	Margin (dB)
2402	-4.6	8	12.6
2440	-4.6	8	12.6
2480	-4.9	8	12.9


Note:

1. Margin(dB)=Limit- Power Density


Channel 0 (2402MHz)



Channel 19 (2440MHz)



Channel 39 (2480MHz)



5 Conducted Spurious emission

Result: Pass


5.1 Applied standard

According to FCC 15.247(d), in any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph FCC 15.247(b)(3), the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in FCC 15.209(a) are not required.

5.2 Measurement Procedure

- a. The EUT was set up per the test configuration figured in the next section of this chapter to simulate the typical usage per the user's manual.
- b. The software provided by client enabled the EUT to transmit data at low and high channel frequencies individually.
- c. Test procedures follow ANSI C63.10 section 11.11.
- d. Spectrum analyzer setting: RBW:100 kHz, VBW=300 kHz, Max peak.
- e. Measurement the conducted spurious emission and compare with the required limit.

5.3 Test configuration



5.4 Test Data

Bandedge

Test Mode : Continuous transmitter **Tester** : Wayne
Ambient Temperature : 25°C **Relative Humidity** : 51%
Test Date : 110/11/9


Operating Frequency (MHz)	Max emission of in band (dBm)	Frequency of out band max emission (MHz)	Max emission of out band (dBm)	Limit (dBm)	Margin (dB)
2402	4.7	2400.0	-52.7	-15.3	37.4
2480	4.3	2484.3	-59.5	-15.7	43.8

Note:

1. Limit(dBm) = Max emission of in band - 20
2. Margin (dB) = Limit – Max emission of out band

Channel 0 (2402MHz)


Band Edge



— Limit — Sum Level × Fail

Channel 39 (2480MHz)

Band Edge



— Limit — Sum Level × Fail

Out of band emission

Test Mode : Continuous transmitter

Tester : Wayne


Ambient Temperature : 25°C

Relative Humidity : 51%

No signal can be detected from 18 GHz to 25 GHz, so the graphs are omitted above 18 GHz

Channel 0 (2402MHz)


Spurious



— Limit — Sum Level — Threshold × Critical × Final Critical

Channel 19 (2440MHz)


Spurious



— Limit — Sum Level — Threshold × Critical × Final Critical

Channel 39 (2480MHz)

Spurious



— Limit — Sum Level — Threshold × Critical × Final Critical

6 Radiated Spurious Emission

Result: Pass

6.1 Applied standard

According to FCC 15.247(d), fall in the restricted bands, as defined in FCC 15.205(a), must also comply with the radiated emission limits specified in FCC 15.209(a).



The amplitude of spurious emission are attenuated by more than 20 dB below the permissible value has no need to be reported.

6.2 Measurement Procedure


- a. The EUT was set up per the test configuration figured in the next section of this chapter to simulate the typical usage per the user's manual.
- b. A software provided by client enabled the EUT to transmit and receive data at operating frequency.(if necessary)
- c. If the EUT is tabletop equipment, it should be placed on a wooden table with a height of 0.8 meters above the reference ground plane in the semi-anechoic chamber. If the EUT is floor-standing equipment, it should be placed on a non-conducted support with a height of 12 millimeters above the reference ground plane in the semi-anechoic chamber.
- d. The EUT is set 3m away from the interference receiving antenna.
- e. Rapidly sweep the signal in the test frequency range by using the spectrum through the Maximum-peak detector.
- f. Rotate the EUT from 0° to 360° and position the receiving antenna at heights from 1 to 4 meters above the reference ground plane continuously to determine at least six frequencies associated with higher emission levels and record them.
- g. Then measure each frequency found from step f. by using the spectrum with rotating the EUT and positioning the receiving antenna height to determine the maximum level.
- h. For measurement of frequency below 1000MHz, set the receiver detector to be Quasi-Peak per CISPR 16-1 to find out the maximum level occurred Receiver Setting is 9 kHz – 150kHz: RBW=200 Hz. 150kHz – 30 MHz: RBW=9 kHz. 30 MHz- 1 GHz: RBW=120 kHz.
- i. For measurement of frequency above 1000MHz, set the spectrum detector to be Peak or Average to find out the maximum level occurred, if any. Spectrum Analyzer Setting is Peak:RBW=1 MHz, VBW=3 MHz. Average: RBW=1 MHz, VBW=3 kHz.
- j. Record frequency, azimuth angle of the turntable, height, and polarization of the receiving antenna and compare the maximum level with the required limit.
- k. Change the receiving antenna to another polarization to measure radiated emission by following step e. to j. again.
- l. If the peak emission level below 1000MHz measured from step f. is 4dB lower than the limit specified, then the emission values presented will be the peak value only. Otherwise, accurate Q.P. value will be measured and presented.
- m. If the peak emission level above 1000MHz measured from step f. is 20dB lower than the limit specified, then the emission values presented will be the peak value only. Otherwise, accurate A.V. value will be measured and presented.

6.3 Test configuration

Below 1GHz




■ : Pre-amplifier



6.4 Test Data

Bandedge

Test Mode : Continuous Transmitting, 2402 MHz
 Polarization : Horizontal Tester : Jeffry
 Ambient Temperature : 24°C Relative Humidity : 58%




Condition : FCC CLASS-B PK 3m EMCO_3117_82847 HORIZONTAL
 POWER :
 OPERATOR : Jeffry T:24 H:58 P:1009

	Read	Limit	Over	APos	TPos			Remark
Freq	Level	Level	Factor	Line	Limit	cm	deg	
MHz	dBuV/m	dBuV	dB/m	dBuV/m	dB			
1	2390.000	28.98	46.21	-17.23	54.00	-25.02	234	327 HORIZONTAL Average
2	2390.000	41.86	59.09	-17.23	74.00	-32.14	234	327 HORIZONTAL Peak

Note:

1. Level (dBuV/m) = Read level + Factor.
2. Factor (dB/m) = Cable Loss + Antenna Factor – Gain of Preamplifier.
3. Over Limit (dB) = Level – Limit line

Test Mode : Continuous Transmitting, 2402 MHz
Polarization : Vertical **Tester** : Jeffry
Ambient Temperature : 24°C **Relative Humidity** : 58%




Condition : FCC CLASS-B PK 3m EMCO_3117_82847 VERTICAL
POWER :
OPERATOR : Jeffry T:24 H:58 P:1009

	Freq	Level	Read Level	Factor	Limit Line	Over Limit	APos	TPos	Pol/Phase	Remark
	MHz	dBuV/m	dBuV	dB/m	dBuV/m	dB	cm	deg		
1	2390.000	28.93	46.16	-17.23	54.00	-25.07	400	321	VERTICAL	Average
2	2390.000	42.09	59.32	-17.23	74.00	-31.91	400	321	VERTICAL	Peak

Note:

1. Level (dBuV/m) = Read level + Factor.
2. Factor (dB/m) = Cable Loss + Antenna Factor – Gain of Preamplifier.
3. Over Limit (dB) = Level – Limit line

Test Mode : Continuous Transmitting, 2480 MHz
Polarization : Horizontal **Tester** : Jeffry
Ambient Temperature : 24°C **Relative Humidity** : 58%




Condition : FCC CLASS-B PK 3m EMCO_3117_82847 HORIZONTAL
POWER :
OPERATOR : Jeffry T:24 H:58 P:1009

	Freq	Level	Read Level	Limit Factor	Over Line	Over Limit	APos	TPos	Pol/Phase	Remark
	MHz	dBUV/m	dBuV	dB/m	dBUV/m	dB	cm	deg		
1	2483.500	30.17	47.10	-16.93	54.00	-23.83	325	285	HORIZONTAL	Average
2	2483.500	42.77	59.70	-16.93	74.00	-31.23	325	285	HORIZONTAL	Peak

Note:

1. Level (dBUV/m) = Read level + Factor.
2. Factor (dB/m) = Cable Loss + Antenna Factor – Gain of Preamplifier.
3. Over Limit (dB) = Level – Limit line

Test Mode : Continuous Transmitting, 2480 MHz
Polarization : Vertical **Tester** : Jeffry
Ambient Temperature : 24°C **Relative Humidity** : 58%



Condition : FCC CLASS-B PK 3m EMCO_3117_82847 VERTICAL
POWER :
OPERATOR : Jeffry T:24 H:58 P:1009


	Freq	Level	Read Level	Factor	Limit Line	Over Limit	APos	TPos	Pol/Phase	Remark
	MHz	dBuV/m	dBuV	dB/m	dBuV/m	dB	cm	deg		
1	2483.500	30.23	47.16	-16.93	54.00	-23.77	365	283	VERTICAL	Average
2	2483.500	42.47	59.40	-16.93	74.00	-31.53	365	283	VERTICAL	Peak

Note:

1. Level (dBuV/m) = Read level + Factor.
2. Factor (dB/m) = Cable Loss + Antenna Factor – Gain of Preamplifier.
3. Over Limit (dB) = Level – Limit line

Radiated Emission Measurement below 1000MHz

Test Mode : Normal
 Test Range : 30 MHz ~1 GHz
 Polarization : Horizontal Tester : Martin
 Ambient Temperature : 27°C Relative Humidity : 52%



Trace: (Discrete)

Site : TR11 9*6*6 chamber
 Condition : FCC CLASS-B 3m VULB_9168-668 HORIZONTAL
 Power : 120V / 60Hz
 Operator : Martin T27 H52 P1010


	Freq	Level	Read	Limit	Over	A/Pos	T/Pos	Pol/Phase	Remark
	MHz	dBuV/m	Level	Line	Limit	dB	cm	deg	
			Factor						
			dB/m	dBuV/m	dB				
1	234.015	22.49	45.27	-22.78	46.00	-23.51	138	69	HORIZONTAL QP
2	500.003	29.12	44.02	-14.90	46.00	-16.88	100	96	HORIZONTAL QP
3	625.000	31.34	43.27	-11.93	46.00	-14.66	225	115	HORIZONTAL QP

Note:

1. Level (dBuV/m) = Read level + Factor.
2. Factor (dB/m) = Cable Loss + Antenna Factor – Gain of Pre-amplifier.
3. Over Limit (dB) = Level – Limit line
4. QK. is abbreviation of Quasi-Peak
5. The emission levels were too lower against the limit of frequency 9 kHz~ 30 MHz.

Test Mode : Normal
 Test Range : 30 MHz ~1 GHz
 Polarization : Vertical
 Ambient Temperature : 27°C

Tester : Martin
 Relative Humidity : 52%



Trace: (Discrete)
 Site : TR11 9*6*6 chamber
 Condition : FCC CLASS-B 3m VULB_9168-668 VERTICAL
 Power : 120V / 60Hz
 Operator : Martin T27 H52 P1010


	Freq	Level	Read	Limit	Over	A/Pos	T/Pos	Pol/Phase	Remark
	MHz	dBuV/m	Level	Factor	Line	Limit			
			dBuV	dB/m	dBuV/m	dB	cm	deg	
1	356.374	28.46	46.92	-18.46	46.00	-17.54	100	360 VERTICAL	QP
2	625.008	33.69	45.60	-11.91	46.00	-12.31	100	209 VERTICAL	QP
3	956.623	28.96	36.48	-7.52	46.00	-17.04	100	0 VERTICAL	QP

Note:

1. Level (dBuV/m) = Read level + Factor.
2. Factor (dB/m) = Cable Loss + Antenna Factor – Gain of Preamplifier.
3. Over Limit (dB) = Level – Limit line
4. QK. is abbreviation of Quasi-Peak
5. The emission levels were too lower against the limit of frequency 9 kHz~ 30 MHz.

Radiated Emission Measurement above 1000MHz

Test Mode : Continuous Transmitting, 2402 MHz
Test Range : 1 GHz ~ 25 GHz
Polarization : Horizontal **Tester** : Jack
Ambient Temperature : 22°C **Relative Humidity** : 63%




Condition : FCC CLASS-B PK 3m EMCO_3117_82847 Horizontal
POWER :
OPERATOR : Jack T:22 H:63 P:1011

	Freq	Level	Read Level	Limit Factor	Over Line	APos	TPos	Pol/Phase	Remark
	MHz	dBuV/m	dBuV	dB/m	dBuV/m	dB	cm	deg	
1	4803.929	43.76	59.30	-15.54	74.00	-30.24	181	193	Horizontal Peak
2	4804.265	29.17	44.71	-15.54	54.00	-24.83	185	197	Horizontal Average
3	7205.934	47.45	59.85	-12.40	74.00	-26.55	146	249	Horizontal Peak
4	7206.588	32.52	44.92	-12.40	54.00	-21.48	151	242	Horizontal Average
5	14760.750	38.97	48.09	-9.12	54.00	-15.03	277	234	Horizontal Average
6	14761.330	52.98	62.10	-9.12	74.00	-21.02	283	230	Horizontal Peak

Note:

1. Level (dBuV/m) = Read level + Factor.
2. Factor (dB/m) = Cable Loss + Antenna Factor – Gain of Preamplifier.
3. Over Limit (dB) = Level – Limit line
4. No signal can be detected above 18 GHz, so the graphs are omitted.

Test Mode : Continuous Transmitting, 2402 MHz
Test Range : 1 GHz ~ 25 GHz
Polarization : Vertical **Tester** : Jack
Ambient Temperature : 22°C **Relative Humidity** : 63%




Condition : FCC CLASS-B PK 3m EMCO_3117_82847 VERTICAL
POWER :
OPERATOR : Jack T:22 H:63 P:1011

	Freq	Level	Read Level	Factor	Limit Line	Over Limit	APos	TPos	Pol/Phase	Remark
	MHz	dBuV/m	dBuV	dB/m	dBuV/m	dB	cm	deg		
1	4803.688	29.02	44.56	-15.54	54.00	-24.98	234	168	VERTICAL	Average
2	4804.374	43.30	58.84	-15.54	74.00	-30.70	238	163	VERTICAL	Peak
3	7205.802	46.30	58.70	-12.40	74.00	-27.70	188	228	VERTICAL	Peak
4	7206.312	32.56	44.96	-12.40	54.00	-21.44	184	233	VERTICAL	Average
5	15697.770	53.10	61.06	-7.96	74.00	-20.90	244	64	VERTICAL	Peak
6	15698.380	39.12	47.08	-7.96	54.00	-14.88	250	67	VERTICAL	Average

Note:

1. Level (dBuV/m) = Read level + Factor.
2. Factor (dB/m) = Cable Loss + Antenna Factor – Gain of Preamplifier.
3. Over Limit (dB) = Level – Limit line
4. No signal can be detected above 18 GHz, so the graphs are omitted.

Test Mode : Continuous Transmitting, 2440 MHz
Test Range : 1 GHz ~ 25 GHz
Polarization : Horizontal **Tester** : Jack
Ambient Temperature : 22°C **Relative Humidity** : 63%




Condition : FCC CLASS-B PK 3m EMCO_3117_82847 Horizontal
POWER :
OPERATOR : Jack T:22 H:63 P:1011

	Freq	Level	Read Level	Limit Factor	Over Line	Limit	APos	TPos	Pol/Phase	Remark
	MHz	dBuV/m	dBuV	dB/m	dBuV/m	dB	cm	deg		
1	4879.659	28.71	44.33	-15.62	54.00	-25.29	212	85	Horizontal	Average
2	4880.328	43.45	59.07	-15.62	74.00	-30.55	217	81	Horizontal	Peak
3	7319.695	31.49	43.85	-12.36	54.00	-22.51	172	138	Horizontal	Average
4	7320.245	45.77	58.13	-12.36	74.00	-28.23	168	132	Horizontal	Peak
5	13806.560	37.58	47.20	-9.62	54.00	-16.42	324	253	Horizontal	Average
6	13807.270	51.60	61.22	-9.62	74.00	-22.40	329	257	Horizontal	Peak

Note:

1. Level (dBuV/m) = Read level + Factor.
2. Factor (dB/m) = Cable Loss + Antenna Factor – Gain of Preamplifier.
3. Over Limit (dB) = Level – Limit line
4. No signal can be detected above 18 GHz, so the graphs are omitted.

Test Mode : Continuous Transmitting, 2440 MHz
Test Range : 1 GHz ~ 25 GHz
Polarization : Vertical **Tester** : Jack
Ambient Temperature : 22°C **Relative Humidity** : 63%




Condition : FCC CLASS-B PK 3m EMCO_3117_82847 Vertical
POWER :
OPERATOR : Jack T:22 H:63 P:1011

	Read	Limit	Over	APos	TPos			Remark	
Freq	Level	Level	Factor	Line	Limit		Pol/Phase		
MHz	dBuV/m	dBuV	dB/m	dBuV/m	dB	cm	deg		
1	4879.711	42.50	58.12	-15.62	74.00	-31.50	273	157 Vertical	Peak
2	4880.216	28.96	44.58	-15.62	54.00	-25.04	278	153 Vertical	Average
3	7319.840	46.36	58.72	-12.36	74.00	-27.64	239	199 Vertical	Peak
4	7320.277	31.43	43.79	-12.36	54.00	-22.57	236	194 Vertical	Average
5	12012.710	50.72	58.13	-7.41	74.00	-23.28	178	320 Vertical	Peak
6	12013.260	36.39	43.80	-7.41	54.00	-17.61	173	324 Vertical	Average

Note:

1. Level (dBuV/m) = Read level + Factor.
2. Factor (dB/m) = Cable Loss + Antenna Factor – Gain of Preamplifier.
3. Over Limit (dB) = Level – Limit line
4. No signal can be detected above 18 GHz, so the graphs are omitted.

Test Mode : Continuous Transmitting, 2480 MHz
Test Range : 1 GHz ~ 25 GHz
Polarization : Horizontal **Tester** : Jack
Ambient Temperature : 22°C **Relative Humidity** : 63%




Condition : FCC CLASS-B PK 3m EMCO_3117_82847 Horizontal
POWER :
OPERATOR : Jack T:22 H:63 P:1011

	Freq	Level	Read Level	Limit Factor	Over Line	APos	TPos	Pol/Phase	Remark
	MHz	dBuV/m	dBuV	dB/m	dBuV/m	dB	cm	deg	
1	4959.913	43.13	58.57	-15.44	74.00	-30.87	152	198	Horizontal Peak
2	4960.247	29.37	44.81	-15.44	54.00	-24.63	156	193	Horizontal Average
3	7439.941	45.86	57.88	-12.02	74.00	-28.14	213	290	Horizontal Peak
4	7440.529	31.99	44.01	-12.02	54.00	-22.01	217	284	Horizontal Average
5	16627.590	39.81	46.07	-6.26	54.00	-14.19	280	66	Horizontal Average
6	16628.340	54.27	60.53	-6.26	74.00	-19.73	285	62	Horizontal Peak

Note:

- Level (dBuV/m) = Read level + Factor.
- Factor (dB/m) = Cable Loss + Antenna Factor – Gain of Preamplifier.
- Over Limit (dB) = Level – Limit line
- No signal can be detected above 18 GHz, so the graphs are omitted.

Test Mode : Continuous Transmitting, 2480 MHz
Test Range : 1 GHz ~ 25 GHz
Polarization : Vertical **Tester** : Jack
Ambient Temperature : 22°C **Relative Humidity** : 63%



Condition : FCC CLASS-B PK 3m EMCO_3117_82847 Vertical
POWER :
OPERATOR : Jack T:22 H:63 P:1011

	Freq	Level	Read Level	Limit Factor	Limit Line	Over Limit	APos	TPos	Pol/Phase	Remark
	MHz	dBuV/m	dBuV	dB/m	dBuV/m	dB	cm	deg		
1	4959.515	42.96	58.40	-15.44	74.00	-31.04	252	135	Vertical	Peak
2	4960.241	29.18	44.62	-15.44	54.00	-24.82	258	131	Vertical	Average
3	7439.526	46.17	58.20	-12.03	74.00	-27.83	179	203	Vertical	Peak
4	7440.106	32.00	44.02	-12.02	54.00	-22.00	172	199	Vertical	Average
5	12103.710	51.39	58.81	-7.42	74.00	-22.61	222	297	Vertical	Peak
6	12104.290	36.72	44.14	-7.42	54.00	-17.28	225	291	Vertical	Average

Note:

1. Level (dBuV/m) = Read level + Factor.
2. Factor (dB/m) = Cable Loss + Antenna Factor – Gain of Preamplifier.
3. Over Limit (dB) = Level – Limit line
4. No signal can be detected above 18 GHz, so the graphs are omitted.

7 Line Conducted Emission Measurement

Result: Pass

7.1 Limits for Emission Measurement

According to FCC 15.207(a), line conduction emission limit is as below table.


Frequency of Emission (MHz)	Conducted Limit (dBuV)	
	Quasi-peak	Average
0.15 – 0.5	66 to 56*	56 to 46*
0.5 - 5	56	46
5 - 30	60	50

* Decreases with the logarithm of the frequency.

7.2 Measurement Procedure


- a. The EUT was set up per the test configuration figured in the next section of this chapter to simulate the typical usage per the user's manual.
- b. If the EUT is tabletop equipment, it was placed on a non-conducted table with a height of 0.8 meters above the reference ground plane and 0.4 meters from the conducting wall of the shielded room. Also if the EUT is floor-standing equipment, it was placed on a non-conducted support with a height of 12 millimeters above the reference ground plane.
- c. Connect the EUT's power source to the appropriate power mains through the LISN.
- d. All the other peripherals are connected to the 2nd LISN, if any.
- e. The LISN was placed 0.8 meters from the EUT and at least 0.8 meters from other units and other metal planes.
- f. Measure the conducted emissions on each power line (Neutral Line and Line 1 – Hot side) of the EUT's power source by using the test receiver connected to the coupling RF output port of LISN.
- g. Rapidly scan the signal from 150 kHz to 30 MHz by using the receiver through the Maximum-Peak detector to determine those frequencies associated with higher emission levels for each measured line. .Receiver setting is IF bandwidth=9 kHz.
- h. Then measure the maximum level of conducted disturbance for each frequency found from step g. by using the receiver through the Quasi-Peak and Average detectors per CISPR 16-1.
- i. Record the level for each frequency and compare with the required limit.

7.3 Test Configurations



7.4 Test Data

Test Mode : Normal
 Phase : Line Tester : David Lu
 Ambient Temperature : 25°C Relative Humidity : 67%



Site : TR20
 Condition : FCC_PART_15C_QP ESH2-25 LINE
 Power : 120V/60Hz
 Operator : David Lu T25 H67 P1016

	Freq	Level	Factor	Read Level	Limit Line	Over Limit	Pol/Phase	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB		
1	0.394	30.32	10.34	19.98	47.98	-17.66	LINE	Average
2	0.394	43.00	10.34	32.66	57.98	-14.98	LINE	QP
3	0.467	18.26	10.34	7.92	46.56	-28.30	LINE	Average
4	0.467	30.56	10.34	20.22	56.56	-26.00	LINE	QP
5	0.721	19.74	10.37	9.37	46.00	-26.26	LINE	Average
6	0.721	31.02	10.37	20.65	56.00	-24.98	LINE	QP
7	1.068	18.46	10.39	8.07	46.00	-27.54	LINE	Average
8	1.068	30.97	10.39	20.58	56.00	-25.03	LINE	QP
9	1.317	24.85	10.41	14.44	46.00	-21.15	LINE	Average
10	1.317	31.33	10.41	20.92	56.00	-24.67	LINE	QP
11	1.590	18.01	10.43	7.58	46.00	-27.99	LINE	Average
12	1.590	29.33	10.43	18.90	56.00	-26.67	LINE	QP

Note:

1. Emission Level = reading value + correction factor.
2. Correction factor = cable loss + insertion loss of LISN.
3. Q.P. is abbreviation of quasi-peak.


Test Mode : Normal

Phase : Neutral

Ambient Temperature : 25°C

Tester : David Lu

Relative Humidity : 67%



Date: 2021-10-25

Site : TR20
 Condition : FCC_PART_15C_QP ESH2-Z5 NEUTRAL
 Power : 120V/60Hz
 Operator : David Lu T25 H67 P1016

	Freq	Level	Factor	Read Level	Limit Line	Over Limit	Pol/Phase	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB		
1	0.209	16.81	10.31	6.50	53.23	-36.42	NEUTRAL	Average
2	0.209	29.33	10.31	19.02	63.23	-33.90	NEUTRAL	QP
3	0.393	27.28	10.35	16.93	48.01	-20.73	NEUTRAL	Average
4	0.393	37.48	10.35	27.13	58.01	-20.53	NEUTRAL	QP
5	0.591	14.29	10.37	3.92	46.00	-31.71	NEUTRAL	Average
6	0.591	24.00	10.37	13.63	56.00	-32.00	NEUTRAL	QP
7	0.719	18.47	10.38	8.09	46.00	-27.53	NEUTRAL	Average
8	0.719	27.05	10.38	16.67	56.00	-28.95	NEUTRAL	QP
9	1.037	16.66	10.40	6.26	46.00	-29.34	NEUTRAL	Average
10	1.037	26.12	10.40	15.72	56.00	-29.88	NEUTRAL	QP
11	1.319	23.67	10.42	13.25	46.00	-22.33	NEUTRAL	Average
12	1.319	29.38	10.42	18.96	56.00	-26.62	NEUTRAL	QP

Note:

1. Emission Level = reading value + correction factor.
2. Correction factor = cable loss + insertion loss of LISN.
3. Q.P. is abbreviation of quasi-peak.