

E-ANT2-900120-0001

Shenzhen Lxc Electronics Technology Co., Ltd

深圳市连兴创电子科技有限公司

王海波

APPROVAL SHEET

承认书

客户 (Customer) : 富斯

产品 (Product) : 868-915MHz 天线 (L=120MM)

型号 (Model) : T型天线

料号 (Part Number) : ANT2-900120-0001

制作人 (Written By) : 唐红交

签发时间 (Issued Date) : 2024-04-26

客户 CUSTOMER

频率范围 Frequency range	(863-928GHz)
驻波比系数 VSWR	<3.0
输入阻抗 Input Impedance	50 (Ω)
极化方式 Polarization	垂直极化 Vertical Polarization
半功率波束 (3dB) HPW	180° H-plane 120° E-plane



RF by		Checked by	
ME by		Date	
Customer Confirm			

8Project:	Author:Wang	File Name:	
Date: 2024-04-26		<b>ANT2-900120-0001</b>	
TEST:	Language:		Check: Zhong
A	English		
地址: 深圳市光明区光明街道白花社区 第一工业区丽霖工业园一栋厂房 4 楼 电话: 0755-29195258 传真: 0755-29590286 Shenzhen Lxc Electronics Technology Co., Ltd			

## Revision History

Date	Revision	Description of Changes
2024-04-26	RA	Measured with SUS301 sample.

深圳市连兴创电子科技有限公司 .....	1
<b>PROJECT .....</b>	<b>2</b>
<b>ANTENNA COMPONENTST .....</b>	<b>3</b>
<b>1 TECHNICAL SUMMARY .....</b>	<b>3</b>
<b>2 GENERAL DESCRIPTION .....</b>	<b>3</b>
2.1 Components/Part revisions .....	3
<b>3 MECHANICAL DESCRIPTION .....</b>	<b>3</b>
<b>4 ELECTRICAL PERFORMANCE .....</b>	<b>3</b>
4.1 Set-up .....	3
4.1.1 VSWR .....	3
4.1.2 Gain & Radiation Patterns .....	3
4.1.3 Matching Circuit Description .....	3
4.2 Measurement Data .....	4
4.2.1 Active result (GSM) .....	4
6 Mechanical drawing .....	5
<b>7 RELIABILITY TESTS .....</b>	<b>8</b>
7.1 Test content .....	8
7.2 Test results .....	8
<b>8 CONCLUSION .....</b>	<b>9</b>

8Project:		Author:Wang	<b>ANT2-900120-0001</b>
Date: 2024-04-26			
TEST:	Language:	Check: Zhong	
A	English		
地址: 深圳市光明区光明街道白花社区 第一工业区丽霖工业园一栋厂房 4 楼 电话: 0755-29195258 传真: 0755-29590286 Shenzhen Lxc Electronics Technology Co., Ltd			

# 1 Technical Summary

This report summarizes the electrical results of the proposed antenna to support the program. We test the antenna with the latest version handset. And it seems to be acceptable.

# 2 General Description

## 2.1 Components/Part revisions

VSWR: Voltage Standing Wave Rate.

# 3 Mechanical Description

# 4 Electrical Performance

## 4.1 Set-up


### 4.1.1 VSWR

VSWR measurements (S11) were performed using an Agilent 8753D Network Analyzer and the previously described test fixture. Coaxial chokes were used to mitigate surface currents on the outside of the cabling. The testing was performed in free space.

### 4.1.2 Gain & Radiation Patterns

The gain of the antenna was measured in the Lxc's anechoic chamber. Coaxial chokes on the feed cable were used to mitigate surface currents. The chamber provides less than -30 dB reflectivity from 800 MHz through 3 GHz and an 18" diameter spherical quiet zone. The measurement results are calibrated using both dipole and leaky wave horn standards.


### 4.1.3 Matching Circuit Description



8Project:		Author:Wang	File Name:  <b>ANT2-900120-0001</b>
Date: 2024-04-26			
TEST:	Language:	Check: Zhong	
A	English		
地址: 深圳市光明区光明街道白花社区 第一工业区丽霖工业园一栋厂房 4 楼 电话: 0755-29195258 传真: 0755-29590286 Shenzhen Lxc Electronics Technology Co., Ltd			

## 4.2 Measurement Data


### 4.2.1 Active result (915)




Freq (MHz)	Effi (%)	Effi (dB)	Gain (dBi)	Gain (dBd)	UHS (%)	DHS (%)	Max (dB)	Min (dB)	irectivit (dBi)
850	30.54	-5.15	0.41	-1.74	13.607	16.936	0.41	-16.66	5.56
860	32.99	-4.82	0.55	-1.6	15.043	17.949	0.55	-16.43	5.36
870	36.87	-4.33	0.99	-1.16	17.09	19.779	0.99	-14.84	5.32
880	38.25	-4.17	1.17	-0.98	17.686	20.568	1.17	-14.32	5.35
890	37.91	-4.21	1.12	-1.03	17.425	20.484	1.12	-14.27	5.34
900	33.25	-4.78	0.43	-1.72	15.22	18.026	0.43	-14.59	5.21
910	36.36	-4.39	0.84	-1.31	16.506	19.857	0.84	-13.52	5.23
920	36	-4.44	0.62	-1.53	16.101	19.894	0.62	-13.38	5.06
930	31.96	-4.95	0.13	-2.02	14.365	17.592	0.13	-13.72	5.08
940	32.75	-4.85	0.02	-2.13	14.694	18.06	0.02	-13.79	4.87
950	33.16	-4.79	0.06	-2.09	14.854	18.309	0.06	-14.72	4.85
960	32.99	-4.82	0.02	-2.13	15.037	17.948	0.02	-14.71	4.84
970	34.12	-4.67	0.14	-2.01	16.196	17.921	0.14	-13.45	4.81
980	34.21	-4.66	0.05	-2.1	16.812	17.399	0.05	-13.57	4.71
990	37.26	-4.29	0.37	-1.78	18.946	18.316	0.37	-12.27	4.66
1000	46.63	-3.31	1.5	-0.65	24.047	22.58	1.5	-13.86	4.82

8Project:		Author:Wang	<b>ANT2-900120-0001</b>
Date: 2024-04-26			
TEST:	Language:	Check: Zhong	
A	English		
地址: 深圳市光明区光明街道白花社区 第一工业区丽霖工业园一栋厂房 4 楼 电话: 0755-29195258 传真: 0755-29590286 Shenzhen Lxc Electronics Technology Co., Ltd			

### 850.00MHz - 1000.00MHz Gain




### 850.00MHz - 1000.00MHz Efficiency




8Project:		Author:Wang	File Name:  <b>ANT2-900120-0001</b>
Date: 2024-04-26			
TEST:	Language:	Check: Zhong	
A	English		
地址: 深圳市光明区光明街道白花社区 第一工业区丽霖工业园一栋厂房 4 楼 电话: 0755-29195258 传真: 0755-29590286 Shenzhen Lxc Electronics Technology Co., Ltd			


920.000MHz




920.000MHz H




920.000MHz E1




920.000MHz E2




870.000MHz




870.000MHz H



870.000MHz E1



870.000MHz E2



8Project:		Author:Wang	<b>ANT2-900120-0001</b>
Date: 2024-04-26			
TEST:	Language:	Check: Zhong	
A	English		
地址: 深圳市光明区光明街道白花社区 第一工业区丽霖工业园一栋厂房 4 楼 电话: 0755-29195258 传真: 0755-29590286 Shenzhen Lxc Electronics Technology Co., Ltd			



# 6 Mechanical drawing

由 Autodesk 教育版产品制作

备注:

1. 端子型号: 一代 内芯: 黑色.
2. 线材规格: 1.13射频线, 灰色, 双锡线
3. 阻抗: 50欧姆
4. 拉力测试: 端子铆压后拉力要达到1.13mm $\geq$ 1.0KG
5. 未标公差尺寸按照 $\pm 0.2$ , 标重点尺寸公差为 $\pm 0.1$
6. 包装方式: 珍珠棉包装
7. 安规要求: ROHS 2.0无卤

Technical drawing showing a cable assembly with dimensions:  $\phi 15.50 \pm 1.0$ ,  $\phi 28.80 \pm 1.0$ ,  $\phi 55.0 \pm 2.0$ ,  $\phi 120.0 \pm 3.0$ ,  $\phi 134.0 \pm 3.0$ , and  $\phi 1.13$ . Callouts 1-6 point to specific features.

NO.	DESCRIPTION	MATERIAL	REMARKS	QTY
1	端子	电子接插件 L 6.0mm 2.0mm		1
2	cable	1.13mm Cable, 灰色 50 $\Omega$ 双锡线材料		1
3	端子	I-PEX 20276-112-13		1
4	PCB	PCB黑色		1
5	PC	PC黑色		1
6	孔塞	PC塞/黑色		1

尺寸	公差	第二公差
0~3	$\pm 0.05$	A 0.02
3~8	$\pm 0.08$	A 0.03
8~30	$\pm 0.10$	A 0.04
30~60	$\pm 0.12$	A 0.05
60~	$\pm 0.15$	A 0.06

项目名称	900-91000-天馈	日期	2024-04-26
产品名称		设计	
产品料号	ANT2-900120-0001	审核	
材料		批准	
		单位	mm
		比例	1:1
		版本	A.1

**深圳市连兴创电子科技有限公司**

标记	姓名	修改内容	日期

由 Autodesk 教育版产品制作

8Project:		Author: Wang	<b>ANT2-900120-0001</b>
Date: 2024-04-26		Check: Zhong	
TEST:	Language:		
A	English		
地址: 深圳市光明区光明街道白花社区 第一工业区丽霖工业园一栋厂房 4 楼 电话: 0755-29195258 传真: 0755-29590286 Shenzhen Lxc Electronics Technology Co., Ltd			

# 7 Reliability tests

## 7.1 Test content

No	试验项目	试验方法	判定基准
1	盐水喷雾试验	把盐浓度 5%的溶液喷雾 48HR	不能有变色, 歪 (变形) 脱落等的缺点 腐蚀面积不能过大

## 7.2 Test results

NO	样品数	试验期间	实验结果	备注
1	50	24 小时	<b>OK</b>	技术等级为 9 级 腐蚀<0.4mm
2	50	48 小时	<b>OK</b>	技术等级为 9 级 腐蚀<0.4mm

## 8 Conclusion

From the above test results, we can know the electrical performance of the antenna is seems good.

Shenzhen Lxc Electronics Technology Co., Ltd, look forward to your confirmation, thank you for your cooperation!

8Project:	Author:Wang	File Name:	
Date: 2024-04-26		<b>ANT2-900120-0001</b>	
TEST:	Language:		Check: Zhong
A	English		
地址: 深圳市光明区光明街道白花社区 第一工业区丽霖工业园一栋厂房 4 楼 电话: 0755-29195258 传真: 0755-29590286 Shenzhen Lxc Electronics Technology Co., Ltd			