

FCC Test Report

Report No.: AGC01689240814FR06

FCC ID : 2A2UU-P8NEO

APPLICATION PURPOSE: Original Equipment

PRODUCT DESIGNATION: AI POS Terminal

BRAND NAME : KOZEN

MODEL NAME : P8 Neo

APPLICANT: Shanghai Xiangcheng Communication Technology Co., Ltd

DATE OF ISSUE : Oct. 30, 2024

STANDARD(S) : FCC Part 15 Subpart C §15.225

REPORT VERSION: V1.0

Attestation of Global Conciliance (Shenzhen) Co., Ltd



Page 2 of 37

Report Revise Record

Report Version	Revise Time	Issued Date	Valid Version	Notes
V1.0	/	Oct. 30, 2024	Valid	Initial Release



Table of Contents

1. General Information	5
2. Product Information	6
2.1 Product Technical Description	6
2.2 Test Frequency List	6
2.3 Related Submittal(S) / Grant (S)	7
2.4 Test Methodology	7
2.5 Special Accessories	7
2.6 Equipment Modifications	7
2.7 Antenna Requirement	7
3. Test Environment	8
3.1 Address of The Test Laboratory	8
3.2 Test Facility	8
3.3 Environmental Conditions	9
3.4 Measurement Uncertainty	9
3.5 List of Equipment Used	10
4. System Test Configuration	11
4.1 EUT Configuration	11
4.2 EUT Exercise	11
4.3 Configuration of Tested System	11
4.4 Equipment Used in Tested System	11
4.5 Summary of Test Results	
5. Description of Test Modes	13
6. Field Strength of Fundamental	14
6.1 Provisions Applicable	14
6.2 Measurement Procedure	
6.3 Measurement Setup (Block Diagram of Configuration)	16
6.4 Measurement Result	17
7. Radiated Spurious Emissions	19
7.1 Provisions Applicable	19
7.2 Measurement Procedure	
7.3 Measurement Setup (Block Diagram of Configuration)	
7.4 Measurement Result	23
8. 20dB Bandwidth Measurement	29
8.1 Provisions Applicable	29
8.2 Measurement Procedure	
8.3 Measurement Setup (Block Diagram of Configuration)	
8.4 Measurement Result	
9. Frequency Stability Measurement	31
9.1 Provisions Applicable	31
9.2 Measurement Procedure	31



Page 4 of 37

9.3 Measurement Setup (Block Diagram of Configuration)	3′
9.4 Measurement Result	32
10. AC Power Line Conducted Emission Test	33
10.1 Measurement Limit	33
10.2 Measurement Setup (Block Diagram of Configuration)	33
10.3 Preliminary Procedure of Line Conducted Emission Test	34
10.4 Final Procedure of Line Conducted Emission Test	34
10.5 Measurement Result	34
Appendix I: Photographs of Test Setup	37
Appendix II: Photographs of Test EUT	37



Report No.: AGC01689240814FR06 Page 5 of 37

1. General Information

Applicant	Shanghai Xiangcheng Communication Technology Co., Ltd		
Address	6th Floor, Building 10, No.3000 Longdong Avenue, Pudong New District,		
71000	Shanghai, China		
Manufacturer	Sichuan Xiangcheng Intelligent Technology Co., Ltd.		
	Factory No. 2 and 7 Zone A, Intelligent Terminal Demonstration Park, West		
Address	Section of Gangyuan Road, Lingang Economic Development Zone, Yibin City, Sichuan Province China		
Factory	Sichuan Xiangcheng Intelligent Technology Co., Ltd.		
	Factory No. 2 and 7 Zone A, Intelligent Terminal Demonstration Park, West		
Address	Section of Gangyuan Road, Lingang Economic Development Zone, Yibin City,		
	Sichuan Province China		
Product Designation	AI POS Terminal		
Brand Name	KOZEN		
Test Model	P8 Neo		
Date of receipt of test item	Aug. 29, 2024		
Date of Test	Aug. 29, 2024~Oct. 30, 2024		
Deviation from Standard	No any deviation from the test method		
Condition of Test Sample	Normal		
Test Result	Pass		
Test Report Form No	AGCER-FCC-NFC-V1		

Note: The test results of this report relate only to the tested sample identified in this report.

Prepared By	Bibo Zhang	
	Bibo Zhang (Project Engineer)	Oct. 30, 2024
Reviewed By	Calvin Lin	
	Calvin Liu (Reviewer)	Oct. 30, 2024
Approved By	Max Zhang	
	Max Zhang (Authorized Officer)	Oct. 30, 2024



Page 6 of 37

2. Product Information

2.1 Product Technical Description

Equipment Category	Near Field Communication (NFC)
Operation Frequency	13.56MHz
Hardware Version	V1.0
Software Version	p0816_kozen_combo
Modulation Type	ASK
Field Strength of Fundamental	63.06dBµV/m (Peak)
Antenna Designation	Coil Antenna
Antenna Gain	0dBi
Power Supply	DC 7.6V by battery or DC 5V from adapter

2.2 Test Frequency List

Frequency Band	Channel Number	Frequency		
13.110~14.010 MHz	01	13.56 MHz		



Page 7 of 37

2.3 Related Submittal(S) / Grant (S)

This submittal(s) (test report) is intended for FCC ID: **2A2UU-P8NEO**, filing to comply with Part 2, Part 15 of the Federal Communication Commission rules.

2.4 Test Methodology

The tests were performed according to following standards:

No.	Identity Document Title			
1	FCC 47 CFR Part 2	Frequency allocations and radio treaty matters; general rules and regulations		
2	FCC 47 CFR Part 15	Radio Frequency Devices		
3	ANSI C63.10-2013	American National Standard for Testing Unlicensed Wireless Devices		

2.5 Special Accessories

Not available for this EUT intended for grant.

2.6 Equipment Modifications

Not available for this EUT intended for grant.

2.7 Antenna Requirement

Standard Requirement

15.203 requirement:

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

EUT Antenna:

The non-detachable antenna inside the device cannot be replaced by the user at will. The gain of the antenna is 0dBi.



Page 8 of 37

3. Test Environment

3.1 Address of The Test Laboratory

Laboratory: Attestation of Global Compliance (Shenzhen) Co., Ltd.

Address: 1-2/F, Building 19, Junfeng Industrial Park, Chongqing Road, Heping Community, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China

3.2 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

CNAS-Lab Code: L5488

Attestation of Global Compliance (Shenzhen) Co., Ltd. has been assessed and proved to follow CNAS-CL01 Accreditation Criteria for Testing and Calibration Laboratories (identical to ISO/IEC17025: 2017 General Requirements for the Competence of Testing and Calibration Laboratories.)

A2LA-Lab Cert. No.: 5054.02

Attestation of Global Compliance (Shenzhen) Co., Ltd. EMC Laboratory has been accredited by A2LA for technical competence in the field of electrical testing, and proved to follow ISO/IEC 17025: 2017 General Requirements for the Competence of Testing and Calibration Laboratories and any additional program requirements in the identified field of testing.

FCC-Registration No.: 975832

Attestation of Global Compliance (Shenzhen) Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the FCC (Federal Communications Commission). The acceptance letter from the FCC is maintained in our files with Registration 975832.

IC-Registration No.: 24842(CAB identifier: CN0063)

Attestation of Global Compliance (Shenzhen) Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the Certification and Engineering Bureau of Industry Canada. The acceptance letter from the IC is maintained in our files with Registration 24842.



Page 9 of 37

3.3 Environmental Conditions

	Normal Conditions	Extreme Conditions				
Temperature range (℃)	15 - 35	-20 - 50				
Relative humidity range	20 % - 75 %	20 % - 75 %				
Pressure range (kPa)	86 - 106	86 - 106				
Power supply	DC 7.6V	LV:DC6.46V/HV:DC8.74V				
Neter The Cuttome Team against and Cuttome Valtages declared by the magnifest year						

Note: The Extreme Temperature and Extreme Voltages declared by the manufacturer.

3.4 Measurement Uncertainty

The reported uncertainty of measurement y ±U, where expended uncertainty U is based on a standard uncertainty multiplied by a coverage factor of k=2, providing a level of confidence of approximately 95%.

Item	Measurement Uncertainty		
Uncertainty of Conducted Emission for AC Port	$U_c = \pm 3.1 \text{ dB}$		
Uncertainty of Radiated Emission below 150kHz	$U_c = \pm 4.2 \text{ dB}$		
Uncertainty of Radiated Emission below 30MHz	$U_c = \pm 3.8 \text{ dB}$		
Uncertainty of Radiated Emission below 1GHz	$U_c = \pm 4.0 \text{ dB}$		
Uncertainty of total RF power, conducted	$U_c = \pm 0.8 \text{ dB}$		
Uncertainty of RF power density, conducted	$U_c = \pm 2.6 \text{ dB}$		
Uncertainty of spurious emissions, conducted	U _c = ±2 %		
Uncertainty of Occupied Channel Bandwidth	$U_c = \pm 2.7 \%$		



Report No.: AGC01689240814FR06 Page 10 of 37

3.5 List of Equipment Used

• R	RF Conducted Test System						
Used	Used Equipment No. Test Equipment Manufacturer Model No. Serial No. Last Cal. Date (YY-MM-DD) (YY-MM-DD)						
	AGC-ER-E036	Spectrum Analyzer	Agilent	N9020A	MY49100060	2024-05-24	2025-05-23
\boxtimes	AGC-ER-E075	Small Environmental Tester	SH-242	ESPEC	93008290	2024-07-24	2026-07-23
\boxtimes	N/A	RF Connection Cable	N/A	2#	N/A	Each time	N/A

• F	Radiated Spurious Emission						
Used	Equipment No.	Test Equipment	Manufacturer	Model No.	Serial No.	Last Cal. Date (YY-MM-DD)	Next Cal. Date (YY-MM-DD)
\boxtimes	AGC-EM-E116	EMI Test Receiver	R&S	ESCI	100034	2024-05-24	2025-05-23
\boxtimes	AGC-EM-E086	Loop Antenna	ZHINAN	ZN30900C	18051	2024-03-05	2026-03-04
\boxtimes	AGC-EM-E001	Wideband Antenna	SCHWARZBECK	VULB9168	D69250	2023-05-11	2025-05-10
\boxtimes	AGC-EM-A138	6dB Attenuator	Eeatsheep	LM-XX-6-5W	N/A	2023-06-09	2025-06-08

A	AC Power Line Conducted Emission									
I lised I Edilinment No. 1 Test Edilinment Manufacturer Model No. 1 Serial No. 1						Next Cal. Date (YY-MM-DD)				
\boxtimes	AGC-EM-E045	EMI Test Receiver	R&S	ESPI	101206	2024-05-28	2025-05-27			
\boxtimes	AGC-EM-E023	AMN	R&S	100086	ESH2-Z5	2024-05-28	2025-05-27			

Test Software								
Used	Jsed Equipment No. Test Equipment Manufacturer Model No. Version Information							
\boxtimes	AGC-EM-S003	RE Test System	FARA	EZ-EMC	V.RA-03A			
\boxtimes	AGC-EM-S001	CE Test System	R&S	ES-K1	V1.71			



Page 11 of 37

4. System Test Configuration

4.1 EUT Configuration

The EUT configuration for testing is installed on RF field strength measurement to meet the Commission's requirement and operating in a manner which intends to maximize its emission characteristics in a continuous normal application.

4.2 EUT Exercise


The Transmitter was operated in the normal operating mode. The TX frequency was fixed which was for the purpose of the measurements.

4.3 Configuration of Tested System

Radiated Emission Configure:



Conducted Emission Configure:



4.4 Equipment Used in Tested System

The following peripheral devices and interface cables were connected during the measurement:

- ☐ Test Accessories Come From The Laboratory
- ☐ Test Accessories Come From The Manufacturer

No	. Equipment	Manufacturer	Model No.	Specification Information	Cable
1	Adapter	Chongqing Lianmao Electronics Co.,Ltd.		Input: AC 100-240V 50/60Hz, 0.35A Output: DC 5V 2A	1.0m unshielded
2	Guangdong		F50114MA	DC 7.6V 2500mAh	



Page 12 of 37

4.5 Summary of Test Results

Item	FCC Rules	Description of Test	Result
1	§15.203	Antenna Equipment	Pass
2	15.225(a)(b)(c)	Field Strength of Fundamental	Pass
3	§15.209	Radiated Spurious Emissions	Pass
4	§15.215(c)	20dB Bandwidth	Pass
5	§15.205(a)	Restricted Bands of Operation	Pass
6	§15.225(e)	Frequency Stability	Pass
7	§15.207	AC Power Line Conducted Emission	Pass



Page 13 of 37

5. Description of Test Modes

	Summary table of Test Cases				
Test Item	Equipment category / Modulation				
iest item	Near Field Communication / ASK				
Radiated & Conducted Test Cases	Mode 1: NFC TX _13.56 MHz (Connect adapter)				
AC Conducted Emission	Mode 2: NFC TX _13.56 MHz (Connect adapter)				

Note:

- 1. Only the result of the worst case was recorded in the report, if no other cases.
- 2. The battery is full-charged during the test.
- 3. For Radiated Emission, 3axis were chosen for testing for each applicable mode.
- 4. For Conducted Test method, a temporary antenna connector is provided by the manufacture.



Page 14 of 37

6. Field Strength of Fundamental

6.1 Provisions Applicable

Rules and specifications	FCC CFR 47 Part 15 section 15.225					
Description	Compliance with the spectrum mask is tested with RBW set to 9kHz.					
Freq. of Emission (MHz)	Field Strength (µV/m) at 30m	Field Strength (dBµV/m) at 30m	Field Strength (dBµV/m) at 10m	Field Strength (dBµV/m) at 3m		
1.705~13.110	30	29.5	48.58	69.5		
13.110~13.410	106	40.5	59.58	80.5		
13.410~13.553	334	50.5	69.58	90.5		
13.553~13.567	15848	84.0	103.08	124.0		
13.567~13.710	334	50.5	69.58	90.5		
13.710~14.010	106	40.5	59.58	80.5		
14.010~30.000	30	29.5	48.58	69.5		

6.2 Measurement Procedure

- The EUT was placed on the top of the turntable 0.8 or 1.5 meter above ground. The phase center of the receiving antenna mounted on the top of a height-variable antenna tower was placed 3 meters far away from the turntable.
- Power on the EUT and all the supporting units. The turntable was rotated by 360 degrees to determine the position of the highest radiation.
- 3. The height of the broadband receiving antenna was varied between one meter and four meters above ground to find the maximum emissions field strength of both horizontal and vertical polarization.
- 4. For each suspected emission, the antenna tower was scan (from 1 M to 4 M) and then the turntable was rotated (from 0 degree to 360 degrees) to find the maximum reading.
- Set the test-receiver system to Peak or CISPR quasi-peak Detect Function with specified bandwidth under Maximum Hold Mode.
- 6. For emissions above 1GHz, use 1MHz RBW and 3MHz VBW for peak reading. Place the measurement antenna away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response. The measurement antenna may have to be higher or lower than the EUT, depending on the radiation pattern of the emission and staying aimed at the emission source for receiving the maximum signal. The final measurement antenna elevation shall be that which maximizes the emissions. The measurement antenna elevation for maximum emissions shall be restricted to a range of heights of from 1 m to 4 m above the ground or reference ground plane.
- 7. When the radiated emissions limits are expressed in terms of the average value of the emissions, and pulsed operation is employed, the measurement field strength shall be determined by averaging over one complete pulse train, including blanking intervals, as long as the pulse train does not exceed 0.1 seconds. As an alternative (provided the transmitter operates for longer than 0.1 seconds) or in cases where the



Report No.: AGC01689240814FR06 Page 15 of 37


pulse train exceeds 0.1 seconds, the measured field strength shall be determined from the average absolute voltage during a 0.1 second interval during which the field strength is at its maximum values.

- 8. If the emissions level of the EUT in peak mode was 3 dB lower than the average limit specified, then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions which do not have 3 dB margin will be repeated one by one using the quasi-peak method for below 1GHz.
- 9. For testing above 1GHz, the emissions level of the EUT in peak mode was lower than average limit (that means the emissions level in peak mode also complies with the limit in average mode), then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.
- 10. In case the emission is lower than 30MHz, loop antenna has to be used for measurement and the recorded data should be QP measured by receiver. High Low scan is not required in this case.

The following table is the setting of spectrum analyzer and receiver.

Spectrum Parameter	Setting		
Start ~Stop Frequency	9kHz~150kHz/RB 200Hz for QP		
Start ~Stop Frequency	150kHz~30MHz/RB 9kHz for QP		
Start ~Stop Frequency	30MHz~1000MHz/RB 120kHz for QP		
Start ~Stop Frequency	1GHz~26.5GHz		
Start ~Stop i requerity	1MHz/3MHz for Peak, 1MHz/3MHz for Average		


Receiver Parameter	Setting		
Start ~Stop Frequency	9kHz~150kHz/RB 200Hz for QP		
Start ~Stop Frequency	150kHz~30MHz/RB 9kHz for QP		
Start ~Stop Frequency	30MHz~1000MHz/RB 120kHz for QP		







6.3 Measurement Setup (Block Diagram of Configuration)

Radiated Emission Test Setup 9kHz-30MHz



Radiated Emission Test Setup 30MHz-1000MHz









6.4 Measurement Result

EUT Name	AI POS Terminal	Model Name	P8 Neo
Temperature	22.4° C	Relative Humidity	58.8%
Pressure	960hPa	Test Voltage	DC 7.6V by battery
Test Mode	Mode 1	Antenna Polarity	Face




No. Mk	. Freq.	Reading Level	Correct Factor	Measure- ment	Limit	Over	
	MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector
1	12.8300	-2.66	23.03	20.37	69.50	-49.13	peak
2	13.5579	39.74	23.32	63.06	124.0	-60.94	peak
3 *	14.2300	-0.74	23.49	22.75	69.50	-46.75	peak

RESULT: Pass





EUT Name	AI POS Terminal	Model Name	P8 Neo
Temperature	22.4° C	Relative Humidity	58.8%
Pressure	960hPa	Test Voltage	DC 7.6V by battery
Test Mode	Mode 1	Antenna Polarity	Side



No. N	/lk. Freq.	Reading Level		Measure- ment	Limit	Over	
	MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector
1	12.9920	-3.25	23.10	19.85	69.50	-49.65	peak
2	13.5600	38.83	23.32	62.15	124.0	-61.85	peak
3 *	14.2780	-2.29	23.49	21.20	69.50	-48.30	peak

RESULT: Pass

- 1. Factor=Antenna Factor + Cable loss, Margin=Measurement-Limit.
- 2. The "Factor" value can be calculated automatically by software of measurement system.



Page 19 of 37

7. Radiated Spurious Emissions

7.1 Provisions Applicable

According to 15.35, on any frequency or frequencies below or equal to 1000 MHz, the limits Shown are based on measuring equipment employing a CISPR quasi-peak detector function and related measurement bandwidths, unless otherwise specified the limit on peak radio frequency emissions is 20dB above the maximum permitted average emission limit applicable to the equipment under test.

The field strength of any emissions which appear outside of 13.110 ~14.010MHz band shall not exceed the general radiated emissions limits.

15.209 Limit in the below table has to be followed:

Frequency	Distance	Field Strengths Limit			
(MHz)	Meters	μV/m	dB(μV)/m		
0.009 ~ 0.490	0.009 ~ 0.490 300				
0.490 ~ 1.705 30		24000/F(kHz)			
1.705 ~ 30	30	30			
30 ~ 88	3	100	40.0		
88 ~ 216	3	150	43.5		
216 ~ 960	3	200	46.0		
960 ~ 1000	3	500	54.0		
Above 1000	3	74.0 dB(μV)/m (Peak) 54.0 dB(μV)/m (Average)			

Remark:

- (1) Emission level $dB\mu V = 20 \log Emission level \mu V/m$
- (2) The smaller limit shall apply at the cross point between two frequency bands.
- (3) Distance is the distance in meters between the measuring instrument, antenna and the closest point of any part of the device or system.

Note: All modes were tested for restricted band radiated emission, the test records reported below are the worst result compared to other modes.



Page 20 of 37

7.2 Measurement Procedure

- 1. The EUT was placed on the top of the turntable 0.8 or 1.5 meter above ground. The phase center of the receiving antenna mounted on the top of a height-variable antenna tower was placed 3 meters far away from the turntable.
- 2. Power on the EUT and all the supporting units. The turntable was rotated by 360 degrees to determine the position of the highest radiation.
- 3. The height of the broadband receiving antenna was varied between one meter and four meters above ground to find the maximum emissions field strength of both horizontal and vertical polarization.
- 4. For each suspected emission, the antenna tower was scan (from 1 M to 4 M) and then the turntable was rotated (from 0 degree to 360 degrees) to find the maximum reading.
- Set the test-receiver system to Peak or CISPR quasi-peak Detect Function with specified bandwidth under Maximum Hold Mode.
- 6. For emissions above 1GHz, use 1MHz RBW and 3MHz VBW for peak reading. Place the measurement antenna away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response. The measurement antenna may have to be higher or lower than the EUT, depending on the radiation pattern of the emission and staying aimed at the emission source for receiving the maximum signal. The final measurement antenna elevation shall be that which maximizes the emissions. The measurement antenna elevation for maximum emissions shall be restricted to a range of heights of from 1 m to 4 m above the ground or reference ground plane.
- 7. When the radiated emissions limits are expressed in terms of the average value of the emissions, and pulsed operation is employed, the measurement field strength shall be determined by averaging over one complete pulse train, including blanking intervals, as long as the pulse train does not exceed 0.1 seconds. As an alternative (provided the transmitter operates for longer than 0.1 seconds) or in cases where the pulse train exceeds 0.1 seconds, the measured field strength shall be determined from the average absolute voltage during a 0.1 second interval during which the field strength is at its maximum values.
- 8. If the emissions level of the EUT in peak mode was 3 dB lower than the average limit specified, then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions which do not have 3 dB margin will be repeated one by one using the quasi-peak method for below 1GHz.
- 9. For testing above 1GHz, the emissions level of the EUT in peak mode was lower than average limit (that means the emissions level in peak mode also complies with the limit in average mode), then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.
- 10. In case the emission is lower than 30MHz, loop antenna has to be used for measurement and the recorded data should be QP measured by receiver. High Low scan is not required in this case.




Report No.: AGC01689240814FR06 Page 21 of 37

The following table is the setting of spectrum analyzer and receiver.

Spectrum Parameter	Setting
Start ~Stop Frequency	9kHz~150kHz/RB 200Hz for QP
Start ~Stop Frequency	150kHz~30MHz/RB 9kHz for QP
Start ~Stop Frequency	30MHz~1000MHz/RB 120kHz for QP
Start ~Stop Frequency	1GHz~26.5GHz 1MHz/3MHz for Peak, 1MHz/3MHz for Average


Receiver Parameter	Setting
Start ~Stop Frequency	9kHz~150kHz/RB 200Hz for QP
Start ~Stop Frequency	150kHz~30MHz/RB 9kHz for QP
Start ~Stop Frequency	30MHz~1000MHz/RB 120kHz for QP






7.3 Measurement Setup (Block Diagram of Configuration)

Radiated Emission Test Setup 9kHz-30MHz



Radiated Emission Test Setup 30MHz-1000MHz





Page 23 of 37


7.4 Measurement Result

Radiated Emission From 9kHz to 30MHz

The amplitude of spurious emissions from 9kHz to 30MHz which are attenuated more than 20 dB below the permissible value need not be reported.


Radiated Emission From 30MHz to 1000MHz

EUT Name	AI POS Terminal	Model Name	P8 Neo
Temperature	22.8° C	Relative Humidity	57.9%
Pressure	960hPa	Test Voltage	DC 7.6V by battery
Test Mode	Mode 1	Antenna Polarity	Horizontal




No.	Mk.	Freq.	Reading Level	Correct Factor	Measure- ment	Limit	Over	,
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector
1	*	0.0106	7.56	43.27	50.83	126.89	-76.06	peak
2		0.0158	5.05	40.34	45.39	123.45	-78.06	peak
3		0.0238	2.46	37.09	39.55	119.91	-80.36	peak
4		0.0354	1.03	34.96	35.99	116.48	-80.49	peak
5		0.0651	-2.95	32.87	29.92	111.22	-81.30	peak
6		0.0991	-7.71	32.14	24.43	107.06	-83.17	peak

RESULT: PASS





EUT Name	AI POS Terminal	Model Name	P8 Neo
Temperature	22.8° C	Relative Humidity	57.9%
Pressure	960hPa	Test Voltage	DC 7.6V by battery
Test Mode	Mode 1	Antenna Polarity	Vertical



	MHz .0100	dBuV	dB (dBuV/m	dBuV/m	4D	
	.0100	2 22				dB	Detector
2 0.		3.22	43.60	46.82	127.40	-80.58	peak
	.0156	1.06	40.45	41.51	123.56	-82.05	peak
3 0.	.0240	0.62	37.05	37.67	119.84	-82.17	peak
4 0.	.0417 -	-0.61	34.23	33.62	115.07	-81.45	peak
5 0.	.0650 -	-1.02	32.87	31.85	111.24	-79.39	peak
6 * 0	.1307 -	-2.17	32.29	30.12	105.12	-75.09	peak


RESULT: PASS



Report No.: AGC01689240814FR06 Page 25 of 37


The Magnetic Field From 150kHz-30MHz

EUT	AI POS Terminal	Model Name	P8 Neo
Temperature	22.8° C	Relative Humidity	57.9%
Pressure	960hPa	Test Voltage	DC 7.6V by battery
Test Mode	Mode 1	Antenna	Face




No. Mk.	Freq.	Reading Level	Correct Factor	Measure- ment	Limit	Over	,
	MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector
1	0.2366	8.27	32.57	40.84	100.0	-59.24	peak
2	0.4994	6.77	32.21	38.98	73.63	-34.65	peak
3 *	1.1111	9.01	31.95	40.96	66.69	-25.73	peak
4	2.8540	9.46	31.27	40.73	69.54	-28.81	peak
5	10.2332	9.39	29.81	39.20	69.54	-30.34	peak
6	13.5600	12.96	29.91	42.87	69.54	-26.67	peak

RESULT: PASS





EUT	AI POS Terminal	Model Name	P8 Neo
Temperature	22.8° C	Relative Humidity	57.9%
Pressure	960hPa	Test Voltage	DC 7.6V by battery
Test Mode	Mode 1	Antenna	Side



No. Mk	. Freq.	Reading Level	Correct Factor	Measure- ment	Limit	Over	
	MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector
1	0.2174	8.50	32.62	41.12	100.8	-59.69	peak
2	1.1114	8.01	31.95	39.96	66.69	-26.73	peak
3	2.8541	7.96	31.27	39.23	69.54	-30.31	peak
4	5.6234	9.00	28.92	37.92	69.54	-31.62	peak
5	10.2332	8.89	29.81	38.70	69.54	-30.84	peak
6 *	13.5600	13.46	29.91	43.37	69.54	-26.17	peak

RESULT: PASS



Page 27 of 37

RADIATED EMISSION FROM 30MHz ~1000MHz

EUT		AI POS	Terminal		Model N	ame	P8 Ne	0						
Tempera	ture	22.8° (22.8° C Relative Humidity				22.8° C Relative Humidity			22.8° C Relative			57.9%	
Pressure	•	960hPa	a		Test Volt	age	DC 7.6	6V by battery						
Test Mod	de	Mode 1			Antenna	1	Horizo	Horizontal						
	130			FCC Part 1	5C									
	120													
	110													
	90													
	80													
(/w/m]	70													
70 60 50 Fenencial														
Leve	50													
	30	2		3			, Ja	as officered the						
	20			my many	man man	and a supplemental property and the supplemental property and supplemental property and the supplemental property and the supp	Wight agree har with the same							
	10				•									
	0													
	-10 30M		100M			1		1G						
				Frequency[Hz]									
_	— QP Limit# QP Detector	Horizontal PK												
NO.	Freq. [MHz]	Level [dBµV/m]	Factor [dB]	Limit [dBµV/m]	Margin [dB]	Height [cm]	Angle [°]	Polarity						
1	34.85	29.58	11.83	40.00	10.42	100	200	Horizontal						
2	50.37	27.98	15.31	40.00	12.02	100	70	Horizontal						
3	106.63	32.22	16.72	43.50	11.28	100	260	Horizontal						
4	460.68	30.69	24.60	46.00	15.31	100	290	Horizontal						
5	626.55	32.77	24.98	46.00	13.23	100	190	Horizontal						

46.00

8.03

100

280

Horizontal


RESULT: PASS

6

865.17

37.97

29.83





EUT	AI POS Terminal	Model Name	P8 Neo
Temperature	22.8° C	Relative Humidity	57.9%
Pressure	960hPa	Test Voltage	DC 7.6V by battery
Test Mode	Mode 1	Antenna	Vertical



NO.	Freq. [MHz]	Level [dBµV/m]	Factor [dB]	Limit [dBµV/m]	Margin [dB]	Height [cm]	Angle [°]	Polarity
1	35.82	31.62	11.52	40.00	8.38	100	220	Vertical
2	66.86	31.65	15.66	40.00	8.35	100	220	Vertical
3	103.72	32.70	16.88	43.50	10.80	100	50	Vertical
4	461.65	30.13	24.36	46.00	15.87	100	150	Vertical
5	623.64	32.90	25.40	46.00	13.10	100	140	Vertical
6	867.11	38.52	29.76	46.00	7.48	100	200	Vertical

RESULT: Pass

- 1. Factor=Antenna Factor + Cable loss, Margin= Limit-Measurement.
- 2. The "Factor" value can be calculated automatically by software of measurement system.
- 3. All test modes had been pre-tested. The mode 1 is the worst case and recorded in the report.



Page 29 of 37

8. 20dB Bandwidth Measurement

8.1 Provisions Applicable


Intentional radiators must be designed to ensure that the 20dB and 99% emission bandwidth in the specific band 13.553~13.567MHz.

8.2 Measurement Procedure

Set the parameters of SPA as below:

- The spectrum analyzer connected via a receive antenna placed near the EUT in peak Max hold mode.
- 2. Centre frequency = Operation Frequency
- 3. The resolution bandwidth of 10 kHz and the video bandwidth of 3 kHz were used.
- 4. Span: 60kHz, Sweep time: Auto
- 5. Set the EUT to continue transmitting mode. Allow the trace to stabilize. Use the "N dB down" function of SPA to define the bandwidth.
- 6. Measured the spectrum width with power higher than 20dB below carrier.
- 7. Measured the 99% OBW.
- 8. Record the plots and reported.

8.3 Measurement Setup (Block Diagram of Configuration)






Report No.: AGC01689240814FR06 Page 30 of 37

8.4 Measurement Result

Test Data of Bandwidth Measurement						
Test Channel (MHz)	Modulation	99% Occupied Bandwidth (kHz)	-20dB Bandwidth (kHz)	Limits (kHz)	Pass or Fail	
13.56	ASK	22.789	26.85	N/A	Pass	

Test Graphs of Occupied Bandwidth and -20dB Bandwidth





Page 31 of 37

9. Frequency Stability Measurement


9.1 Provisions Applicable

The frequency tolerance of the carrier signal shall be maintained within +/- 0.01% (100ppm) of the operating frequency over a temperature variation of -20 degrees to +50 degrees C at normal supply voltage, and for a variation in the primary supply voltage from 85% to 115% of the rated supply voltage at a temperature of 20 degrees C. For battery operated equipment, the equipment tests shall be performed using a new battery.

9.2 Measurement Procedure

- 1. The spectrum analyzer connected via a receive antenna placed near the EUT.
- 2. EUT have transmitted signal and fixed channelize.
- 3. Set the spectrum analyzer span to view the entire emissions bandwidth.
- 4. Set RBW = 1 kHz, VBW = 3 kHz with peak detector and max hold settings.
- 5. The fc is declaring of channel frequency. Then the frequency error formula is $(fc-f)/fc \times 106$ ppm and the limit is less than ± 100 ppm.
- 6. Extreme temperature rule is -20°C~50°C.

9.3 Measurement Setup (Block Diagram of Configuration)





Page 32 of 37

9.4 Measurement Result

Test Data of Frequency Stability Measurement								
Test Channel	Measurement	Conditions	Measurement Result	Limits				
(MHz)	Voltage (V)	Temperature (°C)	(ppm)	(ppm)	Pass or Fail			
		-20	45	±100	Pass			
		-10	51	±100	Pass			
	7.60	0	60	±100	Pass			
		10	58	±100	Pass			
		25	55	±100	Pass			
13.56		30	56	±100	Pass			
		40	57	±100	Pass			
		50	52	±100	Pass			
		25	54	±100	Pass			
	6.46	25	56	±100	Pass			
	8.74	25	51	±100	Pass			



Page 33 of 37

10. AC Power Line Conducted Emission Test


10.1 Measurement Limit

Fraguenay Danga	Maximum RF Line Voltage				
Frequency Range	Q.P. (dBµV)	Average (dBµV)			
150kHz~500kHz	66-56	56-46			
500kHz~5MHz	56	46			
5MHz~30MHz	60	50			

Note:

- 1. The lower limit shall apply at the transition frequency.
- 2. The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.50 MHz.

10.2 Measurement Setup (Block Diagram of Configuration)





Page 34 of 37

10.3 Preliminary Procedure of Line Conducted Emission Test

- 1. The equipment was set up as per the test configuration to simulate typical actual usage per the user's manual. When the EUT is a tabletop system, a wooden table with a height of 0.8 meters is used and is placed on the ground plane as per ANSI C63.10 (see Test Facility for the dimensions of the ground plane used). When the EUT is a floor-standing equipment, it is placed on the ground plane which has a 3-12 mm non-conductive covering to insulate the EUT from the ground plane.
- 2. Support equipment, if needed, was placed as per ANSI C63.10.
- 3. All I/O cables were positioned to simulate typical actual usage as per ANSI C63.10.
- 4. All support equipment received AC120V/60Hz power from a LISN, if any.
- 5. The EUT received DC 5V power from adapter which received AC120V/60Hz power from a LISN.
- 6. The test program was started. Emissions were measured on each current carrying line of the EUT using a spectrum Analyzer / Receiver connected to the LISN powering the EUT. The LISN has two monitoring points: Line 1 (Hot Side) and Line 2 (Neutral Side). Two scans were taken: one with Line 1 connected to Analyzer / Receiver and Line 2 connected to a 50 ohm load; the second scan had Line 1 connected to a 50 ohm load and Line 2 connected to the Analyzer / Receiver.
- 7. Analyzer / Receiver scanned from 150 kHz to 30MHz for emissions in each of the test modes.
- 8. During the above scans, the emissions were maximized by cable manipulation.
- 9. The test mode(s) were scanned during the preliminary test.


Then, the EUT configuration and cable configuration of the above highest emission level were recorded for reference of final testing.

10.4 Final Procedure of Line Conducted Emission Test

- 1. EUT and support equipment was set up on the test bench as per step 2 of the preliminary test.
- 2. A scan was taken on both power lines, Line 1 and Line 2, recording at least the six highest emissions. Emission frequency and amplitude were recorded into a computer in which correction factors were used to calculate the emission level and compare reading to the applicable limit. If EUT emission level was less 2dB to the A.V. limit in Peak mode, then the emission signal was re-checked using Q.P and Average detector.
- 3. The test data of the worst case condition(s) was reported on the Summary Data page.

10.5 Measurement Result





MEASUREMENT RESULT: "agc_fin"


2024/9/18 9:53	1					
Frequency MHz	Level dBµV	Transd dB	Limit dBµV	Margin dB	Detector	Line
0.478000	33.10	6.1	56	23.3	QP	L1
0.686000	24.60	6.2	56	31.4	QP	L1
0.978000	25.70	6.2	56	30.3	QP	L1
1.586000	23.30	6.2	56	32.7	QP	L1
1.706000	21.70	6.2	56	34.3	QP	L1
1.790000	22.10	6.2	56	33.9	OP	L1

MEASUREMENT RESULT: "agc fin2"

2024/9/18 9:5	1					
Frequency MHz	Level dBµV	Transd dB	Limit dBµV	Margin dB	Detector	Line
0.362000	17.90	6.1	49	30.8	AV	L1
0.474000	27.00	6.1	46	19.4	AV	L1
1.238000	17.30	6.2	46	28.7	AV	L1
2.138000	14.20	6.2	46	31.8	AV	L1
5.442000	10.40	6.4	50	39.6	AV	L1
21.442000	10.80	7.4	50	39.2	AV	L1

RESULT: Pass





RESULT: Pass



Page 37 of 37

Appendix I: Photographs of Test Setup

Refer to the Report No.: AGC01689240814AP01

Appendix II: Photographs of Test EUT

Refer to the Report No.: AGC01689240814AP02

----End of Report----



Conditions of Issuance of Test Reports

- 1. All samples and goods are accepted by the Attestation of Global Compliance (Shenzhen) Co., Ltd (the "Company") solely for testing and reporting in accordance with the following terms and conditions. The company provides its services on the basis that such terms and conditions constitute express agreement between the company and any person, firm or company requesting its services (the "Clients").
- 2. Any report issued by Company as a result of this application for testing services (the "Report") shall be issued in confidence to the Clients and the Report will be strictly treated as such by the Company. It may not be reproduced either in its entirety or in part and it may not be used for advertising or other unauthorized purposes without the written consent of the Company. The Clients to whom the Report is issued may, however, show or send it, or a certified copy thereof prepared by the Company to its customer, supplier or other persons directly concerned. The Company will not, without the consent of the Clients, enter into any discussion or correspondence with any third party concerning the contents of the Report, unless required by the relevant governmental authorities, laws or court orders.
- 3. The Company shall not be called or be liable to be called to give evidence or testimony on the Report in a court of law without its prior written consent, unless required by the relevant governmental authorities, laws or court orders.
- 4. In the event of the improper use of the report as determined by the Company, the Company reserves the right to withdraw it, and to adopt any other additional remedies which may be appropriate.
- 5. Samples submitted for testing are accepted on the understanding that the Report issued cannot form the basis of, or be the instrument for, any legal action against the Company.
- 6. The Company will not be liable for or accept responsibility for any loss or damage however arising from the use of information contained in any of its Reports or in any communication whatsoever about its said tests or investigations.
- 7.Clients wishing to use the Report in court proceedings or arbitration shall inform the Company to that effect prior to submitting the sample for testing.
- 8. The Company is not responsible for recalling the electronic version of the original report when any revision is made to them. The Client assumes the responsibility to providing the revised version to any interested party who uses them.
- 9. Subject to the variable length of retention time for test data and report stored hereinto as otherwise specifically required by individual accreditation authorities, the Company will only keep the supporting test data and information of the test report for a period of six years. The data and information will be disposed of after the aforementioned retention period has elapsed. Under no circumstances shall we provide any data and information which has been disposed of after retention period. Under no circumstances shall we be liable for damage of any kind, including (but not limited to) compensatory damages, lost profits, lost data, or any form of special, incidental, indirect, consequential or punitive damages of any kind, whether based on breach of contract of warranty, tort (including negligence), product liability or otherwise, even if we are informed in advance of the possibility of such damages.