



Shenzhen DEWEIMA Communication Equipment Co.,Ltd

SPECIFICATION SHEET FOR APPROVAL

CUSTOMER NAME	Shenzhen Subject Technology Co., Ltd.
CUSTOMER P/N	VFS335-PUS
PART NAME	BT Antenna
DWM NO.	
APPROVAL REV.	DWM-V1.0

CONTRACTOR			DATE : 2023-07-02
QA CHECKED	ME CHECKED	RF CHECKED	MANAGER CHECKED

CUSTOMER		DATE :
Approved By	Checked By	Prepared By

Content

1. Product Application	3
2. The test environment, equipment	3
3. BT Antenna description	6



Product Specification

P/N:

BT Antenna

Rev.:

A


Page:

3/10

1. Product Application

Terminal of the antenna products can only be used for BT antenna.

2. The test environment, equipment

Item	Description	Test Condition	Requirement
2.1	Passive testing	The VSWR measurement devices are connected in sequence: Agilent5071B Network Analyzer → measurement Cable → Customer-providing Devices.	VSWR: 2400-2500MHz ≤ 2
		Test equipment	
			
Item	Description	Test Condition	
2.2	Active test	The antenna is tested within the cell mainboard provided by clients. Follow picture shows the measurement condition of the antenna been put on the measurement device, which is used for all measurement of electric performances.	
2.3	Microwave	Test equipment	



Product Specification

P/N:

BT Antenna



Rev.:

A

Page:

4/10

Anechoic
chamber
(Satimo&ETS
)





Product Specification

P/N:

BT Antenna


Rev.:

A

Page:

5/10

CMW500
Agilent5071B
2.4 AgilentE4405B
Agilent8960





Product Specification

P/N:

BT Antenna

Rev.:

A

Page:

6/10

3. BT Antenna description

3.1 BT Technology Parameters

BT Frequency Range: 2400MHz-2500MHz


BT antenna type: IFA Antenna (PCB Antenna)

Operating Humidity: 90% R.H.MAX

Temperature Rating: 0°C ~ +40°C


3.2 BT matching circuit

Element	Value
E1(0402)	NC
E2(0402)	1.2nH
E3(0402)	NC
Parameter not changed	



3.3 BT antenna position

3.4 BT VSWR/Return Loss/Smith:





Product Specification

P/N:


BT Antenna

Rev.:

A

Page:

7/10



3.5 BT Efficiency And Gain:

Frequency/Mhz	Efficiency / %	MaxGain/dBi
2400	40.27	2.12
2410	38.9	1.98
2420	41.02	2.59
2430	41.98	2.81
2440	41.11	2.08
2450	43.35	2.18
2460	44.36	2.26
2470	43.25	1.89
2480	43.85	1.89
2490	44.67	2.35
2500	41.59	1.87

3.6. BT 3D Pattern 2400MHz



Product Specification

P/N:


BT Antenna

Rev.:


A

Page:

8/10



2450MHz



2500MHz



Product Specification

P/N:


BT Antenna

Rev.:


A

Page:


9/10



3.7 BT Engineering drawings:



Professional RF R&D institutions



Thank You !

公司地址: 深圳市宝安23区创业二路友谊大厦1栋3楼 邮编: 518101
3rd Floor,first unit,Friendships Building,Chuangye 2rd Road,Baoan
23 district,Shenzhen,China Post NO:518101
TEL: 0755-27885759 FAX: 0755-27885739
E-mail: 2880181958@qq.com