



Maximum Permissible Exposure Report

1. Product Information

FCC ID	: 2A2VW-C2E
EUT	: AOSU IndoorCam P1
Test Model	: C2E2BH11
Additional Model No.	: C2E2BH12,C2E2BH13,C2E2BH14,C2E2BH15,C2E2BH16,C2E2BH17 ,C2E2BH18,C2L2BH11,C2L2BH12,C2L2BH13,C2L2BH14,C2L2BH15, C2L2BH16,C2L2BH17,C2P2BH11,C2P2BH12,C2P2BH13,C2P2BH14, C2P2BH15,C2P2BH16,C2P2BH17
Model Declaration	: PCB board, structure and internal of these model(s) are the same, So no additional models were tested Input: 5V $\overline{=}$ 1A
Power Supply	: For Adapter Input: 100-240V~, 50/60Hz, 0.2A MAX Adapter Output: 5.0V $\overline{=}$ 1.0A
Hardware Version	: /
Software Version	: /
WIFI(2.4G Band)	:
Frequency Range	: 2412 – 2462 MHz
Channel Number	: 11 Channels for 20MHz bandwidth (2412~2462MHz) 7 Channels for 40MHz bandwidth (2422~2452MHz)
Channel Spacing	: 5MHz
Modulation Type	: IEEE 802.11b: DSSS (CCK, DQPSK, DBPSK) IEEE 802.11g: OFDM (64QAM, 16QAM, QPSK, BPSK) IEEE 802.11n: OFDM (64QAM, 16QAM,QPSK,BPSK)
Antenna Description	: Internal Antenna, 2.34dBi (max.)
5G WLAN	:
Frequency Range	: 5180-5240MHz, 5260-5320MHz, 5500-5700MHz 4 Channels for 20MHz bandwidth(5180MHz-5240MHz) 4 Channels for 20MHz bandwidth(5260MHz-5320MHz) 11 Channels for 20MHz bandwidth(5500MHz-5700MHz) 2 channels for 40MHz bandwidth(5190MHz~5230MHz)
Channel Number	: 2 channels for 40MHz bandwidth(5270MHz~5310MHz) 5 Channels for 40MHz bandwidth(5510MHz-5670MHz) 1 channels for 80MHz bandwidth(5210MHz) 1 channels for 80MHz bandwidth(5290MHz) 2 Channels for 80MHz bandwidth(5530MHz, 5610MHz)
Modulation Type	: IEEE 802.11a/n/ac: OFDM (256QAM, 64QAM, 16QAM, QPSK, BPSK)
Antenna Description	: Internal Antenna, 1.54dBi (max.)
5.8G WLAN	:
Frequency Range	: 5745MHz-5825MHz





Channel Number	: 5 channels for 20MHz bandwidth (5745-5825MHz) : 2 channels for 40MHz bandwidth (5755~5795MHz) : 1 channels for 80MHz bandwidth (5775MHz)
Modulation Type	: IEEE 802.11a/n/ac: OFDM (256QAM, 64QAM, 16QAM, QPSK, BPSK)
Antenna Description	: Internal Antenna, 1.54dBi (max.)
DFS Operation Mode	: <input type="checkbox"/> Master <input type="checkbox"/> Client with Radar detection capability <input checked="" type="checkbox"/> Client without radar detection capability
Exposure category	: General population/uncontrolled environment
EUT Type	: Production Unit
Device Type	: Mobile Device

2. Evaluation Method

Systems operating under the provisions of FCC 47 CFR section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines. In accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091 this device has been defined as mobile device whereby a distance of 0.2m normally can be maintained between the user and the device, and below RF Permissible Exposure limit shall comply with.

In accordance with KDB447498D01 for Simultaneous transmission MPE test exclusion applies when the sum of the MPE ratios for all simultaneous transmitting antennas incorporated in a host device, based on the calculated/estimated, numerically modelled or measured field strengths or power density, is ≤ 1.0 . The MPE ratio of each antenna is determined at the minimum test separation distance required by the operating configurations and exposure conditions of the host device, according to the ratio of field strengths or power density to MPE limit, at the test frequency. Either the maximum peak or spatially averaged results from measurements or numerical simulations may be used to determine the MPE ratios. Spatial averaging does not apply when MPE is estimated using simple calculations based on far-field plane-wave equivalent conditions. The antenna installation and operating requirements for the host device must meet the minimum test separation distances required by all antennas, in both standalone and simultaneous transmission operations, to satisfy compliance.

3. Limit

3.1 Refer Evaluation Method

[ANSI C95.1-2019](#): IEEE Standard for Safety Levels with Respect to Human Exposure to Electric, Magnetic, and Electromagnetic Fields, 0 Hz to 300 GHz

[FCC KDB publication 447498 D01 General 1 RF Exposure Guidance v06](#): Mobile and Portable Devices RF Exposure Procedures and Equipment Authorization Policies.

[FCC CFR 47 part1 1.1310](#): Radiofrequency radiation exposure limits.

[FCC CFR 47 part2 2.1091](#): Radiofrequency radiation exposure evaluation: mobile devices.





3.2 Limit

Limits for Maximum Permissible Exposure (MPE)/Controlled Exposure

Frequency Range(MHz)	Electric Field Strength(V/m)	Magnetic Field Strength(A/m)	Power Density (mW/cm ²)	Averaging Time (minute)
Limits for Occupational/Controlled Exposure				
0.3 – 3.0	614	1.63	(100) *	6
3.0 – 30	1842/f	4.89/f	(900/f ²)*	6
30 – 300	61.4	0.163	1.0	6
300 – 1500	/	/	f/300	6
1500 – 100,000	/	/	5	6

Limits for Maximum Permissible Exposure (MPE)/Uncontrolled Exposure

Frequency Range(MHz)	Electric Field Strength(V/m)	Magnetic Field Strength(A/m)	Power Density (mW/cm ²)	Averaging Time (minute)
Limits for Occupational/Uncontrolled Exposure				
0.3 – 3.0	614	1.63	(100) *	30
3.0 – 30	824/f	2.19/f	(180/f ²)*	30
30 – 300	27.5	0.073	0.2	30
300 – 1500	/	/	f/1500	30
1500 – 100,000	/	/	1.0	30

F=frequency in MHz

*=Plane-wave equivalent power density

4. MPE Calculation Method

Predication of MPE limit at a given distance
Equation from page 18 of OET Bulletin 65, Edition 97-01

$$S=PG/4\pi R^2$$

- Where: S=power density
- P=power input to antenna
- G=power gain of the antenna in the direction of interest relative to an isotropic radiator
- R=distance to the center of radiation of the antenna

5. Antenna Information

Internal Antenna can only use antennas certificated as follows provided by manufacturer;

Internal/External Identification	Antenna type and antenna number	Operate frequency band	Maximum antenna gain	Notes
Antenna	Internal Antenna	2400-2483.5 MHz	2.34 dBi	WIFI Antenna
Antenna	Internal Antenna	5000-6000 MHz	1.54 dBi	WIFI Antenna



**6. Conducted Power***[2.4G WLAN]*

Mode	Channel	Frequency (MHz)	Peak Conducted Output Power (dBm)
IEEE 802.11b	1	2412	15.80
	6	2437	15.79
	11	2462	15.45
IEEE 802.11g	1	2412	14.94
	6	2437	14.46
	11	2462	14.21
IEEE 802.11n HT20	1	2412	13.21
	6	2437	13.93
	11	2462	13.70
IEEE 802.11n HT40	3	2422	13.05
	6	2437	12.97
	9	2462	12.70

[5.2GHz WLAN]

Mode	Channel	Frequency (MHz)	Average Conducted Output Power (dBm)
IEEE 802.11a	36	5180	12.10
	44	5220	12.10
	48	5240	12.22
IEEE 802.11n HT20	36	5180	11.95
	44	5220	12.05
	48	5240	12.01
IEEE 802.11n HT40	38	5190	11.90
	46	5230	12.17
IEEE 802.11ac VHT20	36	5180	12.10
	44	5220	11.98
	48	5240	11.40
IEEE 802.11ac VHT40	38	5190	11.45
	46	5230	11.61
IEEE 802.11ac VHT80	42	5210	11.65



[5.3GHz WLAN]

Mode	Channel	Frequency (MHz)	Average Conducted Output Power (dBm)
IEEE 802.11a	52	5260	11.50
	60	5280	11.78
	64	5320	12.01
IEEE 802.11n HT20	52	5260	11.38
	60	5280	11.59
	64	5320	11.85
IEEE 802.11n HT40	54	5270	11.43
	62	5310	11.75
IEEE 802.11ac VHT20	52	5260	11.38
	60	5280	11.60
	64	5320	11.89
IEEE 802.11ac VHT40	54	5270	11.53
	62	5310	11.78
IEEE 802.11ac VHT80	58	5290	11.59

[5.5GHz WLAN]

Mode	Channel	Frequency (MHz)	Average Conducted Output Power (dBm)
IEEE 802.11a	100	5500	8.54
	116	5580	8.60
	140	5700	8.64
IEEE 802.11n HT20	100	5500	8.50
	116	5580	7.85
	140	5700	8.00
IEEE 802.11n HT40	102	5510	7.91
	110	5550	8.06
	134	5670	7.92
IEEE 802.11ac VHT20	100	5500	7.75
	116	5580	7.77
	140	5700	7.98
IEEE 802.11ac VHT40	102	5510	7.78
	110	5550	7.97
	134	5670	7.89
IEEE 802.11ac VHT80	106	5530	8.05
	122	5610	8.02



Shenzhen LCS Compliance Testing Laboratory Ltd.

Add: 101, 201 Bldg A & 301 Bldg C, Juji Industrial Park Yabianxueziwei, Shajing Street, Baoan District, Shenzhen, 518000, China

Tel: +(86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com

Scan code to check authenticity

**[5.8GHz WLAN]**

Mode	Channel	Frequency (MHz)	Average Conducted Output Power (dBm)
IEEE 802.11a	149	5745	10.26
	157	5785	10.60
	165	5825	10.66
IEEE 802.11n HT20	149	5745	10.03
	157	5785	10.39
	165	5825	10.50
IEEE 802.11n HT40	151	5755	10.18
	159	5795	10.42
IEEE 802.11ac VHT20	149	5745	10.05
	157	5785	10.35
	165	5825	10.45
IEEE 802.11ac VHT40	151	5755	10.12
	159	5795	10.39
IEEE 802.11ac VHT80	155	5775	10.37

7. Manufacturing Tolerance

IEEE 802.11b(Peak)			
Channel	Channel 01	Channel 06	Channel 11
Target (dBm)	15.0	15.0	15.0
Tolerance ± (dB)	1.0	1.0	1.0
IEEE 802.11g(Peak)			
Channel	Channel 01	Channel 06	Channel 11
Target (dBm)	14.0	14.0	14.0
Tolerance ± (dB)	1.0	1.0	1.0
IEEE 802.11n20(Peak)			
Channel	Channel 01	Channel 06	Channel 11
Target (dBm)	13.0	13.0	13.0
Tolerance ± (dB)	1.0	1.0	1.0
IEEE 802.11n40(Peak)			
Channel	Channel 03	Channel 06	Channel 09
Target (dBm)	13.0	12.0	12.0
Tolerance ± (dB)	1.0	1.0	1.0



Shenzhen LCS Compliance Testing Laboratory Ltd.

Add: 101, 201 Bldg A & 301 Bldg C, Juji Industrial Park Yabianxueziwei, Shajing Street, Baoan District, Shenzhen, 518000, China

Tel: +(86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com

Scan code to check authenticity



[5.2GHz WLAN]			
<i>IEEE 802.11a (Average)</i>			
Channel	Channel 36	Channel 40	Channel 48
Target (dBm)	12.0	12.0	12.0
Tolerance ± (dB)	1.0	1.0	1.0
<i>IEEE 802.11n HT20 (Average)</i>			
Channel	Channel 36	Channel 40	Channel 48
Target (dBm)	11.0	12.0	12.0
Tolerance ± (dB)	1.0	1.0	1.0
<i>IEEE 802.11n HT40 (Average)</i>			
Channel	Channel 38	Channel 46	
Target (dBm)	11.0	12.0	
Tolerance ± (dB)	1.0	1.0	
<i>IEEE 802.11ac VHT20 (Average)</i>			
Channel	Channel 36	Channel 40	Channel 48
Target (dBm)	12.0	11.0	11.0
Tolerance ± (dB)	1.0	1.0	1.0
<i>IEEE 802.11ac VHT40 (Average)</i>			
Channel	Channel 38	Channel 46	
Target (dBm)	11.0	11.0	
Tolerance ± (dB)	1.0	1.0	
<i>IEEE 802.11ac VHT80(Average)</i>			
Channel	Channel 42		
Target (dBm)	11.0		
Tolerance ± (dB)	1.0		





[5.3GHz WLAN]			
<i>IEEE 802.11a (Average)</i>			
Channel	Channel 52	Channel 60	Channel 64
Target (dBm)	11.0	11.0	12.0
Tolerance ± (dB)	1.0	1.0	1.0
<i>IEEE 802.11n HT20 (Average)</i>			
Channel	Channel 52	Channel 60	Channel 64
Target (dBm)	11.0	11.0	11.0
Tolerance ± (dB)	1.0	1.0	1.0
<i>IEEE 802.11n HT40 (Average)</i>			
Channel	Channel 54	Channel 62	
Target (dBm)	11.0	11.0	
Tolerance ± (dB)	1.0	1.0	
<i>IEEE 802.11ac VHT20 (Average)</i>			
Channel	Channel 52	Channel 60	Channel 64
Target (dBm)	11.0	11.0	11.0
Tolerance ± (dB)	1.0	1.0	1.0
<i>IEEE 802.11ac VHT40 (Average)</i>			
Channel	Channel 54	Channel 62	
Target (dBm)	11.0	11.0	
Tolerance ± (dB)	1.0	1.0	
<i>IEEE 802.11ac VHT80(Average)</i>			
Channel	Channel 58		
Target (dBm)	11.0		
Tolerance ± (dB)	1.0		





[5.5GHz WLAN]			
<i>IEEE 802.11a (Average)</i>			
Channel	Channel 100	Channel 116	Channel 140
Target (dBm)	8.0	8.0	8.0
Tolerance ± (dB)	1.0	1.0	1.0
<i>IEEE 802.11n HT20 (Average)</i>			
Channel	Channel 100	Channel 116	Channel 140
Target (dBm)	8.0	7.0	8.0
Tolerance ± (dB)	1.0	1.0	1.0
<i>IEEE 802.11n HT40 (Average)</i>			
Channel	Channel 102	Channel 110	Channel 134
Target (dBm)	7.0	8.0	7.0
Tolerance ± (dB)	1.0	1.0	1.0
<i>IEEE 802.11ac VHT20 (Average)</i>			
Channel	Channel 100	Channel 116	Channel 140
Target (dBm)	7.0	7.0	7.0
Tolerance ± (dB)	1.0	1.0	1.0
<i>IEEE 802.11ac HT40 (Average)</i>			
Channel	Channel 102	Channel 110	Channel 134
Target (dBm)	7.0	7.0	7.0
Tolerance ± (dB)	1.0	1.0	1.0
<i>IEEE 802.11ac VHT80(Average)</i>			
Channel	Channel 106	Channel 122	
Target (dBm)	8.0	8.0	
Tolerance ± (dB)	1.0	1.0	





[5.8GHz WLAN]			
<i>IEEE 802.11a (Average)</i>			
Channel	Channel 149	Channel 157	Channel 165
Target (dBm)	10.0	10.0	10.0
Tolerance ± (dB)	1.0	1.0	1.0
<i>IEEE 802.11n HT20 (Average)</i>			
Channel	Channel 149	Channel 157	Channel 165
Target (dBm)	10.0	10.0	10.0
Tolerance ± (dB)	1.0	1.0	1.0
<i>IEEE 802.11n HT40 (Average)</i>			
Channel	Channel 151	Channel 159	
Target (dBm)	10.0	10.0	
Tolerance ± (dB)	1.0	1.0	
<i>IEEE 802.11ac VHT20 (Average)</i>			
Channel	Channel 149	Channel 157	Channel 165
Target (dBm)	10.0	10.0	10.0
Tolerance ± (dB)	1.0	1.0	1.0
<i>IEEE 802.11ac VHT40 (Average)</i>			
Channel	Channel 151	Channel 159	
Target (dBm)	10.0	10.0	
Tolerance ± (dB)	1.0	1.0	
<i>IEEE 802.11ac VHT80(Average)</i>			
Channel	Channel 155		
Target (dBm)	10.0		
Tolerance ± (dB)	1.0		





8. Measurement Results

8.1 Standalone MPE Evaluation

As declared by the Applicant, the EUT is a wireless device used in a fix application, at least 20 cm from any body part of the user or nearby persons; from the maximum EUT RF output power, the minimum separation distance, $r = 20\text{cm}$, as well as the gain of the used antenna refer to antenna information, the RF power density can be obtained.

[2.4GWLAN]

Modulation Type	Output power		Antenna Gain (dBi)	Antenna Gain (linear)	MPE (mW/cm^2)	MPE Limits (mW/cm^2)
	dBm	mW				
IEEE 802.11b	16.0	39.8107	2.34	1.7140	0.0136	1.0000
IEEE 802.11g	15.0	31.6228	2.34	1.7140	0.0108	1.0000
IEEE 802.11n HT20	14.0	25.1189	2.34	1.7140	0.0086	1.0000
IEEE 802.11n HT40	14.0	25.1189	2.34	1.7140	0.0086	1.0000

[5.2GHz WLAN]

Modulation Type	Output power		Antenna Gain (dBi)	Antenna Gain (linear)	MPE (mW/cm^2)	MPE Limits (mW/cm^2)
	dBm	mW				
IEEE 802.11a	13.0	19.9526	1.54	1.4256	0.0057	1.0000
IEEE 802.11n HT20	13.0	19.9526	1.54	1.4256	0.0057	1.0000
IEEE 802.11n HT40	13.0	19.9526	1.54	1.4256	0.0057	1.0000
IEEE 802.11ac VHT20	13.0	19.9526	1.54	1.4256	0.0057	1.0000
IEEE 802.11ac VHT40	12.0	15.8489	1.54	1.4256	0.0045	1.0000
IEEE 802.11ac VHT80	12.0	15.8489	1.54	1.4256	0.0045	1.0000

[5.3GHz WLAN]

Modulation Type	Output power		Antenna Gain (dBi)	Antenna Gain (linear)	MPE (mW/cm^2)	MPE Limits (mW/cm^2)
	dBm	mW				
IEEE 802.11a	13.0	19.9526	1.54	1.4256	0.0057	1.0000
IEEE 802.11n HT20	12.0	15.8489	1.54	1.4256	0.0045	1.0000
IEEE 802.11n HT40	12.0	15.8489	1.54	1.4256	0.0045	1.0000
IEEE 802.11ac VHT20	12.0	15.8489	1.54	1.4256	0.0045	1.0000
IEEE 802.11ac VHT40	12.0	15.8489	1.54	1.4256	0.0045	1.0000
IEEE 802.11ac VHT80	12.0	15.8489	1.54	1.4256	0.0045	1.0000



Shenzhen LCS Compliance Testing Laboratory Ltd.

Add: 101, 201 Bldg A & 301 Bldg C, Juji Industrial Park Yabianxueziwei, Shajing Street, Baoan District, Shenzhen, 518000, China

Tel: +(86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com

Scan code to check authenticity

**[5.5GHz WLAN]**

Modulation Type	Output power		Antenna Gain (dBi)	Antenna Gain (linear)	MPE (mW/cm ²)	MPE Limits (mW/cm ²)
	dBm	mW				
IEEE 802.11a	9.0	7.9433	1.54	1.4256	0.0023	1.0000
IEEE 802.11n HT20	9.0	7.9433	1.54	1.4256	0.0023	1.0000
IEEE 802.11n HT40	9.0	7.9433	1.54	1.4256	0.0023	1.0000
IEEE 802.11ac VHT20	8.0	6.3096	1.54	1.4256	0.0018	1.0000
IEEE 802.11ac VHT40	8.0	6.3096	1.54	1.4256	0.0018	1.0000
IEEE 802.11ac VHT80	9.0	7.9433	1.54	1.4256	0.0023	1.0000

[5.8GHz WLAN]

Modulation Type	Output power		Antenna Gain (dBi)	Antenna Gain (linear)	MPE (mW/cm ²)	MPE Limits (mW/cm ²)
	dBm	mW				
IEEE 802.11a	11.0	12.5893	1.54	1.4256	0.0036	1.0000
IEEE 802.11n HT20	11.0	12.5893	1.54	1.4256	0.0036	1.0000
IEEE 802.11n HT40	11.0	12.5893	1.54	1.4256	0.0036	1.0000
IEEE 802.11ac VHT20	11.0	12.5893	1.54	1.4256	0.0036	1.0000
IEEE 802.11ac VHT40	11.0	12.5893	1.54	1.4256	0.0036	1.0000
IEEE 802.11ac VHT80	11.0	12.5893	1.54	1.4256	0.0036	1.0000

Remark:

1. Output power including turn-up tolerance;
2. Output power was adjust to duty cycle at 100% if measured duty cycle less than 98%;
3. MPE evaluate distance is 20cm from user manual provide by manufacturer.

8.2 Simultaneous Transmission MPE Evaluation

The EUT equipped with one module and one antenna. So no need consider simultaneous transmission.

9. Conclusion

The measurement results comply with the FCC Limit per 47 CFR 2.1091 for the uncontrolled RF Exposure of mobile device.

-----THE END OF REPORT-----

