

1. MAXIMUM PERMISSIBLE EXPOSURE (MPE)

1.1 General Information

Client Information

Applicant: ST Engineering Electronics Ltd.
Address of applicant: 100 Jurong East Street 21, ST Electronic East Building.
Singapore 609602

Manufacturer: ZHEJIANG FONDA TECHNOLOGY CO.,LTD
Address of manufacturer: 9TH FLOOR SHUYU BUILDING, NO.98 WENYI WEST
ROAD, XIHU DISTRICT, HANGZHOU, ZHEJIANG, CHINA

General Description of EUT:

Product Name: Remote Lamp Controller
Trade Name: /
Model No.: AGIL LCU 2AS
Adding Model(s): AGIL LCU 2US, AGIL LCU 2AU
Rated Voltage: AC 100-240V, 50/60Hz
Power Adapter: /
FCC ID: 2A2WV-AGILLCU

Technical Characteristics of EUT:

Frequency Range: 902.3-926.8MHz
RF Output Power: 17.86dBm (Conducted)
Modulation: LoRa
Quantity of Channels: 123
Channel Separation: $\geq 200\text{kHz}$
Type of Antenna: Integral Antenna
Antenna Gain: 2dBi

1.2 Standard Applicable

According to § 1.1307(b)(1) and KDB 447498 D01 General RF Exposure Guidance v06, system operating under the provisions of this section shall be operating in a manner that the public is not exposed to radio frequency energy level in excess limit for maximum permissible exposure.

(a) Limits for Occupational / Controlled Exposure

Frequency range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm ²)	Averaging Times E ² , H ² or S (minutes)
0.3-3.0	614	1.63	(100)*	6
3.0-30	1842/f	4.89/f	(900/f)*	6
30-300	61.4	0.163	1.0	6
300-1500	/	/	F/300	6
1500-100000	/	/	5	6

(b) Limits for General Population / Uncontrolled Exposure

Frequency range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm ²)	Averaging Times E ² , H ² or S (minutes)
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f)*	30
30-300	27.5	0.073	0.2	30
300-1500	/	/	F/1500	30
1500-100000	/	/	1	30

Note: f = frequency in MHz; * = Plane-wave equivalents power density

1.3 MPE Calculation Method

$$S = (30*P*G) / (377*R^2)$$

S = power density (in appropriate units, e.g., mw/cm²)

P = power input to the antenna (in appropriate units, e.g., mw)

G = power gain of the antenna in the direction of interest relative to an isotropic radiator,
the power gain factor is normally numeric gain.

R = distance to the center of radiation of the antenna (in appropriate units, e.g., cm)

1.4 MPE Calculation Result

For 900MHz DSS

Maximum Tune-Up output power: 18(dBm)

Maximum peak output power at antenna input terminal:63.10(mW)

Prediction distance: >20(cm)

Prediction frequency: 902.3 (MHz)

Antenna gain: 2.0 (dBi)

Directional gain (numeric gain): 1.58

The worst case is power density at prediction frequency at 20cm: 0.0199(mw/cm²)

MPE limit for general population exposure at prediction frequency: 0.6015 (mw/cm²)

Result: Pass