

TEST REPORT

Applicant: Wenzhou Pure Tone Technology Co.,Ltd.

Address of Applicant: Room 118,1st floor,building 1,No.518 Jiguang Road,Louqiao street,Ouhai District,Wenzhou City,Zhejiang Province,China.

Manufacturer/Factory: Wenzhou Pure Tone Technology Co.,Ltd.

Address of Manufacturer/Factory: Room 118,1st floor,building 1,No.518 Jiguang Road,Louqiao street,Ouhai District,Wenzhou City,Zhejiang Province,China.

Equipment Under Test (EUT)

Product Name: Bluetooth Audio Smart Glass

Model No.: PT01A010

Trade Mark: N/A

FCC ID: 2A2YJ-PT01A010

Applicable standards: FCC CFR Title 47 Part 15 Subpart C Section 15.247

Date of sample receipt: Aug. 18,2021

Date of Test: Aug. 18,2021-Aug. 27,2021

Date of report issued: Aug. 27,2021

Test Result : PASS *

* In the configuration tested, the EUT complied with the standards specified above.

Authorized Signature:



Robinson Luo

Laboratory Manager

This results shown in this test report refer only to the sample(s) tested, this test report cannot be reproduced, except in full, without prior written permission of the company. The report would be invalid without specific stamp of test institute and the signatures of compiler and approver.

2 Version

Version No.	Date	Description
00	Aug. 27,2021	Original

Prepared By:




Date:

Aug. 27,2021

Project Engineer

Check By:


Reviewer

Date:

Aug. 27,2021

3 Contents

Page

1	COVER PAGE	1
2	VERSION	2
3	CONTENTS	3
4	TEST SUMMARY	4
5	GENERAL INFORMATION	5
5.1	GENERAL DESCRIPTION OF EUT	5
5.2	TEST MODE	7
5.3	DESCRIPTION OF SUPPORT UNITS	7
5.4	DEVIATION FROM STANDARDS	7
5.5	ABNORMALITIES FROM STANDARD CONDITIONS	7
5.6	TEST FACILITY	7
5.7	TEST LOCATION	7
6	TEST INSTRUMENTS LIST	8
7	TEST RESULTS AND MEASUREMENT DATA	10
7.1	ANTENNA REQUIREMENT	10
7.2	CONDUCTED EMISSIONS	11
7.3	CONDUCTED PEAK OUTPUT POWER	14
7.4	20dB EMISSION BANDWIDTH	16
7.5	CARRIER FREQUENCIES SEPARATION	24
7.6	HOPPING CHANNEL NUMBER	28
7.7	DWELL TIME	32
7.8	BAND EDGE	41
7.8.1	Conducted Emission Method	41
7.8.2	Radiated Emission Method	48
7.9	SPURIOUS EMISSION	50
7.9.1	Conducted Emission Method	50
7.9.2	Radiated Emission Method	59
8	TEST SETUP PHOTO	67
9	EUT CONSTRUCTIONAL DETAILS	67

4 Test Summary

Test Item	Section in CFR 47	Result
Antenna Requirement	15.203/15.247(c)	Pass
AC Power Line Conducted Emission	15.207	Pass
Conducted Peak Output Power	15.247 (b)(1)	Pass
20dB Occupied Bandwidth	15.247 (a)(1)	Pass
Carrier Frequencies Separation	15.247 (a)(1)	Pass
Hopping Channel Number	15.247 (a)(1)(iii)	Pass
Dwell Time	15.247 (a)(1)(iii)	Pass
Radiated Emission	15.205/15.209	Pass
Band Edge	15.247(d)	Pass

Remarks:

1. Pass: The EUT complies with the essential requirements in the standard.
2. Test according to ANSI C63.10:2013

Measurement Uncertainty

Test Item	Frequency Range	Measurement Uncertainty	Notes
Radiated Emission	30MHz-200MHz	3.8039dB	(1)
Radiated Emission	200MHz-1GHz	3.9679dB	(1)
Radiated Emission	1GHz-18GHz	4.29dB	(1)
Radiated Emission	18GHz-40GHz	3.30dB	(1)
AC Power Line Conducted Emission	0.15MHz ~ 30MHz	3.44dB	(1)

Note (1): The measurement uncertainty is for coverage factor of k=2 and a level of confidence of 95%.

5 General Information

5.1 General Description of EUT

Product Name:	Bluetooth Audio Smart Glass
Model No.:	PT01A010, PT01A004, PT01A005, PT01A006, PT01A007, PT01A008, PT01A009, PT01A011, PT01A012, PT01A013, PT01A014, PT01A015, PT01A016, PT01A017, PT01A022, PT01A023, PT01A024, PT01A025, PT01A026, PT01A027, PT01A028, PT01A029, PT01A030, PT01A031, PT01A032, PT01A033, PT01A034, PT01A035, PT01A036, PT01A037, PT01A038, PT01A039, PT01A040, PT01A041, PT01A042, PT01A043, PT01A044, PT01A045, PT01A046, PT01A047, PT01A048, PT01A049, PT01A050, PT01A051, PT01A052, PT01A053, PT01A054, PT01A055, PT01A056, PT01A057, PT01A058, PT01A059, PT01A060, PT01A061, PT01A062, PT01A063, PT01A064, PT01A065, PT01A066, PT01A067, PT01A068, PT01A069, PT01A070, PT01A071, PT01A072, PT01A073, PT01A074, PT01A075, PT01A076, PT01A077, PT01A078, PT01A079, PT01A080, PT01A081, PT01A082, PT01A083, PT01A084, PT01A085, PT01A086, PT01A087, PT01A088, PT01A089, PT01A090, PT01A091, PT01A092, PT01A093, PT01A094, PT01A095, PT01A096, PT01A097, PT01A098, PT01A099, PT01A0100.
Model Declaration:	PCB board, structure and internal of these model(s) are the same, So no additional models were tested.
Test sample(s) ID:	GTSL202108000202-1
Sample(s) Status:	Engineer sample
Hardware Version:	V1.0
Software Version:	V1.4
Operation Frequency:	2402MHz~2480MHz
Channel numbers:	79
Channel separation:	1MHz
Modulation type:	GFSK, $\pi/4$ -DQPSK, 8-DPSK
Antenna Type:	Chip ANT1(L); Chip ANT2(R)
Antenna gain:	0.00dBi
Power Supply:	DC 3.7V Form Battery and DC 5V From External Circuit
Adapter Information (Auxiliary test provided by the lab):	Mode: CD122 Input: AC100-240V, 50/60Hz, 500mA Output: DC 5V, 2A

Operation Frequency each of channel							
Channel	Frequency	Channel	Frequency	Channel	Frequency	Channel	Frequency
1	2402MHz	21	2422MHz	41	2442MHz	61	2462MHz
2	2403MHz	22	2423MHz	42	2443MHz	62	2463MHz
3	2404MHz	23	2424MHz	43	2444MHz	63	2464MHz
4	2405MHz	24	2425MHz	44	2445MHz	64	2465MHz
5	2406MHz	25	2426MHz	45	2446MHz	65	2466MHz
6	2407MHz	26	2427MHz	46	2447MHz	66	2467MHz
7	2408MHz	27	2428MHz	47	2448MHz	67	2468MHz
8	2409MHz	28	2429MHz	48	2449MHz	68	2469MHz
9	2410MHz	29	2430MHz	49	2450MHz	69	2470MHz
10	2411MHz	30	2431MHz	50	2451MHz	70	2471MHz
11	2412MHz	31	2432MHz	51	2452MHz	71	2472MHz
12	2413MHz	32	2433MHz	52	2453MHz	72	2473MHz
13	2414MHz	33	2434MHz	53	2454MHz	73	2474MHz
14	2415MHz	34	2435MHz	54	2455MHz	74	2475MHz
15	2416MHz	35	2436MHz	55	2456MHz	75	2476MHz
16	2417MHz	36	2437MHz	56	2457MHz	76	2477MHz
17	2418MHz	37	2438MHz	57	2458MHz	77	2478MHz
18	2419MHz	38	2439MHz	58	2459MHz	78	2479MHz
19	2420MHz	39	2440MHz	59	2460MHz	79	2480MHz
20	2421MHz	40	2441MHz	60	2461MHz		

Note:

In section 15.31(m), regards to the operating frequency range over 10 MHz, the Lowest frequency, the middle frequency, and the highest frequency of channel were selected to perform the test, and the selected channel see below:

Channel	Frequency
The lowest channel	2402MHz
The middle channel	2441MHz
The Highest channel	2480MHz

5.2 Test mode

Transmitting mode	Keep the EUT in continuously transmitting mode.
<i>Remark: During the test, the test voltage was tuned from 85% to 115% of the nominal rated supply voltage, and found that the worst case was under the nominal rated supply condition. So the report just shows that condition's data.</i>	

5.3 Description of Support Units

None.

5.4 Deviation from Standards

None.

5.5 Abnormalities from Standard Conditions

None.

5.6 Test Facility

The test facility is recognized, certified, or accredited by the following organizations: ● FCC—Registration No.: 381383 Designation Number: CN5029 Global United Technology Services Co., Ltd., Shenzhen EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in files. ● IC —Registration No.: 9079A CAB identifier: CN0091 The 3m Semi-anechoic chamber of Global United Technology Services Co., Ltd. has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing. ● NVLAP (LAB CODE:600179-0) Global United Technology Services Co., Ltd., is accredited by the National Voluntary Laboratory Accreditation Program (NVLAP).

5.7 Test Location

All tests were performed at:
Global United Technology Services Co., Ltd. Address: No. 123-128, Tower A, Jinyuan Business Building, No.2, Laodong Industrial Zone, Xixiang Road, Baoan District, Shenzhen, Guangdong, China 518102 Tel: 0755-27798480 Fax: 0755-27798960

6 Test Instruments list

Radiated Emission:						
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal.Date (mm-dd-yy)	Cal.Due date (mm-dd-yy)
1	3m Semi- Anechoic Chamber	ZhongYu Electron	9.2(L)*6.2(W)* 6.4(H)	GTS250	July. 02 2020	July. 01 2025
2	Control Room	ZhongYu Electron	6.2(L)*2.5(W)* 2.4(H)	GTS251	N/A	N/A
3	EMI Test Receiver	Rohde & Schwarz	ESU26	GTS203	June. 24 2021	June. 23 2022
4	BiConiLog Antenna	SCHWARZBECK MESS-ELEKTRONIK	VULB9163	GTS214	June. 24 2021	June. 23 2022
5	Double -ridged waveguide horn	SCHWARZBECK MESS-ELEKTRONIK	BBHA 9120 D	GTS208	June. 24 2021	June. 23 2022
6	Horn Antenna	ETS-LINDGREN	3160	GTS217	June. 24 2021	June. 23 2022
7	EMI Test Software	AUDIX	E3	N/A	N/A	N/A
8	Coaxial Cable	GTS	N/A	GTS213	June. 24 2021	June. 23 2022
9	Coaxial Cable	GTS	N/A	GTS211	June. 24 2021	June. 23 2022
10	Coaxial cable	GTS	N/A	GTS210	June. 24 2021	June. 23 2022
11	Coaxial Cable	GTS	N/A	GTS212	June. 24 2021	June. 23 2022
12	Amplifier(100kHz-3GHz)	HP	8347A	GTS204	June. 24 2021	June. 23 2022
13	Amplifier(2GHz-20GHz)	HP	84722A	GTS206	June. 24 2021	June. 23 2022
14	Amplifier (18-26GHz)	Rohde & Schwarz	AFS33-18002 650-30-8P-44	GTS218	June. 24 2021	June. 23 2022
15	Band filter	Amindeon	82346	GTS219	June. 24 2021	June. 23 2022
16	Power Meter	Anritsu	ML2495A	GTS540	June. 24 2021	June. 23 2022
17	Power Sensor	Anritsu	MA2411B	GTS541	June. 24 2021	June. 23 2022
18	Wideband Radio Communication Tester	Rohde & Schwarz	CMW500	GTS575	June. 24 2021	June. 23 2022
19	Splitter	Agilent	11636B	GTS237	June. 24 2021	June. 23 2022
20	Loop Antenna	ZHINAN	ZN30900A	GTS534	June. 24 2021	June. 23 2022
21	Breitband hornantenne	SCHWARZBECK	BBHA 9170	GTS579	Oct. 18 2020	Oct. 17 2021
22	Amplifier	TDK	PA-02-02	GTS574	Oct. 18 2020	Oct. 17 2021
23	Amplifier	TDK	PA-02-03	GTS576	Oct. 18 2020	Oct. 17 2021
24	PSA Series Spectrum Analyzer	Rohde & Schwarz	FSP	GTS578	June. 24 2021	June. 23 2022

Conducted Emission						
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal.Date (mm-dd-yy)	Cal.Due date (mm-dd-yy)
1	Shielding Room	ZhongYu Electron	7.3(L)x3.1(W)x2.9(H)	GTS252	May.15 2019	May.14 2022
2	EMI Test Receiver	R&S	ESCI 7	GTS552	June. 24 2021	June. 23 2022
3	Coaxial Switch	ANRITSU CORP	MP59B	GTS225	June. 24 2021	June. 23 2022
4	ENV216 2-L-V-NETZNACHB.DE	ROHDE&SCHWARZ	ENV216	GTS226	June. 24 2021	June. 23 2022
5	Coaxial Cable	GTS	N/A	GTS227	N/A	N/A
6	EMI Test Software	AUDIX	E3	N/A	N/A	N/A
7	Thermo meter	KTJ	TA328	GTS233	June. 24 2021	June. 23 2022
8	Absorbing clamp	Elektronik-Feinmechanik	MDS21	GTS229	June. 24 2021	June. 23 2022
9	ISN	SCHWARZBECK	NTFM 8158	GTS565	June. 24 2021	June. 23 2022
10	High voltage probe	SCHWARZBECK	TK9420	GTS537	July. 09 2021	July. 08 2022

RF Conducted Test:						
Item	Test Equipment	Manufacturer	Model No.	Serial No.	Cal.Date (mm-dd-yy)	Cal.Due date (mm-dd-yy)
1	MXA Signal Analyzer	Agilent	N9020A	GTS566	June. 24 2021	June. 23 2022
2	EMI Test Receiver	R&S	ESCI 7	GTS552	June. 24 2021	June. 23 2022
3	Spectrum Analyzer	Agilent	E4440A	GTS533	June. 24 2021	June. 23 2022
4	MXG vector Signal Generator	Agilent	N5182A	GTS567	June. 24 2021	June. 23 2022
5	ESG Analog Signal Generator	Agilent	E4428C	GTS568	June. 24 2021	June. 23 2022
6	USB RF Power Sensor	DARE	RPR3006W	GTS569	June. 24 2021	June. 23 2022
7	RF Switch Box	Shongyi	RFSW3003328	GTS571	June. 24 2021	June. 23 2022
8	Programmable Constant Temp & Humi Test Chamber	WEWON	WHTH-150L-40-880	GTS572	June. 24 2021	June. 23 2022


General used equipment:						
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal.Date (mm-dd-yy)	Cal.Due date (mm-dd-yy)
1	Humidity/ Temperature Indicator	KTJ	TA328	GTS243	June. 24 2021	June. 23 2022
2	Barometer	ChangChun	DYM3	GTS255	June. 24 2021	June. 23 2022

7 Test results and Measurement Data

7.1 Antenna requirement

Standard requirement:	FCC Part15 C Section 15.203 /15.247(c)
15.203 requirement: An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. 15.247(c) (1)(i) requirement: (i) Systems operating in the 2400-2483.5 MHz band that is used exclusively for fixed. Point-to-point operations may employ transmitting antennas with directional gain greater than 6dBi provided the maximum conducted output power of the intentional radiator is reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6dBi.	
E.U.T Antenna:	
<i>The antenna is Chip antenna, the best case gain of the is 0.00dBi, reference to the appendix II for details</i>	

7.2 Conducted Emissions


Test Requirement:	FCC Part15 C Section 15.207					
Test Method:	ANSI C63.10:2013					
Test Frequency Range:	150KHz to 30MHz					
Class / Severity:	Class B					
Receiver setup:	RBW=9KHz, VBW=30KHz, Sweep time=auto					
Limit:	Frequency range (MHz)		Limit (dBuV)			
			Quasi-peak		Average	
	0.15-0.5		66 to 56*		56 to 46*	
	0.5-5		56		46	
	5-30		60		50	
* Decreases with the logarithm of the frequency.						
Test setup:	Reference Plane  Remark: E.U.T: Equipment Under Test LISN: Line Impedance Stabilization Network Test table height=0.8m					
Test procedure:	1. The E.U.T and simulators are connected to the main power through a line impedance stabilization network (L.I.S.N.). This provides a 50ohm/50uH coupling impedance for the measuring equipment. 2. The peripheral devices are also connected to the main power through a LISN that provides a 50ohm/50uH coupling impedance with 50ohm termination. (Please refer to the block diagram of the test setup and photographs). 3. Both sides of A.C. line are checked for maximum conducted interference. In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.10:2013 on conducted measurement.					
Test Instruments:	Refer to section 6.0 for details					
Test mode:	Refer to section 5.2 for details					
Test environment:	Temp.:	25 °C	Humid.:	52%	Press.:	1012mbar
Test voltage:	AC 120V, 60Hz					
Test results:	Pass					

Remark: Both high and low voltages have been tested to show only the worst low voltage test data.

Measurement data:


Pre-scan all test modes of ANT1 and ANT2, found worst case at ANT1 GFSK 2480MHz, and so only show the test result of ANT1 GFSK 2480MHz

Line:



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	
		MHz	dBuV	dB	dBuV	dBuV	dB	Detector
1	*	0.1578	21.10	10.93	32.03	65.58	-33.55	QP
2		0.1578	7.80	10.93	18.73	55.58	-36.85	AVG
3		0.3645	6.93	10.92	17.85	58.63	-40.78	QP
4		0.3645	-0.76	10.92	10.16	48.63	-38.47	AVG
5		0.5712	9.11	10.92	20.03	56.00	-35.97	QP
6		0.5712	-0.72	10.92	10.20	46.00	-35.80	AVG
7		1.3239	8.74	10.94	19.68	56.00	-36.32	QP
8		1.3239	-0.58	10.94	10.36	46.00	-35.64	AVG
9		1.8933	8.16	10.96	19.12	56.00	-36.88	QP
10		1.8933	-1.04	10.96	9.92	46.00	-36.08	AVG
11		9.4857	8.96	11.33	20.29	60.00	-39.71	QP
12		9.4857	-0.78	11.33	10.55	50.00	-39.45	AVG

Neutral:




No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over	
		MHz	Level	Factor	ment			Detector
			dBuV	dB	dBuV	dBuV	dB	
1	*	0.1578	20.90	10.93	31.83	65.58	-33.75	QP
2		0.1578	6.87	10.93	17.80	55.58	-37.78	AVG
3		0.3645	7.29	10.92	18.21	58.63	-40.42	QP
4		0.3645	-0.71	10.92	10.21	48.63	-38.42	AVG
5		0.5868	8.17	10.92	19.09	56.00	-36.91	QP
6		0.5868	0.00	10.92	10.92	46.00	-35.08	AVG
7		1.3550	8.11	10.94	19.05	56.00	-36.95	QP
8		1.3550	-0.61	10.94	10.33	46.00	-35.67	AVG
9		2.3925	8.34	10.98	19.32	56.00	-36.68	QP
10		2.3925	-1.23	10.98	9.75	46.00	-36.25	AVG
11		8.8227	8.93	11.29	20.22	60.00	-39.78	QP
12		8.8227	-0.75	11.29	10.54	50.00	-39.46	AVG

Notes:

1. An initial pre-scan was performed on the line and neutral lines with peak detector.
2. Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission.
3. Final Level = Receiver Read level + LISN Factor + Cable Loss

7.3 Conducted Peak Output Power

Test Requirement:	FCC Part15 C Section 15.247 (a)(1)					
Test Method:	ANSI C63.10:2013					
Limit:	30dBm(for GFSK),20.97dBm(for EDR)					
Test setup:						
Test Instruments:	Refer to section 6.0 for details					
Test mode:	Refer to section 5.2 for details					
Test environment:	Temp.:	24 °C	Humid.:	51%	Press.:	1012mbar
Test voltage:	AC 120V, 60Hz					
Test results:	Pass					

Measurement Data


ANT1:

Mode	Test channel	Peak Output Power (dBm)	Limit (dBm)	Result
GFSK	Lowest	-5.68	30.00	Pass
	Middle	-5.93		
	Highest	-6.18		
$\pi/4$ -DQPSK	Lowest	-5.69	20.97	Pass
	Middle	-5.95		
	Highest	-6.21		
8-DPSK	Lowest	-5.43	20.97	Pass
	Middle	-5.84		
	Highest	-5.97		

ANT2:

Mode	Test channel	Peak Output Power (dBm)	Limit (dBm)	Result
GFSK	Lowest	-4.03	30.00	Pass
	Middle	-4.90		
	Highest	-5.15		
$\pi/4$ -DQPSK	Lowest	-4.04	20.97	Pass
	Middle	-4.91		
	Highest	-5.14		
8-DPSK	Lowest	-3.87	20.97	Pass
	Middle	-4.74		
	Highest	-5.10		

7.4 20dB Emission Bandwidth

Test Requirement:	FCC Part15 C Section 15.247 (a)(1)				
Test Method:	ANSI C63.10:2013				
Limit:	N/A				
Test setup:					
Test Instruments:	Refer to section 6.0 for details				
Test mode:	Refer to section 5.2 for details				
Test environment:	Temp.:	24 °C	Humid.:	51%	Press.: 1012mbar
Test voltage:	AC 120V, 60Hz				
Test results:	Pass				


Measurement Data

ANT1:


Mode	Test channel	20dB Emission Bandwidth (MHz)	Result
GFSK	Lowest	0.923	Pass
	Middle	0.927	
	Highest	0.927	
$\pi/4$ -DQPSK	Lowest	1.269	Pass
	Middle	1.224	
	Highest	1.225	
8-DPSK	Lowest	1.242	Pass
	Middle	1.246	
	Highest	1.240	

Test plot as follows:


Test mode:	GFSK mode
------------	-----------



Lowest channel




Middle channel




Highest channel

Test mode:


$\pi/4$ -DQPSK mode



Lowest channel




Middle channel




Highest channel

Test mode:


8-DPSK mode



Lowest channel



Middle channel




Highest channel

ANT2:


Mode	Test channel	20dB Emission Bandwidth (MHz)	Result
GFSK	Lowest	0.919	Pass
	Middle	0.922	
	Highest	0.927	
$\pi/4$ -DQPSK	Lowest	1.287	Pass
	Middle	1.283	
	Highest	1.223	
8-DPSK	Lowest	1.246	Pass
	Middle	1.245	
	Highest	1.243	

Test plot as follows:


Test mode:	GFSK mode
------------	-----------



Lowest channel




Middle channel




Highest channel

Test mode:


$\pi/4$ -DQPSK mode



Lowest channel




Middle channel




Highest channel

Test mode:


8-DPSK mode



Lowest channel




Middle channel



Highest channel

7.5 Carrier Frequencies Separation

Test Requirement:	FCC Part15 C Section 15.247 (a)(1)					
Test Method:	ANSI C63.10:2013					
Receiver setup:	RBW=100KHz, VBW=300KHz, detector=Peak					
Limit:	0.025MHz or 2/3 of the 20dB bandwidth (whichever is greater)					
Test setup:						
Test Instruments:	Refer to section 6.0 for details					
Test mode:	Refer to section 5.2 for details					
Test environment:	Temp.:	24 °C	Humid.:	51%	Press.:	1012mbar
Test voltage:	AC 120V, 60Hz					
Test results:	Pass					

Measurement Data

ANT1:


Mode	Carrier Frequencies Separation (MHz)	20dB bandwidth (MHz) (worse case)	Limit (MHz)	Result
GFSK	1.000	0.927	≥0.927	Pass
$\pi/4$ -DQPSK	0.981	1.269	≥0.846	
8-DPSK	0.999	1.246	≥0.831	

Note: According to section 7.4

Test plot as follows:


Modulation mode:

GFSK




Test mode:

$\pi/4$ -DQPSK



Test mode:

8-DPSK



ANT2:


Mode	Carrier Frequencies Separation (MHz)	20dB bandwidth (MHz) (worse case)	Limit (MHz)	Result
GFSK	0.990	0.927	≥ 0.927	Pass
$\pi/4$ -DQPSK	1.002	1.287	≥ 0.858	
8-DPSK	0.999	1.246	≥ 0.831	

Note: According to section 7.4

Test plot as follows:


Modulation mode:

GFSK




Test mode:

$\pi/4$ -DQPSK




Test mode:

8-DPSK



7.6 Hopping Channel Number

Test Requirement:	FCC Part15 C Section 15.247 (a)(1)(iii)				
Test Method:	ANSI C63.10:2013				
Receiver setup:	RBW=100kHz, VBW=300kHz, Frequency range=2400MHz-2483.5MHz, Detector=Peak				
Limit:	15 channels				
Test setup:	 The diagram illustrates the test setup. A Spectrum Analyzer is connected via a red cable to an E.U.T. (Equipment Under Test). Both are placed on a Non-Conducted Table. Below the table is a Ground Reference Plane.				
Test Instruments:	Refer to section 6.0 for details				
Test mode:	Refer to section 5.2 for details				
Test environment:	Temp.:	24 °C	Humid.:	51%	Press.: 1012mbar
Test voltage:	AC 120V, 60Hz				
Test results:	Pass				

Measurement Data:


ANT1:

Mode	Hopping channel numbers	Limit	Result
GFSK	79	≥15	Pass
π/4-DQPSK	79	≥15	Pass
8-DPSK	79	≥15	Pass

Test plot as follows:


Test mode:

GFSK




Test mode:

π/4-DQPSK



Test mode:

8-DPSK




ANT2:

Mode	Hopping channel numbers	Limit	Result
GFSK	79	≥ 15	Pass
$\pi/4$ -DQPSK	79	≥ 15	Pass
8-DPSK	79	≥ 15	Pass

Test plot as follows:


Test mode:

GFSK




Test mode:

$\pi/4$ -DQPSK




Test mode:

8-DPSK



7.7 Dwell Time

Test Requirement:	FCC Part15 C Section 15.247 (a)(1)(iii)					
Test Method:	ANSI C63.10:2013					
Receiver setup:	RBW=1MHz, VBW=1MHz, Span=0Hz, Detector=Peak					
Limit:	0.4 Second					
Test setup:	 The diagram illustrates the test setup. A Spectrum Analyzer is connected to an E.U.T (Equipment Under Test) via a red cable. Both the Spectrum Analyzer and the E.U.T are placed on a Non-Conducted Table. The table is supported by a Ground Reference Plane.					
Test Instruments:	Refer to section 6.0 for details					
Test mode:	Refer to section 5.2 for details					
Test environment:	Temp.:	24 °C	Humid.:	51%	Press.:	1012mbar
Test voltage:	AC 120V, 60Hz					
Test results:	Pass					

Measurement Data

ANT1:

GFSK mode:

Frequency	Packet	Dwell time(ms)	Limit(ms)	Result
2441MHz	DH1	120.000	400	Pass
2441MHz	DH3	259.360	400	Pass
2441MHz	DH5	304.114	400	Pass

Remarks:

The test period: $T = 0.4 \text{ Second/Channel} \times 79 \text{ Channel} = 31.6 \text{ s}$

Test channel: 2441MHz as blow

DH1 time slot = $0.375(\text{ms}) \times (1600 / (2 \times 79)) \times 31.6 = 120.000\text{ms}$

DH3 time slot = $1.621(\text{ms}) \times (1600 / (4 \times 79)) \times 31.6 = 259.360\text{ms}$

DH5 time slot = $2.869(\text{ms}) \times (1600 / (6 \times 79)) \times 31.6 = 304.114\text{ms}$

$\pi/4$ -DQPSK mode:

Frequency	Packet	Dwell time(ms)	Limit(ms)	Result
2441MHz	2DH1	130.560	400	Pass
2441MHz	2DH3	261.440	400	Pass
2441MHz	2DH5	308.374	400	Pass

Remarks:

The test period: $T = 0.4 \text{ Second/Channel} \times 79 \text{ Channel} = 31.6 \text{ s}$

Test channel: 2441MHz as blow

DH1 time slot = $0.408(\text{ms}) \times (1600 / (2 \times 79)) \times 31.6 = 124.80\text{ms}$

DH3 time slot = $1.634(\text{ms}) \times (1600 / (4 \times 79)) \times 31.6 = 263.20\text{ms}$

DH5 time slot = $2.882(\text{ms}) \times (1600 / (6 \times 79)) \times 31.6 = 308.48\text{ms}$

8-DPSK mode:

Frequency	Packet	Dwell time(ms)	Limit(ms)	Result
2441MHz	3DH1	130.560	400	Pass
2441MHz	3DH3	261.280	400	Pass
2441MHz	3DH5	308.588	400	Pass

Remarks:

The test period: $T = 0.4 \text{ Second/Channel} \times 79 \text{ Channel} = 31.6 \text{ s}$

Test channel: 2441MHz as blow

DH1 time slot = $0.408(\text{ms}) \times (1600 / (2 \times 79)) \times 31.6 = 124.80\text{ms}$

DH3 time slot = $1.633(\text{ms}) \times (1600 / (4 \times 79)) \times 31.6 = 262.40\text{ms}$


DH5 time slot = $2.884(\text{ms}) \times (1600 / (6 \times 79)) \times 31.6 = 308.48\text{ms}$

Test plot as follows:


GFSK mode:

Test channel:


2441MHz



DH1




DH3




DH5

$\pi/4$ -DQPSK mode:


Test channel:	2441MHz
---------------	---------



DH1




DH3




DH5

8-DPSK mode:


Test channel:	2441MHz
---------------	---------



DH1



DH3



DH5

ANT2:
GFSK mode:

Frequency	Packet	Dwell time(ms)	Limit(ms)	Result
2441MHz	DH1	120.000	400	Pass
2441MHz	DH3	259.360	400	Pass
2441MHz	DH5	304.114	400	Pass

Remarks:

The test period: $T = 0.4 \text{ Second/Channel} \times 79 \text{ Channel} = 31.6 \text{ s}$

Test channel: 2441MHz as blow

DH1 time slot = $0.375(\text{ms}) \times (1600 / (2 \times 79)) \times 31.6 = 120.000\text{ms}$

DH3 time slot = $1.621(\text{ms}) \times (1600 / (4 \times 79)) \times 31.6 = 259.360\text{ms}$

DH5 time slot = $2.869(\text{ms}) \times (1600 / (6 \times 79)) \times 31.6 = 304.114\text{ms}$

 $\pi/4$ -DQPSK mode:

Frequency	Packet	Dwell time(ms)	Limit(ms)	Result
2441MHz	2DH1	130.240	400	Pass
2441MHz	2DH3	261.280	400	Pass
2441MHz	2DH5	308.267	400	Pass

Remarks:

The test period: $T = 0.4 \text{ Second/Channel} \times 79 \text{ Channel} = 31.6 \text{ s}$

Test channel: 2441MHz as blow

DH1 time slot = $0.407(\text{ms}) \times (1600 / (2 \times 79)) \times 31.6 = 130.240\text{ms}$

DH3 time slot = $1.633(\text{ms}) \times (1600 / (4 \times 79)) \times 31.6 = 261.280\text{ms}$

DH5 time slot = $2.881(\text{ms}) \times (1600 / (6 \times 79)) \times 31.6 = 308.267\text{ms}$

8-DPSK mode:

Frequency	Packet	Dwell time(ms)	Limit(ms)	Result
2441MHz	3DH1	130.240	400	Pass
2441MHz	3DH3	261.280	400	Pass
2441MHz	3DH5	308.481	400	Pass

Remarks:

The test period: $T = 0.4 \text{ Second/Channel} \times 79 \text{ Channel} = 31.6 \text{ s}$

Test channel: 2441MHz as blow

DH1 time slot = $0.407(\text{ms}) \times (1600 / (2 \times 79)) \times 31.6 = 130.240\text{ms}$


DH3 time slot = $1.633(\text{ms}) \times (1600 / (4 \times 79)) \times 31.6 = 261.280\text{ms}$

DH5 time slot = $2.883(\text{ms}) \times (1600 / (6 \times 79)) \times 31.6 = 308.481\text{ms}$


Test plot as follows:

GFSK mode:


Test channel:	2441MHz
---------------	---------



DH1




DH3




DH5

$\pi/4$ -DQPSK mode:


Test channel:	2441MHz
---------------	---------



DH1




DH3




DH5

8-DPSK mode:


Test channel:	2441MHz
---------------	---------



DH1




DH3



DH5

7.8 Band Edge

7.8.1 Conducted Emission Method


Test Requirement:	FCC Part15 C Section 15.247 (d)					
Test Method:	ANSI C63.10:2013					
Receiver setup:	RBW=100kHz, VBW=300kHz, Detector=Peak					
Limit:	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.					
Test setup:						
Test Instruments:	Refer to section 6.0 for details					
Test mode:	Refer to section 5.2 for details					
Test environment:	Temp.:	24 °C	Humid.:	51%	Press.:	1012mbar
Test voltage:	AC 120V, 60Hz					
Test results:	Pass					

Test plot as follows:


ANT1:

GFSK Mode:

Test channel:	Lowest channel
---------------	----------------




No-hopping mode




Hopping mode

Test channel:	Highest channel
---------------	-----------------




No-hopping mode




Hopping mode

$\pi/4$ -DQPSK Mode:




8-DPSK Mode:




ANT2:
GFSK Mode:

Test channel:	Lowest channel
---------------	----------------




No-hopping mode




Hopping mode

Test channel:	Highest channel
---------------	-----------------




No-hopping mode




Hopping mode

$\pi/4$ -DQPSK Mode:




8-DPSK Mode:

Test channel:	Lowest channel
---------------	----------------




No-hopping mode




Hopping mode

Test channel:	Highest channel
---------------	-----------------




No-hopping mode



Hopping mode

7.8.2 Radiated Emission Method

Test Requirement:	FCC Part15 C Section 15.209 and 15.205					
Test Method:	ANSI C63.10:2013					
Test Frequency Range:	All of the restrict bands were tested, only the worst band's (2310MHz to 2500MHz) data was showed.					
Test site:	Measurement Distance: 3m					
Receiver setup:	Frequency	Detector	RBW	VBW	Remark	
	Above 1GHz	Peak	1MHz	3MHz	Peak Value	
		Peak	1MHz	10Hz	Average Value	
Limit:	Frequency		Limit (dBuV/m @3m)		Remark	
	Above 1GHz		54.00		Average Value	
			74.00		Peak Value	
Test setup:						
Test Procedure:	1. The EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter camber. The table was rotated 360 degrees to determine the position of the highest radiation. 2. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower. 3. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement. 4. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rota table was turned from 0 degrees to 360 degrees to find the maximum reading. 5. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode. 6. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.					
Test Instruments:	Refer to section 6.0 for details					
Test mode:	Refer to section 5.2 for details					
Test environment:	Temp.:	25 °C	Humid.:	52%	Press.:	1012mbar
Test voltage:	AC 120V, 60Hz					
Test results:	Pass					

Measurement Data

Test channel:	Lowest channel
---------------	----------------

Peak value:

Frequency (MHz)	Read Level (dBuV)	Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2390	59.44	-5.68	53.76	74	-20.24	Horizontal
2390	60.37	-5.68	54.69	74	-19.31	Vertical

Remark: Factor = Antenna Factor + Cable Loss – Pre-amplifier.

Average value:

Frequency (MHz)	Read Level (dBuV)	Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2390	42.39	-5.68	36.71	54	-17.29	Horizontal
2390	43.01	-5.68	37.33	54	-16.67	Vertical

Remark: Factor = Antenna Factor + Cable Loss – Pre-amplifier.

Test channel:	Highest channel
---------------	-----------------

Peak value:

Frequency (MHz)	Read Level (dBuV)	Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2483.5	60.21	-5.85	54.36	74	-19.64	Horizontal
2483.5	59.77	-5.85	53.92	74	-20.08	Vertical

Remark: Factor = Antenna Factor + Cable Loss – Pre-amplifier.

Average value:

Frequency (MHz)	Read Level (dBuV)	Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2483.5	43.11	-5.85	37.26	54	-16.74	Horizontal
2483.5	42.79	-5.85	36.94	54	-17.06	Vertical


Remark: Factor = Antenna Factor + Cable Loss – Pre-amplifier.

Remarks:

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor
2. The emission levels of other frequencies are very lower than the limit and not show in test report.
3. The pre-test were performed on lowest, middle and highest frequencies, only the worst case's (lowest and highest frequencies) data was showed.
4. During the test, pre-scan the ANT1 and ANT2 GFSK, $\pi/4$ -DQPSK, 8-DPSK modulation, and found the ANT1 GFSK modulation which it is worse case.


7.9 Spurious Emission

7.9.1 Conducted Emission Method


Test Requirement:	FCC Part15 C Section 15.247 (d)					
Test Method:	ANSI C63.10:2013					
Limit:	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.					
Test setup:	 The diagram illustrates the test setup for conducted emission measurement. A Spectrum Analyzer is connected via a red cable to an E.U.T (Equipment Under Test). Both are placed on a Non-Conducted Table, which sits on a Ground Reference Plane.					
Test Instruments:	Refer to section 6.0 for details					
Test mode:	Refer to section 5.2 for details					
Test environment:	Temp.:	24 °C	Humid.:	51%	Press.:	1012mbar
Test voltage:	AC 120V, 60Hz					
Test results:	Pass					

ANT1:


Reference



GFSK



$\pi/4$ DQPSK




8-DPSK

GFSK mode:

Test channel:


Lowest channel



30MHz~25GHz

Test channel:


Middle channel



30MHz~25GHz

Test channel:

Highest channel




30MHz~25GHz

$\pi/4$ -DQPSK mode:

Test channel:


Lowest channel



30MHz~25GHz

Test channel:


Middle channel



30MHz~25GHz

Test channel:

Highest channel




30MHz~25GHz

8-DPSK mode:

Test channel:


Lowest channel



30MHz~25GHz

Test channel:


Middle channel



30MHz~25GHz

Test channel:


Highest channel




30MHz~25GHz

ANT2:


Reference



GFSK



$\pi/4$ DQPSK




8-DPSK

GFSK mode:

Test channel:


Lowest channel



30MHz~25GHz

Test channel:


Middle channel



30MHz~25GHz

Test channel:

Highest channel




30MHz~25GHz

$\pi/4$ -DQPSK mode:

Test channel:


Lowest channel



30MHz~25GHz

Test channel:


Middle channel



30MHz~25GHz

Test channel:

Highest channel




30MHz~25GHz

8-DPSK mode:

Test channel:


Lowest channel



30MHz~25GHz

Test channel:


Middle channel



30MHz~25GHz


Test channel:



Highest channel



30MHz~25GHz

7.9.2 Radiated Emission Method

Test Requirement:	FCC Part15 C Section 15.209				
Test Method:	ANSI C63.10:2013				
Test Frequency Range:	9kHz to 25GHz				
Test site:	Measurement Distance: 3m				
Receiver setup:	Frequency	Detector	RBW	VBW	Value
	9KHz-150KHz	Quasi-peak	200Hz	600Hz	Quasi-peak
	150KHz-30MHz	Quasi-peak	9KHz	30KHz	Quasi-peak
	30MHz-1GHz	Quasi-peak	120KHz	300KHz	Quasi-peak
	Above 1GHz	Peak	1MHz	3MHz	Peak
		Peak	1MHz	10Hz	Average
Limit:	Frequency	Limit (uV/m)		Value	Measurement Distance
	0.009MHz-0.490MHz	2400/F(KHz)		QP	300m
	0.490MHz-1.705MHz	24000/F(KHz)		QP	30m
	1.705MHz-30MHz	30		QP	30m
	30MHz-88MHz	100		QP	3m
	88MHz-216MHz	150		QP	
	216MHz-960MHz	200		QP	
	960MHz-1GHz	500		QP	
	Above 1GHz	500		Average	
		5000		Peak	
Test setup:	For radiated emissions from 9kHz to 30MHz				
					

	For radiated emissions from 30MHz to1GHz  For radiated emissions above 1GHz 
Test Procedure:	1. The EUT was placed on the top of a rotating table (0.8m for below 1G and 1.5m for above 1G) above the ground at a 3 meter camber. The table was rotated 360 degrees to determine the position of the highest radiation. 2. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower. 3. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement. 4. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rota table was turned from 0 degrees to 360 degrees to find the maximum reading. 5. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode. 6. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.
Test Instruments:	Refer to section 6.0 for details
Test mode:	Refer to section 5.2 for details

Test environment:	Temp.:	25 °C	Humid.:	52%	Press.:	1012mbar
Test voltage:	AC 120V, 60Hz					
Test results:	Pass					

Measurement data:*Remarks:*

1. *During the test, pre-scan the GFSK, $\pi/4$ -DQPSK, 8-DPSK modulation, and found the GFSK modulation which it is worse case.*
2. *Pre-scan all kind of the place mode (X-axis, Y-axis, Z-axis), and found the Y-axis which it is worse case.*

■ 9kHz~30MHz

The low frequency, which started from 9 kHz to 30 MHz, was pre-scanned and the result which was 20 dB lower than the limit line per 15.31(o) was not reported.

■ Below 1GHz

Pre-scan all test modes of ANT1 and ANT2, found worst case at ANT1 GFSK 2480MHz, and so only show the test result of ANT1 GFSK 2480MHz


Horizontal:



No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over	
		MHz	Level	Factor	ment			
			dBuV	dB	dBuV/m	dB/m	dB	Detector
1	*	46.0164	34.87	-18.31	16.56	40.00	-23.44	QP
2		67.9129	34.83	-19.68	15.15	40.00	-24.85	QP
3		84.9995	35.54	-21.06	14.48	40.00	-25.52	QP
4		113.3163	36.73	-20.11	16.62	43.50	-26.88	QP
5		217.5443	37.55	-19.49	18.06	46.00	-27.94	QP
6		261.9753	36.80	-19.21	17.59	46.00	-28.41	QP

Final Level = Receiver Read level + Correct Factor

Vertical:



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	
		MHz	dBuV	dB	dBuV/m	dB/m	dB	Detector
1		47.4918	35.17	-18.37	16.80	40.00	-23.20	QP
2		59.8588	39.38	-18.75	20.63	40.00	-19.37	QP
3	*	67.9129	40.95	-19.68	21.27	40.00	-18.73	QP
4		106.3850	37.87	-20.32	17.55	43.50	-25.95	QP
5		255.6231	37.74	-19.27	18.47	46.00	-27.53	QP
6		365.5391	30.12	-17.38	12.74	46.00	-33.26	QP

Final Level =Receiver Read level + Correct Factor

■ Above 1-26.5GHz

Test channel:	Lowest channel
---------------	----------------

Peak value:

Frequency (MHz)	Read Level (dBuV)	Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4804	61.35	-3.61	57.74	74	-16.26	Vertical
7206	59.21	-0.85	58.36	74	-15.64	Vertical
4804	62.30	-3.61	58.69	74	-15.31	Horizontal
7206	57.81	-0.85	56.96	74	-17.04	Horizontal
---	---	---	---	---	---	---
---	---	---	---	---	---	---

Remark: Factor = Antenna Factor + Cable Loss – Pre-amplifier.

Average value:

Frequency (MHz)	Read Level (dBuV)	Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4804	45.55	-3.61	41.94	54	-12.06	Vertical
7206	46.21	-0.85	45.36	54	-8.64	Vertical
4804	46.27	-3.61	42.66	54	-11.34	Horizontal
7206	46.41	-0.85	45.56	54	-8.44	Horizontal
---	---	---	---	---	---	---
---	---	---	---	---	---	---

Remark: Factor = Antenna Factor + Cable Loss – Pre-amplifier.

Test channel:	Middle channel
---------------	----------------

Peak value:

Frequency (MHz)	Read Level (dBuV)	Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4882	62.21	-3.49	58.72	74	-15.28	Vertical
7326	55.92	-0.80	55.12	74	-18.88	Vertical
4882	62.14	-3.49	58.65	74	-15.35	Horizontal
7326	56.37	-0.80	55.57	74	-18.43	Horizontal
---	---	---	---	---	---	---
---	---	---	---	---	---	---

Remark: Factor = Antenna Factor + Cable Loss – Pre-amplifier.

Average value:

Frequency (MHz)	Read Level (dBuV)	Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4882	44.52	-3.49	41.03	54	-12.97	Vertical
7326	45.06	-0.80	44.26	54	-9.74	Vertical
4882	46.11	-3.49	42.62	54	-11.38	Horizontal
7326	45.93	-0.80	45.13	54	-8.87	Horizontal
---	---	---	---	---	---	---
---	---	---	---	---	---	---

Remark: Factor = Antenna Factor + Cable Loss – Pre-amplifier.

Test channel:	Highest channel
---------------	-----------------

Peak value:

Frequency (MHz)	Read Level (dBuV)	Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4960	60.24	-3.41	56.83	74	-17.17	Vertical
7440	59.88	-0.72	59.16	74	-14.84	Vertical
4960	62.14	-3.41	58.73	74	-15.27	Horizontal
7440	57.34	-0.72	56.62	74	-17.38	Horizontal
---	---	---	---	---	---	---
---	---	---	---	---	---	---

Remark: Factor = Antenna Factor + Cable Loss – Pre-amplifier.

Average value:

Frequency (MHz)	Read Level (dBuV)	Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4960	45.33	-3.41	41.92	54	-12.08	Vertical
7440	42.19	-0.80	41.39	54	-12.61	Vertical
4960	45.59	-3.41	42.18	54	-11.82	Horizontal
7440	43.14	-0.80	42.34	54	-11.66	Horizontal
---	---	---	---	---	---	---
---	---	---	---	---	---	---

Remark: Factor = Antenna Factor + Cable Loss – Pre-amplifier.

Remarks:

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor
2. “*”, means this data is the too weak instrument of signal is unable to test.
3. The emission levels of other frequencies are very lower than the limit and not show in test report.
4. During the test, pre-scan the ANT1 and ANT2 GFSK, $\pi/4$ -DQPSK, 8-DPSK modulation, and found the ANT1 GFSK modulation which it is worse case.

8 Test Setup Photo

Reference to the **appendix I** for details.

9 EUT Constructional Details

Reference to the **appendix II** for details.

-----End-----