

Letter of Declaration

Company: Shenzhen Meskey Technology Co., Ltd

Address: Room 501, Building 1, No.72,Xikeng Road, Xikeng, Fucheng, Longhua District,
Shenzhen, China

Product Name: wireless charger

Trade Mark: N/A

Model Number: W58,W30,W31,W32,W33,W34,W35,W36,W37,W38,W39,W40,W51,
W55,W56,W57,W59,W60,W61,W62,W63,W64,W65,W66,W67,W68,
W69,W70,W71,W72,W73,W74,W75,W76

FCC Identifier: 2A323-W58

Compliant with KDB 680106 D01 RF Exposure Wireless Charging Apps v03 section 5, b:

- a) Power transfer frequency is less than 1MHz.
Yes, the working frequency is 125KHz.
- b) Output power from each primary coil is less than or equal to 15 watts.
Yes, the maximum output power of mobile phone Charging Port is 15 watts, others are 5 watts.
- c) The system may consist of more than one source primary coils, charging one or more clients. If more than one primary coil is present, the coil pairs may be powered on at the same time.
Yes, three primary coils can work at the same time to charge three clients.
- d) Client device is placed directly in contact with the transmitter.
Yes, client device is placed directly in contact with the transmitter.
- e) Mobile exposure conditions only (portable exposure conditions are not covered by this exclusion).
Yes, EUT is for mobile exposure conditions only.
- f) The aggregate H-field strengths at 15 cm surrounding the device and 20 cm above the top surface from all simultaneous transmitting coils are demonstrated to be less than 50% of the MPE limit.
Yes, EUT h-field strengths levels are less than 50% of the MPE limit.

Name: Ivan zhang

Date: May 10, 2022

Title: Manager

Signature of applicant: *Ivan Zhang*