

# FCC Test Report

**Client Name** : Shenzhen Radiomaster Technology Co.,Ltd

**Client Address** : 4F Yang Tian Building, Area 72 Xing Dong  
community Xin An Street, Bao An district,  
Shen Zhen city, Guangdong Province, China

**Product Name** : Ranger

**Report Date** : Apr. 04, 2023

**Shenzhen Anbotek Compliance Laboratory Limited**



**Shenzhen Anbotek Compliance Laboratory Limited**

Address: 1/F., Building D, Sogood Science and Technology Park, Sanwei Community,  
Hangcheng Street, Bao'an District, Shenzhen, Guangdong, China.  
Tel: (86) 0755-26066440 Fax: (86) 0755-26014772 Email: service@anbotek.com

Code: AB-RF-05-b



Hotline

400-003-0500

www.anbotek.com.cn



# Contents

1. General Information .....	6
1.1. Client Information .....	6
1.2. Description of Device (EUT) .....	6
1.3. Auxiliary Equipment Used During Test .....	7
1.4. Description of Test Configuration .....	7
1.5. Description Of Test Setup .....	8
1.6. Test Equipment List .....	9
1.7. Measurement Uncertainty .....	10
1.8. Description of Test Facility .....	10
2. Summary of Test Results .....	11
3. Conducted Emission Test .....	12
3.1. Test Standard and Limit .....	12
3.2. Test Setup .....	12
3.3. Test Procedure .....	12
3.4. Test Data .....	12
4. Radiation Spurious Emission and Band Edge .....	15
4.1. Test Standard and Limit .....	15
4.2. Test Setup .....	15
4.3. Test Procedure .....	16
4.4. Test Data .....	17
5. Maximum Peak Output Power Test .....	25
5.1. Test Standard and Limit .....	25
5.2. Test Setup .....	25
5.3. Test Procedure .....	25
5.4. Test Data .....	25
6. 20DB Occupy Bandwidth Test .....	26
6.1. Test Standard .....	26
6.2. Test Setup .....	26
6.3. Test Procedure .....	26
6.4. Test Data .....	26
7. Carrier Frequency Separation Test .....	27
7.1. Test Standard and Limit .....	27
7.2. Test Setup .....	27
7.3. Test Procedure .....	27
7.4. Test Data .....	27
8. Number of Hopping Channel Test .....	28
8.1. Test Standard and Limit .....	28



8.2. Test Setup .....	28
8.3. Test Procedure .....	28
8.4. Test Data .....	28
9. Dwell Time Test .....	29
9.1. Test Standard and Limit .....	29
9.2. Test Setup .....	29
9.3. Test Procedure .....	29
9.4. Test Data .....	29
10. 100kHz Bandwidth of Frequency Band Edge Requirement .....	30
10.1. Test Standard and Limit .....	30
10.2. Test Setup .....	30
10.3. Test Procedure .....	30
10.4. Test Data .....	30
11. Antenna Requirement .....	31
11.1. Test Standard and Requirement .....	31
11.2. Antenna Connected Construction .....	31
APPENDIX I -- TEST SETUP PHOTOGRAPH .....	32
APPENDIX II -- EXTERNAL PHOTOGRAPH .....	32
APPENDIX III -- INTERNAL PHOTOGRAPH .....	32



# TEST REPORT

Applicant : Shenzhen Radiomaster Technology Co.,Ltd  
Manufacturer : Shenzhen Radiomaster Technology Co.,Ltd  
Product Name : Ranger  
Model No. : Ranger, Ranger MAX, Ranger MAXPRO, Ranger PRO  
Trade Mark : Radiomaster  
Rating(s) : Input: DC 6-16.8V

**Test Standard(s) : FCC Part15 Subpart C, Section 15.247**

**Test Method(s) : ANSI C63.10: 2020**

The device described above is tested by Shenzhen Anbotek Compliance Laboratory Limited to determine the maximum emission levels emanating from the device and the severe levels of the device can endure and its performance criterion. The measurement results are contained in this test report and Shenzhen Anbotek Compliance Laboratory Limited is assumed full of responsibility for the accuracy and completeness of these measurements. Also, this report shows that the EUT (Equipment Under Test) is technically compliant with the FCC Part 15 Subpart C requirements.

This report applies to above tested sample only and shall not be reproduced in part without written approval of Shenzhen Anbotek Compliance Laboratory Limited.

Date of receipt

Nov. 22, 2022

Date of Test

Nov. 22~Dec. 30, 2022

Prepared by

*Tu Tu Hong*

(TuTu Hong)

Approved & Authorized Signer

*Kingkong Jin*

(Kingkong Jin)



**Revision History**

Report Version	Description	Issued Date
R00	Original Issue.	Apr. 04, 2023



## 1. General Information

### 1.1. Client Information

Applicant	:	Shenzhen Radiomaster Technology Co.,Ltd
Address	:	4F Yang Tian Building, Area 72 Xing Dong community Xin An Street, Bao An district, Shen Zhen city, Guangdong Province, China
Manufacturer	:	Shenzhen Radiomaster Technology Co.,Ltd
Address	:	4F Yang Tian Building, Area 72 Xing Dong community Xin An Street, Bao An district, Shen Zhen city, Guangdong Province, China
Factory	:	Shenzhen Radiomaster Technology Co.,Ltd
Address	:	4F Yang Tian Building, Area 72 Xing Dong community Xin An Street, Bao An district, Shen Zhen city, Guangdong Province, China

### 1.2. Description of Device (EUT)

Product Name	:	Ranger Nano
Model No.	:	Ranger, Ranger MAX, Ranger MAXPRO, Ranger PRO (Note: All samples are the same except the model number, so we prepare "Ranger" for test only.)
Trade Mark	:	Radiomaster
Test Power Supply	:	AC 120V, 60Hz for adapter
Test Sample No.	:	1-2-1(Normal Sample), 1-2-2(Engineering Sample)
Adapter	:	N.A
<b>RF Specification</b>		
Operation Mode	:	<input type="checkbox"/> DSSS <input checked="" type="checkbox"/> FHSS
Operation Frequency	:	2402.4~2479.4 MHz
Number of Channel	:	78 Channels
Modulation Type	:	GFSK
Antenna Type	:	External antenna
Antenna Gain(Peak)	:	4.11 dBi (Provided by customer)
<b>Remark:</b> 1) For a more detailed features description, please refer to the manufacturer's specifications or the User's Manual.		



### 1.3. Auxiliary Equipment Used During Test

Description	Rating(s)
Adapter	M/N: A2023 Input: AC 100-240V 0.7A 50-60Hz USB1 Output: DC 5V 2.4A USB2 Output: DC 5V 2.4A

### 1.4. Description of Test Configuration



Channel	Freq. (MHz)	Channel	Freq. (MHz)	Channel	Freq. (MHz)	Channel	Freq. (MHz)	Channel	Freq. (MHz)
01	2402.40	17	2418.40	33	2434.40	49	2450.40	65	2466.40
02	2403.40	18	2419.40	34	2435.40	50	2451.40	66	2467.40
03	2404.40	19	2420.40	35	2436.40	51	2452.40	67	2468.40
04	2405.40	20	2421.40	36	2437.40	52	2453.40	68	2469.40
05	2406.40	21	2422.40	37	2438.40	53	2454.40	69	2470.40
06	2407.40	22	2423.40	38	2439.40	54	2455.40	70	2471.40
07	2408.40	23	2424.40	39	2440.40	55	2456.40	71	2472.40
08	2409.40	24	2425.40	40	2441.40	56	2457.40	72	2473.40
09	2410.40	25	2426.40	41	2442.40	57	2458.40	73	2474.40
10	2411.40	26	2427.40	42	2443.40	58	2459.40	74	2475.40
11	2412.40	27	2428.40	43	2444.40	59	2460.40	75	2476.40
12	2413.40	28	2429.40	44	2445.40	60	2461.40	76	2477.40
13	2414.40	29	2430.40	45	2446.40	61	2462.40	77	2478.40
14	2415.40	30	2431.40	46	2447.40	62	2463.40	78	2479.40
15	2416.40	31	2432.40	47	2448.40	63	2464.40	/	/
16	2417.40	32	2433.40	48	2449.40	64	2465.40	/	/

**Note:**

1. The engineering test program was provided and the EUT was programmed to be in continuously transmitting mode.
2. EUT was tested with channel 01, 40 and 78.



## 1.5. Description Of Test Setup





## 1.6. Test Equipment List

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1.	L.I.S.N. Artificial Mains Network	Rohde & Schwarz	ENV216	100055	Oct. 23, 2022	1 Year
2.	Three Phase V-type Artificial Power Network	CYBERTEK	EM5040DT	E215040DT001	Jul. 05, 2022	1 Year
3.	EMI Test Receiver	Rohde & Schwarz	ESCI	100627	Oct. 13, 2022	1 Year
4.	EMI Test Receiver	Rohde & Schwarz	ESR26	101481	Oct. 23, 2022	1 Year
5.	RF Switching Unit	Compliance Direction	RSU-M2	38303	Oct. 22, 2022	1 Year
6.	MXA Spectrum Analysis	Agilent	N9020A	MY51170037	Oct. 13, 2022	1 Year
7.	EMI Preamplifier	SKET Electronic	LNPA-0118G -45	SKET-PA-002	Oct. 13, 2022	1 Year
8.	Double Ridged Horn Antenna	SCHWARZBECK	BBHA 9120D	02555	Oct. 16, 2022	3 Year
9.	Bilog Broadband Antenna	Schwarzbeck	VULB9163	VULB 9163-289	Oct. 23, 2022	1 Year
10.	Loop Antenna	Schwarzbeck	FMZB1519B	00053	Oct. 23, 2022	1 Year
11.	Horn Antenna	A-INFO	LB-180400-K F	J211060628	Oct. 23, 2022	1 Year
12.	Pre-amplifier	SONOMA	310N	186860	Oct. 23, 2022	1 Year
13.	EMI Test Software EZ-EMC	SHURPLE	N/A	N/A	N/A	N/A
14.	MXA Spectrum Analysis	KEYSIGHT	N9020A	MY53280032	Oct. 13, 2022	1 Year
15.	MXG RF Vector Signal Generator	Agilent	N5182A	MY48180656	Oct. 13, 2022	1 Year
16.	Signal Generator	Agilent	E4421B	MY41000743	Oct. 13, 2022	1 Year
17.	DC Power Supply	IVYTECH	IV3605	1804D360510	Oct. 22, 2022	1 Year
18.	Constant Temperature Humidity Chamber	ZHONGJIAN	ZJ-KHWS80 B	N/A	Oct. 19, 2022	1 Year



### 1.7. Measurement Uncertainty

Radiation Uncertainty	:	Ur = 3.9 dB (Horizontal)
	:	Ur = 3.8 dB (Vertical)
Conduction Uncertainty	:	Uc = 3.4 dB

### 1.8. Description of Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

#### FCC-Registration No.: 184111

Shenzhen Anbotek Compliance Laboratory Limited, EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration No. 184111.

#### ISED-Registration No.: 8058A

Shenzhen Anbotek Compliance Laboratory Limited, EMC Laboratory has been registered and fully described in a report filed with the (ISED) Innovation, Science and Economic Development Canada. The acceptance letter from the ISED is maintained in our files. Registration 8058A.

#### Test Location

Shenzhen Anbotek Compliance Laboratory Limited.

1/F, Building D, Sogood Science and Technology Park, Sanwei community, Hangcheng Street, Bao'an District, Shenzhen, Guangdong, China.518102



## 2. Summary of Test Results

Standard Section	Test Item	Result
15.203/15.247(c)	Antenna Requirement	PASS
15.207	Conducted Emission	PASS
15.205/15.209	Spurious Emission	PASS
15.247(b)(1)	Conducted Peak Output Power	PASS
15.247(a)(1)	20dB Occupied Bandwidth	PASS
15.247(a)(1)	Carrier Frequencies Separation	PASS
15.247(a)(1)(iii)	Number of Hopping Channel	PASS
15.247(a)(1)(iii)	Dwell Time	PASS
15.247(d)	Band Edge	PASS
<b>Remark:</b> "N/A" is an abbreviation for Not Applicable.		




## 3. Conducted Emission Test

### 3.1. Test Standard and Limit

Test Standard	FCC Part15 Section 15.207		
	Frequency	Maximum RF Line Voltage (dBuV)	
		Quasi-peak Level	Average Level
Test Limit	150kHz~500kHz	66 ~ 56 *	56 ~ 46 *
	500kHz~5MHz	56	46
	5MHz~30MHz	60	50

**Remark:** (1) \*Decreasing linearly with logarithm of the frequency.  
 (2) The lower limit shall apply at the transition frequency.

### 3.2. Test Setup



### 3.3. Test Procedure

The EUT system is connected to the power mains through a line impedance stabilization network (L.I.S.N.). This provides a 50ohm coupling impedance for the EUT system. Please refer the block diagram of the test setup and photographs. Both sides of AC line are checked to find out the maximum conducted emission. In order to find the maximum emission levels, the relative positions of equipment and all of the interface cables shall be changed according to FCC ANSI C63.10: 2020 on Conducted Emission Measurement.

The bandwidth of test receiver (ESCI) set at 9kHz.

The frequency range from 150kHz to 30MHz is checked.

### 3.4. Test Data

#### PASS

During the test, pre-scan all modes, only the worst case is recorded in the report.


AC conducted emission pre-test at both at AC 120V/60Hz and AC 240V/60Hz modes, recorded worst case AC 120V/60Hz.

Please to see the following pages.



### Conducted Emission Test Data

Test Site: 1# Shielded Room  
 Operating Condition: Low CH (2402.4MHz)  
 Test Specification: AC 120V, 60Hz for adapter  
 Comment: Live Line  
 Temp.(°C)/Hum.(%RH): 22.8°C/51%RH




No.	Freq. (MHz)	Reading (dBuV)	Factor (dB)	Result (dBuV)	Limit (dBuV)	Over Limit (dB)	Detector	Remark
1	0.1500	26.44	9.82	36.26	65.99	-29.73	QP	
2	0.5540	26.54	9.86	36.40	56.00	-19.60	QP	
3	0.5580	19.38	9.86	29.24	46.00	-16.76	AVG	
4	1.2460	21.09	9.85	30.94	56.00	-25.06	QP	
5	1.2460	12.77	9.85	22.62	46.00	-23.38	AVG	
6	1.8500	11.64	9.85	21.49	46.00	-24.51	AVG	
7	1.9260	21.09	9.85	30.94	56.00	-25.06	QP	
8	2.6619	18.93	9.85	28.78	56.00	-27.22	QP	
9	2.6619	11.85	9.85	21.70	46.00	-24.30	AVG	
10	4.2380	18.02	9.85	27.87	56.00	-28.13	QP	
11	4.2380	10.96	9.85	20.81	46.00	-25.19	AVG	
12	5.7100	9.45	9.87	19.32	50.00	-30.68	AVG	



### Conducted Emission Test Data

Test Site: 1# Shielded Room  
 Operating Condition: Low CH (2402.4MHz)  
 Test Specification: AC 120V, 60Hz for adapter  
 Comment: Neutral Line  
 Temp.(°C)/Hum.(%RH): 22.8°C/51%RH



No.	Freq. (MHz)	Reading (dBuV)	Factor (dB)	Result (dBuV)	Limit (dBuV)	Over Limit (dB)	Detector	Remark
1	0.1500	25.63	9.82	35.45	65.99	-30.54	QP	
2	0.4900	12.31	9.86	22.17	46.17	-24.00	AVG	
3	0.5580	24.13	9.86	33.99	56.00	-22.01	QP	
4	0.5580	18.27	9.86	28.13	46.00	-17.87	AVG	
5	0.7539	15.97	9.87	25.84	56.00	-30.16	QP	
6	1.1380	10.00	9.86	19.86	46.00	-26.14	AVG	
7	1.1580	18.20	9.86	28.06	56.00	-27.94	QP	
8	1.8900	17.28	9.85	27.13	56.00	-28.87	QP	
9	1.9780	9.57	9.85	19.42	46.00	-26.58	AVG	
10	2.6900	9.92	9.85	19.77	46.00	-26.23	AVG	
11	3.4260	9.48	9.85	19.33	46.00	-26.67	AVG	
12	3.4500	17.15	9.85	27.00	56.00	-29.00	QP	



## 4. Radiation Spurious Emission and Band Edge

### 4.1. Test Standard and Limit

Test Standard	FCC Part15 C Section 15.209 and 15.205				
Test Limit	Frequency (MHz)	Field strength (microvolt/meter)	Limit (dBuV/m)	Remark	Measurement distance (m)
	0.009MHz~0.490MHz	2400/F(kHz)	-	-	300
	0.490MHz-1.705MHz	24000/F(kHz)	-	-	30
	1.705MHz-30MHz	30	-	-	30
	30MHz~88MHz	100	40.0	Quasi-peak	3
	88MHz~216MHz	150	43.5	Quasi-peak	3
	216MHz~960MHz	200	46.0	Quasi-peak	3
	960MHz~1000MHz	500	54.0	Quasi-peak	3
	Above 1000MHz		500	54.0	Average
		-	74.0	Peak	3

**Remark:**

(1)The lower limit shall apply at the transition frequency.

(2) 15.35(b), Unless otherwise specified, the limit on peak radio frequency emissions is 20dB above the maximum permitted average emission limit applicable to the equipment under test. This peak limit applies to the total peak emission level radiated by the device.

### 4.2. Test Setup




Figure 1. Below 30MHz




Figure 2. 30MHz to 1GHz




Figure 3. Above 1 GHz

### 4.3. Test Procedure

For below 1GHz: The EUT is placed on a turntable, which is 0.8m above the ground plane.

For above 1GHz: The EUT is placed on a turntable, which is 1.5m above the ground plane.

The turn table can rotate 360 degrees to determine the position of the maximum emission level. The EUT is set 3 meters away from the receiving antenna which is mounted on a antenna tower. The antenna can be moved up and down from 1 to 4 meters to find out the maximum emission level. Rotated the EUT through three orthogonal axes to determine the maximum emissions, both horizontal





and vertical polarization of the antenna are set on test. The EUT is tested in 9\*6\*6 Chamber. The device is evaluated in xyz orientation.

For the radiated emission test above 1GHz:

Place the measurement antenna away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response. The measurement antenna may have to be higher or lower than the EUT, depending on the radiation pattern of the emission and staying aimed at the emission source for receiving the maximum signal. The final measurement antenna elevation shall be that which maximizes the emissions. The measurement antenna elevation for maximum emissions shall be restricted to a range of heights of from 1 m to 4 m above the ground or reference ground plane.

For 9kHz to 150kHz, Set the spectrum analyzer as:

RBW = 200Hz, VBW =1kHz, Detector= Quasi-Peak, Trace mode= Max hold, Sweep- auto couple.

For 150kHz to 30MHz, Set the spectrum analyzer as:

RBW = 9KHz, VBW =30kHz, Detector= Quasi-Peak, Trace mode= Max hold, Sweep- auto couple.

For 30MHz to 1000MHz, Set the spectrum analyzer as:

RBW = 120kHz, VBW =300kHz, Detector= Quasi-Peak, Trace mode= Max hold, Sweep- auto couple.

For above 1GHz, Set the spectrum analyzer as:

RBW =1MHz, VBW =1MHz, Detector= Peak, Trace mode= Max hold, Sweep- auto couple.

For average measurement: use duty cycle correction factor method (DCCF)

Average level = Peak level + DCCF

#### 4.4. Test Data

##### PASS

During the test, Pre-scan all kind of the place mode (X-axis, Y-axis, Z-axis), and found the X-axis is the worst case.


The test results of 9kHz-30MHz was attenuated more than 20dB below the permissible limits, so the results don't record in the report.

During the test, pre-scan all modes, only the worst case is recorded in the report.



### Test Results (30~1000MHz)

Test Mode: Low CH (2402.4MHz)  
 Power Source: AC 120V, 60Hz for adapter  
 Polarization: Vertical  
 Temp.(°C)/Hum.(%RH): 24.1°C/48%RH




No.	Freq. (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	Detector	Height (cm)	degree (deg)	Remark
1	36.3814	42.00	-16.43	25.57	40.00	-14.43	QP			
2	80.9275	49.65	-19.17	30.48	40.00	-9.52	QP			
3	109.4116	49.26	-18.09	31.17	43.50	-12.33	QP			
4	167.8243	51.67	-21.24	30.43	43.50	-13.07	QP			
5	455.9058	44.32	-13.51	30.81	46.00	-15.19	QP			
6	504.7062	47.21	-12.17	35.04	46.00	-10.96	QP			



### Test Results (30~1000MHz)

Test Mode: Low CH (2402.4MHz)  
 Power Source: AC 120V, 60Hz for adapter  
 Polarization: Horizontal  
 Temp.(°C)/Hum.(%RH): 24.1°C/48%RH



No.	Freq. (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	Detector	Height (cm)	degree (deg)	Remark
1	32.9791	45.44	-19.18	26.26	40.00	-13.74	QP			
2	79.8003	45.42	-23.31	22.11	40.00	-17.89	QP			
3	455.9058	43.16	-15.28	27.88	46.00	-18.12	QP			
4	504.7062	44.30	-13.57	30.73	46.00	-15.27	QP			
5	827.4934	45.24	-7.83	37.41	46.00	-8.59	QP			
6	938.8326	34.69	-5.77	28.92	46.00	-17.08	QP			



**Test Results (1GHz-25GHz)**

Test channel: Lowest						
Peak value:						
Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4804.80	27.48	15.27	42.75	74.00	-31.25	Vertical
7207.20	28.71	18.09	46.80	74.00	-27.20	Vertical
9609.60	29.54	23.76	53.30	74.00	-20.70	Vertical
12012.00	*			74.00		Vertical
14414.40	*			74.00		Vertical
4804.80	27.89	15.27	43.16	74.00	-30.84	Horizontal
7207.20	28.63	18.09	46.72	74.00	-27.28	Horizontal
9609.60	28.46	23.76	52.22	74.00	-21.78	Horizontal
12012.00	*			74.00		Horizontal
14414.40	*			74.00		Horizontal
Average value:						
Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	polarization
4804.80	16.86	15.27	32.13	54.00	-21.87	Vertical
7207.20	17.74	18.09	35.83	54.00	-18.17	Vertical
9609.60	18.56	23.76	42.32	54.00	-11.68	Vertical
12012.00	*			54.00		Vertical
14414.40	*			54.00		Vertical
4804.80	16.24	15.27	31.51	54.00	-22.49	Horizontal
7207.20	17.69	18.09	35.78	54.00	-18.22	Horizontal
9609.60	17.77	23.76	41.53	54.00	-12.47	Horizontal
12012.00	*			54.00		Horizontal
14414.40	*			54.00		Horizontal



**Test Results (1GHz-25GHz)**

Test channel: Middle						
Peak value:						
Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4882.80	27.50	15.42	42.92	74.00	-31.08	Vertical
7324.20	28.56	18.02	46.58	74.00	-27.42	Vertical
9765.60	28.55	23.80	52.35	74.00	-21.65	Vertical
12207.00	*			74.00		Vertical
14648.40	*			74.00		Vertical
4882.80	27.59	15.42	43.01	74.00	-30.99	Horizontal
7324.20	28.62	18.02	46.64	74.00	-27.36	Horizontal
9765.60	28.16	23.80	51.96	74.00	-22.04	Horizontal
12207.00	*			74.00		Horizontal
14648.40	*			74.00		Horizontal
Average value:						
Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	polarization
4882.80	16.59	15.42	32.01	54.00	-21.99	Vertical
7324.20	17.84	18.02	35.86	54.00	-18.14	Vertical
9765.60	18.42	23.80	42.22	54.00	-11.78	Vertical
12207.00	*			54.00		Vertical
14648.40	*			54.00		Vertical
4882.80	16.15	15.42	31.57	54.00	-22.43	Horizontal
7324.20	17.25	18.02	35.27	54.00	-18.73	Horizontal
9765.60	18.28	23.80	42.08	54.00	-11.92	Horizontal
12207.00	*			54.00		Horizontal
14648.40	*			54.00		Horizontal



## Test Results (1GHz-25GHz)

Test channel: Highest						
Peak value:						
Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4958.80	27.77	15.58	43.35	74.00	-30.65	Vertical
7438.20	28.57	17.93	46.50	74.00	-27.50	Vertical
9917.60	29.10	23.83	52.93	74.00	-21.07	Vertical
12397.00	*			74.00		Vertical
14876.40	*			74.00		Vertical
4958.80	27.66	15.58	43.24	74.00	-30.76	Horizontal
7438.20	28.65	17.93	46.58	74.00	-27.42	Horizontal
9917.60	28.84	23.83	52.67	74.00	-21.33	Horizontal
12397.00	*			74.00		Horizontal
14876.40	*			74.00		Horizontal
Average value:						
Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	polarization
4958.80	17.71	15.58	33.29	54.00	-20.71	Vertical
7438.20	18.85	17.93	36.78	54.00	-17.22	Vertical
9917.60	18.97	23.83	42.80	54.00	-11.20	Vertical
12397.00	*			54.00		Vertical
14876.40	*			54.00		Vertical
4958.80	17.59	15.58	33.17	54.00	-20.83	Horizontal
7438.20	18.62	17.93	36.55	54.00	-17.45	Horizontal
9917.60	18.18	23.83	42.01	54.00	-11.99	Horizontal
12397.00	*			54.00		Horizontal
14876.40	*			54.00		Horizontal


Remark:


1. Result = Reading + Factor

2. "\*" means the test results were attenuated more than 20dB below the permissible limits, so the results don't record in the report.



### Radiated Band Edge:








## 5. Maximum Peak Output Power Test

### 5.1. Test Standard and Limit

Test Standard	FCC Part15 C Section 15.247 (b)(1)
Test Limit	For frequency hopping systems operating in the 2400-2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725-5850 MHz band: 1 watt. For all other frequency hopping systems in the 2400-2483.5 MHz band: 0.125 watts.

### 5.2. Test Setup



### 5.3. Test Procedure

1. The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram above,
2. Spectrum Setting:
  - RBW > the 20 dB bandwidth of the emission being measured
  - Span = approximately 5 times the 20 dB bandwidth, centered on a hopping channel
  - VBW ≥ RBW
  - Sweep = auto
  - Detector function = peak
  - Trace = max hold

### 5.4. Test Data

Pass

*Please refer to Appendix C of the Appendix Test Data.*




## 6. 20DB Occupy Bandwidth Test

### 6.1. Test Standard

Test Standard	FCC Part15 C Section 15.247 (a)(1)
---------------	------------------------------------

### 6.2. Test Setup



### 6.3. Test Procedure

Using the following spectrum analyzer settings:

1. Span= approximately 2 to 3 times the 20dB bandwidth, centered on a hopping channel.
2. Set the RBW  $\geq 1\%$  of the 20 dB bandwidth.
3. Set the VBW  $\geq$ RBW
4. Sweep time = auto couple.
5. Detector function = peak.
6. Trace mode = max hold.
7. Allow trace to fully stabilize.

### 6.4. Test Data

Pass

*Please refer to Appendix A of the Appendix Test Data.*




## 7. Carrier Frequency Separation Test

### 7.1. Test Standard and Limit

Test Standard	FCC Part15 C Section 15.247 (a)(1)
Test Limit	2/3 of the 20dB bandwidth base on the transmission power is less than 0.125W.

### 7.2. Test Setup



### 7.3. Test Procedure

The EUT must have its hopping function enabled. Using the following spectrum analyzer settings:

1. Span= Wide enough to capture the peaks of two adjacent channels
2. Set the RBW =approximately 30% of the channel spacing.
3. Set the VBW  $\geq$  RBW.
4. Sweep time = auto couple.
5. Detector function = peak.
6. Trace mode = max hold.
7. Allow trace to fully stabilize.

### 7.4. Test Data

Pass

*Please refer to Appendix D of the Appendix Test Data.*




## 8. Number of Hopping Channel Test

### 8.1. Test Standard and Limit

Test Standard	FCC Part15 C Section 15.247 (a)(1)(iii)
Test Limit	>15 channels

### 8.2. Test Setup



### 8.3. Test Procedure

The EUT must have its hopping function enabled. Using the following spectrum analyzer setting:

1. Span= the frequency band of operation
2. Set the RBW = less than 30% of the channel spacing or the 20 dB bandwidth, whichever is smaller.
3. Set the VBW  $\geq$  RBW.
4. Sweep time = auto couple.
5. Detector function = peak.
6. Trace mode = max hold.
7. Allow trace to fully stabilize.

### 8.4. Test Data

Pass

*Please refer to Appendix F of the Appendix Test Data.*




## 9. Dwell Time Test

### 9.1. Test Standard and Limit

Test Standard	FCC Part15 C Section 15.247 (a)(1)(iii)
Test Limit	0.4 s

### 9.2. Test Setup



### 9.3. Test Procedure

The EUT must have its hopping function enabled. Use the following spectrum analyzer settings:

1. Span= zero span, centered on a hopping channel
2. Set the RBW = 1 MHz.
3. Set the VBW  $\geq$  RBW.
4. Sweep time = as necessary to capture the entire dwell time per hopping channel.
5. Detector function = peak.
6. Trace mode = max hold.
7. Allow trace to fully stabilize.

### 9.4. Test Data

Pass

*Please refer to Appendix E of the Appendix Test Data.*




## 10. 100kHz Bandwidth of Frequency Band Edge Requirement

### 10.1. Test Standard and Limit

Test Standard	FCC Part15 C Section 15.247 (d)
Test Limit	In any 100 kHz bandwidth outside the frequency bands in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power, In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in 15.209(a).

### 10.2. Test Setup



### 10.3. Test Procedure

The EUT must have its hopping/Non-hopping function enabled. Using the following spectrum analyzer setting:

1. Set the RBW = 100kHz.
2. Set the VBW = 300kHz.
3. Sweep time = auto couple.
4. Detector function = peak.
5. Trace mode = max hold.
6. Allow trace to fully stabilize.

### 10.4. Test Data

Pass

Please refer to Appendix G & Appendix H of the Appendix Test Data.



## 11. Antenna Requirement

### 11.1. Test Standard and Requirement

Test Standard	FCC Part15 Section 15.203 /247(c)
Requirement	<p>1) 15.203 requirement: An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.</p> <p>2) 15.247(c) (1)(i) requirement: Systems operating in the 2400-2483.5 MHz band that is used exclusively for fixed. Point-to-point operations may employ transmitting antennas with directional gain greater than 6dBi provided the maximum conducted output power of the intentional radiator is reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6 dBi.</p>

### 11.2. Antenna Connected Construction

The antenna is External antenna which permanently attached, and the best case gain of the antenna is 4.11dBi. It complies with the standard requirement.



## **APPENDIX I -- TEST SETUP PHOTOGRAPH**

Please refer to separated files Appendix I -- Test Setup Photograph

## **APPENDIX II -- EXTERNAL PHOTOGRAPH**

Please refer to separated files Appendix II -- External Photograph

## **APPENDIX III -- INTERNAL PHOTOGRAPH**

Please refer to separated files Appendix III -- Internal Photograph

----- End of Report -----

