

# Maximum Permissible Exposure(MPE) Report

## 1. Applicable Standard

FCC Part §1.1310

## 2. Requirements

Limits For Maximum Permissible Exposure (MPE)				
Frequency range (MHz)	Electric field strength(V/m)	Magnetic field Strength(A/m)	Power density (mw/cm <sup>2</sup> )	Averaging time (minutes)
0.3-1.34	614	1.63	*100	30
1.34-30	824/f	2.19/f	*180/f <sup>2</sup>	30
30-300	27.5	0.0173	0.2	30
300-1,500			f/1500	30
1,500-100,000			1.0	30

## 3. MPE Calculation

Predication of MPE limit at a given distance

$$S = \frac{PG}{4\pi R^2}$$

S = Power density (In appropriate units, e.g., mW/cm<sup>2</sup>)

P = Power input to the antenna ( In appropriate units, e.g., mW)

G = Power gain og the antenna in the direction of interest relative to an isotropic radiator, the power gain factor,

Is normally numeric gain

R =Distance tp the center of radiation of the antenna(In appropriate units, e.g., cm

## 4. Test Result

Operation Bands	Frequency(MHz)	Max. Output power(dBm)	Cable loss (dB)	Power to Antenna(mW)	Antenna gain	
					Isotropic	Numeric
UL1850-1915	1858.71	19.05	3.6	35.08	10	10.00
UL1710-1755	1715.94	18.44	3.6	30.48	10	10.00
UL824-869	837.40	20.22	2.5	59.16	8	6.31
UL698-716	700.50	19.80	2.1	58.88	8	6.31
UL776-787	780.62	19.81	2.1	59.02	8	6.31
DL1930-1995	1946.25	2.20	3.1	0.81	10	10.00
DL2110-2155	2118.64	2.57	3.2	0.86	10	10.00
DL869-894	874.95	2.81	1.9	1.23	8	6.31
DL728-746	740.74	5.89	1.8	2.56	8	6.31
DL746-757	749.80	5.81	1.8	2.52	8	6.31

Operation Bands	Power (mW)	Antenna gain(G)	Measure Distance(cm)	Power density (mW/cm <sup>2</sup> )	MPE limit (mW/cm <sup>2</sup> )
UL1850-1915	35.08	10.00	20	0.0698	1
UL1710-1755	30.48	10.00	20	0.0606	1
UL824-869	59.16	6.31	20	0.0743	0.56
UL698-716	58.88	6.31	20	0.0739	0.47
UL776-787	59.02	6.31	20	0.0741	0.52
DL1930-1995	0.81	10.00	20	0.0016	1
DL2110-2155	0.86	10.00	20	0.0017	1
DL869-894	1.23	6.31	20	0.0015	0.58
DL728-746	2.56	6.31	20	0.0032	0.49
DL746-757	2.52	6.31	20	0.0032	0.50

**Results: PASS**