

# Maximum Permissible Exposure(MPE) Report

## 1. Applicable Standard

FCC Part §1.1310

## 2. Requirements

Limits For Maximum Permissible Exposure (MPE)				
Frequency range (MHz)	Electric field strength(V/m)	Magnetic field Strength(A/m)	Power density (mw/cm <sup>2</sup> )	Averaging time (minutes)
0.3-1.34	614	1.63	*100	30
1.34-30	824/f	2.19/f	*180/f <sup>2</sup>	30
30-300	27.5	0.0173	0.2	30
300-1,500			f/1500	30
1,500-100,000			1.0	30

## 3. MPE Calculation

Predication of MPE limit at a given distance

$$S = \frac{PG}{4\pi R^2}$$

S = Power density (In appropriate units, e.g., mW/cm<sup>2</sup>)

P = Power input to the antenna ( In appropriate units, e.g., mW)

G = Power gain og the antenna in the direction of interest relative to an isotropic radiator, the power gain factor,

Is normally numeric gain

R =Distance tp the center of radiation of the antenna(In appropriate units, e.g., cm

## 4. Test Result

Operation Bands	Frequency(MHz)	Max. Output power(dBm)	Cable loss (dB)	Power to Antenna(mW)	Antenna gain	
					Isotropic	Numeric
UL1850-1915	1889.91	21.12	3.6	56.49	10	10.00
UL1710-1755	1748.90	20.27	3.6	46.45	10	10.00
UL824-869	832.45	21.33	2.5	76.38	8	6.31
UL698-716	704.26	23.52	2.1	138.68	8	6.31
UL776-787	784.12	21.05	2.1	78.52	8	6.31
DL1930-1995	1940.27	6.08	3.1	1.99	10	10.00
DL2110-2155	2122.90	2.54	3.2	0.86	10	10.00
DL869-894	880.00	3.17	1.9	1.34	8	6.31
DL728-746	741.10	6.05	1.8	2.66	8	6.31
DL746-757	750.36	3.36	1.8	1.43	8	6.31

Operation Bands	Power (mW)	Antenna gain(G)	Measure Distance(cm)	Power density (mW/cm <sup>2</sup> )	MPE limit (mW/cm <sup>2</sup> )
UL1850-1915	56.49	10.00	20	0.1124	1
UL1710-1755	46.45	10.00	20	0.0924	1
UL824-869	76.38	6.31	20	0.0959	0.55
UL698-716	138.68	6.31	20	0.1741	0.47
UL776-787	78.52	6.31	20	0.0986	0.52
DL1930-1995	1.99	10.00	20	0.0040	1
DL2110-2155	0.86	10.00	20	0.0017	1
DL869-894	1.34	6.31	20	0.0017	0.59
DL728-746	2.66	6.31	20	0.0033	0.49
DL746-757	1.43	6.31	20	0.0018	0.50

**Results: PASS**