






<div> <div>FRANKLINWH</div> <div>Franklin Home Power</div> </div>	
Model	aGate X
Compliance	UL 1741 PCS;UL67;UL869A; UL916;FCC Part 15,Class B
<div> <div>   </div> </div>	
Electrical	
Rated Voltage	120/240VAC Split-phase
Rated Input	160A
Rated Frequency	60Hz
O.C. Protection Device Max.	200A
Short-Circuit Breaking Capacity	20kA
FCC ID:	2A34J-AGATEX
IC:	28082-AGATEX
Contains FCC ID:	XMR201909EC25AFX
Contains IC:	10224A-2019EC25AFX
Environment	
Operation Temperature Range	-20 °C to 50 °C (-4°F to 122°F)
Enclosure Type	NEMA Type 3R
Ingress Protection	IP 44
Protective Class	Class I
Environment	Indoor/Outdoor
Maximum Elevation	3000m(9843ft)
Weight	23kg(50lbs)
WARNING: Installation and service should be performed by qualified technicians only. Risk of electrical shock. Hazardous live parts inside. Keep the equipment terminal cover in place and securely fastened at all times. Do not remove the inner panel cover until the aPower unit has been powered off using the side mounted power button for at least 5 minutes. Do not remove the inner panel cover until all live connections have been disconnected by switching off at the breakers including the grid, solar PV, fuel generator, and aPower(s). <div>    </div>	
Manufacturer:FranklinWH Technologies Co., Ltd. Website :www.franklinwh.com Email :service@franklinwh.com	
Made in China	

200 mm

技术要求:

- 1.印刷清晰无毛边，位置大小准确；
- 2.印刷图案、字体如图墨稿，印刷字体Iato；
- 3.印刷底色为材料原色，印刷图文内容颜色为黑色；
- 4.最外圈细线为裁切轮廓线，非印刷线。

	A03						编码/料号	10120003
ZZJ202204024	A02	如A02图纸所示增加内容				20220426		
ZZJ202203066	A01	更改内容				20220329	名 称	aGate铭牌
ZZJ202111050	A00	/				20211123	材 质	3M-7818
归档单号		版 本		更改内容		日期		表面处理
设 计	邓金平	标准化	巫晓冰	视 角 	重 量	比 例 1:1	产品型号	FRANKLINWIH 深圳市富兰瓦时技术有限公司
审 核	张训银	审 定						
批 准	鬲新海	第 1 张	共 1 张					