

Matosinhos, July 5, 2023

RF Exposure Analysis – SAR Test Exemption – ILOGGER CASE 4

FCC ID: 2A350-ILOGGERCASE4

The ILOGGER CASE 4 equipment operates using a 13.56 MHz transmitter.

The following FCC Rule Parts and Procedures are applicable:

KDB447498 DO4 VO1 – Interim General RF Exposure Guidance

Part 1.1307(b)(3)(i)(A) - Blanket RF exposure exemption (i)

Part 1.1307(b)(3)(i)(C) - SAR test exemption (ii)

Part 1.1307(b)(3)(i)(B) - SAR test exemption (iii)

For the ILOGGER CASE 4

Operating Frequency: 13.56 MHz

Tx Power_{max} (declared): 66.2 dB μ V/m @3m = -29.1 dBm EIRP = -32.1 dBm ERP

Measured radiated power – Ref KDB447498 DO4 Section 3.1.2 –

When an antenna port is not available on the device to support conducted power measurement, e.g.: with built-in integral antennas, the available maximum output power or ERP, whichever is larger, and tolerance allowed for production units shall be used to determine RF exposure test exemption and compliance.

Evaluation


From Part 1.1307, RF exposure exemption applies if the maximum transmitted power is less than the maximum of the following three criteria:

- i) Less than 1 mw Blanket exemption. $P_{TH} = 0.001 W$ – §1.1307(b)(3)(i)(A)
- ii) determination of exemption under the MPE-based §1.1307(b)(3)(i)(C), if i) not met
- iii) determination of exemption under the SAR-based §1.1307(b)(3)(i)(B) if both i) and ii) are not met;

Conclusion

The ILOGGER CASE 4 source-based, time-averaged power is -32.1 dBm.

i.e.: less than 1 mW (0 dBm), so complies with the RF exposure blanket exemption in accordance with §1.1307(b)(3)(i)(A).



André Toga
Operations Manager