

S

5

A

RADIO TEST REPORT

Report No: STS2111204H02

Issued for

Shenzhen Maxima Electronic Technology Co., Ltd.

3rd Floor, Building B2, Hengfeng Industrial Town, Xixiang, Baoan, Shenzhen, Guangdong, China

Product Name:	Bluetooth tire pressure monitoring system
Brand Name:	KTD KINGAUTO
Model Name:	KTD330
Series Model:	KTD336, KTD333, KTD360
FCC ID:	2A38CAUTO330
Test Standard:	FCC 47CFR §2.1093

Any reproduction of this document must be done in full. No single part of this document may be reproduced without permission from STS, all test data presented in this report is only applicable to presented test sample.

Shenzhen STS Test Services Co., Ltd. A 1/F, Building B, Zhuoke Science Park, No.190 Chongqing Road, HepingShequ, Fuyong Sub-District, Bao'an District, Shenzhen, Guang Dong, China TEL: +86-755 3688 6288 FAX: +86-755 3688 6277 E-mail:sts@stsapp.com



Test Report Certification

	Shenzhen Maxima Electronic Technology Co., Ltd. 3rd Floor, Building B2, Hengfeng Industrial Town,Xixiang, Baoan, Shenzhen, Guangdong, China
Manufacturer's Name:	Shenzhen Maxima Electronic Technology Co., Ltd.
Address:	3rd Floor, Building B2, Hengfeng Industrial Town,Xixiang, Baoan, Shenzhen, Guangdong, China
Product Description	
Product Name:	Bluetooth tire pressure monitoring system
Brand Name:	KTD KINGAUTO
Model Name	. KTD330
Series Model:	KTD336, KTD333, KTD360
Standards	FCC 47CFR §2.1093

This report shall not be reproduced except in full, without the written approval of STS, this document only be altered or revised by STS, personal only, and shall be noted in the revision of the document.

Date of Test:	
Date of receipt of test item:	30 Nov. 2021
Date (s) of performance of tests:	30 Nov. 2021 ~ 26 Jan. 2022
Date of Issue	26 Jan. 2022
Test Result	Pass

Testing Engineer

(Chris Chen)

Technical Manager :

ean She



Authorized Signatory :

ali

(Sean she)

(Vita Li)

Page 3 of 9





TABLE OF CONTENTS

1. GENERAL INFORMATION	5
1.1 GENERAL DESCRIPTION OF THE EUT	5
1.2 TEST FACTORY	6
2. FCC 47CFR §2.1093 REQUIREMENT	7
2.1 TEST STANDARDS	7
2.2 LIMIT	7
2.3 TEST RESULT	9





Page 4 of 9

Report No.: STS2111204H02

Revision History

Rev.	Issue Date	Report No.	Effect Page	Contents
00	26 Jan. 2022	STS2111204H02	ALL	Initial Issue



Shenzhen STS Test Services Co., Ltd.



Page 5 of 9

Report No.: STS2111204H02

1. GENERAL INFORMATION

1.1 GENERAL DESCRIPTION OF THE EUT

Product Name	Bluetooth tire pressure monitoring system		
Brand Name	KTD KINGAUTO		
Model Name	KTD330		
Series Model	KTD336, KTD333, KTD360		
Model Difference	Different appearance		
Product Description	The EUT is Blueto Operation Frequency: Modulation Type: Antenna gain: Antenna Designation:	oth tire pressure monitoring system 2402~2480 MHz GFSK 1.99dBi PIFA	
Battery	Rated Voltage: 3.7V Charge Limit Voltage: 500mAh		
Adapter	Input: DC 12V Output: DC 12V		
Hardware Version	HouCheV03		
Software Version	HB-E2.2		

Page 6 of 9



Report No.: STS2111204H02

1.2 TEST FACTORY

SHENZHEN STS TEST SERVICES CO., LTD Add. : A 1/F, Building B, Zhuoke Science Park, No.190 Chongqing Road, HepingShequ, Fuyong Sub-District, Bao'an District, Shenzhen, Guang Dong, China FCC test Firm Registration Number: 625569

IC test Firm Registration Number: 12108A

A2LA Certificate No.: 4338.01



Shenzhen STS Test Services Co., Ltd.





2. FCC 47CFR §2.1093 REQUIREMENT

2.1 TEST STANDARDS

The limit for Maximum Permissible Exposure (MPE) specified in KDB 447498 D01 General RF Exposure Guidance v06 is followed. The gain of the antennas used in the product is extracted from the Antenna data sheets provided and also the maximum total power input to the antenna is measured. Through the Friis transmission formula and the maximum gain of the antenna, we can calculate the distance, away from the product, where the limit of MPE is reached. Although the Friis Transmission formula is far field assumption, the calculated result of that is an over-prediction for near field power density. It is taken as worst case to specify the safety range.

2.2 LIMIT

Approximate SAR Test Exclusion Power Thresholds at Selected Frequencies and Test Separation Distances are illustrated in the following Table.

MHz	5	10	15	20	25	mm
150	39	77	116	155	194	
300	27	55	82	110	137	
450	22	45	67	89	112	
835	16	33	49	66	82	
900	16	32	47	63	79	
1500	12	24	37	49	61	SAR Test Exclusion
1900	11	22	33	44	54	Threshold (mW)
2450	10	19	29	38	48	
3600	8	16	24	32	40	
5200	7	13	20	26	33	
5400	6	13	19	26	32	
5800	6	12	19	25	31	
MHz	30	35	40	45	50	mm
150	232	271	310	349	387	
300	164	192	219	246	274	
450	134	157	179	201	224	
835	98	115	131	148	164	
900	95	111	126	142	158	
1500	73	86	98	110	122	SAR Test Exclusion
1900	65	76	87	98	109	Threshold (mW)
2450	57	67	77	86	96	
3600	47	55	63	71	79	
5200	39	46	53	59	66	
5400	39	45	52	58	65	
5800	37	44	50	56	62	



The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances \leq 50 mm are determined by:

[(max. power of channel, including tune-up tolerance, mW)/(min. test separation distance, mm)] • $[\sqrt{f(GHz)}] \le 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR,where f(GHz) is the RF channel transmit frequency in GHz.

Page 8 of 9

Power and distance are rounded to the nearest mW and mm before calculation

The result is rounded to one decimal place for comparison

The test exclusions are applicable only when the minimum test separation distance is \leq 50 mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion.



Shenzhen STS Test Services Co., Ltd.



Page 9 of 9

Report No.: STS2111204H02

2.3 TEST RESULT

Maximum measured transmitter power.

The Worst Case

Mode frequency GHz		Maximum AV Output Power	Tune up tolerance	Max Tune up
		dBm	dBm	dBm
GFSK	2.480	-0.23	-1±1	0

Remark: The worst case gain of the antenna is 1.99dBi.

1.99dBi logarithmic terms convert to numeric result is nearly 1.58.

Maximum Tune up Power₍₂₄₈₀₎= 1mW

[(GFSK power of channel, including tune-up tolerance, mW)/(min. test separation distance,mm)] $\cdot \left[\sqrt{f(GHz)}\right] = 1/5^* \sqrt{2.480} = 0.315 \le 3.0$

Threshold at which no SAR required is $0.315 \le 3.0$ for 1-g SAR, Separation distance ≤ 5 mm.

** ** ** ** END OF THE REPORT ** ** **

Shenzhen STS Test Services Co., Ltd.