

TEST REPORT

Product Name : E BIKE
Brand Mark : N/A
Model No. : U4
Report Number : BLA-EMC-202202-A9902
FCC ID : 2A39V-U4
Date of Sample Receipt : 2022/6/2
Date of Test : 2022/6/2 to 2022/6/16
Date of Issue : 2022/6/16
Test Standard : 47 CFR Part 15, Subpart C 15.247
Test Result : Pass

Prepared for:

HONBIKE INC

**16192 Coastal Highway, city of Lewes, County of Sussex, state of
Delaware 19958, United States**


Prepared by:

BlueAsia of Technical Services(Shenzhen) Co.,Ltd.


**Building C, No. 107, Shihuan Road, Shiyan Sub-District, Baoan District,
Shenzhen, Guangdong Province, China**

TEL: +86-755-23059481

Compiled by:



Review by:



Approved by:



Date:

2022/6/16



REPORT REVISE RECORD

Version No.	Date	Description
00	2022/6/16	Original

BlueAsia

TABLE OF CONTENTS

1	TEST SUMMARY	5
2	GENERAL INFORMATION	6
3	GENERAL DESCRIPTION OF E.U.T.	6
4	TEST ENVIRONMENT	7
5	TEST MODE	7
6	MEASUREMENT UNCERTAINTY	7
7	DESCRIPTION OF SUPPORT UNIT	8
8	LABORATORY LOCATION	8
9	TEST INSTRUMENTS LIST	9
10	CONDUCTED EMISSIONS AT AC POWER LINE (150KHZ-30MHZ)	12
10.1	LIMITS	12
10.2	BLOCK DIAGRAM OF TEST SETUP	12
10.3	PROCEDURE	12
10.4	TEST DATA	14
11	CONDUCTED BAND EDGES MEASUREMENT	16
11.1	LIMITS	16
11.2	BLOCK DIAGRAM OF TEST SETUP	16
11.3	TEST DATA	17
12	ANTENNA REQUIREMENT	18
12.1	CONCLUSION	18
13	RADIATED SPURIOUS EMISSIONS	19
13.1	LIMITS	19
13.2	BLOCK DIAGRAM OF TEST SETUP	20
13.3	PROCEDURE	20
13.4	TEST DATA	22
14	RADIATED EMISSIONS WHICH FALL IN THE RESTRICTED BANDS	31
14.1	LIMITS	31
14.2	BLOCK DIAGRAM OF TEST SETUP	32
14.3	PROCEDURE	32
14.4	TEST DATA	34

15 CONDUCTED SPURIOUS EMISSIONS	38
15.1 LIMITS	38
15.2 BLOCK DIAGRAM OF TEST SETUP	38
15.3 TEST DATA	39
16 POWER SPECTRUM DENSITY	40
16.1 LIMITS	40
16.2 BLOCK DIAGRAM OF TEST SETUP	40
16.3 TEST DATA	40
17 CONDUCTED PEAK OUTPUT POWER	41
17.1 LIMITS	41
17.2 BLOCK DIAGRAM OF TEST SETUP	41
17.3 TEST DATA	42
18 MINIMUM 6DB BANDWIDTH	43
18.1 LIMITS	43
18.2 BLOCK DIAGRAM OF TEST SETUP	43
18.3 TEST DATA	43
19 APPENDIX	44
APPENDIX A: PHOTOGRAPHS OF TEST SETUP	72
APPENDIX B: PHOTOGRAPHS OF EUT	74

1 TEST SUMMARY

Test item	Test Requirement	Test Method	Class/Severity	Result
Conducted Emissions at AC Power Line (150kHz-30MHz)	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 6.2	47 CFR Part 15, Subpart C 15.207	Pass
Conducted Band Edges Measurement	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 7.8.8 & Section 11.13.3.2	47 CFR Part 15, Subpart C 15.247(d)	Pass
Antenna Requirement	47 CFR Part 15, Subpart C 15.247	N/A	47 CFR Part 15, Subpart C 15.203 & 15.247(c)	Pass
Radiated Spurious Emissions	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 6.4,6.5,6.6	47 CFR Part 15, Subpart C 15.209 & 15.247(d)	Pass
Radiated Emissions which fall in the restricted bands	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 6.10.5	47 CFR Part 15, Subpart C 15.209 & 15.247(d)	Pass
Conducted Spurious Emissions	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 7.8.6 & Section 11.11	47 CFR Part 15, Subpart C 15.247(d)	Pass
Power Spectrum Density	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 11.10.2	47 CFR Part 15, Subpart C 15.247(e)	Pass
Conducted Peak Output Power	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 7.8.5	47 CFR Part 15, Subpart C 15.247(b)(3)	Pass
Minimum 6dB Bandwidth	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 11.8.1	47 CFR Part 15, Subpart C 15.247a(2)	Pass

2 GENERAL INFORMATION

Applicant	HONBIKE INC
Address	16192 Coastal Highway, city of Lewes, County of Sussex, state of Delaware 19958, United States
Manufacturer	HONGJI INTELLIGENT BIKE CO.,LTD
Address	No.12 West Park Road, Rulin Town, Jintan District
Factory	HONGJI INTELLIGENT BIKE CO.,LTD
Address	No.12 West Park Road, Rulin Town, Jintan District
Product Name	E BIKE
Test Model No.	U4

3 GENERAL DESCRIPTION OF E.U.T.

Hardware Version	N/A
Software Version	N/A
Operation Frequency:	2402MHz-2480MHz
Modulation Type:	GFSK
Rate data	1Mbps(BLE1M), 2Mbps(BLE2M)
Channel Spacing:	2MHz
Number of Channels:	40
Antenna Type:	PCB Antenna
Antenna Gain:	0dBi(Provided by the applicant)

4 TEST ENVIRONMENT

Environment	Temperature	Voltage
Normal	25°C	DC41V

5 TEST MODE

TEST MODE	TEST MODE DESCRIPTION
Transmitting mode	Keep the EUT in continuously transmitting mode with modulation.
Remark: Full battery is used during all test except ac conducted emission, BLE1M, BLE2M all have been tested, during the test, BLE1M, BLE2M modulation were all pre-scanned only BLE1M worse case is reported.	

6 MEASUREMENT UNCERTAINTY

Parameter	Expanded Uncertainty (Confidence of 95%)
Radiated Emission(9kHz-30MHz)	±4.34dB
Radiated Emission(30Mz-1000MHz)	±4.24dB
Radiated Emission(1GHz-18GHz)	±4.68dB
AC Power Line Conducted Emission(150kHz-30MHz)	±3.45dB

7 DESCRIPTION OF SUPPORT UNIT

Device Type	Manufacturer	Model Name	Serial No.	Remark
N/A	N/A	N/A	N/A	N/A

8 LABORATORY LOCATION

All tests were performed at:

BlueAsia of Technical Services(Shenzhen) Co., Ltd.

Building C, No. 107, Shihuan Road, Shiyan Sub-District, Baoan District, Shenzhen, Guangdong Province, China

Telephone: TEL: +86-755-28682673 FAX: +86-755-28682673

No tests were sub-contracted.

BlueAsia

9 TEST INSTRUMENTS LIST

Test Equipment Of Conducted Emissions at AC Power Line (150kHz-30MHz)

Equipment	Manufacturer	Model	S/N	Cal.Date	Cal.Due
Shield room	SKET	833	N/A	25/11/2020	24/11/2023
Receiver	R&S	ESPI3	101082	24/9/2021	23/9/2022
LISN	R&S	ENV216	3560.6550.15	24/9/2021	23/9/2022
LISN	AT	AT166-2	AKK1806000003	26/9/2021	25/9/2022
EMI software	EZ	EZ-EMC	N/A	N/A	N/A

Test Equipment Of Conducted Band Edges Measurement

Equipment	Manufacturer	Model	S/N	Cal.Date	Cal.Due
Spectrum	R&S	FSP40	100817	24/9/2021	23/9/2022
Spectrum	Agilent	N9020A	MY49100060	24/9/2021	23/9/2022
Signal Generator	Agilent	N5182A	MY49060650	24/9/2021	23/9/2022
Signal Generator	Agilent	E8257D	MY44320250	24/9/2021	23/9/2022

Test Equipment Of Radiated Spurious Emissions

Equipment	Manufacturer	Model	S/N	Cal.Date	Cal.Due
Chamber	SKET	966	N/A	10/11/2020	9/11/2023
Spectrum	R&S	FSP40	100817	24/9/2021	23/9/2022
Receiver	R&S	ESR7	101199	24/9/2021	23/9/2022
broadband Antenna	Schwarzbeck	VULB9168	00836 P:00227	26/9/2020	25/9/2022
Horn Antenna	Schwarzbeck	9120D	01892 P:00331	26/9/2020	25/9/2022

Amplifier	SKET	LNPA-0118-45	N/A	24/9/2021	23/9/2022
EMI software	EZ	EZ-EMC	N/A	N/A	N/A
Loop antenna	SCHNARZBECK	FMZB1519B	00102	26/9/2020	25/9/2022

Test Equipment Of Radiated Emissions which fall in the restricted bands

Equipment	Manufacturer	Model	S/N	Cal.Date	Cal.Due
Chamber	SKET	966	N/A	10/11/2020	9/11/2023
Spectrum	R&S	FSP40	100817	24/9/2021	23/9/2022
Receiver	R&S	ESR7	101199	24/9/2021	23/9/2022
broadband Antenna	Schwarzbeck	VULB9168	00836 P:00227	26/9/2020	25/9/2022
Horn Antenna	Schwarzbeck	9120D	01892 P:00331	26/9/2020	25/9/2022
Amplifier	SKET	LNPA-0118-45	N/A	24/9/2021	23/9/2022
EMI software	EZ	EZ-EMC	N/A	N/A	N/A
Loop antenna	SCHNARZBECK	FMZB1519B	00102	26/9/2020	25/9/2022

Test Equipment Of Conducted Spurious Emissions

Equipment	Manufacturer	Model	S/N	Cal.Date	Cal.Due
Spectrum	R&S	FSP40	100817	24/9/2021	23/9/2022
Spectrum	Agilent	N9020A	MY49100060	24/9/2021	23/9/2022
Signal Generator	Agilent	N5182A	MY49060650	24/9/2021	23/9/2022
Signal Generator	Agilent	E8257D	MY44320250	24/9/2021	23/9/2022

Test Equipment Of Power Spectrum Density

Equipment	Manufacturer	Model	S/N	Cal.Date	Cal.Due

Spectrum	R&S	FSP40	100817	24/9/2021	23/9/2022
Spectrum	Agilent	N9020A	MY49100060	24/9/2021	23/9/2022
Signal Generator	Agilent	N5182A	MY49060650	24/9/2021	23/9/2022
Signal Generator	Agilent	E8257D	MY44320250	24/9/2021	23/9/2022

Test Equipment Of Conducted Peak Output Power

Equipment	Manufacturer	Model	S/N	Cal.Date	Cal.Due
Spectrum	R&S	FSP40	100817	24/9/2021	23/9/2022
Spectrum	Agilent	N9020A	MY49100060	24/9/2021	23/9/2022
Signal Generator	Agilent	N5182A	MY49060650	24/9/2021	23/9/2022
Signal Generator	Agilent	E8257D	MY44320250	24/9/2021	23/9/2022

Test Equipment Of Minimum 6dB Bandwidth

Equipment	Manufacturer	Model	S/N	Cal.Date	Cal.Due
Spectrum	R&S	FSP40	100817	24/9/2021	23/9/2022
Spectrum	Agilent	N9020A	MY49100060	24/9/2021	23/9/2022
Signal Generator	Agilent	N5182A	MY49060650	24/9/2021	23/9/2022
Signal Generator	Agilent	E8257D	MY44320250	24/9/2021	23/9/2022

10 CONDUCTED EMISSIONS AT AC POWER LINE (150KHZ-30MHZ)


Test Standard	47 CFR Part 15, Subpart C 15.247
Test Method	ANSI C63.10 (2013) Section 6.2
Test Mode (Pre-Scan)	TX
Test Mode (Final Test)	TX
Tester	Jozu
Temperature	25°C
Humidity	60%

10.1 LIMITS

Frequency of emission(MHz)	Conducted limit(dB μ V)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency.

10.2 BLOCK DIAGRAM OF TEST SETUP



10.3 PROCEDURE

- 1) The mains terminal disturbance voltage test was conducted in a shielded room.
- 2) The EUT was connected to AC power source through a LISN 1 (Line Impedance Stabilization Network) which provides a 50ohm/50H + 50hm linear impedance. The power cables of all other units of the EUT were connected to a second LISN 2, which was bonded to the ground reference plane in the same way as the LISN 1 for the unit being measured. A multiple socket outlet strip was used to connect multiple power cables to a single LISN provided the rating of the LISN was not exceeded.


- 3) The tabletop EUT was placed upon a non-metallic table 0.8m above the ground reference plane. And for floor-standing arrangement, the EUT was placed on the horizontal ground reference plane,
- 4) The test was performed with a vertical ground reference plane. The rear of the EUT shall be 0.4 m from the vertical ground reference plane. The vertical ground reference plane was bonded to the horizontal ground reference plane. The LISN 1 was placed 0.8 m from the boundary of the unit under test and bonded to a ground reference plane for LISNs mounted on top of the ground reference plane. This distance was between the closest points of the LISN 1 and the EUT. All other units of the EUT and associated equipment was at least 0.8 m from the LISN 2.
- 5) In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.10 on conducted measurement.

Remark: LISN=Read Level+ Cable Loss+ LISN Factor

BlueAsia

10.4 TEST DATA

[TestMode: TX]; [Line: Line] ;[Power:AC120V/60Hz]




*:Maximum data x:Over limit !:over margin

(Reference Only)

Test Result: Pass

[TestMethod: TX]; [Line: Line] ;[Power:AC120V/60Hz]


Site Phase: **N** Temperature: (C)

Limit: FCC Class B Conduction(QP) Power: Humidity: %RH

EUT: E BIKE

M/N: U4

Mode: BLE mode

Note:

No. Mk.	Freq. MHz	Reading Level	Correct Factor	Measure- ment	Limit	Over	Detector	Comment
		dBuV	dB	dBuV	dB			
1	0.2040	28.49	10.15	38.64	53.45	-14.81	AVG	
2	0.2100	37.55	10.17	47.72	63.21	-15.49	QP	
3	0.3460	31.13	9.77	40.90	59.06	-18.16	QP	
4	0.4860	18.77	9.79	28.56	46.24	-17.68	AVG	
5	0.7620	17.03	9.82	26.85	46.00	-19.15	AVG	
6	0.8300	27.70	9.83	37.53	56.00	-18.47	QP	
7	1.3340	29.20	9.85	39.05	56.00	-16.95	QP	
8	1.7740	21.14	9.86	31.00	46.00	-15.00	AVG	
9	4.9860	37.58	9.95	47.53	56.00	-8.47	QP	
10 *	4.9860	31.18	9.95	41.13	46.00	-4.87	AVG	
11	15.5500	34.80	10.31	45.11	50.00	-4.89	AVG	
12	15.8140	42.39	10.31	52.70	60.00	-7.30	QP	

*:Maximum data x:Over limit !:over margin

(Reference Only)

Test Result: Pass


11 CONDUCTED BAND EDGES MEASUREMENT

Test Standard	47 CFR Part 15, Subpart C 15.247
Test Method	ANSI C63.10 (2013) Section 7.8.8 & Section 11.13.3.2
Test Mode (Pre-Scan)	TX
Test Mode (Final Test)	TX
Tester	Jozu
Temperature	25 °C
Humidity	60%

11.1 LIMITS

Limit:	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).
---------------	----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

11.2 BLOCK DIAGRAM OF TEST SETUP



11.3 TEST DATA

Pass: Please Refer To Appendix: Appendix1 For Details

BlueAsia

12 ANTENNA REQUIREMENT

Test Standard	47 CFR Part 15, Subpart C 15.247
Test Method	N/A


12.1 CONCLUSION

Standard Requirement:

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit permanently attached antenna or of an so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

EUT Antenna:

The antenna is integrated on the main PCB and no consideration of replacement. The best case gain of the antenna is 0dBi.



13 RADIATED SPURIOUS EMISSIONS


Test Standard	47 CFR Part 15, Subpart C 15.247
Test Method	ANSI C63.10 (2013) Section 6.4,6.5,6.6
Test Mode (Pre-Scan)	TX
Test Mode (Final Test)	TX
Tester	Jozu
Temperature	25°C
Humidity	60%

13.1 LIMITS

Frequency(MHz)	Field strength(microvolts/meter)	Measurement distance(meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

Remark: The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90kHz, 110-490kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation.

13.2 BLOCK DIAGRAM OF TEST SETUP



13.3 PROCEDURE

- For below 1GHz, the EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 or 10 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- For above 1GHz, the EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter fully-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- The EUT was set 3 or 10 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.

- h. Test the EUT in the lowest channel, the middle channel, the Highest channel.
- i. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.
- j. Repeat above procedures until all frequencies measured was complete.


Remark:

- 1) For emission below 1GHz, through pre-scan found the worst case is the lowest channel. Only the worst case is recorded in the report.
- 2) The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:
Final Test Level = Receiver Reading + Antenna Factor + Cable Factor - Preamplifier Factor
- 3) Scan from 9kHz to 25GHz, the disturbance above 12.75GHz and below 30MHz was very low. The points marked on above plots are the highest emissions could be found when testing, so only above points had been displayed. The amplitude of spurious emissions from the radiator which are attenuated more than 20dB below the limit need not be reported. fundamental frequency is blocked by filter, and only spurious emission is shown.
- 4) For frequencies above 1GHz, the field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. For the emissions whose peak level is lower than the average limit, only the peak measurement is shown in the report.

13.4 TEST DATA

[TestMode: TX mode (SE) below 1G]; [Polarity: Horizontal]

Test Lab: BlueAsia EMC Lab (RE #1)	Project: BLA-EMC-202202-A99
EUT: E BIKE	Test Engineer: York
M/N: U4	Temperature:
S/N:	Humidity:
Test Mode: BLE TX mode	Test Voltage:
Note:	Test Data: 2022-06-14 20:51:37




No.	Frequency	Limit dBuV/m	Level dBuV/m	Delta dB	Reading dBuV	Factor dB/m	Detector	Polar	Height cm	Angle deg
1*	43.216MHz	40.0	24.2	-15.8	0.2	24.0	QP	Hor	100.0	0.0
2*	141.065MHz	43.5	28.0	-15.5	4.3	23.7	QP	Hor	100.0	0.0
3*	221.090MHz	46.0	29.3	-16.7	7.5	21.8	QP	Hor	100.0	315.0
4*	430.974MHz	46.0	31.9	-14.1	4.3	27.6	QP	Hor	100.0	99.0
5*	600.239MHz	46.0	33.4	-12.6	2.1	31.3	QP	Hor	100.0	0.0
6*	954.653MHz	46.0	37.5	-8.5	1.9	35.6	QP	Hor	100.0	0.0

Test Result: Pass

[**TestMode:** TX mode (SE) below 1G]; [**Polarity:** Vertical]

Test Lab: BlueAsia EMC Lab (RE #1)	Project: BLA-EMC-202202-A99
EUT: E BIKE	Test Engineer: York
M/N: U4	Temperature:
S/N:	Humidity:
Test Mode: BLE TX mode	Test Voltage:
Note:	Test Data: 2022-06-14 20:54:39




No.	Frequency	Limit dBuV/m	Level dBuV/m	Delta dB	Reading dBuV	Factor dB/m	Detector	Polar	Height cm	Angle deg
1*	34.850MHz	40.0	24.9	-15.1	1.3	23.6	QP	Ver	100.0	0.0
2*	62.859MHz	40.0	23.4	-16.6	0.5	22.9	QP	Ver	100.0	0.0
3*	140.580MHz	43.5	29.7	-13.8	6.0	23.7	QP	Ver	100.0	0.0
4*	226.910MHz	46.0	27.1	-18.9	5.0	22.1	QP	Ver	100.0	0.0
5*	432.308MHz	46.0	30.6	-15.4	2.9	27.7	QP	Ver	100.0	337.0
6*	694.450MHz	46.0	33.8	-12.2	1.9	31.9	QP	Ver	100.0	37.0

Test Result: Pass

BlueAsia

Remark: During the test, pre-scan the BLE1M, BLE2M mode, and found the BLE1M mode which it is worse case.

[TestMode: TX low channel]; [Polarity: Horizontal]



Test Result: Pass

[TestMode: TX low channel]; [Polarity: Vertical]

Radiated Emission Measurement

Project No.: RE
80.0 dBuV/m

Data :#4

2022/6/14

17:03:14



Site

Polarization: **Vertical**

Temperature: (C)

Limit: FCC Part15 (PK)

Power-

Humidity: 0%RH

FUT: E BIKE

M/N: 14

Mode: BLE1M-TX-L

Note:-


No.	Mk.	Freq.	Reading Level	Correct Factor	Measure- ment	Over							
						MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector	Comment
1		3773.000	42.10	7.67	49.77	74.00	-24.23	peak					
2		4807.000	50.02	3.71	53.73	74.00	-20.27	peak					
3	*	4807.000	44.30	3.71	48.01	54.00	-5.99	AVG					
4		7206.000	39.16	5.96	45.12	74.00	-28.88	peak					
5		8191.000	41.03	8.20	49.23	74.00	-24.77	peak					
6		9608.000	38.57	9.29	47.86	74.00	-26.14	peak					
7		11246.000	38.99	11.98	50.97	74.00	-23.03	peak					

*:Maximum data x:Over limit !:over margin

⟨Reference Only

Test Result: Pass

[TestMode: TX mid channel]; [Polarity: Horizontal]



Site	Polarization: <i>Horizontal</i>	Temperature: (C)
Limit: FCC Part15 (PK)	Power:	Humidity: %RH
EUT: E BIKE		
M/N: U4		
Mode: BLE1M-TX-M		
Note:		

No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over	
			Level	Factor	ment			
		MHz	dBuV	dB/m	dBuV/m	dB	Detector	Comment
1		3632.000	41.37	7.77	49.14	74.00	-24.86	peak
2	*	4877.500	48.09	3.37	51.46	74.00	-22.54	peak
3		7326.000	39.13	6.44	45.57	74.00	-28.43	peak
4		8261.500	40.68	8.23	48.91	74.00	-25.09	peak
5		9768.000	37.51	9.63	47.14	74.00	-26.86	peak
6		11293.000	38.43	11.91	50.34	74.00	-23.66	peak

*:Maximum data x:Over limit !:over margin

(Reference Only

Test Result: Pass

[TestMode: TX mid channel]; [Polarity: Vertical]

Radiated Emission Measurement

Project No.: RE
80.0 dBuV/m

Data :#6

2022/6/14

17:27:33



Site

Polarization: *Vertical*

Temperature: (C)

Limit: FCC Part15 (PK)

Power:

Humidity: %RH

EUT: E BIKE

M/N: U4

Mode: BLE1M-TX-M

Note:

No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over		
			Level	Factor	ment				
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector	Comment
1		3655.500	41.37	7.76	49.13	74.00	-24.87	peak	
2	*	4877.500	49.78	3.37	53.15	74.00	-20.85	peak	
3		7326.000	39.61	6.44	46.05	74.00	-27.95	peak	
4		8120.500	40.63	8.11	48.74	74.00	-25.26	peak	
5		9768.000	37.40	9.63	47.03	74.00	-26.97	peak	
6		11363.500	38.81	11.81	50.62	74.00	-23.38	peak	

*:Maximum data x:Over limit !:over margin

⟨Reference Only

Test Result: Pass

[TestMode: TX high channel]; [Polarity: Horizontal]

Radiated Emission Measurement

Project No.: RE

Data :#10

2022/6/14

17:41:13



Site

Polarization: *Horizontal*

Temperature: (C)

Limit: FCC Part15 (PK)

Power:

Humidity: %RH

FUT: E BIKE

M/N: U4

Mode: BLE1M-TX-H

Note:-

No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over	
			Level	Factor	ment			
		MHz	dBuV	dB/m	dBuV/m	dB	Detector	Comment
1		3679.000	41.95	7.73	49.68	74.00	-24.32	peak
2		4948.000	46.14	3.65	49.79	74.00	-24.21	peak
3		7440.000	39.48	6.86	46.34	74.00	-27.66	peak
4		8332.000	41.00	8.26	49.26	74.00	-24.74	peak
5		9920.000	36.93	10.16	47.09	74.00	-26.91	peak
6	*	11457.500	39.07	11.84	50.91	74.00	-23.09	peak

*:Maximum data x:Over limit l:over margin

Reference Only

Test Result: Pass

[TestMode: TX high channel]; [Polarity: Vertical]

Radiated Emission Measurement

Project No.: RE

Data :#9

2022/6/14

17:38:26



Site

Polarization: **Vertical**

Temperature: (C)

Limit: FCC Part15 (PK)

Power:

Humidity: %RH

FUT: E BIKE

M/N: U4

Mode: BLE1M-TX-H

Note:-

No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over	Detector	Comment
			Level	Factor	ment				
1		3820.000	41.80	7.41	49.21	74.00	-24.79	peak	
2		4948.000	47.64	3.65	51.29	74.00	-22.71	peak	
3		7440.000	38.98	6.86	45.84	74.00	-28.16	peak	
4		8167.500	40.89	8.17	49.06	74.00	-24.94	peak	
5		9920.000	37.79	10.16	47.95	74.00	-26.05	peak	
6	*	11363.500	40.29	11.81	52.10	74.00	-21.90	peak	

*:Maximum data x:Over limit !:over margin

Reference Only

Test Result: Pass

14 RADIATED EMISSIONS WHICH FALL IN THE RESTRICTED BANDS


Test Standard	47 CFR Part 15, Subpart C 15.247
Test Method	ANSI C63.10 (2013) Section 6.10.5
Test Mode (Pre-Scan)	TX
Test Mode (Final Test)	TX
Tester	Jozu
Temperature	25°C
Humidity	60%

14.1 LIMITS

Frequency(MHz)	Field strength(microvolts/meter)	Measurement distance(meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

Remark: The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90kHz, 110-490kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation.

14.2 BLOCK DIAGRAM OF TEST SETUP



14.3 PROCEDURE

- For below 1GHz, the EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 or 10 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- For above 1GHz, the EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter fully-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- The EUT was set 3 or 10 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.

- h. Test the EUT in the lowest channel, the middle channel, the Highest channel.
- i. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.
- j. Repeat above procedures until all frequencies measured was complete.


Remark 1: Level= Read Level+ Cable Loss+ Antenna Factor- Preamp Factor

Remark 2: For frequencies above 1GHz, the field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. For the emissions whose peak level is lower than the average limit, only the peak measurement is shown in the report.

BlueAsia

14.4 TEST DATA

[TestMode: TX high channel]; [Polarity: Horizontal]




*:Maximum data x:Over limit !:over margin

(Reference Only)

Test Result: Pass

[TestMode: TX high channel]; [Polarity: Vertical]

Radiated Emission Measurement

Site Polarization: **Vertical** Temperature: (C)

Limit: FCC Part15 (PK) Power: Humidity: %RH

EUT: E BIKE

M/N: U4

Mode: BLE1M-TX-H

Note:

No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB/m	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1	*	2483.500	62.95	-3.14	59.81	74.00	-14.19	peak	
2		2483.500	34.00	-3.14	30.86	54.00	-23.14	AVG	
3		2484.996	60.47	-3.14	57.33	74.00	-16.67	peak	
4		2484.996	31.81	-3.14	28.67	54.00	-25.33	AVG	
5		2500.000	47.94	-3.08	44.86	74.00	-29.14	peak	

*:Maximum data x:Over limit !:over margin

(Reference Only)

Test Result: Pass

[TestMode: TX low channel]; [Polarity: Horizontal]

Radiated Emission Measurement

Project No.: RE

Data :#1

2022/6/14

16:58:06



Site

Polarization: *Horizontal*

Temperature: (C)

Limit: FCC Part15 (PK)

Power

Humidity: %RH

EUT: E BIKE

M/N: U4

Mode: BLE1M-TX-L

Note:


No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over	
			Level	Factor	ment			
1		2310.000	44.31	-3.93	40.38	74.00	-33.62	peak
2	*	2390.000	53.28	-3.58	49.70	74.00	-24.30	peak

*:Maximum data x:Over limit !:over margin

(Reference Only

Test Result: Pass

[TestMode: TX low channel]; [Polarity: Vertical]

Radiated Emission Measurement


Site

Polarization: **Vertical**

Temperature: (C)

Limit: FCC Part15 (PK)

Power:

Humidity: %RH

EUT: E BIKE

M/N: U4

Mode: BLE1M-TX-L

Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	
		MHz	dBuV	dB/m	dBuV/m	dB	Detector	Comment
1		2310.000	43.69	-3.93	39.76	74.00	-34.24	peak
2	*	2390.000	52.81	-3.58	49.23	74.00	-24.77	peak

*:Maximum data x:Over limit !:over margin

(Reference Only)

Test Result: Pass


15 CONDUCTED SPURIOUS EMISSIONS

Test Standard	47 CFR Part 15, Subpart C 15.247
Test Method	ANSI C63.10 (2013) Section 7.8.6 & Section 11.11
Test Mode (Pre-Scan)	TX
Test Mode (Final Test)	TX
Tester	Jozu
Temperature	25 °C
Humidity	60%

15.1 LIMITS

Limit:	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).
---------------	----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

15.2 BLOCK DIAGRAM OF TEST SETUP



15.3 TEST DATA

Pass: Please Refer To Appendix: Appendix1 For Details

BlueAsia


16 POWER SPECTRUM DENSITY

Test Standard	47 CFR Part 15, Subpart C 15.247
Test Method	ANSI C63.10 (2013) Section 11.10.2
Test Mode (Pre-Scan)	TX
Test Mode (Final Test)	TX
Tester	Jozu
Temperature	25 °C
Humidity	60%

16.1 LIMITS

Limit: $\leq 8\text{dBm}$ in any 3 kHz band during any time interval of continuous transmission

16.2 BLOCK DIAGRAM OF TEST SETUP



16.3 TEST DATA

Pass: Please Refer To Appendix: Appendix1 For Details


17 CONDUCTED PEAK OUTPUT POWER

Test Standard	47 CFR Part 15, Subpart C 15.247
Test Method	ANSI C63.10 (2013) Section 7.8.5
Test Mode (Pre-Scan)	TX
Test Mode (Final Test)	TX
Tester	Jozu
Temperature	25 °C
Humidity	60%

17.1 LIMITS

Frequency range(MHz)	Output power of the intentional radiator(watt)
902-928	1 for ≥ 50 hopping channels
	0.25 for $25 \leq$ hopping channels < 50
	1 for digital modulation
2400-2483.5	1 for ≥ 75 non-overlapping hopping channels
	0.125 for all other frequency hopping systems
	1 for digital modulation
5725-5850	1 for frequency hopping systems and digital modulation

17.2 BLOCK DIAGRAM OF TEST SETUP



17.3 TEST DATA

Pass: Please Refer To Appendix: Appendix1 For Details

BlueAsia


18 MINIMUM 6DB BANDWIDTH

Test Standard	47 CFR Part 15, Subpart C 15.247
Test Method	ANSI C63.10 (2013) Section 11.8.1
Test Mode (Pre-Scan)	TX
Test Mode (Final Test)	TX
Tester	Jozu
Temperature	25 °C
Humidity	60%

18.1 LIMITS

Limit: ≥ 500 kHz

18.2 BLOCK DIAGRAM OF TEST SETUP



18.3 TEST DATA


Pass: Please Refer To Appendix: Appendix1 For Details

19 APPENDIX


Maximum Conducted Output Power

Condition	Mode	Frequency (MHz)	Antenna	Conducted Power (dBm)	Limit (dBm)	Verdict
NVNT	BLE 1M	2402	Ant1	-12.192	30	Pass
NVNT	BLE 1M	2442	Ant1	-12.447	30	Pass
NVNT	BLE 1M	2480	Ant1	-12.803	30	Pass
NVNT	BLE 2M	2402	Ant1	-12.148	30	Pass
NVNT	BLE 2M	2442	Ant1	-12.529	30	Pass
NVNT	BLE 2M	2480	Ant1	-12.755	30	Pass


Power NVNT BLE 1M 2402MHz Ant1



Power NVNT BLE 1M 2442MHz Ant1




Power NVNT BLE 1M 2480MHz Ant1




Power NVNT BLE 2M 2402MHz Ant1



Power NVNT BLE 2M 2442MHz Ant1



Power NVNT BLE 2M 2480MHz Ant1




BlueX

-6dB Bandwidth


Condition	Mode	Frequency (MHz)	Antenna	-6 dB Bandwidth (MHz)	Limit -6 dB Bandwidth (MHz)	Verdict
NVNT	BLE 1M	2402	Ant1	0.659	0.5	Pass
NVNT	BLE 1M	2442	Ant1	0.646	0.5	Pass
NVNT	BLE 1M	2480	Ant1	0.661	0.5	Pass
NVNT	BLE 2M	2402	Ant1	1.142	0.5	Pass
NVNT	BLE 2M	2442	Ant1	1.14	0.5	Pass
NVNT	BLE 2M	2480	Ant1	1.143	0.5	Pass

-6dB Bandwidth NVNT BLE 1M 2402MHz Ant1


-6dB Bandwidth NVNT BLE 1M 2442MHz Ant1



-6dB Bandwidth NVNT BLE 1M 2480MHz Ant1



-6dB Bandwidth NVNT BLE 2M 2402MHz Ant1



-6dB Bandwidth NVNT BLE 2M 2442MHz Ant1



-6dB Bandwidth NVNT BLE 2M 2480MHz Ant1




Occupied Channel Bandwidth


Condition	Mode	Frequency (MHz)	Antenna	99% OBW (MHz)
NVNT	BLE 1M	2402	Ant1	1.0256
NVNT	BLE 1M	2442	Ant1	1.0281
NVNT	BLE 1M	2480	Ant1	1.0217
NVNT	BLE 2M	2402	Ant1	2.3117
NVNT	BLE 2M	2442	Ant1	2.3181
NVNT	BLE 2M	2480	Ant1	2.2967

OBW NVNT BLE 1M 2402MHz Ant1


OBW NVNT BLE 1M 2442MHz Ant1




OBW NVNT BLE 1M 2480MHz Ant1




OBW NVNT BLE 2M 2402MHz Ant1



OBW NVNT BLE 2M 2442MHz Ant1



OBW NVNT BLE 2M 2480MHz Ant1



Maximum Power Spectral Density Level

Condition	Mode	Frequency (MHz)	Antenna	Max PSD (dBm)	Limit (dBm)	Verdict
NVNT	BLE 1M	2402	Ant1	-12.308	8	Pass
NVNT	BLE 1M	2442	Ant1	-12.743	8	Pass
NVNT	BLE 1M	2480	Ant1	-13.069	8	Pass
NVNT	BLE 2M	2402	Ant1	-12.305	8	Pass
NVNT	BLE 2M	2442	Ant1	-12.746	8	Pass
NVNT	BLE 2M	2480	Ant1	-13.058	8	Pass

PSD NVNT BLE 1M 2402MHz Ant1

PSD NVNT BLE 1M 2442MHz Ant1


PSD NVNT BLE 1M 2480MHz Ant1

PSD NVNT BLE 2M 2402MHz Ant1


PSD NVNT BLE 2M 2442MHz Ant1

PSD NVNT BLE 2M 2480MHz Ant1



Band Edge

Condition	Mode	Frequency (MHz)	Antenna	Max Value (dBc)	Limit (dBc)	Verdict
NVNT	BLE 1M	2402	Ant1	-43.18	-30	Pass
NVNT	BLE 1M	2480	Ant1	-40.56	-30	Pass
NVNT	BLE 2M	2402	Ant1	-43.12	-30	Pass
NVNT	BLE 2M	2480	Ant1	-40.2	-30	Pass

Band Edge NVNT BLE 1M 2402MHz Ant1 Ref



Band Edge NVNT BLE 1M 2402MHz Ant1 Emission



Band Edge NVNT BLE 1M 2480MHz Ant1 Ref



Band Edge NVNT BLE 1M 2480MHz Ant1 Emission



Band Edge NVNT BLE 2M 2402MHz Ant1 Ref



Band Edge NVNT BLE 2M 2402MHz Ant1 Emission



Band Edge NVNT BLE 2M 2480MHz Ant1 Ref



Band Edge NVNT BLE 2M 2480MHz Ant1 Emission



Conducted RF Spurious Emission

Condition	Mode	Frequency (MHz)	Antenna	Max Value (dBc)	Limit (dBc)	Verdict
NVNT	BLE 1M	2402	Ant1	-32.51	-30	Pass
NVNT	BLE 1M	2442	Ant1	-32.25	-30	Pass
NVNT	BLE 1M	2480	Ant1	-31.48	-30	Pass
NVNT	BLE 2M	2402	Ant1	-32.27	-30	Pass
NVNT	BLE 2M	2442	Ant1	-32.3	-30	Pass
NVNT	BLE 2M	2480	Ant1	-31.33	-30	Pass

Tx. Spurious NVNT BLE 1M 2402MHz Ant1 Ref



Tx. Spurious NVNT BLE 1M 2402MHz Ant1 Emission



Tx. Spurious NVNT BLE 1M 2442MHz Ant1 Ref



Tx. Spurious NVNT BLE 1M 2442MHz Ant1 Emission



Tx. Spurious NVNT BLE 1M 2480MHz Ant1 Ref



Tx. Spurious NVNT BLE 1M 2480MHz Ant1 Emission



Tx. Spurious NVNT BLE 2M 2402MHz Ant1 Ref



Tx. Spurious NVNT BLE 2M 2402MHz Ant1 Emission



Tx. Spurious NVNT BLE 2M 2442MHz Ant1 Ref




Tx. Spurious NVNT BLE 2M 2442MHz Ant1 Emission



Tx. Spurious NVNT BLE 2M 2480MHz Ant1 Ref



Tx. Spurious NVNT BLE 2M 2480MHz Ant1 Emission



APPENDIX A: PHOTOGRAPHS OF TEST SETUP

Conducted Emissions at AC Power Line (150kHz-30MHz)



BlueX



APPENDIX B: PHOTOGRAPHS OF EUT

Reference to the test report No. BLA-EMC-202202-A9901

----END OF REPORT----

The test report is effective only with both signature and specialized stamp, The result(s) shown in this report refer only to the sample(s) tested. Without written approval of BlueAsia, this report can't be reproduced except in full.

BlueAsia