



8.6.5 Test Results

Bluetooth (GFSK, pi/4-DQPSK, 8DPSK) mode have been tested, and the worst result(GFSK) was report as below:


Test Model	Maximum Conduced Level RBW=100kHz
	Bluetooth V5.3
	Channel 0: 2402MHz
	GFSK




Test Model	Conduced Spurious RF Conducted Emission
	Bluetooth V5.3
	Channel 0: 2402MHz
	GFSK




Test Model Band-edge Conducted Emissions
Bluetooth V5.3
Channel 0: 2402MHz GFSK




Test Model Maximum Conducted Level RBW=100kHz
Bluetooth V5.3
Channel 39: 2441MHz GFSK




Test Model	Conducted Spurious RF Conducted Emission	
	Bluetooth V5.3	
	Channel 39: 2441MHz	GFSK




Test Model	Maximum Conduced Level RBW=100kHz	
	Bluetooth V5.3	
	Channel 78: 2480MHz	GFSK




Test Model **Conducted Spurious RF Conducted Emission**
Bluetooth V5.3
Channel 78: 2480MHz **GFSK**




Test Model **Band-edge Conducted Emissions**
Bluetooth V5.3
Channel 78: 2480MHz **GFSK**




Test Model	Maximum Conduced Level RBW=100kHz
	Bluetooth V5.3
	Hopping GFSK




Test Model	Conducted Spurious RF Conducted Emission
	Bluetooth V5.3
	Hopping GFSK



Test Model: Band-edge Conducted Emissions
Bluetooth V5.3
Hopping GFSK



Test Model: Band-edge Conducted Emissions
Bluetooth V5.3
Hopping GFSK



8.7 RADIATED SPURIOUS EMISSION

8.7.1 Applicable Standard

According to FCC Part 15.247(d) and 15.209 and KDB 558074 D01 15.247 MEAS GUIDANCE v05r02

8.7.2 Conformance Limit

According to FCC Part 15.247(d): radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

According to FCC Part 15.205, Restricted bands

MHz	MHz	MHz	GHz
0.090-0.110	16.42-16.423	399.9-410	4.5-5.15
10.495-0.505	16.69475-16.69525	608-614	5.35-5.46
2.1735-2.1905	16.80425-16.80475	960-1240	7.25-7.75
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5
4.17725-4.17775	37.5-38.25	1435-1626.5	9.0-9.2
4.20725-4.20775	73-74.6	1645.5-1646.5	9.3-9.5
6.215-6.218	74.8-75.2	1660-1710	10.6-12.7
6.26775-6.26825	123-138	2200-2300	14.47-14.5
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2
8.362-8.366	156.52475-156.52525	2483.5-2500	17.7-21.4
8.37625-8.38675	156.7-156.9	2690-2900	22.01-23.12
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0
12.29-12.293	167.72-173.2	3332-3339	31.2-31.8
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5
12.57675-12.57725	322-335.4	3600-4400	(2)
13.36-13.41			

According to FCC Part 15.205, the level of any transmitter spurious emission in Restricted bands shall not exceed the level of the emission specified in the following table

Restricted Frequency(MHz)	Field Strength ($\mu\text{V}/\text{m}$)	Field Strength ($\text{dB}\mu\text{V}/\text{m}$)	Measurement Distance
0.009-0.490	2400/F(KHz)	20 log ($\mu\text{V}/\text{m}$)	300
0.490-1.705	24000/F(KHz)	20 log ($\mu\text{V}/\text{m}$)	30
1.705-30	30	29.5	30
30-88	100	40	3
88-216	150	43.5	3
216-960	200	46	3
Above 960	500	54	3

8.7.3 Test Configuration

Test according to clause 6.2 radio frequency test setup 2

8.7.4 Test Procedure

This test is required for any spurious emission that falls in a Restricted Band, as defined in Section 15.205. It must be performed with the highest gain of each type of antenna proposed for use with the EUT. Use the following spectrum analyzer settings:

For Above 1GHz:

The EUT was placed on a turn table which is 1.5m above ground plane.

Maximum procedure was performed on the highest emissions to ensure EUT compliance.

Span = wide enough to fully capture the emission being measured

RBW = 1 MHz

VBW \geq RBW

Sweep = auto

Detector function = peak

Trace = max hold

For Below 1GHz:

The EUT was placed on a turn table which is 0.8m above ground plane.

Maximum procedure was performed on the highest emissions to ensure EUT compliance.

Span = wide enough to fully capture the emission being measured

RBW = 100 kHz for

VBW \geq RBW

Sweep = auto

Detector function = peak

Trace = max hold

For Below 30MHz:

The EUT was placed on a turn table which is 0.8m above ground plane.

Maximum procedure was performed on the highest emissions to ensure EUT compliance.

Span = wide enough to fully capture the emission being measured

RBW = 9kHz

VBW \geq RBW

Sweep = auto

Detector function = peak

Trace = max hold

For Below 150KHz:

The EUT was placed on a turn table which is 0.8m above ground plane.

Maximum procedure was performed on the highest emissions to ensure EUT compliance.

Span = wide enough to fully capture the emission being measured

RBW = 200Hz

VBW \geq RBW

Sweep = auto

Detector function = peak

Trace = max hold

Follow the guidelines in ANSI C63.10-2013 with respect to maximizing the emission by rotating the EUT, measuring the emission while the EUT is situated in three orthogonal planes (if appropriate), adjusting the measurement antenna height and polarization, etc. A pre-amp and a high pass filter are required for this test, in order to provide the measuring system with sufficient sensitivity. Allow the trace to stabilize. The peak reading of the emission, after being corrected by the antenna factor, cable loss, pre-amp gain, etc., is the peak field strength, which must comply with the limit specified in Section 15.35(b). Submit this data.

Now set the VBW to 10 Hz, while maintaining all of the other instrument settings. This peak level, once corrected, must comply with the limit specified in Section 15.209. If the dwell time per channel of the hopping signal is less than 100 ms, then the reading obtained with the 10 Hz VBW may be further adjusted by a "duty cycle correction factor", derived from $20\log(\text{dwell time}/100 \text{ ms})$, in an effort to demonstrate compliance with the 15.209 limit. Submit this data.

Repeat above procedures until all frequency measured was complete.

8.7.5 Test Results

■ Spurious Emission below 30MHz (9KHz to 30MHz)

Temperature:	26° C
Relative Humidity:	54%
ATM Pressure:	1011 mbar

Freq. (MHz)	Ant.Pol. H/V	Emission Level(dBuV/m)		Limit 3m(dBuV/m)		Over(dB)	
		PK	AV	PK	AV	PK	AV
--	--	--	--	--	--	--	--

Note: the amplitude of spurious emission that is attenuated by more than 20dB below the permissible limit has no need to be reported.

Distance extrapolation factor = $40 \log(\text{Specific distance} / \text{test distance})$ (dB);

Limit line = Specific limits(dBuV) + distance extrapolation factor

■ Spurious Emission Above 1GHz (1GHz to 25GHz)

Bluetooth (GFSK, pi/4-DQPSK, 8DPSK) mode have been tested, and the worst result(GFSK) was report as below:

Test mode: GFSK Frequency: Channel 0: 2402MHz

Freq. (MHz)	Ant. Pol. H/V	Emission Level(dBuV/m)		Limit 3m(dBuV/m)		Over(dB)	
		PK	AV	PK	AV	PK	AV
4804.57	V	57.43	35.53	74	54	-16.57	-18.47
7207.3	V	56.56	35.13	74	54	-17.44	-18.87
4320.22	V	56.94	31.45	74	54	-17.06	-22.55
4804.65	H	65.91	43.53	74	54	-8.09	-10.47
7207.45	H	59.67	40.71	74	54	-14.33	-13.29
4513.81	H	53.57	37.55	74	54	-20.43	-16.45

Test mode: GFSK Frequency: Channel 39: 2441MHz

Freq. (MHz)	Ant. Pol. H/V	Emission Level(dBuV/m)		Limit 3m(dBuV/m)		Over(dB)	
		PK	AV	PK	AV	PK	AV
4884.21	V	57.83	29.83	74	54	-16.17	-24.17
7325.35	V	50.28	34.15	74	54	-23.72	-19.85
4310.29	V	51.36	30.12	74	54	-22.64	-23.88
4883.24	H	64.41	45.34	74	54	-9.59	-8.66
7326.05	H	57.18	34.98	74	54	-16.82	-19.02
4521.57	H	52.89	37.62	74	54	-21.11	-16.38

Test mode: GFSK Frequency: Channel 78: 2480MHz

Freq. (MHz)	Ant. Pol. H/V	Emission Level(dBuV/m)		Limit 3m(dBuV/m)		Over(dB)	
		PK	AV	PK	AV	PK	AV
4961.98	V	58.33	49.66	74	54	-15.67	-4.34
7441.52	V	55.77	46.37	74	54	-18.23	-7.63
4310.44	V	55.79	48.39	74	54	-18.21	-5.61
4962.37	H	58.24	47.92	74	54	-15.76	-6.08
7443.08	H	56.45	48.17	74	54	-17.55	-5.83
4512.09	H	55.66	45.75	74	54	-18.34	-8.25

Note: (1) All Readings are Peak Value (VBW=3MHz) and Peak Value (VBW=10Hz).

(2) Emission Level= Reading Level+Probe Factor +Cable Loss.

(3) Data of measurement within this frequency range shown "--" in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.

■ Spurious Emission in Restricted Band 2310-2390MHz and 2483.5-2500MHz Bluetooth (GFSK, pi/4-DQPSK, 8DPSK, Hopping) mode have been tested, and the worst result(GFSK, Hopping) was report as below:

Test mode: GFSK Frequency: Channel 0: 2402MHz

Frequency (MHz)	Polarity H/V	PK(dBuV/m) (VBW=3MHz)	Limit 3m (dBuV/m)	AV(dBuV/m) (VBW=10Hz)	Limit 3m (dBuV/m)
2347.12	H	44.75	74	37.65	54
2349.04	V	45.51	74	38.82	54

Test mode: GFSK Frequency: Channel 78: 2480MHz

Frequency (MHz)	Polarity H/V	PK(dBuV/m) (VBW=3MHz)	Limit 3m (dBuV/m)	AV(dBuV/m) (VBW=10Hz)	Limit 3m (dBuV/m)
2485.67	H	45.39	74	37.62	54
2485.18	V	45.99	74	35.99	54

Test mode: GFSK Frequency: Hopping


Frequency (MHz)	Polarity H/V	PK(dBuV/m) (VBW=3MHz)	Limit 3m (dBuV/m)	AV(dBuV/m) (VBW=10Hz)	Limit 3m (dBuV/m)
2317.15	H	48.27	74	34.30	54
2483.50	H	41.52	74	34.63	54
2400.00	V	51.84	74	42.20	54
2483.00	V	48.38	74	39.50	54

Note: (1) All Readings are Peak Value (VBW=3MHz) and Peak Value (VBW=10Hz).


(2) Emission Level= Reading Level+Probe Factor +Cable Loss.

(3) Data of measurement within this frequency range shown "--" in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.


Test Model	Spurious Emission in Restricted Band 2310-2390MHz		
	Bluetooth V5.3		
	Channel 0: 2402MHz	GFSK	H
		Test By: King Kong	




Test Model	Spurious Emission in Restricted Band 2310-2390MHz		
	Bluetooth V5.3		
	Channel 0: 2402MHz	GFSK	V
		Test By: King Kong	




Test Model	Spurious Emission in Restricted Band 2483.5-2500MHz		
	Bluetooth V5.3		
	Channel 78: 2480MHz	GFSK	H
		Test By: King Kong	



Test Model	Spurious Emission in Restricted Band 2483.5-2500MHz		
	Bluetooth V5.3		
	Channel 78: 2480MHz	GFSK	V
		Test By: King Kong	




Test Model	Spurious Emission in Restricted Band 2310-2390MHz and 2400-2483.5MHz		
	Bluetooth V5.3		
	Hopping	GFSK	H
Test By: King Kong			



Test Model	Spurious Emission in Restricted Band 2310-2390MHz and 2400-2483.5MHz		
	Bluetooth V5.3		
	Hopping	GFSK	V
Test By: King Kong			




■ Spurious Emission below 1GHz (30MHz to 1GHz)
Bluetooth (GFSK, pi/4-DQPSK, 8DPSK) mode have been tested, and the worst result(GFSK) was report as below:




Site:	Antenna::Vertical	Temperature(C):24.5(C)
Limit: FCC Part 15C 3M Radiation(QP)		Humidity(%):55%
M/N.: ANC BD228	Power Rating: AC 120V 60Hz	
Mode: BT 2402	Test Engineer: Ken	
Note:		

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.			
1	30.7454	23.58	-0.43	23.15	40.00	-16.85	QP			
2	38.6160	26.47	-5.03	21.44	40.00	-18.56	QP			
3	47.9940	26.88	-8.69	18.19	40.00	-21.81	QP			
4	107.1337	25.16	-4.34	20.82	43.50	-22.68	QP			
5	129.9225	23.88	-3.27	20.61	43.50	-22.89	QP			
6	140.8350	25.66	-2.64	23.02	43.50	-20.48	QP			




Site:		Antenna:: Horizontal	Temperature(C): 24.5(C)
Limit:	FCC Part 15C 3M Radiation(QP)		Humidity(%): 55%
M/N.:	ANC BD228	Power Rating:	AC 120V 60Hz
Mode:	BT 2402	Test Engineer:	Ken
Note:			

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.			
1	30.4237	21.69	-0.08	21.61	40.00	-18.39	QP			
2	38.6160	24.54	-5.03	19.51	40.00	-20.49	QP			
3	103.4421	26.36	-4.57	21.79	43.50	-21.71	QP			
4	129.9225	23.91	-3.27	20.64	43.50	-22.86	QP			
5	159.2251	24.54	-4.39	20.15	43.50	-23.35	QP			
6	192.4185	34.36	-7.06	27.30	43.50	-16.20	QP			




Site:		Antenna:: Vertical	Temperature(C): 24.5(C)
Limit:	FCC Part 15C 3M Radiation(QP)		Humidity(%): 55%
M/N.:	ANC BD228	Power Rating:	AC 120V 60Hz
Mode:	BT 2441	Test Engineer:	Ken
Note:			

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.			
1	30.2111	20.39	0.14	20.53	40.00	-19.47	QP			
2	41.4215	24.43	-5.59	18.84	40.00	-21.16	QP			
3	101.6443	24.38	-4.68	19.70	43.50	-23.80	QP			
4	116.5400	24.47	-3.52	20.95	43.50	-22.55	QP			
5	140.8350	23.84	-2.64	21.20	43.50	-22.30	QP			
6	176.2686	25.19	-6.33	18.86	43.50	-24.64	QP			




Site:		Antenna:: Horizontal	Temperature(C): 24.5(C)
Limit:	FCC Part 15C 3M Radiation(QP)		Humidity(%): 55%
M/N.:	ANC BD228	Power Rating:	AC 120V 60Hz
Mode:	BT 2441	Test Engineer:	Ken
Note:			

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.			
1	30.2111	23.47	0.14	23.61	40.00	-16.39	QP			
2	38.8878	24.53	-5.04	19.49	40.00	-20.51	QP			
3	44.1202	23.87	-6.63	17.24	40.00	-22.76	QP			
4	104.9033	26.11	-4.48	21.63	43.50	-21.87	QP			
5	143.3261	24.21	-2.87	21.34	43.50	-22.16	QP			
6	191.7450	25.24	-7.07	18.17	43.50	-25.33	QP			



Site:		Antenna:: Vertical	Temperature(C): 24.5(C)
Limit:	FCC Part 15C 3M Radiation(QP)		Humidity(%): 55%
M/N.:	ANC BD228	Power Rating:	AC 120V 60Hz
Mode:	BT 2480	Test Engineer:	Ken
Note:			

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.			
1	30.0000	21.78	0.38	22.16	40.00	-17.84	QP			
2	40.4170	25.50	-5.20	20.30	40.00	-19.70	QP			
3	56.5929	29.29	-13.09	16.20	40.00	-23.80	QP			
4	108.2666	25.17	-4.28	20.89	43.50	-22.61	QP			
5	121.9755	24.75	-3.19	21.56	43.50	-21.94	QP			
6	153.7385	24.43	-3.85	20.58	43.50	-22.92	QP			



Site:		Antenna::Horizontal	Temperature(C):24.5(C)
Limit:	FCC Part 15C 3M Radiation(QP)		Humidity(%):55%
M/N.:	ANC BD228	Power Rating:	AC 120V 60Hz
Mode:	BT 2480	Test Engineer:	Ken
Note:			

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.			
1	30.4237	22.87	-0.08	22.79	40.00	-17.21	QP			
2	38.6160	26.54	-5.03	21.51	40.00	-18.49	QP			
3	46.8302	24.61	-8.02	16.59	40.00	-23.41	QP			
4	103.8054	26.93	-4.55	22.38	43.50	-21.12	QP			
5	140.3420	25.01	-2.60	22.41	43.50	-21.09	QP			
6	210.7860	25.10	-6.86	18.24	43.50	-25.26	QP			

8.8 CONDUCTED EMISSION TEST

8.8.1 Applicable Standard

According to FCC Part 15.207(a)

8.8.2 Conformance Limit

Conducted Emission Limit		
Frequency(MHz)	Quasi-peak	Average
0.15-0.5	66-56	56-46
0.5-5.0	56	46
5.0-30.0	60	50

Note: 1. The lower limit shall apply at the transition frequencies
 2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50MHz.

Remark: Test results were obtained from the following equation:

$$\text{Measurement (dB}\mu\text{V)} = \text{LISN Factor (dB)} + \text{Cable Loss (dB)} + \text{Reading (dB}\mu\text{V)}$$

$$\text{Over (dB)} = \text{Measurement (dB}\mu\text{V)} - \text{Limit (dB}\mu\text{V)}$$

8.8.3 Test Configuration

Test according to clause 6.3 conducted emission test setup

8.8.4 Test Procedure

The EUT was placed on a table which is 0.8m above ground plane.

Maximum procedure was performed on the highest emissions to ensure EUT compliance.

Repeat above procedures until all frequency measured were complete.

8.8.5 Test Results

Stop working while charging, not applicable

8.9 ANTENNA APPLICATION

8.9.1 Antenna Requirement

Standard	Requirement
FCC CRF Part 15.203	An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. This requirement does not apply to carrier current devices or to devices operated under the provisions of §15.211, §15.213, §15.217, §15.219, or §15.221. Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with §15.31(d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this part are not exceeded.

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. And according to FCC 47 CFR Section 15.247 (b), if transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

8.9.2 Result

PASS.

The EUT has 1 antenna: a Internal Antenna for BT V5.3 with classic model, the gain is 1.2 dBi;

Note: Antenna use a permanently attached antenna which is not replaceable.
 Not using a standard antenna jack or electrical connector for antenna replacement
 The antenna has to be professionally installed (please provide method of installation)

which in accordance to section 15.203, please refer to the internal photos.

----- END OF REPORT -----