

SPECIFICATION FOR APPROVAL

CUSTOMER: Shenzhen Future Charger Technology Co. Ltd.

CUST P/N:

DESC:

J-FCA12L15

DATE:

20221203

VERSION:

A.0

PREPARED BY	CHECKED BY	APPROVED BY	CUSTOMER APPROVE
杨茂新	刘惜姜	罗杰	

东莞市吉欧电子科技有限公司

DONGGUAN JIOU ELECTRONIC TECHNOLOGY CO,LTD

ADDR: Xinfu Industrial Zone, Shijie Town, Dongguan City

TEL:[0769-83067050](tel:0769-83067050)E-mail: lybofmana@163.com

Version Change History

Rev	Before Change	After Change	Change Date	Approved BY
A.0	New Issue		20221203	罗杰

SPECIFICATION

DESC	J-FCA12L15	REV:A.O	CUST	分寸
			CUST P/N	
一、 DIMENSION(MM)				
			A	$46 \pm 1\text{mm}$
			B	$18 \pm 0.5\text{ mm}$
			C	$5 \pm 0.5\text{ mm}$
			D	$50 \pm 1\text{mm}$
			E	$15 \pm 2\text{ mm}$
			F	$3 \pm 2\text{ mm}$
			G	$2 \pm 0.1\text{ mm}$
			H	4.0Max
<p>notes:</p> <ol style="list-style-type: none"> 1. Paste 1.5~2 circles of 8mm high temperature tape at the lead 2. Middle sticker of magnetic separator and coil inner hole $\Phi 15 * 1.0$EVA double-sided adhesive 				

二、Winding Specification:

Wire	Turns	Winding Direction
silk wire 0.08*90P	13TS	Rewind

三、ELECTRICAL CHARACTERISTICS:

TEMPERATURE:25 ± 10°C,RELATIVE HUMIDITY :65 ± 20%

TIEM	SPECIFICATION	TEST FREQUENCY	TEST EQUIPMENTS
IND	10.0UH ± 10%	100 KHZ/1.0V	LCZ METER 1062B
DCR	65m Ω Max		LCZ METER 1062B

PREPARED BY	CHECKED BY	DATE
杨茂新	刘惜姜	20221203

